Autoconf

Creating Automatic Configuration Scripts
for version 2.62, 8 April 2008

David MacKenzie
Ben Elliston
Akim Demaille

This manual is for GNU Autoconf (version 2.62, 8 April 2008), a package for creating scripts to configure source code packages using templates and an M4 macro package.

Copyright © 1992, 1993, 1994, 1995, 1996, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 Free Software Foundation, Inc.

> Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, with the Front-Cover texts being "A GNU Manual," and with the Back-Cover Texts as in (a) below. A copy of the license is included in the section entitled "GNU Free Documentation License."
>
> (a) The FSF's Back-Cover Text is: "You have the freedom to copy and modify this GNU manual. Buying copies from the FSF supports it in developing GNU and promoting software freedom."

Table of Contents

1 Introduction 1

2 The GNU Build System 3

2.1 Automake 3
2.2 Gnulib 3
2.3 Libtool 4
2.4 Pointers 4

3 Making `configure` Scripts 7

3.1 Writing '`configure.ac`' 8
3.1.1 A Shell Script Compiler 8
3.1.2 The Autoconf Language 9
3.1.3 Standard '`configure.ac`' Layout 10
3.2 Using `autoscan` to Create '`configure.ac`' 11
3.3 Using `ifnames` to List Conditionals 12
3.4 Using `autoconf` to Create `configure` 12
3.5 Using `autoreconf` to Update `configure` Scripts 15

4 Initialization and Output Files 17

4.1 Initializing `configure` 17
4.2 Dealing with Autoconf versions 18
4.3 Notices in `configure` 18
4.4 Finding `configure` Input 19
4.5 Outputting Files 20
4.6 Performing Configuration Actions 20
4.7 Creating Configuration Files 22
4.8 Substitutions in Makefiles 23
4.8.1 Preset Output Variables 23
4.8.2 Installation Directory Variables 26
4.8.3 Changed Directory Variables 29
4.8.4 Build Directories 30
4.8.5 Automatic Remaking 31
4.9 Configuration Header Files 32
4.9.1 Configuration Header Templates 33
4.9.2 Using `autoheader` to Create '`config.h.in`' 33
4.9.3 Autoheader Macros 35
4.10 Running Arbitrary Configuration Commands 35
4.11 Creating Configuration Links 36
4.12 Configuring Other Packages in Subdirectories 37
4.13 Default Prefix 37

5 Existing Tests 39
5.1 Common Behavior 39
5.1.1 Standard Symbols 39
5.1.2 Default Includes 39
5.2 Alternative Programs 40
5.2.1 Particular Program Checks 41
5.2.2 Generic Program and File Checks 43
5.3 Files 46
5.4 Library Files 46
5.5 Library Functions 47
5.5.1 Portability of C Functions 47
5.5.2 Particular Function Checks 50
5.5.3 Generic Function Checks 56
5.6 Header Files 58
5.6.1 Portability of Headers 58
5.6.2 Particular Header Checks 60
5.6.3 Generic Header Checks 65
5.7 Declarations 66
5.7.1 Particular Declaration Checks 66
5.7.2 Generic Declaration Checks 66
5.8 Structures 67
5.8.1 Particular Structure Checks 67
5.8.2 Generic Structure Checks 68
5.9 Types 69
5.9.1 Particular Type Checks 69
5.9.2 Generic Type Checks 71
5.10 Compilers and Preprocessors 72
5.10.1 Specific Compiler Characteristics 72
5.10.2 Generic Compiler Characteristics 73
5.10.3 C Compiler Characteristics 74
5.10.4 C++ Compiler Characteristics 80
5.10.5 Objective C Compiler Characteristics 80
5.10.6 Erlang Compiler and Interpreter Characteristics 81
5.10.7 Fortran Compiler Characteristics 81
5.11 System Services 86
5.12 Posix Variants 87
5.13 Erlang Libraries 88

6 Writing Tests 91
6.1 Language Choice 91
6.2 Writing Test Programs 92
6.2.1 Guidelines for Test Programs 93
6.2.2 Test Functions 93
6.2.3 Generating Sources 94
6.3 Running the Preprocessor 96
6.4 Running the Compiler 97
6.5 Running the Linker 98
6.6 Checking Runtime Behavior 98

6.7 Systemology 100
6.8 Multiple Cases 101

7 Results of Tests 103

7.1 Defining C Preprocessor Symbols 103
7.2 Setting Output Variables 104
7.3 Special Characters in Output Variables 106
7.4 Caching Results 107
7.4.1 Cache Variable Names 108
7.4.2 Cache Files 108
7.4.3 Cache Checkpointing 109
7.5 Printing Messages 110

8 Programming in M4 113

8.1 M4 Quotation 113
8.1.1 Active Characters 113
8.1.2 One Macro Call 114
8.1.3 Quoting and Parameters 115
8.1.4 Quotation and Nested Macros 116
8.1.5 `changequote` is Evil 117
8.1.6 Quadrigraphs 118
8.1.7 Quotation Rule Of Thumb 119
8.2 Using `autom4te` 120
8.2.1 Invoking `autom4te` 120
8.2.2 Customizing `autom4te` 124
8.3 Programming in M4sugar 125
8.3.1 Redefined M4 Macros 125
8.3.2 Diagnostic messages from M4sugar 127
8.3.3 Diversion support 128
8.3.4 Conditional constructs 130
8.3.5 Looping constructs 131
8.3.6 Evaluation Macros 133
8.3.7 String manipulation in M4 136
8.3.8 Arithmetic computation in M4 139
8.3.9 Forbidden Patterns 141
8.4 Programming in M4sh 141
8.5 File Descriptor Macros 143

9 Writing Autoconf Macros 145

9.1 Macro Definitions 145
9.2 Macro Names 145
9.3 Reporting Messages 147
9.4 Dependencies Between Macros 147
9.4.1 Prerequisite Macros 147
9.4.2 Suggested Ordering 149
9.4.3 One-Shot Macros 149
9.5 Obsoleting Macros 150
9.6 Coding Style 150

10 Portable Shell Programming 155

10.1 Shellology 155
10.2 Here-Documents 157
10.3 File Descriptors 158
10.4 File System Conventions 160
10.5 Shell Pattern Matching 162
10.6 Shell Substitutions 162
10.7 Assignments 166
10.8 Parentheses in Shell Scripts 167
10.9 Slashes in Shell Scripts 167
10.10 Special Shell Variables 168
10.11 Shell Functions 172
10.12 Limitations of Shell Builtins 173
10.13 Limitations of Usual Tools 182

11 Portable Make Programming 197

11.1 `$<` in Ordinary Make Rules 197
11.2 Failure in Make Rules 197
11.3 Special Characters in Make Macro Names 197
11.4 Backslash-Newline-Newline in Make Macro Values 198
11.5 Backslash-Newline in Make Comments 198
11.6 Long Lines in Makefiles 198
11.7 `make macro=value` and Submakes 198
11.8 The Make Macro MAKEFLAGS 199
11.9 The Make Macro `SHELL` 200
11.10 Comments in Make Rules 200
11.11 The '`obj/`' Subdirectory and Make 201
11.12 Exit Status of `make -k` 201
11.13 `VPATH` and Make 201
11.13.1 `VPATH` and Double-colon Rules 202
11.13.2 `$<` Not Supported in Explicit Rules 202
11.13.3 Automatic Rule Rewriting 202
11.13.4 Tru64 `make` Creates Prerequisite Directories Magically 205
11.13.5 Make Target Lookup 205
11.14 Single Suffix Rules and Separated Dependencies 207
11.15 Timestamp Resolution and Make 208

12 Portable C and C++ Programming 211

12.1 Varieties of Unportability 211
12.2 Integer Overflow 212
12.2.1 Basics of Integer Overflow 212
12.2.2 Examples of Code Assuming Wraparound Overflow 212
12.2.3 Optimizations That Break Wraparound Arithmetic 214
12.2.4 Practical Advice for Signed Overflow Issues 215
12.2.5 Signed Integer Division and Integer Overflow 216
12.3 Preprocessor Arithmetic 216

12.4 Properties of Null Pointers 216
12.5 Buffer Overruns and Subscript Errors 216
12.6 Volatile Objects 217
12.7 Floating Point Portability 219
12.8 Exiting Portably 219

13 Manual Configuration 221

13.1 Specifying the System Type 221
13.2 Getting the Canonical System Type 222
13.3 Using the System Type 223

14 Site Configuration 225

14.1 Controlling Help Output 225
14.2 Working With External Software 225
14.3 Choosing Package Options 227
14.4 Making Your Help Strings Look Pretty 228
14.5 Controlling Checking of `configure` Options 229
14.6 Configuring Site Details 230
14.7 Transforming Program Names When Installing 230
14.7.1 Transformation Options 230
14.7.2 Transformation Examples 231
14.7.3 Transformation Rules 231
14.8 Setting Site Defaults 232

15 Running `configure` Scripts 235

15.1 Basic Installation 235
15.2 Compilers and Options 236
15.3 Compiling For Multiple Architectures 236
15.4 Installation Names 236
15.5 Optional Features 236
15.6 Specifying the System Type 237
15.7 Sharing Defaults 237
15.8 Defining Variables 237
15.9 `configure` Invocation 237

16 config.status Invocation 239

17 Obsolete Constructs 241
17.1 Obsolete ‘`config.status`’ Invocation 241
17.2 ‘`acconfig.h`’ 242
17.3 Using `autoupdate` to Modernize ‘`configure.ac`’ 242
17.4 Obsolete Macros 243
17.5 Upgrading From Version 1 255
17.5.1 Changed File Names 256
17.5.2 Changed Makefiles 256
17.5.3 Changed Macros 256
17.5.4 Changed Results 257
17.5.5 Changed Macro Writing 257
17.6 Upgrading From Version 2.13 258
17.6.1 Changed Quotation 258
17.6.2 New Macros 259
17.6.3 Hosts and Cross-Compilation 260
17.6.4 `AC_LIBOBJ` vs. `LIBOBJS` 261
17.6.5 `AC_FOO_IFELSE` vs. `AC_TRY_FOO` 262

18 Generating Test Suites with Autotest 263
18.1 Using an Autotest Test Suite 263
18.1.1 `testsuite` Scripts 263
18.1.2 Autotest Logs 265
18.2 Writing ‘`testsuite.at`’ 265
18.3 Running `testsuite` Scripts 267
18.4 Making `testsuite` Scripts 269

19 Frequent Autoconf Questions, with answers 271
19.1 Distributing `configure` Scripts 271
19.2 Why Require GNU M4? 271
19.3 How Can I Bootstrap? 271
19.4 Why Not Imake? 272
19.5 How Do I `#define` Installation Directories? 273
19.6 What is ‘`autom4te.cache`’? 274
19.7 Header Present But Cannot Be Compiled 274

20 History of Autoconf 277
20.1 Genesis 277
20.2 Exodus 277
20.3 Leviticus 278
20.4 Numbers 278
20.5 Deuteronomy 279

Appendix A GNU Free Documentation License 281

Appendix B Indices 289
B.1 Environment Variable Index 289
B.2 Output Variable Index 289
B.3 Preprocessor Symbol Index 291
B.4 Autoconf Macro Index 293
B.5 M4 Macro Index 297
B.6 Autotest Macro Index 299
B.7 Program and Function Index 299
B.8 Concept Index 301

1 Introduction

> A physicist, an engineer, and a computer scientist were discussing the nature of God. "Surely a Physicist," said the physicist, "because early in the Creation, God made Light; and you know, Maxwell's equations, the dual nature of electromagnetic waves, the relativistic consequences. . ." "An Engineer!," said the engineer, "because before making Light, God split the Chaos into Land and Water; it takes a hell of an engineer to handle that big amount of mud, and orderly separation of solids from liquids. . ." The computer scientist shouted: "And the Chaos, where do you think it was coming from, hmm?"
>
> —Anonymous

Autoconf is a tool for producing shell scripts that automatically configure software source code packages to adapt to many kinds of Posix-like systems. The configuration scripts produced by Autoconf are independent of Autoconf when they are run, so their users do not need to have Autoconf.

The configuration scripts produced by Autoconf require no manual user intervention when run; they do not normally even need an argument specifying the system type. Instead, they individually test for the presence of each feature that the software package they are for might need. (Before each check, they print a one-line message stating what they are checking for, so the user doesn't get too bored while waiting for the script to finish.) As a result, they deal well with systems that are hybrids or customized from the more common Posix variants. There is no need to maintain files that list the features supported by each release of each variant of Posix.

For each software package that Autoconf is used with, it creates a configuration script from a template file that lists the system features that the package needs or can use. After the shell code to recognize and respond to a system feature has been written, Autoconf allows it to be shared by many software packages that can use (or need) that feature. If it later turns out that the shell code needs adjustment for some reason, it needs to be changed in only one place; all of the configuration scripts can be regenerated automatically to take advantage of the updated code.

Those who do not understand Autoconf are condemned to reinvent it, poorly. The primary goal of Autoconf is making the *user's* life easier; making the *maintainer's* life easier is only a secondary goal. Put another way, the primary goal is not to make the generation of '`configure`' automatic for package maintainers (although patches along that front are welcome, since package maintainers form the user base of Autoconf); rather, the goal is to make '`configure`' painless, portable, and predictable for the end user of each *autoconfiscated* package. And to this degree, Autoconf is highly successful at its goal — most complaints to the Autoconf list are about difficulties in writing Autoconf input, and not in the behavior of the resulting '`configure`'. Even packages that don't use Autoconf will generally provide a '`configure`' script, and the most common complaint about these alternative home-grown scripts is that they fail to meet one or more of the GNU Coding Standards that users have come to expect from Autoconf-generated '`configure`' scripts.

The Metaconfig package is similar in purpose to Autoconf, but the scripts it produces require manual user intervention, which is quite inconvenient when configuring large source

trees. Unlike Metaconfig scripts, Autoconf scripts can support cross-compiling, if some care is taken in writing them.

Autoconf does not solve all problems related to making portable software packages—for a more complete solution, it should be used in concert with other GNU build tools like Automake and Libtool. These other tools take on jobs like the creation of a portable, recursive makefile with all of the standard targets, linking of shared libraries, and so on. See Chapter 2 [The GNU Build System], page 3, for more information.

Autoconf imposes some restrictions on the names of macros used with `#if` in C programs (see Section B.3 [Preprocessor Symbol Index], page 291).

Autoconf requires GNU M4 version 1.4.5 or later in order to generate the scripts. It uses features that some versions of M4, including GNU M4 1.3, do not have. Autoconf works better with GNU M4 version 1.4.11 or later, though this is not required.

See Section 17.5 [Autoconf 1], page 255, for information about upgrading from version 1. See Chapter 20 [History], page 277, for the story of Autoconf's development. See Chapter 19 [FAQ], page 271, for answers to some common questions about Autoconf.

See the Autoconf web page (`http://www.gnu.org/software/autoconf/`) for up-to-date information, details on the mailing lists, pointers to a list of known bugs, etc.

Mail suggestions to the Autoconf mailing list (`autoconf@gnu.org`). Past suggestions are archived (`http://lists.gnu.org/archive/html/autoconf/`).

Mail bug reports to the Autoconf Bugs mailing list (`bug-autoconf@gnu.org`). Past bug reports are archived (`http://lists.gnu.org/archive/html/bug-autoconf/`).

If possible, first check that your bug is not already solved in current development versions, and that it has not been reported yet. Be sure to include all the needed information and a short '`configure.ac`' that demonstrates the problem.

Autoconf's development tree is accessible via `git`; see the Autoconf Summary (`http://savannah.gnu.org/projects/autoconf/`) for details, or view the actual repository (`http://git.sv.gnu.org/gitweb/?p=autoconf.git`). Anonymous CVS access is also available, see '`README`' for more details. Patches relative to the current `git` version can be sent for review to the Autoconf Patches mailing list (`autoconf-patches@gnu.org`). Discussions on past patches are archived (`http://lists.gnu.org/archive/html/autoconf-patches/`), and all commits are archived in the read-only Autoconf Commit mailing list (`autoconf-commit@gnu.org`), which is also archived (`http://lists.gnu.org/archive/html/autoconf-commit/`).

Because of its mission, the Autoconf package itself includes only a set of often-used macros that have already demonstrated their usefulness. Nevertheless, if you wish to share your macros, or find existing ones, see the Autoconf Macro Archive (`http://autoconf-archive.cryp.to/`), which is kindly run by Peter Simons (`simons@cryp.to`).

2 The GNU Build System

Autoconf solves an important problem—reliable discovery of system-specific build and run-time information—but this is only one piece of the puzzle for the development of portable software. To this end, the GNU project has developed a suite of integrated utilities to finish the job Autoconf started: the GNU build system, whose most important components are Autoconf, Automake, and Libtool. In this chapter, we introduce you to those tools, point you to sources of more information, and try to convince you to use the entire GNU build system for your software.

2.1 Automake

The ubiquity of `make` means that a makefile is almost the only viable way to distribute automatic build rules for software, but one quickly runs into its numerous limitations. Its lack of support for automatic dependency tracking, recursive builds in subdirectories, reliable timestamps (e.g., for network file systems), and so on, mean that developers must painfully (and often incorrectly) reinvent the wheel for each project. Portability is non-trivial, thanks to the quirks of `make` on many systems. On top of all this is the manual labor required to implement the many standard targets that users have come to expect (`make install`, `make distclean`, `make uninstall`, etc.). Since you are, of course, using Autoconf, you also have to insert repetitive code in your `Makefile.in` to recognize `@CC@`, `@CFLAGS@`, and other substitutions provided by `configure`. Into this mess steps *Automake*.

Automake allows you to specify your build needs in a `Makefile.am` file with a vastly simpler and more powerful syntax than that of a plain makefile, and then generates a portable `Makefile.in` for use with Autoconf. For example, the `Makefile.am` to build and install a simple "Hello world" program might look like:

```
bin_PROGRAMS = hello
hello_SOURCES = hello.c
```

The resulting `Makefile.in` (~400 lines) automatically supports all the standard targets, the substitutions provided by Autoconf, automatic dependency tracking, `VPATH` building, and so on. `make` builds the `hello` program, and `make install` installs it in '`/usr/local/bin`' (or whatever prefix was given to `configure`, if not '`/usr/local`').

The benefits of Automake increase for larger packages (especially ones with subdirectories), but even for small programs the added convenience and portability can be substantial. And that's not all. . .

2.2 Gnulib

GNU software has a well-deserved reputation for running on many different types of systems. While our primary goal is to write software for the GNU system, many users and developers have been introduced to us through the systems that they were already using.

Gnulib is a central location for common GNU code, intended to be shared among free software packages. Its components are typically shared at the source level, rather than being a library that gets built, installed, and linked against. The idea is to copy files from Gnulib into your own source tree. There is no distribution tarball; developers should just

grab source modules from the repository. The source files are available online, under various licenses, mostly GNU GPL or GNU LGPL.

Gnulib modules typically contain C source code along with Autoconf macros used to configure the source code. For example, the Gnulib `stdbool` module implements a '`stdbool.h`' header that nearly conforms to C99, even on old-fashioned hosts that lack '`stdbool.h`'. This module contains a source file for the replacement header, along with an Autoconf macro that arranges to use the replacement header on old-fashioned systems.

2.3 Libtool

Often, one wants to build not only programs, but libraries, so that other programs can benefit from the fruits of your labor. Ideally, one would like to produce *shared* (dynamically linked) libraries, which can be used by multiple programs without duplication on disk or in memory and can be updated independently of the linked programs. Producing shared libraries portably, however, is the stuff of nightmares—each system has its own incompatible tools, compiler flags, and magic incantations. Fortunately, GNU provides a solution: *Libtool*.

Libtool handles all the requirements of building shared libraries for you, and at this time seems to be the *only* way to do so with any portability. It also handles many other headaches, such as: the interaction of Make rules with the variable suffixes of shared libraries, linking reliably with shared libraries before they are installed by the superuser, and supplying a consistent versioning system (so that different versions of a library can be installed or upgraded without breaking binary compatibility). Although Libtool, like Autoconf, can be used without Automake, it is most simply utilized in conjunction with Automake—there, Libtool is used automatically whenever shared libraries are needed, and you need not know its syntax.

2.4 Pointers

Developers who are used to the simplicity of `make` for small projects on a single system might be daunted at the prospect of learning to use Automake and Autoconf. As your software is distributed to more and more users, however, you otherwise quickly find yourself putting lots of effort into reinventing the services that the GNU build tools provide, and making the same mistakes that they once made and overcame. (Besides, since you're already learning Autoconf, Automake is a piece of cake.)

There are a number of places that you can go to for more information on the GNU build tools.

- Web

  The home pages for Autoconf (`http://www.gnu.org/software/autoconf/`), Automake (`http://www.gnu.org/software/automake/`), Gnulib (`http://www.gnu.org/software/gnulib/`), and Libtool (`http://www.gnu.org/software/libtool/`).

- Automake Manual

  See section "Automake" in *GNU Automake*, for more information on Automake.

- Books

The book *GNU Autoconf, Automake and Libtool*[1] describes the complete GNU build environment. You can also find the entire book on-line (`http://sources.redhat.com/autobook/`).

[1] *GNU Autoconf, Automake and Libtool*, by G. V. Vaughan, B. Elliston, T. Tromey, and I. L. Taylor. SAMS (originally New Riders), 2000, ISBN 1578701902.

3 Making configure Scripts

The configuration scripts that Autoconf produces are by convention called configure. When run, configure creates several files, replacing configuration parameters in them with appropriate values. The files that configure creates are:

- one or more 'Makefile' files, usually one in each subdirectory of the package (see Section 4.8 [Makefile Substitutions], page 23);
- optionally, a C header file, the name of which is configurable, containing #define directives (see Section 4.9 [Configuration Headers], page 32);
- a shell script called 'config.status' that, when run, recreates the files listed above (see Chapter 16 [config.status Invocation], page 239);
- an optional shell script normally called 'config.cache' (created when using 'configure --config-cache') that saves the results of running many of the tests (see Section 7.4.2 [Cache Files], page 108);
- a file called 'config.log' containing any messages produced by compilers, to help debugging if configure makes a mistake.

To create a configure script with Autoconf, you need to write an Autoconf input file 'configure.ac' (or 'configure.in') and run autoconf on it. If you write your own feature tests to supplement those that come with Autoconf, you might also write files called 'aclocal.m4' and 'acsite.m4'. If you use a C header file to contain #define directives, you might also run autoheader, and you can distribute the generated file 'config.h.in' with the package.

Here is a diagram showing how the files that can be used in configuration are produced. Programs that are executed are suffixed by '*'. Optional files are enclosed in square brackets ('[]'). autoconf and autoheader also read the installed Autoconf macro files (by reading 'autoconf.m4').

Files used in preparing a software package for distribution:

```
your source files --> [autoscan*] --> [configure.scan] --> configure.ac

configure.ac --.
               |   .------> autoconf* -----> configure
[aclocal.m4] --+---+
               |   `-----> [autoheader*] --> [config.h.in]
[acsite.m4] ---'

Makefile.in -------------------------------> Makefile.in
```

Files used in configuring a software package:

```
                      .-------------> [config.cache]
configure* ------------+-------------> config.log
                      |
[config.h.in] -.       v            .-> [config.h] -.
               +--> config.status* -+               +--> make*
Makefile.in ---'                    `-> Makefile ---'
```

3.1 Writing 'configure.ac'

To produce a configure script for a software package, create a file called 'configure.ac' that contains invocations of the Autoconf macros that test the system features your package needs or can use. Autoconf macros already exist to check for many features; see Chapter 5 [Existing Tests], page 39, for their descriptions. For most other features, you can use Autoconf template macros to produce custom checks; see Chapter 6 [Writing Tests], page 91, for information about them. For especially tricky or specialized features, 'configure.ac' might need to contain some hand-crafted shell commands; see Chapter 10 [Portable Shell], page 155. The autoscan program can give you a good start in writing 'configure.ac' (see Section 3.2 [autoscan Invocation], page 11, for more information).

Previous versions of Autoconf promoted the name 'configure.in', which is somewhat ambiguous (the tool needed to process this file is not described by its extension), and introduces a slight confusion with 'config.h.in' and so on (for which '.in' means "to be processed by configure"). Using 'configure.ac' is now preferred.

3.1.1 A Shell Script Compiler

Just as for any other computer language, in order to properly program 'configure.ac' in Autoconf you must understand *what* problem the language tries to address and *how* it does so.

The problem Autoconf addresses is that the world is a mess. After all, you are using Autoconf in order to have your package compile easily on all sorts of different systems, some of them being extremely hostile. Autoconf itself bears the price for these differences: configure must run on all those systems, and thus configure must limit itself to their lowest common denominator of features.

Naturally, you might then think of shell scripts; who needs autoconf? A set of properly written shell functions is enough to make it easy to write configure scripts by hand. Sigh! Unfortunately, shell functions do not belong to the least common denominator; therefore, where you would like to define a function and use it ten times, you would instead need to copy its body ten times. Even in 2007, where shells without any function support are far and few between, there are pitfalls to avoid when making use of them.

So, what is really needed is some kind of compiler, autoconf, that takes an Autoconf program, 'configure.ac', and transforms it into a portable shell script, configure.

How does autoconf perform this task?

There are two obvious possibilities: creating a brand new language or extending an existing one. The former option is attractive: all sorts of optimizations could easily be implemented in the compiler and many rigorous checks could be performed on the Autoconf program (e.g., rejecting any non-portable construct). Alternatively, you can extend an existing language, such as the sh (Bourne shell) language.

Autoconf does the latter: it is a layer on top of sh. It was therefore most convenient to implement autoconf as a macro expander: a program that repeatedly performs *macro expansions* on text input, replacing macro calls with macro bodies and producing a pure sh script in the end. Instead of implementing a dedicated Autoconf macro expander, it is natural to use an existing general-purpose macro language, such as M4, and implement the extensions as a set of M4 macros.

3.1.2 The Autoconf Language

The Autoconf language differs from many other computer languages because it treats actual code the same as plain text. Whereas in C, for instance, data and instructions have different syntactic status, in Autoconf their status is rigorously the same. Therefore, we need a means to distinguish literal strings from text to be expanded: quotation.

When calling macros that take arguments, there must not be any white space between the macro name and the open parenthesis. Arguments should be enclosed within the M4 quote characters '[' and ']', and be separated by commas. Any leading blanks or newlines in arguments are ignored, unless they are quoted. You should always quote an argument that might contain a macro name, comma, parenthesis, or a leading blank or newline. This rule applies recursively for every macro call, including macros called from other macros.

For instance:

```
AC_CHECK_HEADER([stdio.h],
                [AC_DEFINE([HAVE_STDIO_H], [1],
                   [Define to 1 if you have <stdio.h>.])],
                [AC_MSG_ERROR([Sorry, can't do anything for you])])
```

is quoted properly. You may safely simplify its quotation to:

```
AC_CHECK_HEADER([stdio.h],
                [AC_DEFINE([HAVE_STDIO_H], 1,
                   [Define to 1 if you have <stdio.h>.])],
                [AC_MSG_ERROR([Sorry, can't do anything for you])])
```

because '1' cannot contain a macro call. Here, the argument of AC_MSG_ERROR must be quoted; otherwise, its comma would be interpreted as an argument separator. Also, the second and third arguments of 'AC_CHECK_HEADER' must be quoted, since they contain macro calls. The three arguments 'HAVE_STDIO_H', 'stdio.h', and 'Define to 1 if you have <stdio.h>.' do not need quoting, but if you unwisely defined a macro with a name like 'Define' or 'stdio' then they would need quoting. Cautious Autoconf users would keep the quotes, but many Autoconf users find such precautions annoying, and would rewrite the example as follows:

```
AC_CHECK_HEADER(stdio.h,
                [AC_DEFINE(HAVE_STDIO_H, 1,
                   [Define to 1 if you have <stdio.h>.])],
                [AC_MSG_ERROR([Sorry, can't do anything for you])])
```

This is safe, so long as you adopt good naming conventions and do not define macros with names like 'HAVE_STDIO_H', 'stdio', or 'h'. Though it is also safe here to omit the quotes around 'Define to 1 if you have <stdio.h>.' this is not recommended, as message strings are more likely to inadvertently contain commas.

The following example is wrong and dangerous, as it is underquoted:

```
AC_CHECK_HEADER(stdio.h,
                AC_DEFINE(HAVE_STDIO_H, 1,
                   Define to 1 if you have <stdio.h>.),
                AC_MSG_ERROR([Sorry, can't do anything for you]))
```

In other cases, you may have to use text that also resembles a macro call. You must quote that text even when it is not passed as a macro argument:

```
echo "Hard rock was here!  --[AC_DC]"
```

which results in:

```
echo "Hard rock was here!  --AC_DC"
```

When you use the same text in a macro argument, you must therefore have an extra quotation level (since one is stripped away by the macro substitution). In general, then, it is a good idea to *use double quoting for all literal string arguments*:

```
AC_MSG_WARN([[AC_DC stinks  --Iron Maiden]])
```

You are now able to understand one of the constructs of Autoconf that has been continually misunderstood... The rule of thumb is that *whenever you expect macro expansion, expect quote expansion*; i.e., expect one level of quotes to be lost. For instance:

```
AC_COMPILE_IFELSE([char b[10];], [], [AC_MSG_ERROR([you lose])])
```

is incorrect: here, the first argument of `AC_COMPILE_IFELSE` is '`char b[10];`' and is expanded once, which results in '`char b10;`'. (There was an idiom common in Autoconf's past to address this issue via the M4 `changequote` primitive, but do not use it!) Let's take a closer look: the author meant the first argument to be understood as a literal, and therefore it must be quoted twice:

```
AC_COMPILE_IFELSE([[char b[10];]], [], [AC_MSG_ERROR([you lose])])
```

Voilà, you actually produce '`char b[10];`' this time!

On the other hand, descriptions (e.g., the last parameter of `AC_DEFINE` or `AS_HELP_STRING`) are not literals—they are subject to line breaking, for example—and should not be double quoted. Even if these descriptions are short and are not actually broken, double quoting them yields weird results.

Some macros take optional arguments, which this documentation represents as [*arg*] (not to be confused with the quote characters). You may just leave them empty, or use '`[]`' to make the emptiness of the argument explicit, or you may simply omit the trailing commas. The three lines below are equivalent:

```
AC_CHECK_HEADERS([stdio.h], [], [], [])
AC_CHECK_HEADERS([stdio.h],,,)
AC_CHECK_HEADERS([stdio.h])
```

It is best to put each macro call on its own line in '`configure.ac`'. Most of the macros don't add extra newlines; they rely on the newline after the macro call to terminate the commands. This approach makes the generated `configure` script a little easier to read by not inserting lots of blank lines. It is generally safe to set shell variables on the same line as a macro call, because the shell allows assignments without intervening newlines.

You can include comments in '`configure.ac`' files by starting them with the '`#`'. For example, it is helpful to begin '`configure.ac`' files with a line like this:

```
# Process this file with autoconf to produce a configure script.
```

3.1.3 Standard '`configure.ac`' Layout

The order in which '`configure.ac`' calls the Autoconf macros is not important, with a few exceptions. Every '`configure.ac`' must contain a call to `AC_INIT` before the checks, and a call to `AC_OUTPUT` at the end (see Section 4.5 [Output], page 20). Additionally, some macros rely on other macros having been called first, because they check previously set values of

some variables to decide what to do. These macros are noted in the individual descriptions (see Chapter 5 [Existing Tests], page 39), and they also warn you when configure is created if they are called out of order.

To encourage consistency, here is a suggested order for calling the Autoconf macros. Generally speaking, the things near the end of this list are those that could depend on things earlier in it. For example, library functions could be affected by types and libraries.

Autoconf requirements
AC_INIT(*package, version, bug-report-address*)
information on the package
checks for programs
checks for libraries
checks for header files
checks for types
checks for structures
checks for compiler characteristics
checks for library functions
checks for system services
AC_CONFIG_FILES([*file...*])
AC_OUTPUT

3.2 Using autoscan to Create 'configure.ac'

The autoscan program can help you create and/or maintain a 'configure.ac' file for a software package. autoscan examines source files in the directory tree rooted at a directory given as a command line argument, or the current directory if none is given. It searches the source files for common portability problems and creates a file 'configure.scan' which is a preliminary 'configure.ac' for that package, and checks a possibly existing 'configure.ac' for completeness.

When using autoscan to create a 'configure.ac', you should manually examine 'configure.scan' before renaming it to 'configure.ac'; it probably needs some adjustments. Occasionally, autoscan outputs a macro in the wrong order relative to another macro, so that autoconf produces a warning; you need to move such macros manually. Also, if you want the package to use a configuration header file, you must add a call to AC_CONFIG_HEADERS (see Section 4.9 [Configuration Headers], page 32). You might also have to change or add some #if directives to your program in order to make it work with Autoconf (see Section 3.3 [ifnames Invocation], page 12, for information about a program that can help with that job).

When using autoscan to maintain a 'configure.ac', simply consider adding its suggestions. The file 'autoscan.log' contains detailed information on why a macro is requested.

autoscan uses several data files (installed along with Autoconf) to determine which macros to output when it finds particular symbols in a package's source files. These data files all have the same format: each line consists of a symbol, one or more blanks, and the Autoconf macro to output if that symbol is encountered. Lines starting with '#' are comments.

autoscan accepts the following options:

'`--help`'
'`-h`' Print a summary of the command line options and exit.

'`--version`'
'`-V`' Print the version number of Autoconf and exit.

'`--verbose`'
'`-v`' Print the names of the files it examines and the potentially interesting symbols it finds in them. This output can be voluminous.

'`--include=dir`'
'`-I dir`' Append *dir* to the include path. Multiple invocations accumulate.

'`--prepend-include=dir`'
'`-B dir`' Prepend *dir* to the include path. Multiple invocations accumulate.

3.3 Using `ifnames` to List Conditionals

`ifnames` can help you write '`configure.ac`' for a software package. It prints the identifiers that the package already uses in C preprocessor conditionals. If a package has already been set up to have some portability, `ifnames` can thus help you figure out what its `configure` needs to check for. It may help fill in some gaps in a '`configure.ac`' generated by `autoscan` (see Section 3.2 [autoscan Invocation], page 11).

`ifnames` scans all of the C source files named on the command line (or the standard input, if none are given) and writes to the standard output a sorted list of all the identifiers that appear in those files in `#if`, `#elif`, `#ifdef`, or `#ifndef` directives. It prints each identifier on a line, followed by a space-separated list of the files in which that identifier occurs.

`ifnames` accepts the following options:

'`--help`'
'`-h`' Print a summary of the command line options and exit.

'`--version`'
'`-V`' Print the version number of Autoconf and exit.

3.4 Using `autoconf` to Create `configure`

To create `configure` from '`configure.ac`', run the `autoconf` program with no arguments. `autoconf` processes '`configure.ac`' with the M4 macro processor, using the Autoconf macros. If you give `autoconf` an argument, it reads that file instead of '`configure.ac`' and writes the configuration script to the standard output instead of to `configure`. If you give `autoconf` the argument '`-`', it reads from the standard input instead of '`configure.ac`' and writes the configuration script to the standard output.

The Autoconf macros are defined in several files. Some of the files are distributed with Autoconf; `autoconf` reads them first. Then it looks for the optional file '`acsite.m4`' in the directory that contains the distributed Autoconf macro files, and for the optional file '`aclocal.m4`' in the current directory. Those files can contain your site's or the package's own Autoconf macro definitions (see Chapter 9 [Writing Autoconf Macros], page 145, for more information). If a macro is defined in more than one of the files that `autoconf` reads, the last definition it reads overrides the earlier ones.

autoconf accepts the following options:

'--help'
'-h' Print a summary of the command line options and exit.

'--version'
'-V' Print the version number of Autoconf and exit.

'--verbose'
'-v' Report processing steps.

'--debug'
'-d' Don't remove the temporary files.

'--force'
'-f' Remake 'configure' even if newer than its input files.

'--include=*dir*'
'-I *dir*' Append *dir* to the include path. Multiple invocations accumulate.

'--prepend-include=*dir*'
'-B *dir*' Prepend *dir* to the include path. Multiple invocations accumulate.

'--output=*file*'
'-o *file*' Save output (script or trace) to *file*. The file '-' stands for the standard output.

'--warnings=*category*'
'-W *category*'
Report the warnings related to *category* (which can actually be a comma separated list). See Section 9.3 [Reporting Messages], page 147, macro AC_DIAGNOSE, for a comprehensive list of categories. Special values include:

'all' report all the warnings

'none' report none

'error' treats warnings as errors

'no-*category*'
disable warnings falling into *category*

Warnings about 'syntax' are enabled by default, and the environment variable WARNINGS, a comma separated list of categories, is honored as well. Passing '-W *category*' actually behaves as if you had passed '--warnings syntax,$WARNINGS,*category*'. If you want to disable the defaults and WARNINGS, but (for example) enable the warnings about obsolete constructs, you would use '-W none,obsolete'.

Because autoconf uses autom4te behind the scenes, it displays a back trace for errors, but not for warnings; if you want them, just pass '-W error'. See Section 8.2.1 [autom4te Invocation], page 120, for some examples.

'--trace=*macro*[:*format*]'
'-t *macro*[:*format*]'
Do not create the configure script, but list the calls to *macro* according to the *format*. Multiple '--trace' arguments can be used to list several macros.

Multiple '`--trace`' arguments for a single macro are not cumulative; instead, you should just make *format* as long as needed.

The *format* is a regular string, with newlines if desired, and several special escape codes. It defaults to '`$f:$l:$n:$%`'; see Section 8.2.1 [autom4te Invocation], page 120, for details on the *format*.

'`--initialization`'
'`-i`' By default, '`--trace`' does not trace the initialization of the Autoconf macros (typically the `AC_DEFUN` definitions). This results in a noticeable speedup, but can be disabled by this option.

It is often necessary to check the content of a '`configure.ac`' file, but parsing it yourself is extremely fragile and error-prone. It is suggested that you rely upon '`--trace`' to scan '`configure.ac`'. For instance, to find the list of variables that are substituted, use:

```
$ autoconf -t AC_SUBST
configure.ac:2:AC_SUBST:ECHO_C
configure.ac:2:AC_SUBST:ECHO_N
configure.ac:2:AC_SUBST:ECHO_T
More traces deleted
```

The example below highlights the difference between '`$@`', '`$*`', and '`$%`'.

```
$ cat configure.ac
AC_DEFINE(This, is, [an
[example]])
$ autoconf -t 'AC_DEFINE:@: $@
*: $*
%: $%'
@: [This],[is],[an
[example]]
*: This,is,an
[example]
%: This:is:an [example]
```

The *format* gives you a lot of freedom:

```
$ autoconf -t 'AC_SUBST:$$ac_subst{"$1"} = "$f:$l";'
$ac_subst{"ECHO_C"} = "configure.ac:2";
$ac_subst{"ECHO_N"} = "configure.ac:2";
$ac_subst{"ECHO_T"} = "configure.ac:2";
More traces deleted
```

A long *separator* can be used to improve the readability of complex structures, and to ease their parsing (for instance when no single character is suitable as a separator):

```
$ autoconf -t 'AM_MISSING_PROG:${|:::::|}*'
ACLOCAL|:::::|aclocal|:::::|$missing_dir
AUTOCONF|:::::|autoconf|:::::|$missing_dir
AUTOMAKE|:::::|automake|:::::|$missing_dir
More traces deleted
```

3.5 Using autoreconf to Update configure Scripts

Installing the various components of the GNU Build System can be tedious: running autopoint for Gettext, automake for 'Makefile.in' etc. in each directory. It may be needed either because some tools such as automake have been updated on your system, or because some of the sources such as 'configure.ac' have been updated, or finally, simply in order to install the GNU Build System in a fresh tree.

autoreconf runs autoconf, autoheader, aclocal, automake, libtoolize, and autopoint (when appropriate) repeatedly to update the GNU Build System in the specified directories and their subdirectories (see Section 4.12 [Subdirectories], page 37). By default, it only remakes those files that are older than their sources. The environment variables AUTOCONF, AUTOHEADER, AUTOMAKE, ACLOCAL, AUTOPOINT, LIBTOOLIZE, M4, and MAKE may be used to override the invocation of the respective tools.

If you install a new version of some tool, you can make autoreconf remake *all* of the files by giving it the '--force' option.

See Section 4.8.5 [Automatic Remaking], page 31, for Make rules to automatically rebuild configure scripts when their source files change. That method handles the timestamps of configuration header templates properly, but does not pass '--autoconf-dir=*dir*' or '--localdir=*dir*'.

Gettext supplies the autopoint command to add translation infrastructure to a source package. If you use autopoint, your 'configure.ac' should invoke both AM_GNU_GETTEXT and AM_GNU_GETTEXT_VERSION(*gettext-version*). See section "Invoking the autopoint Program" in *GNU* gettext *utilities*, for further details.

autoreconf accepts the following options:

'--help'
'-h' Print a summary of the command line options and exit.

'--version'
'-V' Print the version number of Autoconf and exit.

'--verbose'
Print the name of each directory autoreconf examines and the commands it runs. If given two or more times, pass '--verbose' to subordinate tools that support it.

'--debug'
'-d' Don't remove the temporary files.

'--force'
'-f' Remake even 'configure' scripts and configuration headers that are newer than their input files ('configure.ac' and, if present, 'aclocal.m4').

'--install'
'-i' Install the missing auxiliary files in the package. By default, files are copied; this can be changed with '--symlink'.

If deemed appropriate, this option triggers calls to 'automake --add-missing', 'libtoolize', 'autopoint', etc.

'`--no-recursive`'
: Do not rebuild files in subdirectories to configure (see Section 4.12 [Subdirectories], page 37, macro `AC_CONFIG_SUBDIRS`).

'`--symlink`'
'`-s`'
: When used with '`--install`', install symbolic links to the missing auxiliary files instead of copying them.

'`--make`'
'`-m`'
: When the directories were configured, update the configuration by running '`./config.status --recheck && ./config.status`', and then run '`make`'.

'`--include=dir`'
'`-I dir`'
: Append *dir* to the include path. Multiple invocations accumulate. Passed on to `autoconf` and `autoheader` internally.

'`--prepend-include=dir`'
'`-B dir`'
: Prepend *dir* to the include path. Multiple invocations accumulate. Passed on to `autoconf` and `autoheader` internally.

'`--warnings=category`'
'`-W category`'
: Report the warnings related to *category* (which can actually be a comma separated list).

  '`cross`' related to cross compilation issues.

  '`obsolete`'
  : report the uses of obsolete constructs.

  '`portability`'
  : portability issues

  '`syntax`' dubious syntactic constructs.

  '`all`' report all the warnings

  '`none`' report none

  '`error`' treats warnings as errors

  '`no-category`'
  : disable warnings falling into *category*

  Warnings about '`syntax`' are enabled by default, and the environment variable `WARNINGS`, a comma separated list of categories, is honored as well. Passing '`-W category`' actually behaves as if you had passed '`--warnings syntax,$WARNINGS,category`'. If you want to disable the defaults and `WARNINGS`, but (for example) enable the warnings about obsolete constructs, you would use '`-W none,obsolete`'.

If you want `autoreconf` to pass flags that are not listed here on to `aclocal`, set `ACLOCAL_AMFLAGS` in your '`Makefile.am`'. Due to a limitation in the Autoconf implementation these flags currently must be set on a single line in '`Makefile.am`', without any backslash-newlines.

4 Initialization and Output Files

Autoconf-generated `configure` scripts need some information about how to initialize, such as how to find the package's source files and about the output files to produce. The following sections describe the initialization and the creation of output files.

4.1 Initializing `configure`

Every `configure` script must call `AC_INIT` before doing anything else. The only other required macro is `AC_OUTPUT` (see Section 4.5 [Output], page 20).

`AC_INIT` (*package*, *version*, [*bug-report*], [*tarname*]) [Macro]

Process any command-line arguments and perform various initializations and verifications.

Set the name of the *package* and its *version*. These are typically used in '`--version`' support, including that of `configure`. The optional argument *bug-report* should be the email to which users should send bug reports. The package *tarname* differs from *package*: the latter designates the full package name (e.g., '`GNU Autoconf`'), while the former is meant for distribution tar ball names (e.g., '`autoconf`'). It defaults to *package* with '`GNU `' stripped, lower-cased, and all characters other than alphanumerics and underscores are changed to '`-`'.

It is preferable that the arguments of `AC_INIT` be static, i.e., there should not be any shell computation, but they can be computed by M4.

The following M4 macros (e.g., `AC_PACKAGE_NAME`), output variables (e.g., `PACKAGE_NAME`), and preprocessor symbols (e.g., `PACKAGE_NAME`), are defined by `AC_INIT`:

`AC_PACKAGE_NAME`, `PACKAGE_NAME`
: Exactly *package*.

`AC_PACKAGE_TARNAME`, `PACKAGE_TARNAME`
: Exactly *tarname*.

`AC_PACKAGE_VERSION`, `PACKAGE_VERSION`
: Exactly *version*.

`AC_PACKAGE_STRING`, `PACKAGE_STRING`
: Exactly '*package version*'.

`AC_PACKAGE_BUGREPORT`, `PACKAGE_BUGREPORT`
: Exactly *bug-report*.

If your `configure` script does its own option processing, it should inspect '`$@`' or '`$*`' immediately after calling `AC_INIT`, because other Autoconf macros liberally use the `set` command to process strings, and this has the side effect of updating '`$@`' and '`$*`'. However, we suggest that you use standard macros like `AC_ARG_ENABLE` instead of attempting to implement your own option processing. See Chapter 14 [Site Configuration], page 225.

4.2 Dealing with Autoconf versions

The following optional macros can be used to help choose the minimum version of Autoconf that can successfully compile a given 'configure.ac'.

AC_PREREQ (*version*) [Macro]

Ensure that a recent enough version of Autoconf is being used. If the version of Autoconf being used to create configure is earlier than *version*, print an error message to the standard error output and exit with failure (exit status is 63). For example:

```
AC_PREREQ([2.62])
```

This macro is the only macro that may be used before AC_INIT, but for consistency, you are invited not to do so.

AC_AUTOCONF_VERSION [Macro]

This macro was introduced in Autoconf 2.62. It identifies the version of Autoconf that is currently parsing the input file, in a format suitable for m4_version_compare (see [m4_version_compare], page 140); in other words, for this release of Autoconf, its value is '2.62'. One potential use of this macro is for writing conditional fallbacks based on when a feature was added to Autoconf, rather than using AC_PREREQ to require the newer version of Autoconf. However, remember that the Autoconf philosophy favors feature checks over version checks.

4.3 Notices in configure

The following macros manage version numbers for configure scripts. Using them is optional.

AC_COPYRIGHT (*copyright-notice*) [Macro]

State that, in addition to the Free Software Foundation's copyright on the Autoconf macros, parts of your configure are covered by the *copyright-notice*.

The *copyright-notice* shows up in both the head of configure and in 'configure --version'.

AC_REVISION (*revision-info*) [Macro]

Copy revision stamp *revision-info* into the configure script, with any dollar signs or double-quotes removed. This macro lets you put a revision stamp from 'configure.ac' into configure without RCS or CVS changing it when you check in configure. That way, you can determine easily which revision of 'configure.ac' a particular configure corresponds to.

For example, this line in 'configure.ac':

```
AC_REVISION([$Revision: 1.30 $])
```

produces this in configure:

```
#!/bin/sh
# From configure.ac Revision: 1.30
```

4.4 Finding `configure` Input

`AC_CONFIG_SRCDIR (unique-file-in-source-dir)` [Macro]

unique-file-in-source-dir is some file that is in the package's source directory; `configure` checks for this file's existence to make sure that the directory that it is told contains the source code in fact does. Occasionally people accidentally specify the wrong directory with '`--srcdir`'; this is a safety check. See Section 15.9 [configure Invocation], page 237, for more information.

Packages that do manual configuration or use the `install` program might need to tell `configure` where to find some other shell scripts by calling `AC_CONFIG_AUX_DIR`, though the default places it looks are correct for most cases.

`AC_CONFIG_AUX_DIR (dir)` [Macro]

Use the auxiliary build tools (e.g., '`install-sh`', '`config.sub`', '`config.guess`', Cygnus `configure`, Automake and Libtool scripts, etc.) that are in directory *dir*. These are auxiliary files used in configuration. *dir* can be either absolute or relative to '*`srcdir`*'. The default is '*`srcdir`*' or '*`srcdir/..`*' or '*`srcdir/../..`*', whichever is the first that contains '`install-sh`'. The other files are not checked for, so that using `AC_PROG_INSTALL` does not automatically require distributing the other auxiliary files. It checks for '`install.sh`' also, but that name is obsolete because some `make` have a rule that creates '`install`' from it if there is no makefile.

The auxiliary directory is commonly named '`build-aux`'. If you need portability to DOS variants, do not name the auxiliary directory '`aux`'. See Section 10.4 [File System Conventions], page 160.

`AC_REQUIRE_AUX_FILE (file)` [Macro]

Declares that *file* is expected in the directory defined above. In Autoconf proper, this macro does nothing: its sole purpose is to be traced by third-party tools to produce a list of expected auxiliary files. For instance it is called by macros like `AC_PROG_INSTALL` (see Section 5.2.1 [Particular Programs], page 41) or `AC_CANONICAL_BUILD` (see Section 13.2 [Canonicalizing], page 222) to register the auxiliary files they need.

Similarly, packages that use `aclocal` should declare where local macros can be found using `AC_CONFIG_MACRO_DIR`.

`AC_CONFIG_MACRO_DIR (dir)` [Macro]

Specify *dir* as the location of additional local Autoconf macros. This macro is intended for use by future versions of commands like `autoreconf` that trace macro calls. It should be called directly from '`configure.ac`' so that tools that install macros for `aclocal` can find the macros' declarations.

Note that if you use `aclocal` from Automake to generate '`aclocal.m4`', you must also set `ACLOCAL_AMFLAGS = -I dir` in your top-level '`Makefile.am`'. Due to a limitation in the Autoconf implementation of `autoreconf`, these include directives currently must be set on a single line in '`Makefile.am`', without any backslash-newlines.

4.5 Outputting Files

Every Autoconf script, e.g., 'configure.ac', should finish by calling AC_OUTPUT. That is the macro that generates and runs 'config.status', which in turn creates the makefiles and any other files resulting from configuration. This is the only required macro besides AC_INIT (see Section 4.4 [Input], page 19).

AC_OUTPUT [Macro]

Generate 'config.status' and launch it. Call this macro once, at the end of 'configure.ac'.

'config.status' performs all the configuration actions: all the output files (see Section 4.7 [Configuration Files], page 22, macro AC_CONFIG_FILES), header files (see Section 4.9 [Configuration Headers], page 32, macro AC_CONFIG_HEADERS), commands (see Section 4.10 [Configuration Commands], page 35, macro AC_CONFIG_COMMANDS), links (see Section 4.11 [Configuration Links], page 36, macro AC_CONFIG_LINKS), subdirectories to configure (see Section 4.12 [Subdirectories], page 37, macro AC_CONFIG_SUBDIRS) are honored.

The location of your AC_OUTPUT invocation is the exact point where configuration actions are taken: any code afterwards is executed by configure once config.status was run. If you want to bind actions to config.status itself (independently of whether configure is being run), see Section 4.10 [Running Arbitrary Configuration Commands], page 35.

Historically, the usage of AC_OUTPUT was somewhat different. See Section 17.4 [Obsolete Macros], page 243, for a description of the arguments that AC_OUTPUT used to support.

If you run make in subdirectories, you should run it using the make variable MAKE. Most versions of make set MAKE to the name of the make program plus any options it was given. (But many do not include in it the values of any variables set on the command line, so those are not passed on automatically.) Some old versions of make do not set this variable. The following macro allows you to use it even with those versions.

AC_PROG_MAKE_SET [Macro]

If the Make command, $MAKE if set or else 'make', predefines $(MAKE), define output variable SET_MAKE to be empty. Otherwise, define SET_MAKE to a macro definition that sets $(MAKE), such as 'MAKE=make'. Calls AC_SUBST for SET_MAKE.

If you use this macro, place a line like this in each 'Makefile.in' that runs MAKE on other directories:

```
@SET_MAKE@
```

4.6 Performing Configuration Actions

'configure' is designed so that it appears to do everything itself, but there is actually a hidden slave: 'config.status'. 'configure' is in charge of examining your system, but it is 'config.status' that actually takes the proper actions based on the results of 'configure'. The most typical task of 'config.status' is to *instantiate* files.

This section describes the common behavior of the four standard instantiating macros: AC_CONFIG_FILES, AC_CONFIG_HEADERS, AC_CONFIG_COMMANDS and AC_CONFIG_LINKS. They all have this prototype:

`AC_CONFIG_FOOS(tag..., [commands], [init-cmds])`

where the arguments are:

tag... A blank-or-newline-separated list of tags, which are typically the names of the files to instantiate.

You are encouraged to use literals as *tags*. In particular, you should avoid

```
... && my_foos="$my_foos fooo"
... && my_foos="$my_foos foooo"
AC_CONFIG_FOOS([$my_foos])
```

and use this instead:

```
... && AC_CONFIG_FOOS([fooo])
... && AC_CONFIG_FOOS([foooo])
```

The macros `AC_CONFIG_FILES` and `AC_CONFIG_HEADERS` use special *tag* values: they may have the form '*output*' or '*output*:*inputs*'. The file *output* is instantiated from its templates, *inputs* (defaulting to '*output*.in').

'`AC_CONFIG_FILES([Makefile:boiler/top.mk:boiler/bot.mk)]`', for example, asks for the creation of the file '`Makefile`' that contains the expansion of the output variables in the concatenation of '`boiler/top.mk`' and '`boiler/bot.mk`'.

The special value '`-`' might be used to denote the standard output when used in *output*, or the standard input when used in the *inputs*. You most probably don't need to use this in '`configure.ac`', but it is convenient when using the command line interface of '`./config.status`', see Chapter 16 [config.status Invocation], page 239, for more details.

The *inputs* may be absolute or relative file names. In the latter case they are first looked for in the build tree, and then in the source tree.

commands

Shell commands output literally into '`config.status`', and associated with a tag that the user can use to tell '`config.status`' which the commands to run. The commands are run each time a *tag* request is given to '`config.status`', typically each time the file '*tag*' is created.

The variables set during the execution of `configure` are *not* available here: you first need to set them via the *init-cmds*. Nonetheless the following variables are precomputed:

`srcdir` The name of the top source directory, assuming that the working directory is the top build directory. This is what the `configure` option '`--srcdir`' sets.

`ac_top_srcdir`
The name of the top source directory, assuming that the working directory is the current build directory.

`ac_top_build_prefix`
The name of the top build directory, assuming that the working directory is the current build directory. It can be empty, or else ends with a slash, so that you may concatenate it.

`ac_srcdir`
: The name of the corresponding source directory, assuming that the working directory is the current build directory.

The *current* directory refers to the directory (or pseudo-directory) containing the input part of *tags*. For instance, running

```
AC_CONFIG_COMMANDS([deep/dir/out:in/in.in], [...], [...])
```

with '`--srcdir=../package`' produces the following values:

```
# Argument of --srcdir
srcdir='../package'
# Reversing deep/dir
ac_top_build_prefix='../../'
# Concatenation of $ac_top_build_prefix and srcdir
ac_top_srcdir='../../../package'
# Concatenation of $ac_top_srcdir and deep/dir
ac_srcdir='../../../package/deep/dir'
```

independently of '`in/in.in`'.

init-cmds
: Shell commands output *unquoted* near the beginning of '`config.status`', and executed each time '`config.status`' runs (regardless of the tag). Because they are unquoted, for example, '`$var`' is output as the value of `var`. *init-cmds* is typically used by '`configure`' to give '`config.status`' some variables it needs to run the *commands*.

You should be extremely cautious in your variable names: all the *init-cmds* share the same name space and may overwrite each other in unpredictable ways. Sorry...

All these macros can be called multiple times, with different *tag* values, of course!

4.7 Creating Configuration Files

Be sure to read the previous section, Section 4.6 [Configuration Actions], page 20.

`AC_CONFIG_FILES` (*file...*, [*cmds*], [*init-cmds*]) [Macro]

Make `AC_OUTPUT` create each '*file*' by copying an input file (by default '*file*`.in`'), substituting the output variable values. This macro is one of the instantiating macros; see Section 4.6 [Configuration Actions], page 20. See Section 4.8 [Makefile Substitutions], page 23, for more information on using output variables. See Section 7.2 [Setting Output Variables], page 104, for more information on creating them. This macro creates the directory that the file is in if it doesn't exist. Usually, makefiles are created this way, but other files, such as '`.gdbinit`', can be specified as well.

Typical calls to `AC_CONFIG_FILES` look like this:

```
AC_CONFIG_FILES([Makefile src/Makefile man/Makefile X/Imakefile])
AC_CONFIG_FILES([autoconf], [chmod +x autoconf])
```

You can override an input file name by appending to *file* a colon-separated list of input files. Examples:

```
AC_CONFIG_FILES([Makefile:boiler/top.mk:boiler/bot.mk]
```

```
[lib/Makefile:boiler/lib.mk])
```

Doing this allows you to keep your file names acceptable to DOS variants, or to prepend and/or append boilerplate to the file.

4.8 Substitutions in Makefiles

Each subdirectory in a distribution that contains something to be compiled or installed should come with a file '`Makefile.in`', from which `configure` creates a file '`Makefile`' in that directory. To create '`Makefile`', `configure` performs a simple variable substitution, replacing occurrences of '`@variable@`' in '`Makefile.in`' with the value that `configure` has determined for that variable. Variables that are substituted into output files in this way are called *output variables*. They are ordinary shell variables that are set in `configure`. To make `configure` substitute a particular variable into the output files, the macro `AC_SUBST` must be called with that variable name as an argument. Any occurrences of '`@variable@`' for other variables are left unchanged. See Section 7.2 [Setting Output Variables], page 104, for more information on creating output variables with `AC_SUBST`.

A software package that uses a `configure` script should be distributed with a file '`Makefile.in`', but no makefile; that way, the user has to properly configure the package for the local system before compiling it.

See section "Makefile Conventions" in *The GNU Coding Standards*, for more information on what to put in makefiles.

4.8.1 Preset Output Variables

Some output variables are preset by the Autoconf macros. Some of the Autoconf macros set additional output variables, which are mentioned in the descriptions for those macros. See Section B.2 [Output Variable Index], page 289, for a complete list of output variables. See Section 4.8.2 [Installation Directory Variables], page 26, for the list of the preset ones related to installation directories. Below are listed the other preset ones. They all are precious variables (see Section 7.2 [Setting Output Variables], page 104, `AC_ARG_VAR`).

`CFLAGS` [Variable]

Debugging and optimization options for the C compiler. If it is not set in the environment when `configure` runs, the default value is set when you call `AC_PROG_CC` (or empty if you don't). `configure` uses this variable when compiling or linking programs to test for C features.

If a compiler option affects only the behavior of the preprocessor (e.g., '`-D name`'), it should be put into `CPPFLAGS` instead. If it affects only the linker (e.g., '`-L directory`'), it should be put into `LDFLAGS` instead. If it affects only the compiler proper, `CFLAGS` is the natural home for it. If an option affects multiple phases of the compiler, though, matters get tricky. One approach to put such options directly into `CC`, e.g., `CC='gcc -m64'`. Another is to put them into both `CPPFLAGS` and `LDFLAGS`, but not into `CFLAGS`.

`configure_input` [Variable]

A comment saying that the file was generated automatically by `configure` and giving the name of the input file. `AC_OUTPUT` adds a comment line containing this variable to the top of every makefile it creates. For other files, you should reference this variable

in a comment at the top of each input file. For example, an input shell script should begin like this:

```
#!/bin/sh
# @configure_input@
```

The presence of that line also reminds people editing the file that it needs to be processed by `configure` in order to be used.

`CPPFLAGS` [Variable]

Preprocessor options for the C, C++, and Objective C preprocessors and compilers. If it is not set in the environment when `configure` runs, the default value is empty. `configure` uses this variable when preprocessing or compiling programs to test for C, C++, and Objective C features.

This variable's contents should contain options like '`-I`', '`-D`', and '`-U`' that affect only the behavior of the preprocessor. Please see the explanation of `CFLAGS` for what you can do if an option affects other phases of the compiler as well.

Currently, `configure` always links as part of a single invocation of the compiler that also preprocesses and compiles, so it uses this variable also when linking programs. However, it is unwise to depend on this behavior because the GNU coding standards do not require it and many packages do not use `CPPFLAGS` when linking programs.

See Section 7.3 [Special Chars in Variables], page 106, for limitations that `CPPFLAGS` might run into.

`CXXFLAGS` [Variable]

Debugging and optimization options for the C++ compiler. It acts like `CFLAGS`, but for C++ instead of C.

`DEFS` [Variable]

'`-D`' options to pass to the C compiler. If `AC_CONFIG_HEADERS` is called, `configure` replaces '`@DEFS@`' with '`-DHAVE_CONFIG_H`' instead (see Section 4.9 [Configuration Headers], page 32). This variable is not defined while `configure` is performing its tests, only when creating the output files. See Section 7.2 [Setting Output Variables], page 104, for how to check the results of previous tests.

`ECHO_C` [Variable]
`ECHO_N` [Variable]
`ECHO_T` [Variable]

How does one suppress the trailing newline from `echo` for question-answer message pairs? These variables provide a way:

```
echo $ECHO_N "And the winner is... $ECHO_C"
sleep 100000000000
echo "${ECHO_T}dead."
```

Some old and uncommon `echo` implementations offer no means to achieve this, in which case `ECHO_T` is set to tab. You might not want to use it.

`ERLCFLAGS` [Variable]

Debugging and optimization options for the Erlang compiler. If it is not set in the environment when `configure` runs, the default value is empty. `configure` uses this variable when compiling programs to test for Erlang features.

`FCFLAGS` [Variable]

Debugging and optimization options for the Fortran compiler. If it is not set in the environment when `configure` runs, the default value is set when you call `AC_PROG_FC` (or empty if you don't). `configure` uses this variable when compiling or linking programs to test for Fortran features.

`FFLAGS` [Variable]

Debugging and optimization options for the Fortran 77 compiler. If it is not set in the environment when `configure` runs, the default value is set when you call `AC_PROG_F77` (or empty if you don't). `configure` uses this variable when compiling or linking programs to test for Fortran 77 features.

`LDFLAGS` [Variable]

Options for the linker. If it is not set in the environment when `configure` runs, the default value is empty. `configure` uses this variable when linking programs to test for C, C++, Objective C, and Fortran features.

This variable's contents should contain options like '`-s`' and '`-L`' that affect only the behavior of the linker. Please see the explanation of `CFLAGS` for what you can do if an option also affects other phases of the compiler.

Don't use this variable to pass library names ('`-l`') to the linker; use `LIBS` instead.

`LIBS` [Variable]

'`-l`' options to pass to the linker. The default value is empty, but some Autoconf macros may prepend extra libraries to this variable if those libraries are found and provide necessary functions, see Section 5.4 [Libraries], page 46. `configure` uses this variable when linking programs to test for C, C++, and Fortran features.

`OBJCFLAGS` [Variable]

Debugging and optimization options for the Objective C compiler. It acts like `CFLAGS`, but for Objective C instead of C.

`builddir` [Variable]

Rigorously equal to '`.`'. Added for symmetry only.

`abs_builddir` [Variable]

Absolute name of `builddir`.

`top_builddir` [Variable]

The relative name of the top level of the current build tree. In the top-level directory, this is the same as `builddir`.

`top_build_prefix` [Variable]

The relative name of the top level of the current build tree with final slash if nonemtpy. This is the same as `top_builddir`, except that it contains of zero of more runs of `../`, so it should not be appended with a slash for concatenation. This helps for `make` implementations that otherwise do not treat '`./file`' and '`file`' as equal in the toplevel build directory.

`abs_top_builddir` [Variable]

Absolute name of `top_builddir`.

`srcdir` [Variable]
The name of the directory that contains the source code for that makefile.

`abs_srcdir` [Variable]
Absolute name of `srcdir`.

`top_srcdir` [Variable]
The name of the top-level source code directory for the package. In the top-level directory, this is the same as `srcdir`.

`abs_top_srcdir` [Variable]
Absolute name of `top_srcdir`.

4.8.2 Installation Directory Variables

The following variables specify the directories for package installation, see section "Variables for Installation Directories" in *The GNU Coding Standards*, for more information. Each variable corresponds to an argument of `configure`; trailing slashes are stripped so that expressions such as '`${prefix}/lib`' expand with only one slash between directory names. See the end of this section for details on when and how to use these variables.

`bindir` [Variable]
The directory for installing executables that users run.

`datadir` [Variable]
The directory for installing idiosyncratic read-only architecture-independent data.

`datarootdir` [Variable]
The root of the directory tree for read-only architecture-independent data files.

`docdir` [Variable]
The directory for installing documentation files (other than Info and man).

`dvidir` [Variable]
The directory for installing documentation files in DVI format.

`exec_prefix` [Variable]
The installation prefix for architecture-dependent files. By default it's the same as *prefix*. You should avoid installing anything directly to *exec_prefix*. However, the default value for directories containing architecture-dependent files should be relative to *exec_prefix*.

`htmldir` [Variable]
The directory for installing HTML documentation.

`includedir` [Variable]
The directory for installing C header files.

`infodir` [Variable]
The directory for installing documentation in Info format.

`libdir` [Variable]
The directory for installing object code libraries.

`libexecdir` [Variable]
The directory for installing executables that other programs run.

`localedir` [Variable]
The directory for installing locale-dependent but architecture-independent data, such as message catalogs. This directory usually has a subdirectory per locale.

`localstatedir` [Variable]
The directory for installing modifiable single-machine data.

`mandir` [Variable]
The top-level directory for installing documentation in man format.

`oldincludedir` [Variable]
The directory for installing C header files for non-GCC compilers.

`pdfdir` [Variable]
The directory for installing PDF documentation.

`prefix` [Variable]
The common installation prefix for all files. If *exec_prefix* is defined to a different value, *prefix* is used only for architecture-independent files.

`psdir` [Variable]
The directory for installing PostScript documentation.

`sbindir` [Variable]
The directory for installing executables that system administrators run.

`sharedstatedir` [Variable]
The directory for installing modifiable architecture-independent data.

`sysconfdir` [Variable]
The directory for installing read-only single-machine data.

Most of these variables have values that rely on `prefix` or `exec_prefix`. It is deliberate that the directory output variables keep them unexpanded: typically '`@datarootdir@`' is replaced by '`${prefix}/share`', not '`/usr/local/share`', and '`@datadir@`' is replaced by '`${datarootdir}`'.

This behavior is mandated by the GNU coding standards, so that when the user runs:

'`make`' she can still specify a different prefix from the one specified to `configure`, in which case, if needed, the package should hard code dependencies corresponding to the make-specified prefix.

'`make install`'
she can specify a different installation location, in which case the package *must* still depend on the location which was compiled in (i.e., never recompile when '`make install`' is run). This is an extremely important feature, as many people may decide to install all the files of a package grouped together, and then install links from the final locations to there.

In order to support these features, it is essential that `datarootdir` remains being defined as '`${prefix}/share`' to depend upon the current value of `prefix`.

A corollary is that you should not use these variables except in makefiles. For instance, instead of trying to evaluate `datadir` in '`configure`' and hard-coding it in makefiles using e.g., '`AC_DEFINE_UNQUOTED([DATADIR], ["$datadir"], [Data directory.])`', you should add '`-DDATADIR='$(datadir)''` to your makefile's definition of `CPPFLAGS` (`AM_CPPFLAGS` if you are also using Automake).

Similarly, you should not rely on `AC_CONFIG_FILES` to replace `datadir` and friends in your shell scripts and other files; instead, let `make` manage their replacement. For instance Autoconf ships templates of its shell scripts ending with '`.in`', and uses a makefile snippet similar to the following to build scripts like `autoheader` and `autom4te`:

```
edit = sed \
        -e 's|@datadir[@]|$(pkgdatadir)|g' \
        -e 's|@prefix[@]|$(prefix)|g'

autoheader autom4te: Makefile
        rm -f $@ $@.tmp
        $(edit) '$(srcdir)/$@.in' >$@.tmp
        chmod +x $@.tmp
        chmod a-w $@.tmp
        mv $@.tmp $@

autoheader: $(srcdir)/autoheader.in
autom4te: $(srcdir)/autom4te.in
```

Some details are noteworthy:

'`@datadir[@]`'
: The brackets prevent `configure` from replacing '`@datadir@`' in the Sed expression itself. Brackets are preferable to a backslash here, since Posix says '`\@`' is not portable.

'`$(pkgdatadir)`'
: Don't use '`@pkgdatadir@`'! Use the matching makefile variable instead.

'`/`'
: Don't use '`/`' in the Sed expressions that replace file names since most likely the variables you use, such as '`$(pkgdatadir)`', contain '`/`'. Use a shell metacharacter instead, such as '`|`'.

special characters
: File names, file name components, and the value of `VPATH` should not contain shell metacharacters or white space. See Section 7.3 [Special Chars in Variables], page 106.

dependency on '`Makefile`'
: Since `edit` uses values that depend on the configuration specific values (`prefix`, etc.) and not only on `VERSION` and so forth, the output depends on '`Makefile`', not '`configure.ac`'.

'`$@`'
: The main rule is generic, and uses '`$@`' extensively to avoid the need for multiple copies of the rule.

Separated dependencies and single suffix rules

You can't use them! The above snippet cannot be (portably) rewritten as:

```
autoconf autoheader: Makefile
.in:
        rm -f $@ $@.tmp
        $(edit) $< >$@.tmp
        chmod +x $@.tmp
        mv $@.tmp $@
```

See Section 11.14 [Single Suffix Rules], page 207, for details.

'`$(srcdir)`'

Be sure to specify the name of the source directory, otherwise the package won't support separated builds.

For the more specific installation of Erlang libraries, the following variables are defined:

`ERLANG_INSTALL_LIB_DIR` [Variable]

The common parent directory of Erlang library installation directories. This variable is set by calling the `AC_ERLANG_SUBST_INSTALL_LIB_DIR` macro in '`configure.ac`'.

`ERLANG_INSTALL_LIB_DIR_`*`library`* [Variable]

The installation directory for Erlang library *library*. This variable is set by calling the '`AC_ERLANG_SUBST_INSTALL_LIB_SUBDIR(`*`library, version`*' macro in '`configure.ac`'.

See Section 5.13 [Erlang Libraries], page 88, for details.

4.8.3 Changed Directory Variables

In Autoconf 2.60, the set of directory variables has changed, and the defaults of some variables have been adjusted (see Section 4.8.2 [Installation Directory Variables], page 26) to changes in the GNU Coding Standards. Notably, '`datadir`', '`infodir`', and '`mandir`' are now expressed in terms of '`datarootdir`'. If you are upgrading from an earlier Autoconf version, you may need to adjust your files to ensure that the directory variables are substituted correctly (see Section 19.5 [Defining Directories], page 273), and that a definition of '`datarootdir`' is in place. For example, in a '`Makefile.in`', adding

```
datarootdir = @datarootdir@
```

is usually sufficient. If you use Automake to create '`Makefile.in`', it will add this for you.

To help with the transition, Autoconf warns about files that seem to use `datarootdir` without defining it. In some cases, it then expands the value of `$datarootdir` in substitutions of the directory variables. The following example shows such a warning:

```
$ cat configure.ac
AC_INIT
AC_CONFIG_FILES([Makefile])
AC_OUTPUT
$ cat Makefile.in
prefix = @prefix@
datadir = @datadir@
```

```
$ autoconf
$ configure
configure: creating ./config.status
config.status: creating Makefile
config.status: WARNING:
               Makefile.in seems to ignore the --datarootdir setting
$ cat Makefile
prefix = /usr/local
datadir = ${prefix}/share
```

Usually one can easily change the file to accommodate both older and newer Autoconf releases:

```
$ cat Makefile.in
prefix = @prefix@
datarootdir = @datarootdir@
datadir = @datadir@
$ configure
configure: creating ./config.status
config.status: creating Makefile
$ cat Makefile
prefix = /usr/local
datarootdir = ${prefix}/share
datadir = ${datarootdir}
```

In some cases, however, the checks may not be able to detect that a suitable initialization of `datarootdir` is in place, or they may fail to detect that such an initialization is necessary in the output file. If, after auditing your package, there are still spurious '`configure`' warnings about `datarootdir`, you may add the line

```
AC_DEFUN([AC_DATAROOTDIR_CHECKED])
```

to your '`configure.ac`' to disable the warnings. This is an exception to the usual rule that you should not define a macro whose name begins with `AC_` (see Section 9.2 [Macro Names], page 145).

4.8.4 Build Directories

You can support compiling a software package for several architectures simultaneously from the same copy of the source code. The object files for each architecture are kept in their own directory.

To support doing this, `make` uses the `VPATH` variable to find the files that are in the source directory. GNU Make can do this. Most other recent `make` programs can do this as well, though they may have difficulties and it is often simpler to recommend GNU `make` (see Section 11.13 [VPATH and Make], page 201). Older `make` programs do not support `VPATH`; when using them, the source code must be in the same directory as the object files.

To support `VPATH`, each '`Makefile.in`' should contain two lines that look like:

```
srcdir = @srcdir@
VPATH = @srcdir@
```

Do not set `VPATH` to the value of another variable, for example '`VPATH = $(srcdir)`', because some versions of `make` do not do variable substitutions on the value of `VPATH`.

`configure` substitutes the correct value for `srcdir` when it produces '`Makefile`'.

Do not use the `make` variable `$<`, which expands to the file name of the file in the source directory (found with `VPATH`), except in implicit rules. (An implicit rule is one such as '`.c.o`', which tells how to create a '`.o`' file from a '`.c`' file.) Some versions of `make` do not set `$<` in explicit rules; they expand it to an empty value.

Instead, Make command lines should always refer to source files by prefixing them with '`$(srcdir)/`'. For example:

```
time.info: time.texinfo
        $(MAKEINFO) '$(srcdir)/time.texinfo'
```

4.8.5 Automatic Remaking

You can put rules like the following in the top-level '`Makefile.in`' for a package to automatically update the configuration information when you change the configuration files. This example includes all of the optional files, such as '`aclocal.m4`' and those related to configuration header files. Omit from the '`Makefile.in`' rules for any of these files that your package does not use.

The '`$(srcdir)/`' prefix is included because of limitations in the `VPATH` mechanism.

The '`stamp-`' files are necessary because the timestamps of '`config.h.in`' and '`config.h`' are not changed if remaking them does not change their contents. This feature avoids unnecessary recompilation. You should include the file '`stamp-h.in`' your package's distribution, so that `make` considers '`config.h.in`' up to date. Don't use `touch` (see Section 10.13 [Limitations of Usual Tools], page 182); instead, use `echo` (using `date` would cause needless differences, hence CVS conflicts, etc.).

```
$(srcdir)/configure: configure.ac aclocal.m4
        cd '$(srcdir)' && autoconf

# autoheader might not change config.h.in, so touch a stamp file.
$(srcdir)/config.h.in: stamp-h.in
$(srcdir)/stamp-h.in: configure.ac aclocal.m4
        cd '$(srcdir)' && autoheader
        echo timestamp > '$(srcdir)/stamp-h.in'

config.h: stamp-h
stamp-h: config.h.in config.status
        ./config.status

Makefile: Makefile.in config.status
        ./config.status

config.status: configure
        ./config.status --recheck
```

(Be careful if you copy these lines directly into your makefile, as you need to convert the indented lines to start with the tab character.)

In addition, you should use

```
AC_CONFIG_FILES([stamp-h], [echo timestamp > stamp-h])
```

so '`config.status`' ensures that '`config.h`' is considered up to date. See Section 4.5 [Output], page 20, for more information about `AC_OUTPUT`.

See Chapter 16 [config.status Invocation], page 239, for more examples of handling configuration-related dependencies.

4.9 Configuration Header Files

When a package contains more than a few tests that define C preprocessor symbols, the command lines to pass '`-D`' options to the compiler can get quite long. This causes two problems. One is that the `make` output is hard to visually scan for errors. More seriously, the command lines can exceed the length limits of some operating systems. As an alternative to passing '`-D`' options to the compiler, `configure` scripts can create a C header file containing '`#define`' directives. The `AC_CONFIG_HEADERS` macro selects this kind of output. Though it can be called anywhere between `AC_INIT` and `AC_OUTPUT`, it is customary to call it right after `AC_INIT`.

The package should '`#include`' the configuration header file before any other header files, to prevent inconsistencies in declarations (for example, if it redefines `const`).

To provide for VPATH builds, remember to pass the C compiler a '`-I.`' option (or '`-I..`'; whichever directory contains '`config.h`'). Even if you use '`#include "config.h"`', the preprocessor searches only the directory of the currently read file, i.e., the source directory, not the build directory.

With the appropriate '`-I`' option, you can use '`#include <config.h>`'. Actually, it's a good habit to use it, because in the rare case when the source directory contains another '`config.h`', the build directory should be searched first.

`AC_CONFIG_HEADERS` (*header* ..., [*cmds*], [*init-cmds*]) [Macro]

This macro is one of the instantiating macros; see Section 4.6 [Configuration Actions], page 20. Make `AC_OUTPUT` create the file(s) in the blank-or-newline-separated list *header* containing C preprocessor `#define` statements, and replace '`@DEFS@`' in generated files with '`-DHAVE_CONFIG_H`' instead of the value of `DEFS`. The usual name for *header* is '`config.h`'.

If *header* already exists and its contents are identical to what `AC_OUTPUT` would put in it, it is left alone. Doing this allows making some changes in the configuration without needlessly causing object files that depend on the header file to be recompiled.

Usually the input file is named '*header*`.in`'; however, you can override the input file name by appending to *header* a colon-separated list of input files. For example, you might need to make the input file name acceptable to DOS variants:

```
AC_CONFIG_HEADERS([config.h:config.hin])
```

`AH_HEADER` [Macro]

This macro is defined as the name of the first declared config header and undefined if no config headers have been declared up to this point. A third-party macro may, for example, require use of a config header without invoking AC_CONFIG_HEADERS twice, like this:

```
AC_CONFIG_COMMANDS_PRE(
        [m4_ifndef([AH_HEADER], [AC_CONFIG_HEADERS([config.h])])])
```

See Section 4.6 [Configuration Actions], page 20, for more details on *header*.

4.9.1 Configuration Header Templates

Your distribution should contain a template file that looks as you want the final header file to look, including comments, with `#undef` statements which are used as hooks. For example, suppose your '`configure.ac`' makes these calls:

```
AC_CONFIG_HEADERS([conf.h])
AC_CHECK_HEADERS([unistd.h])
```

Then you could have code like the following in '`conf.h.in`'. On systems that have '`unistd.h`', `configure` defines '`HAVE_UNISTD_H`' to 1. On other systems, the whole line is commented out (in case the system predefines that symbol).

```
/* Define as 1 if you have unistd.h.  */
#undef HAVE_UNISTD_H
```

Pay attention that '`#undef`' is in the first column, and there is nothing after '`HAVE_UNISTD_H`', not even white space. You can then decode the configuration header using the preprocessor directives:

```
#include <conf.h>

#ifdef HAVE_UNISTD_H
# include <unistd.h>
#else
/* We are in trouble.  */
#endif
```

The use of old form templates, with '`#define`' instead of '`#undef`' is strongly discouraged. Similarly with old templates with comments on the same line as the '`#undef`'. Anyway, putting comments in preprocessor macros has never been a good idea.

Since it is a tedious task to keep a template header up to date, you may use `autoheader` to generate it, see Section 4.9.2 [autoheader Invocation], page 33.

4.9.2 Using `autoheader` to Create '`config.h.in`'

The `autoheader` program can create a template file of C '`#define`' statements for `configure` to use. It searches for the first invocation of `AC_CONFIG_HEADERS` in '`configure`' sources to determine the name of the template. (If the first call of `AC_CONFIG_HEADERS` specifies more than one input file name, `autoheader` uses the first one.)

It is recommended that only one input file is used. If you want to append a boilerplate code, it is preferable to use '`AH_BOTTOM([#include <conf_post.h>])`'. File '`conf_post.h`' is not processed during the configuration then, which make things clearer. Analogically, `AH_TOP` can be used to prepend a boilerplate code.

In order to do its job, `autoheader` needs you to document all of the symbols that you might use. Typically this is done via an `AC_DEFINE` or `AC_DEFINE_UNQUOTED` call whose first argument is a literal symbol and whose third argument describes the symbol (see Section 7.1 [Defining Symbols], page 103). Alternatively, you can use `AH_TEMPLATE` (see Section 4.9.3 [Autoheader Macros], page 35), or you can supply a suitable input file for a subsequent configuration header file. Symbols defined by Autoconf's builtin tests are already documented properly; you need to document only those that you define yourself.

You might wonder why `autoheader` is needed: after all, why would `configure` need to "patch" a '`config.h.in`' to produce a '`config.h`' instead of just creating '`config.h`' from scratch? Well, when everything rocks, the answer is just that we are wasting our time maintaining `autoheader`: generating '`config.h`' directly is all that is needed. When things go wrong, however, you'll be thankful for the existence of `autoheader`.

The fact that the symbols are documented is important in order to *check* that '`config.h`' makes sense. The fact that there is a well-defined list of symbols that should be defined (or not) is also important for people who are porting packages to environments where `configure` cannot be run: they just have to *fill in the blanks*.

But let's come back to the point: the invocation of `autoheader`...

If you give `autoheader` an argument, it uses that file instead of '`configure.ac`' and writes the header file to the standard output instead of to '`config.h.in`'. If you give `autoheader` an argument of '`-`', it reads the standard input instead of '`configure.ac`' and writes the header file to the standard output.

`autoheader` accepts the following options:

'`--help`'
'`-h`' Print a summary of the command line options and exit.

'`--version`'
'`-V`' Print the version number of Autoconf and exit.

'`--verbose`'
'`-v`' Report processing steps.

'`--debug`'
'`-d`' Don't remove the temporary files.

'`--force`'
'`-f`' Remake the template file even if newer than its input files.

'`--include=dir`'
'`-I dir`' Append *dir* to the include path. Multiple invocations accumulate.

'`--prepend-include=dir`'
'`-B dir`' Prepend *dir* to the include path. Multiple invocations accumulate.

'`--warnings=category`'
'`-W category`'
Report the warnings related to *category* (which can actually be a comma separated list). Current categories include:

'`obsolete`'
report the uses of obsolete constructs

'`all`' report all the warnings

'`none`' report none

'`error`' treats warnings as errors

'`no-category`'
disable warnings falling into *category*

4.9.3 Autoheader Macros

autoheader scans 'configure.ac' and figures out which C preprocessor symbols it might define. It knows how to generate templates for symbols defined by AC_CHECK_HEADERS, AC_CHECK_FUNCS etc., but if you AC_DEFINE any additional symbol, you must define a template for it. If there are missing templates, autoheader fails with an error message.

The template for a *symbol* is created by autoheader from the *description* argument to an AC_DEFINE; see Section 7.1 [Defining Symbols], page 103.

For special needs, you can use the following macros.

AH_TEMPLATE (*key*, *description*) [Macro]

Tell autoheader to generate a template for *key*. This macro generates standard templates just like AC_DEFINE when a *description* is given.

For example:

```
AH_TEMPLATE([CRAY_STACKSEG_END],
            [Define to one of _getb67, GETB67, getb67
             for Cray-2 and Cray-YMP systems.  This
             function is required for alloca.c support
             on those systems.])
```

generates the following template, with the description properly justified.

```
/* Define to one of _getb67, GETB67, getb67 for Cray-2 and
   Cray-YMP systems.  This function is required for alloca.c
   support on those systems.  */
#undef CRAY_STACKSEG_END
```

AH_VERBATIM (*key*, *template*) [Macro]

Tell autoheader to include the *template* as-is in the header template file. This *template* is associated with the *key*, which is used to sort all the different templates and guarantee their uniqueness. It should be a symbol that can be defined via AC_DEFINE.

AH_TOP (*text*) [Macro]

Include *text* at the top of the header template file.

AH_BOTTOM (*text*) [Macro]

Include *text* at the bottom of the header template file.

Please note that *text* gets included "verbatim" to the template file, not to the resulting config header, so it can easily get mangled when the template is processed. There is rarely a need for something other than

```
AH_BOTTOM([#include <custom.h>])
```

4.10 Running Arbitrary Configuration Commands

You can execute arbitrary commands before, during, and after 'config.status' is run. The three following macros accumulate the commands to run when they are called multiple times. AC_CONFIG_COMMANDS replaces the obsolete macro AC_OUTPUT_COMMANDS; see Section 17.4 [Obsolete Macros], page 243, for details.

AC_CONFIG_COMMANDS (*tag...*, [*cmds*], [*init-cmds*]) [Macro]

Specify additional shell commands to run at the end of 'config.status', and shell commands to initialize any variables from configure. Associate the commands with *tag*. Since typically the *cmds* create a file, *tag* should naturally be the name of that file. If needed, the directory hosting *tag* is created. This macro is one of the instantiating macros; see Section 4.6 [Configuration Actions], page 20.

Here is an unrealistic example:

```
fubar=42
AC_CONFIG_COMMANDS([fubar],
                   [echo this is extra $fubar, and so on.],
                   [fubar=$fubar])
```

Here is a better one:

```
AC_CONFIG_COMMANDS([timestamp], [date >timestamp])
```

The following two macros look similar, but in fact they are not of the same breed: they are executed directly by 'configure', so you cannot use 'config.status' to rerun them.

AC_CONFIG_COMMANDS_PRE (*cmds*) [Macro]

Execute the *cmds* right before creating 'config.status'.

This macro presents the last opportunity to call AC_SUBST, AC_DEFINE, or AC_CONFIG_FOOS macros.

AC_CONFIG_COMMANDS_POST (*cmds*) [Macro]

Execute the *cmds* right after creating 'config.status'.

4.11 Creating Configuration Links

You may find it convenient to create links whose destinations depend upon results of tests. One can use AC_CONFIG_COMMANDS but the creation of relative symbolic links can be delicate when the package is built in a directory different from the source directory.

AC_CONFIG_LINKS (*dest:source...*, [*cmds*], [*init-cmds*]) [Macro]

Make AC_OUTPUT link each of the existing files *source* to the corresponding link name *dest*. Makes a symbolic link if possible, otherwise a hard link if possible, otherwise a copy. The *dest* and *source* names should be relative to the top level source or build directory. This macro is one of the instantiating macros; see Section 4.6 [Configuration Actions], page 20.

For example, this call:

```
AC_CONFIG_LINKS([host.h:config/$machine.h
                object.h:config/$obj_format.h])
```

creates in the current directory 'host.h' as a link to '*srcdir*/config/$machine.h', and 'object.h' as a link to '*srcdir*/config/$obj_format.h'.

The tempting value '.' for *dest* is invalid: it makes it impossible for 'config.status' to guess the links to establish.

One can then run:

```
./config.status host.h object.h
```

to create the links.

4.12 Configuring Other Packages in Subdirectories

In most situations, calling `AC_OUTPUT` is sufficient to produce makefiles in subdirectories. However, `configure` scripts that control more than one independent package can use `AC_CONFIG_SUBDIRS` to run `configure` scripts for other packages in subdirectories.

`AC_CONFIG_SUBDIRS (dir ...)` [Macro]

Make `AC_OUTPUT` run `configure` in each subdirectory *dir* in the given blank-or-newline-separated list. Each *dir* should be a literal, i.e., please do not use:

```
if test "$package_foo_enabled" = yes; then
  $my_subdirs="$my_subdirs foo"
fi
AC_CONFIG_SUBDIRS([$my_subdirs])
```

because this prevents '`./configure --help=recursive`' from displaying the options of the package `foo`. Instead, you should write:

```
if test "$package_foo_enabled" = yes; then
  AC_CONFIG_SUBDIRS([foo])
fi
```

If a given *dir* is not found, an error is reported: if the subdirectory is optional, write:

```
if test -d "$srcdir/foo"; then
  AC_CONFIG_SUBDIRS([foo])
fi
```

If a given *dir* contains `configure.gnu`, it is run instead of `configure`. This is for packages that might use a non-Autoconf script `Configure`, which can't be called through a wrapper `configure` since it would be the same file on case-insensitive file systems. Likewise, if a *dir* contains '`configure.in`' but no `configure`, the Cygnus `configure` script found by `AC_CONFIG_AUX_DIR` is used.

The subdirectory `configure` scripts are given the same command line options that were given to this `configure` script, with minor changes if needed, which include:

- adjusting a relative name for the cache file;
- adjusting a relative name for the source directory;
- propagating the current value of `$prefix`, including if it was defaulted, and if the default values of the top level and of the subdirectory '`configure`' differ.

This macro also sets the output variable `subdirs` to the list of directories '*dir* ...'. Make rules can use this variable to determine which subdirectories to recurse into.

This macro may be called multiple times.

4.13 Default Prefix

By default, `configure` sets the prefix for files it installs to '`/usr/local`'. The user of `configure` can select a different prefix using the '`--prefix`' and '`--exec-prefix`' options. There are two ways to change the default: when creating `configure`, and when running it.

Some software packages might want to install in a directory other than '`/usr/local`' by default. To accomplish that, use the `AC_PREFIX_DEFAULT` macro.

`AC_PREFIX_DEFAULT (prefix)` [Macro]

Set the default installation prefix to *prefix* instead of '`/usr/local`'.

It may be convenient for users to have `configure` guess the installation prefix from the location of a related program that they have already installed. If you wish to do that, you can call `AC_PREFIX_PROGRAM`.

`AC_PREFIX_PROGRAM (program)` [Macro]

If the user did not specify an installation prefix (using the '`--prefix`' option), guess a value for it by looking for *program* in `PATH`, the way the shell does. If *program* is found, set the prefix to the parent of the directory containing *program*, else default the prefix as described above ('`/usr/local`' or `AC_PREFIX_DEFAULT`). For example, if *program* is `gcc` and the `PATH` contains '`/usr/local/gnu/bin/gcc`', set the prefix to '`/usr/local/gnu`'.

5 Existing Tests

These macros test for particular system features that packages might need or want to use. If you need to test for a kind of feature that none of these macros check for, you can probably do it by calling primitive test macros with appropriate arguments (see Chapter 6 [Writing Tests], page 91).

These tests print messages telling the user which feature they're checking for, and what they find. They cache their results for future `configure` runs (see Section 7.4 [Caching Results], page 107).

Some of these macros set output variables. See Section 4.8 [Makefile Substitutions], page 23, for how to get their values. The phrase "define *name*" is used below as a shorthand to mean "define the C preprocessor symbol *name* to the value 1". See Section 7.1 [Defining Symbols], page 103, for how to get those symbol definitions into your program.

5.1 Common Behavior

Much effort has been expended to make Autoconf easy to learn. The most obvious way to reach this goal is simply to enforce standard interfaces and behaviors, avoiding exceptions as much as possible. Because of history and inertia, unfortunately, there are still too many exceptions in Autoconf; nevertheless, this section describes some of the common rules.

5.1.1 Standard Symbols

All the generic macros that `AC_DEFINE` a symbol as a result of their test transform their *argument* values to a standard alphabet. First, *argument* is converted to upper case and any asterisks ('`*`') are each converted to '`P`'. Any remaining characters that are not alphanumeric are converted to underscores.

For instance,

```
AC_CHECK_TYPES([struct $Expensive*])
```

defines the symbol '`HAVE_STRUCT__EXPENSIVEP`' if the check succeeds.

5.1.2 Default Includes

Several tests depend upon a set of header files. Since these headers are not universally available, tests actually have to provide a set of protected includes, such as:

```
#ifdef TIME_WITH_SYS_TIME
# include <sys/time.h>
# include <time.h>
#else
# ifdef HAVE_SYS_TIME_H
#  include <sys/time.h>
# else
#  include <time.h>
# endif
#endif
```

Unless you know exactly what you are doing, you should avoid using unconditional includes, and check the existence of the headers you include beforehand (see Section 5.6 [Header Files], page 58).

Most generic macros use the following macro to provide the default set of includes:

`AC_INCLUDES_DEFAULT` ([*include-directives*]) [Macro]

Expand to *include-directives* if defined, otherwise to:

```
#include <stdio.h>
#ifdef HAVE_SYS_TYPES_H
# include <sys/types.h>
#endif
#ifdef HAVE_SYS_STAT_H
# include <sys/stat.h>
#endif
#ifdef STDC_HEADERS
# include <stdlib.h>
# include <stddef.h>
#else
# ifdef HAVE_STDLIB_H
#  include <stdlib.h>
# endif
#endif
#ifdef HAVE_STRING_H
# if !defined STDC_HEADERS && defined HAVE_MEMORY_H
#  include <memory.h>
# endif
# include <string.h>
#endif
#ifdef HAVE_STRINGS_H
# include <strings.h>
#endif
#ifdef HAVE_INTTYPES_H
# include <inttypes.h>
#endif
#ifdef HAVE_STDINT_H
# include <stdint.h>
#endif
#ifdef HAVE_UNISTD_H
# include <unistd.h>
#endif
```

If the default includes are used, then check for the presence of these headers and their compatibility, i.e., you don't need to run `AC_HEADER_STDC`, nor check for '`stdlib.h`' etc.

These headers are checked for in the same order as they are included. For instance, on some systems '`string.h`' and '`strings.h`' both exist, but conflict. Then `HAVE_STRING_H` is defined, not `HAVE_STRINGS_H`.

5.2 Alternative Programs

These macros check for the presence or behavior of particular programs. They are used to choose between several alternative programs and to decide what to do once one has been chosen. If there is no macro specifically defined to check for a program you need, and you don't need to check for any special properties of it, then you can use one of the general program-check macros.

5.2.1 Particular Program Checks

These macros check for particular programs—whether they exist, and in some cases whether they support certain features.

`AC_PROG_AWK` [Macro]

Check for `gawk`, `mawk`, `nawk`, and `awk`, in that order, and set output variable `AWK` to the first one that is found. It tries `gawk` first because that is reported to be the best implementation.

`AC_PROG_GREP` [Macro]

Look for the best available `grep` or `ggrep` that accepts the longest input lines possible, and that supports multiple '`-e`' options. Set the output variable `GREP` to whatever is chosen. See Section 10.13 [Limitations of Usual Tools], page 182, for more information about portability problems with the `grep` command family.

`AC_PROG_EGREP` [Macro]

Check whether `$GREP -E` works, or else look for the best available `egrep` or `gegrep` that accepts the longest input lines possible. Set the output variable `EGREP` to whatever is chosen.

`AC_PROG_FGREP` [Macro]

Check whether `$GREP -F` works, or else look for the best available `fgrep` or `gfgrep` that accepts the longest input lines possible. Set the output variable `FGREP` to whatever is chosen.

`AC_PROG_INSTALL` [Macro]

Set output variable `INSTALL` to the name of a BSD-compatible `install` program, if one is found in the current `PATH`. Otherwise, set `INSTALL` to '*dir*`/install-sh -c`', checking the directories specified to `AC_CONFIG_AUX_DIR` (or its default directories) to determine *dir* (see Section 4.5 [Output], page 20). Also set the variables `INSTALL_PROGRAM` and `INSTALL_SCRIPT` to '`${INSTALL}`' and `INSTALL_DATA` to '`${INSTALL} -m 644`'.

'`@INSTALL@`' is special, as its value may vary for different configuration files.

This macro screens out various instances of `install` known not to work. It prefers to find a C program rather than a shell script, for speed. Instead of '`install-sh`', it can also use '`install.sh`', but that name is obsolete because some `make` programs have a rule that creates '`install`' from it if there is no makefile. Further, this macro requires `install` to be able to install multiple files into a target directory in a single invocation.

Autoconf comes with a copy of '`install-sh`' that you can use. If you use `AC_PROG_INSTALL`, you must include either '`install-sh`' or '`install.sh`' in your distribution;

otherwise `configure` produces an error message saying it can't find them—even if the system you're on has a good `install` program. This check is a safety measure to prevent you from accidentally leaving that file out, which would prevent your package from installing on systems that don't have a BSD-compatible `install` program.

If you need to use your own installation program because it has features not found in standard `install` programs, there is no reason to use `AC_PROG_INSTALL`; just put the file name of your program into your '`Makefile.in`' files.

`AC_PROG_MKDIR_P` [Macro]

Set output variable `MKDIR_P` to a program that ensures that for each argument, a directory named by this argument exists, creating it and its parent directories if needed, and without race conditions when two instances of the program attempt to make the same directory at nearly the same time.

This macro uses the '`mkdir -p`' command if possible. Otherwise, it falls back on invoking `install-sh` with the '`-d`' option, so your package should contain '`install-sh`' as described under `AC_PROG_INSTALL`. An '`install-sh`' file that predates Autoconf 2.60 or Automake 1.10 is vulnerable to race conditions, so if you want to support parallel installs from different packages into the same directory you need to make sure you have an up-to-date '`install-sh`'. In particular, be careful about using '`autoreconf -if`' if your Automake predates Automake 1.10.

This macro is related to the `AS_MKDIR_P` macro (see Section 8.4 [Programming in M4sh], page 141), but it sets an output variable intended for use in other files, whereas `AS_MKDIR_P` is intended for use in scripts like `configure`. Also, `AS_MKDIR_P` does not accept options, but `MKDIR_P` supports the '`-m`' option, e.g., a makefile might invoke `$(MKDIR_P) -m 0 dir` to create an inaccessible directory, and conversely a makefile should use `$(MKDIR_P) -- $(FOO)` if *FOO* might yield a value that begins with '`-`'. Finally, `AS_MKDIR_P` does not check for race condition vulnerability, whereas `AC_PROG_MKDIR_P` does.

'`@MKDIR_P@`' is special, as its value may vary for different configuration files.

`AC_PROG_LEX` [Macro]

If `flex` is found, set output variable `LEX` to '`flex`' and `LEXLIB` to '`-lfl`', if that library is in a standard place. Otherwise set `LEX` to '`lex`' and `LEXLIB` to '`-ll`'.

Define `YYTEXT_POINTER` if `yytext` defaults to '`char *`' instead of to '`char []`'. Also set output variable `LEX_OUTPUT_ROOT` to the base of the file name that the lexer generates; usually '`lex.yy`', but sometimes something else. These results vary according to whether `lex` or `flex` is being used.

You are encouraged to use Flex in your sources, since it is both more pleasant to use than plain Lex and the C source it produces is portable. In order to ensure portability, however, you must either provide a function `yywrap` or, if you don't use it (e.g., your scanner has no '`#include`'-like feature), simply include a '`%noyywrap`' statement in the scanner's source. Once this done, the scanner is portable (unless *you* felt free to use nonportable constructs) and does not depend on any library. In this case, and in this case only, it is suggested that you use this Autoconf snippet:

```
AC_PROG_LEX
```

```
if test "$LEX" != flex; then
  LEX="$SHELL $missing_dir/missing flex"
  AC_SUBST([LEX_OUTPUT_ROOT], [lex.yy])
  AC_SUBST([LEXLIB], [''])
fi
```

The shell script `missing` can be found in the Automake distribution.

To ensure backward compatibility, Automake's `AM_PROG_LEX` invokes (indirectly) this macro twice, which causes an annoying but benign "`AC_PROG_LEX` invoked multiple times" warning. Future versions of Automake will fix this issue; meanwhile, just ignore this message.

As part of running the test, this macro may delete any file in the configuration directory named '`lex.yy.c`' or '`lexyy.c`'.

`AC_PROG_LN_S` [Macro]

If '`ln -s`' works on the current file system (the operating system and file system support symbolic links), set the output variable `LN_S` to '`ln -s`'; otherwise, if '`ln`' works, set `LN_S` to '`ln`', and otherwise set it to '`cp -p`'.

If you make a link in a directory other than the current directory, its meaning depends on whether '`ln`' or '`ln -s`' is used. To safely create links using '`$(LN_S)`', either find out which form is used and adjust the arguments, or always invoke `ln` in the directory where the link is to be created.

In other words, it does not work to do:

```
$(LN_S) foo /x/bar
```

Instead, do:

```
(cd /x && $(LN_S) foo bar)
```

`AC_PROG_RANLIB` [Macro]

Set output variable `RANLIB` to '`ranlib`' if `ranlib` is found, and otherwise to '`:`' (do nothing).

`AC_PROG_SED` [Macro]

Set output variable `SED` to a Sed implementation that conforms to Posix and does not have arbitrary length limits. Report an error if no acceptable Sed is found. See Section 10.13 [Limitations of Usual Tools], page 182, for more information about portability problems with Sed.

`AC_PROG_YACC` [Macro]

If `bison` is found, set output variable `YACC` to '`bison -y`'. Otherwise, if `byacc` is found, set `YACC` to '`byacc`'. Otherwise set `YACC` to '`yacc`'.

5.2.2 Generic Program and File Checks

These macros are used to find programs not covered by the "particular" test macros. If you need to check the behavior of a program as well as find out whether it is present, you have to write your own test for it (see Chapter 6 [Writing Tests], page 91). By default, these macros use the environment variable `PATH`. If you need to check for a program that might not be in the user's `PATH`, you can pass a modified path to use instead, like this:

```
AC_PATH_PROG([INETD], [inetd], [/usr/libexec/inetd],
             [$PATH$PATH_SEPARATOR/usr/libexec$PATH_SEPARATOR]dnl
[/usr/sbin$PATH_SEPARATOR/usr/etc$PATH_SEPARATOR/etc])
```

You are strongly encouraged to declare the *variable* passed to `AC_CHECK_PROG` etc. as precious, See Section 7.2 [Setting Output Variables], page 104, `AC_ARG_VAR`, for more details.

`AC_CHECK_PROG` (*variable*, *prog-to-check-for*, *value-if-found*, [*value-if-not-found*], [*path* = '`$PATH`'], [*reject*]) [Macro]

Check whether program *prog-to-check-for* exists in *path*. If it is found, set *variable* to *value-if-found*, otherwise to *value-if-not-found*, if given. Always pass over *reject* (an absolute file name) even if it is the first found in the search path; in that case, set *variable* using the absolute file name of the *prog-to-check-for* found that is not *reject*. If *variable* was already set, do nothing. Calls `AC_SUBST` for *variable*.

`AC_CHECK_PROGS` (*variable*, *progs-to-check-for*, [*value-if-not-found*], [*path* = '`$PATH`']) [Macro]

Check for each program in the blank-separated list *progs-to-check-for* existing in the *path*. If one is found, set *variable* to the name of that program. Otherwise, continue checking the next program in the list. If none of the programs in the list are found, set *variable* to *value-if-not-found*; if *value-if-not-found* is not specified, the value of *variable* is not changed. Calls `AC_SUBST` for *variable*.

`AC_CHECK_TARGET_TOOL` (*variable*, *prog-to-check-for*, [*value-if-not-found*], [*path* = '`$PATH`']) [Macro]

Like `AC_CHECK_PROG`, but first looks for *prog-to-check-for* with a prefix of the target type as determined by `AC_CANONICAL_TARGET`, followed by a dash (see Section 13.2 [Canonicalizing], page 222). If the tool cannot be found with a prefix, and if the build and target types are equal, then it is also searched for without a prefix.

As noted in Section 13.1 [Specifying the system type], page 221, the target is rarely specified, because most of the time it is the same as the host: it is the type of system for which any compiler tool in the package produces code. What this macro looks for is, for example, *a tool* (assembler, linker, etc.) *that the compiler driver* (`gcc` for the GNU C Compiler) *uses to produce objects, archives or executables.*

`AC_CHECK_TOOL` (*variable*, *prog-to-check-for*, [*value-if-not-found*], [*path* = '`$PATH`']) [Macro]

Like `AC_CHECK_PROG`, but first looks for *prog-to-check-for* with a prefix of the host type as specified by '`--host`', followed by a dash. For example, if the user runs '`configure --build=x86_64-gnu --host=i386-gnu`', then this call:

```
AC_CHECK_TOOL([RANLIB], [ranlib], [:])
```

sets `RANLIB` to '`i386-gnu-ranlib`' if that program exists in *path*, or otherwise to '`ranlib`' if that program exists in *path*, or to '`:`' if neither program exists.

In the future, when cross-compiling this macro will *only* accept program names that are prefixed with the host type. For more information, see Section 13.1 [Specifying the system type], page 221.

AC_CHECK_TARGET_TOOLS (*variable*, *progs-to-check-for*, [*value-if-not-found*], [*path* = '$PATH']) [Macro]

Like AC_CHECK_TARGET_TOOL, each of the tools in the list *progs-to-check-for* are checked with a prefix of the target type as determined by AC_CANONICAL_TARGET, followed by a dash (see Section 13.2 [Canonicalizing], page 222). If none of the tools can be found with a prefix, and if the build and target types are equal, then the first one without a prefix is used. If a tool is found, set *variable* to the name of that program. If none of the tools in the list are found, set *variable* to *value-if-not-found*; if *value-if-not-found* is not specified, the value of *variable* is not changed. Calls AC_SUBST for *variable*.

AC_CHECK_TOOLS (*variable*, *progs-to-check-for*, [*value-if-not-found*], [*path* = '$PATH']) [Macro]

Like AC_CHECK_TOOL, each of the tools in the list *progs-to-check-for* are checked with a prefix of the host type as determined by AC_CANONICAL_HOST, followed by a dash (see Section 13.2 [Canonicalizing], page 222). If none of the tools can be found with a prefix, then the first one without a prefix is used. If a tool is found, set *variable* to the name of that program. If none of the tools in the list are found, set *variable* to *value-if-not-found*; if *value-if-not-found* is not specified, the value of *variable* is not changed. Calls AC_SUBST for *variable*.

In the future, when cross-compiling this macro will *not* accept program names that are not prefixed with the host type.

AC_PATH_PROG (*variable*, *prog-to-check-for*, [*value-if-not-found*], [*path* = '$PATH']) [Macro]

Like AC_CHECK_PROG, but set *variable* to the absolute name of *prog-to-check-for* if found.

AC_PATH_PROGS (*variable*, *progs-to-check-for*, [*value-if-not-found*], [*path* = '$PATH']) [Macro]

Like AC_CHECK_PROGS, but if any of *progs-to-check-for* are found, set *variable* to the absolute name of the program found.

AC_PATH_PROGS_FEATURE_CHECK (*variable*, *progs-to-check-for*, *feature-test*, [*action-if-not-found*], [*path* = '$PATH']) [Macro]

This macro was introduced in Autoconf 2.62. If *variable* is not empty, then set the cache variable $ac_cv_path_*variable* to its value. Otherwise, check for each program in the blank-separated list *progs-to-check-for* existing in *path*. For each program found, execute *feature-test* with $ac_path_*variable* set to the absolute name of the candidate program. If no invocation of *feature-test* sets the shell variable $ac_cv_path_*variable*, then *action-if-not-found* is executed. *feature-test* will be run even when ac_cv_path_*variable* is set, to provide the ability to choose a better candidate found later in *path*; to accept the current setting and bypass all futher checks, *feature-test* can execute ac_path_*variable*_found=:.

Note that this macro has some subtle differences from AC_CHECK_PROGS. It is designed to be run inside AC_CACHE_VAL, therefore, it should have no side effects. In

particular, *variable* is not set to the final value of `ac_cv_path_variable`, nor is `AC_SUBST` automatically run. Also, on failure, any action can be performed, whereas `AC_CHECK_PROGS` only performs `variable=value-if-not-found`.

Here is an example, similar to what Autoconf uses in its own configure script. It will search for an implementation of `m4` that supports the `indir` builtin, even if it goes by the name `gm4` or is not the first implementation on `PATH`.

```
AC_CACHE_CHECK([for m4 that supports indir], [ac_cv_path_M4],
  [AC_PATH_PROGS_FEATURE_CHECK([M4], [m4 gm4],
    [[m4out=`echo 'changequote([,])indir([divnum])' | $ac_path_M4`
      test "x$m4out" = x0 \
      && ac_cv_path_M4=$ac_path_M4 ac_path_M4_found=:]],
    [AC_MSG_ERROR([could not find m4 that supports indir])])])
AC_SUBST([M4], [$ac_cv_path_M4])
```

`AC_PATH_TARGET_TOOL` (*variable*, *prog-to-check-for*, [*value-if-not-found*], [*path* = '`$PATH`']) [Macro]

Like `AC_CHECK_TARGET_TOOL`, but set *variable* to the absolute name of the program if it is found.

`AC_PATH_TOOL` (*variable*, *prog-to-check-for*, [*value-if-not-found*], [*path* = '`$PATH`']) [Macro]

Like `AC_CHECK_TOOL`, but set *variable* to the absolute name of the program if it is found.

In the future, when cross-compiling this macro will *not* accept program names that are not prefixed with the host type.

5.3 Files

You might also need to check for the existence of files. Before using these macros, ask yourself whether a runtime test might not be a better solution. Be aware that, like most Autoconf macros, they test a feature of the host machine, and therefore, they die when cross-compiling.

`AC_CHECK_FILE` (*file*, [*action-if-found*], [*action-if-not-found*]) [Macro]

Check whether file *file* exists on the native system. If it is found, execute *action-if-found*, otherwise do *action-if-not-found*, if given.

`AC_CHECK_FILES` (*files*, [*action-if-found*], [*action-if-not-found*]) [Macro]

Executes `AC_CHECK_FILE` once for each file listed in *files*. Additionally, defines '`HAVE_file`' (see Section 5.1.1 [Standard Symbols], page 39) for each file found.

5.4 Library Files

The following macros check for the presence of certain C, C++, or Fortran library archive files.

`AC_CHECK_LIB` (*library*, *function*, [*action-if-found*], [*action-if-not-found*], [*other-libraries*]) [Macro]

Test whether the library *library* is available by trying to link a test program that calls function *function* with the library. *function* should be a function provided by

the library. Use the base name of the library; e.g., to check for '`-lmp`', use '`mp`' as the *library* argument.

action-if-found is a list of shell commands to run if the link with the library succeeds; *action-if-not-found* is a list of shell commands to run if the link fails. If *action-if-found* is not specified, the default action prepends '`-l`*library*' to `LIBS` and defines '`HAVE_LIB`*library*' (in all capitals). This macro is intended to support building `LIBS` in a right-to-left (least-dependent to most-dependent) fashion such that library dependencies are satisfied as a natural side effect of consecutive tests. Linkers are sensitive to library ordering so the order in which `LIBS` is generated is important to reliable detection of libraries.

If linking with *library* results in unresolved symbols that would be resolved by linking with additional libraries, give those libraries as the *other-libraries* argument, separated by spaces: e.g., '`-lXt -lX11`'. Otherwise, this macro fails to detect that *library* is present, because linking the test program always fails with unresolved symbols. The *other-libraries* argument should be limited to cases where it is desirable to test for one library in the presence of another that is not already in `LIBS`.

`AC_CHECK_LIB` requires some care in usage, and should be avoided in some common cases. Many standard functions like `gethostbyname` appear in the standard C library on some hosts, and in special libraries like `nsl` on other hosts. On some hosts the special libraries contain variant implementations that you may not want to use. These days it is normally better to use `AC_SEARCH_LIBS([gethostbyname], [nsl])` instead of `AC_CHECK_LIB([nsl], [gethostbyname])`.

`AC_SEARCH_LIBS` (*function*, *search-libs*, [*action-if-found*], [*action-if-not-found*], [*other-libraries*]) [Macro]

Search for a library defining *function* if it's not already available. This equates to calling '`AC_LINK_IFELSE([AC_LANG_CALL([], [`*function*`])])`' first with no libraries, then for each library listed in *search-libs*.

Add '`-l`*library*' to `LIBS` for the first library found to contain *function*, and run *action-if-found*. If the function is not found, run *action-if-not-found*.

If linking with *library* results in unresolved symbols that would be resolved by linking with additional libraries, give those libraries as the *other-libraries* argument, separated by spaces: e.g., '`-lXt -lX11`'. Otherwise, this macro fails to detect that *function* is present, because linking the test program always fails with unresolved symbols.

5.5 Library Functions

The following macros check for particular C library functions. If there is no macro specifically defined to check for a function you need, and you don't need to check for any special properties of it, then you can use one of the general function-check macros.

5.5.1 Portability of C Functions

Most usual functions can either be missing, or be buggy, or be limited on some architectures. This section tries to make an inventory of these portability issues. By definition, this list always requires additions. Please help us keeping it as complete as possible.

`exit` On ancient hosts, `exit` returned `int`. This is because `exit` predates `void`, and there was a long tradition of it returning `int`.

On current hosts, the problem more likely is that `exit` is not declared, due to C++ problems of some sort or another. For this reason we suggest that test programs not invoke `exit`, but return from `main` instead.

`free` The C standard says a call `free (NULL)` does nothing, but some old systems don't support this (e.g., NextStep).

`isinf`
`isnan` The C99 standard says that `isinf` and `isnan` are macros. On some systems just macros are available (e.g., HP-UX and Solaris 10), on some systems both macros and functions (e.g., glibc 2.3.2), and on some systems only functions (e.g., IRIX 6 and Solaris 9). In some cases these functions are declared in nonstandard headers like `<sunmath.h>` and defined in non-default libraries like '`-lm`' or '`-lsunmath`'.

The C99 `isinf` and `isnan` macros work correctly with `long double` arguments, but pre-C99 systems that use functions typically assume `double` arguments. On such a system, `isinf` incorrectly returns true for a finite `long double` argument that is outside the range of `double`.

To work around this porting mess, you can use code like the following.

```
#include <math.h>

#ifndef isnan
# define isnan(x) \
    (sizeof (x) == sizeof (long double) ? isnan_ld (x) \
     : sizeof (x) == sizeof (double) ? isnan_d (x) \
     : isnan_f (x))
static inline int isnan_f  (float       x) { return x != x; }
static inline int isnan_d  (double      x) { return x != x; }
static inline int isnan_ld (long double x) { return x != x; }
#endif

#ifndef isinf
# define isinf(x) \
    (sizeof (x) == sizeof (long double) ? isinf_ld (x) \
     : sizeof (x) == sizeof (double) ? isinf_d (x) \
     : isinf_f (x))
static inline int isinf_f  (float       x) { return isnan (x - x); }
static inline int isinf_d  (double      x) { return isnan (x - x); }
static inline int isinf_ld (long double x) { return isnan (x - x); }
#endif
```

Use `AC_C_INLINE` (see Section 5.10.3 [C Compiler], page 74) so that this code works on compilers that lack the `inline` keyword. Some optimizing compilers mishandle these definitions, but systems with that bug typically have missing or broken `isnan` functions anyway, so it's probably not worth worrying about.

`malloc` The C standard says a call `malloc (0)` is implementation dependent. It can return either `NULL` or a new non-null pointer. The latter is more common (e.g., the GNU C Library) but is by no means universal. `AC_FUNC_MALLOC` can be used to insist on non-`NULL` (see Section 5.5.2 [Particular Functions], page 50).

`putenv` Posix prefers `setenv` to `putenv`; among other things, `putenv` is not required of all Posix implementations, but `setenv` is.

Posix specifies that `putenv` puts the given string directly in `environ`, but some systems make a copy of it instead (e.g., glibc 2.0, or BSD). And when a copy is made, `unsetenv` might not free it, causing a memory leak (e.g., FreeBSD 4).

On some systems `putenv ("FOO")` removes '`FOO`' from the environment, but this is not standard usage and it dumps core on some systems (e.g., AIX).

On MinGW, a call `putenv ("FOO=")` removes '`FOO`' from the environment, rather than inserting it with an empty value.

`realloc` The C standard says a call `realloc (NULL, size)` is equivalent to `malloc (size)`, but some old systems don't support this (e.g., NextStep).

`signal` handler

Normally `signal` takes a handler function with a return type of `void`, but some old systems required `int` instead. Any actual `int` value returned is not used; this is only a difference in the function prototype demanded.

All systems we know of in current use return `void`. The `int` was to support K&R C, where of course `void` is not available. `AC_TYPE_SIGNAL` (see Section 5.9.1 [Particular Types], page 69) can be used to establish the correct type in all cases.

`snprintf` The C99 standard says that if the output array isn't big enough and if no other errors occur, `snprintf` and `vsnprintf` truncate the output and return the number of bytes that ought to have been produced. Some older systems return the truncated length (e.g., GNU C Library 2.0.x or IRIX 6.5), some a negative value (e.g., earlier GNU C Library versions), and some the buffer length without truncation (e.g., 32-bit Solaris 7). Also, some buggy older systems ignore the length and overrun the buffer (e.g., 64-bit Solaris 7).

`sprintf` The C standard says `sprintf` and `vsprintf` return the number of bytes written. On some ancient systems (SunOS 4 for instance) they return the buffer pointer instead, but these no longer need to be worried about.

`sscanf` On various old systems, e.g., HP-UX 9, `sscanf` requires that its input string be writable (though it doesn't actually change it). This can be a problem when using `gcc` since it normally puts constant strings in read-only memory (see section "Incompatibilities" in *Using and Porting the GNU Compiler Collection*). Apparently in some cases even having format strings read-only can be a problem.

`strerror_r`

Posix specifies that `strerror_r` returns an `int`, but many systems (e.g., GNU C Library version 2.2.4) provide a different version returning a `char *`. `AC_FUNC_STRERROR_R` can detect which is in use (see Section 5.5.2 [Particular Functions], page 50).

`strnlen` AIX 4.3 provides a broken version which produces the following results:

```
strnlen ("foobar", 0) = 0
strnlen ("foobar", 1) = 3
```

```
strnlen ("foobar", 2) = 2
strnlen ("foobar", 3) = 1
strnlen ("foobar", 4) = 0
strnlen ("foobar", 5) = 6
strnlen ("foobar", 6) = 6
strnlen ("foobar", 7) = 6
strnlen ("foobar", 8) = 6
strnlen ("foobar", 9) = 6
```

`sysconf` `_SC_PAGESIZE` is standard, but some older systems (e.g., HP-UX 9) have `_SC_PAGE_SIZE` instead. This can be tested with `#ifdef`.

`unlink` The Posix spec says that `unlink` causes the given file to be removed only after there are no more open file handles for it. Some non-Posix hosts have trouble with this requirement, though, and some DOS variants even corrupt the file system.

`unsetenv` On MinGW, `unsetenv` is not available, but a variable '`FOO`' can be removed with a call `putenv ("FOO=")`, as described under `putenv` above.

`va_copy` The C99 standard provides `va_copy` for copying `va_list` variables. It may be available in older environments too, though possibly as `__va_copy` (e.g., `gcc` in strict pre-C99 mode). These can be tested with `#ifdef`. A fallback to `memcpy (&dst, &src, sizeof (va_list))` gives maximum portability.

`va_list` `va_list` is not necessarily just a pointer. It can be a `struct` (e.g., `gcc` on Alpha), which means `NULL` is not portable. Or it can be an array (e.g., `gcc` in some PowerPC configurations), which means as a function parameter it can be effectively call-by-reference and library routines might modify the value back in the caller (e.g., `vsnprintf` in the GNU C Library 2.1).

Signed `>>` Normally the C `>>` right shift of a signed type replicates the high bit, giving a so-called "arithmetic" shift. But care should be taken since Standard C doesn't require that behavior. On those few processors without a native arithmetic shift (for instance Cray vector systems) zero bits may be shifted in, the same as a shift of an unsigned type.

Integer `/` C divides signed integers by truncating their quotient toward zero, yielding the same result as Fortran. However, before C99 the standard allowed C implementations to take the floor or ceiling of the quotient in some cases. Hardly any implementations took advantage of this freedom, though, and it's probably not worth worrying about this issue nowadays.

5.5.2 Particular Function Checks

These macros check for particular C functions—whether they exist, and in some cases how they respond when given certain arguments.

`AC_FUNC_ALLOCA` [Macro]

Check how to get `alloca`. Tries to get a builtin version by checking for '`alloca.h`' or the predefined C preprocessor macros `__GNUC__` and `_AIX`. If this macro finds '`alloca.h`', it defines `HAVE_ALLOCA_H`.

If those attempts fail, it looks for the function in the standard C library. If any of those methods succeed, it defines `HAVE_ALLOCA`. Otherwise, it sets the output variable `ALLOCA` to '`${LIBOBJDIR}alloca.o`' and defines `C_ALLOCA` (so programs can periodically call '`alloca (0)`' to garbage collect). This variable is separate from `LIBOBJS` so multiple programs can share the value of `ALLOCA` without needing to create an actual library, in case only some of them use the code in `LIBOBJS`. The '`${LIBOBJDIR}`' prefix serves the same purpose as in `LIBOBJS` (see Section 17.6.4 [AC_LIBOBJ vs LIBOBJS], page 261).

This macro does not try to get `alloca` from the System V R3 '`libPW`' or the System V R4 '`libucb`' because those libraries contain some incompatible functions that cause trouble. Some versions do not even contain `alloca` or contain a buggy version. If you still want to use their `alloca`, use `ar` to extract '`alloca.o`' from them instead of compiling '`alloca.c`'.

Source files that use `alloca` should start with a piece of code like the following, to declare it properly.

```
#ifdef HAVE_ALLOCA_H
# include <alloca.h>
#elif defined __GNUC__
# define alloca __builtin_alloca
#elif defined _AIX
# define alloca __alloca
#elif defined _MSC_VER
# include <malloc.h>
# define alloca _alloca
#else
# include <stddef.h>
# ifdef  __cplusplus
extern "C"
# endif
void *alloca (size_t);
#endif
```

`AC_FUNC_CHOWN` [Macro]

If the `chown` function is available and works (in particular, it should accept '`-1`' for `uid` and `gid`), define `HAVE_CHOWN`.

`AC_FUNC_CLOSEDIR_VOID` [Macro]

If the `closedir` function does not return a meaningful value, define `CLOSEDIR_VOID`. Otherwise, callers ought to check its return value for an error indicator.

Currently this test is implemented by running a test program. When cross compiling the pessimistic assumption that `closedir` does not return a meaningful value is made.

This macro is obsolescent, as `closedir` returns a meaningful value on current systems. New programs need not use this macro.

`AC_FUNC_ERROR_AT_LINE` [Macro]

If the `error_at_line` function is not found, require an `AC_LIBOBJ` replacement of '`error`'.

AC_FUNC_FNMATCH [Macro]

If the fnmatch function conforms to Posix, define HAVE_FNMATCH. Detect common implementation bugs, for example, the bugs in Solaris 2.4.

Unlike the other specific AC_FUNC macros, AC_FUNC_FNMATCH does not replace a broken/missing fnmatch. This is for historical reasons. See AC_REPLACE_FNMATCH below.

This macro is obsolescent. New programs should use Gnulib's fnmatch-posix module. See Section 2.2 [Gnulib], page 3.

AC_FUNC_FNMATCH_GNU [Macro]

Behave like AC_REPLACE_FNMATCH (*replace*) but also test whether fnmatch supports GNU extensions. Detect common implementation bugs, for example, the bugs in the GNU C Library 2.1.

This macro is obsolescent. New programs should use Gnulib's fnmatch-gnu module. See Section 2.2 [Gnulib], page 3.

AC_FUNC_FORK [Macro]

This macro checks for the fork and vfork functions. If a working fork is found, define HAVE_WORKING_FORK. This macro checks whether fork is just a stub by trying to run it.

If 'vfork.h' is found, define HAVE_VFORK_H. If a working vfork is found, define HAVE_WORKING_VFORK. Otherwise, define vfork to be fork for backward compatibility with previous versions of autoconf. This macro checks for several known errors in implementations of vfork and considers the system to not have a working vfork if it detects any of them. It is not considered to be an implementation error if a child's invocation of signal modifies the parent's signal handler, since child processes rarely change their signal handlers.

Since this macro defines vfork only for backward compatibility with previous versions of autoconf you're encouraged to define it yourself in new code:

```
#ifndef HAVE_WORKING_VFORK
# define vfork fork
#endif
```

AC_FUNC_FSEEKO [Macro]

If the fseeko function is available, define HAVE_FSEEKO. Define _LARGEFILE_SOURCE if necessary to make the prototype visible on some systems (e.g., glibc 2.2). Otherwise linkage problems may occur when compiling with AC_SYS_LARGEFILE on largefile-sensitive systems where off_t does not default to a 64bit entity.

AC_FUNC_GETGROUPS [Macro]

If the getgroups function is available and works (unlike on Ultrix 4.3, where 'getgroups (0, 0)' always fails), define HAVE_GETGROUPS. Set GETGROUPS_LIBS to any libraries needed to get that function. This macro runs AC_TYPE_GETGROUPS.

AC_FUNC_GETLOADAVG [Macro]

Check how to get the system load averages. To perform its tests properly, this macro needs the file 'getloadavg.c'; therefore, be sure to set the AC_LIBOBJ replacement directory properly (see Section 5.5.3 [Generic Functions], page 56, AC_CONFIG_LIBOBJ_DIR).

If the system has the `getloadavg` function, define `HAVE_GETLOADAVG`, and set `GETLOADAVG_LIBS` to any libraries necessary to get that function. Also add `GETLOADAVG_LIBS` to `LIBS`. Otherwise, require an `AC_LIBOBJ` replacement for '`getloadavg`' with source code in '*dir*`/getloadavg.c`', and possibly define several other C preprocessor macros and output variables:

1. Define `C_GETLOADAVG`.
2. Define `SVR4`, `DGUX`, `UMAX`, or `UMAX4_3` if on those systems.
3. If '`nlist.h`' is found, define `HAVE_NLIST_H`.
4. If '`struct nlist`' has an '`n_un.n_name`' member, define `HAVE_STRUCT_NLIST_N_UN_N_NAME`. The obsolete symbol `NLIST_NAME_UNION` is still defined, but do not depend upon it.
5. Programs may need to be installed set-group-ID (or set-user-ID) for `getloadavg` to work. In this case, define `GETLOADAVG_PRIVILEGED`, set the output variable `NEED_SETGID` to '`true`' (and otherwise to '`false`'), and set `KMEM_GROUP` to the name of the group that should own the installed program.

The `AC_FUNC_GETLOADAVG` macro is obsolescent. New programs should use Gnulib's `getloadavg` module. See Section 2.2 [Gnulib], page 3.

`AC_FUNC_GETMNTENT` [Macro]

Check for `getmntent` in the standard C library, and then in the '`sun`', '`seq`', and '`gen`' libraries, for UNICOS, IRIX 4, PTX, and UnixWare, respectively. Then, if `getmntent` is available, define `HAVE_GETMNTENT`.

`AC_FUNC_GETPGRP` [Macro]

Define `GETPGRP_VOID` if it is an error to pass 0 to `getpgrp`; this is the Posix behavior. On older BSD systems, you must pass 0 to `getpgrp`, as it takes an argument and behaves like Posix's `getpgid`.

```
#ifdef GETPGRP_VOID
  pid = getpgrp ();
#else
  pid = getpgrp (0);
#endif
```

This macro does not check whether `getpgrp` exists at all; if you need to work in that situation, first call `AC_CHECK_FUNC` for `getpgrp`.

This macro is obsolescent, as current systems have a `getpgrp` whose signature conforms to Posix. New programs need not use this macro.

`AC_FUNC_LSTAT_FOLLOWS_SLASHED_SYMLINK` [Macro]

If '`link`' is a symbolic link, then `lstat` should treat '`link/`' the same as '`link/.`'. However, many older `lstat` implementations incorrectly ignore trailing slashes.

It is safe to assume that if `lstat` incorrectly ignores trailing slashes, then other symbolic-link-aware functions like `unlink` also incorrectly ignore trailing slashes.

If `lstat` behaves properly, define `LSTAT_FOLLOWS_SLASHED_SYMLINK`, otherwise require an `AC_LIBOBJ` replacement of `lstat`.

AC_FUNC_MALLOC [Macro]

If the malloc function is compatible with the GNU C library malloc (i.e., 'malloc (0)' returns a valid pointer), define HAVE_MALLOC to 1. Otherwise define HAVE_MALLOC to 0, ask for an AC_LIBOBJ replacement for 'malloc', and define malloc to rpl_malloc so that the native malloc is not used in the main project.

Typically, the replacement file 'malloc.c' should look like (note the '#undef malloc'):

```
#include <config.h>
#undef malloc

#include <sys/types.h>

void *malloc ();

/* Allocate an N-byte block of memory from the heap.
   If N is zero, allocate a 1-byte block.  */

void *
rpl_malloc (size_t n)
{
  if (n == 0)
    n = 1;
  return malloc (n);
}
```

AC_FUNC_MEMCMP [Macro]

If the memcmp function is not available, or does not work on 8-bit data (like the one on SunOS 4.1.3), or fails when comparing 16 bytes or more and with at least one buffer not starting on a 4-byte boundary (such as the one on NeXT x86 OpenStep), require an AC_LIBOBJ replacement for 'memcmp'.

This macro is obsolescent, as current systems have a working memcmp. New programs need not use this macro.

AC_FUNC_MBRTOWC [Macro]

Define HAVE_MBRTOWC to 1 if the function mbrtowc and the type mbstate_t are properly declared.

AC_FUNC_MKTIME [Macro]

If the mktime function is not available, or does not work correctly, require an AC_LIBOBJ replacement for 'mktime'. For the purposes of this test, mktime should conform to the Posix standard and should be the inverse of localtime.

AC_FUNC_MMAP [Macro]

If the mmap function exists and works correctly, define HAVE_MMAP. This checks only private fixed mapping of already-mapped memory.

AC_FUNC_OBSTACK [Macro]

If the obstacks are found, define HAVE_OBSTACK, else require an AC_LIBOBJ replacement for 'obstack'.

AC_FUNC_REALLOC [Macro]

If the realloc function is compatible with the GNU C library realloc (i.e., 'realloc (NULL, 0)' returns a valid pointer), define HAVE_REALLOC to 1. Otherwise define HAVE_REALLOC to 0, ask for an AC_LIBOBJ replacement for 'realloc', and define realloc to rpl_realloc so that the native realloc is not used in the main project. See AC_FUNC_MALLOC for details.

AC_FUNC_SELECT_ARGTYPES [Macro]

Determines the correct type to be passed for each of the select function's arguments, and defines those types in SELECT_TYPE_ARG1, SELECT_TYPE_ARG234, and SELECT_TYPE_ARG5 respectively. SELECT_TYPE_ARG1 defaults to 'int', SELECT_TYPE_ARG234 defaults to 'int *', and SELECT_TYPE_ARG5 defaults to 'struct timeval *'.

This macro is obsolescent, as current systems have a select whose signature conforms to Posix. New programs need not use this macro.

AC_FUNC_SETPGRP [Macro]

If setpgrp takes no argument (the Posix version), define SETPGRP_VOID. Otherwise, it is the BSD version, which takes two process IDs as arguments. This macro does not check whether setpgrp exists at all; if you need to work in that situation, first call AC_CHECK_FUNC for setpgrp.

This macro is obsolescent, as current systems have a setpgrp whose signature conforms to Posix. New programs need not use this macro.

AC_FUNC_STAT [Macro]
AC_FUNC_LSTAT [Macro]

Determine whether stat or lstat have the bug that it succeeds when given the zero-length file name as argument. The stat and lstat from SunOS 4.1.4 and the Hurd (as of 1998-11-01) do this.

If it does, then define HAVE_STAT_EMPTY_STRING_BUG (or HAVE_LSTAT_EMPTY_STRING_BUG) and ask for an AC_LIBOBJ replacement of it.

These macros are obsolescent, as no current systems have the bug. New programs need not use these macros.

AC_FUNC_STRCOLL [Macro]

If the strcoll function exists and works correctly, define HAVE_STRCOLL. This does a bit more than 'AC_CHECK_FUNCS(strcoll)', because some systems have incorrect definitions of strcoll that should not be used.

AC_FUNC_STRERROR_R [Macro]

If strerror_r is available, define HAVE_STRERROR_R, and if it is declared, define HAVE_DECL_STRERROR_R. If it returns a char * message, define STRERROR_R_CHAR_P; otherwise it returns an int error number. The Thread-Safe Functions option of Posix requires strerror_r to return int, but many systems (including, for example, version 2.2.4 of the GNU C Library) return a char * value that is not necessarily equal to the buffer argument.

AC_FUNC_STRFTIME [Macro]

Check for strftime in the 'intl' library, for SCO Unix. Then, if strftime is available, define HAVE_STRFTIME.

This macro is obsolescent, as no current systems require the 'intl' library for strftime. New programs need not use this macro.

AC_FUNC_STRTOD [Macro]

If the strtod function does not exist or doesn't work correctly, ask for an AC_LIBOBJ replacement of 'strtod'. In this case, because 'strtod.c' is likely to need 'pow', set the output variable POW_LIB to the extra library needed.

AC_FUNC_STRTOLD [Macro]

If the strtold function exists and conforms to C99, define HAVE_STRTOLD.

AC_FUNC_STRNLEN [Macro]

If the strnlen function is not available, or is buggy (like the one from AIX 4.3), require an AC_LIBOBJ replacement for it.

AC_FUNC_UTIME_NULL [Macro]

If 'utime (*file*, NULL)' sets *file*'s timestamp to the present, define HAVE_UTIME_NULL.

This macro is obsolescent, as all current systems have a utime that behaves this way. New programs need not use this macro.

AC_FUNC_VPRINTF [Macro]

If vprintf is found, define HAVE_VPRINTF. Otherwise, if _doprnt is found, define HAVE_DOPRNT. (If vprintf is available, you may assume that vfprintf and vsprintf are also available.)

This macro is obsolescent, as all current systems have vprintf. New programs need not use this macro.

AC_REPLACE_FNMATCH [Macro]

If the fnmatch function does not conform to Posix (see AC_FUNC_FNMATCH), ask for its AC_LIBOBJ replacement.

The files 'fnmatch.c', 'fnmatch_loop.c', and 'fnmatch_.h' in the AC_LIBOBJ replacement directory are assumed to contain a copy of the source code of GNU fnmatch. If necessary, this source code is compiled as an AC_LIBOBJ replacement, and the 'fnmatch_.h' file is linked to 'fnmatch.h' so that it can be included in place of the system <fnmatch.h>.

This macro is obsolescent, as it assumes the use of particular source files. New programs should use Gnulib's fnmatch-posix module, which provides this macro along with the source files. See Section 2.2 [Gnulib], page 3.

5.5.3 Generic Function Checks

These macros are used to find functions not covered by the "particular" test macros. If the functions might be in libraries other than the default C library, first call AC_CHECK_LIB for those libraries. If you need to check the behavior of a function as well as find out whether it is present, you have to write your own test for it (see Chapter 6 [Writing Tests], page 91).

AC_CHECK_FUNC (*function*, [*action-if-found*], [*action-if-not-found*]) [Macro]

If C function *function* is available, run shell commands *action-if-found*, otherwise *action-if-not-found*. If you just want to define a symbol if the function is available, consider using AC_CHECK_FUNCS instead. This macro checks for functions with C linkage even when AC_LANG(C++) has been called, since C is more standardized than C++. (see Section 6.1 [Language Choice], page 91, for more information about selecting the language for checks.)

AC_CHECK_FUNCS (*function*..., [*action-if-found*], [*action-if-not-found*]) [Macro]

For each *function* enumerated in the blank-or-newline-separated argument list, define HAVE_*function* (in all capitals) if it is available. If *action-if-found* is given, it is additional shell code to execute when one of the functions is found. You can give it a value of 'break' to break out of the loop on the first match. If *action-if-not-found* is given, it is executed when one of the functions is not found.

AC_CHECK_FUNCS_ONCE (*function*...) [Macro]

For each *function* enumerated in the blank-or-newline-separated argument list, define HAVE_*function* (in all capitals) if it is available. This is a once-only variant of AC_CHECK_FUNCS. It generates the checking code at most once, so that configure is smaller and faster; but the checks cannot be conditionalized and are always done once, early during the configure run.

Autoconf follows a philosophy that was formed over the years by those who have struggled for portability: isolate the portability issues in specific files, and then program as if you were in a Posix environment. Some functions may be missing or unfixable, and your package must be ready to replace them.

Suitable replacements for many such problem functions are available from Gnulib (see Section 2.2 [Gnulib], page 3).

AC_LIBOBJ (*function*) [Macro]

Specify that '*function*.c' must be included in the executables to replace a missing or broken implementation of *function*.

Technically, it adds '*function*.$ac_objext' to the output variable LIBOBJS if it is not already in, and calls AC_LIBSOURCE for '*function*.c'. You should not directly change LIBOBJS, since this is not traceable.

AC_LIBSOURCE (*file*) [Macro]

Specify that *file* might be needed to compile the project. If you need to know what files might be needed by a 'configure.ac', you should trace AC_LIBSOURCE. *file* must be a literal.

This macro is called automatically from AC_LIBOBJ, but you must call it explicitly if you pass a shell variable to AC_LIBOBJ. In that case, since shell variables cannot be traced statically, you must pass to AC_LIBSOURCE any possible files that the shell variable might cause AC_LIBOBJ to need. For example, if you want to pass a variable $foo_or_bar to AC_LIBOBJ that holds either "foo" or "bar", you should do:

```
AC_LIBSOURCE([foo.c])
AC_LIBSOURCE([bar.c])
AC_LIBOBJ([$foo_or_bar])
```

There is usually a way to avoid this, however, and you are encouraged to simply call `AC_LIBOBJ` with literal arguments.

Note that this macro replaces the obsolete `AC_LIBOBJ_DECL`, with slightly different semantics: the old macro took the function name, e.g., `foo`, as its argument rather than the file name.

`AC_LIBSOURCES (files)` [Macro]

Like `AC_LIBSOURCE`, but accepts one or more *files* in a comma-separated M4 list. Thus, the above example might be rewritten:

```
AC_LIBSOURCES([foo.c, bar.c])
AC_LIBOBJ([$foo_or_bar])
```

`AC_CONFIG_LIBOBJ_DIR (directory)` [Macro]

Specify that `AC_LIBOBJ` replacement files are to be found in *directory*, a name relative to the top level of the source tree. The replacement directory defaults to '`.`', the top level directory, and the most typical value is '`lib`', corresponding to '`AC_CONFIG_LIBOBJ_DIR([lib])`'.

`configure` might need to know the replacement directory for the following reasons: (i) some checks use the replacement files, (ii) some macros bypass broken system headers by installing links to the replacement headers (iii) when used in conjunction with Automake, within each makefile, *directory* is used as a relative path from `$(top_srcdir)` to each object named in `LIBOBJS` and `LTLIBOBJS`, etc.

It is common to merely check for the existence of a function, and ask for its `AC_LIBOBJ` replacement if missing. The following macro is a convenient shorthand.

`AC_REPLACE_FUNCS (function...)` [Macro]

Like `AC_CHECK_FUNCS`, but uses '`AC_LIBOBJ(function)`' as *action-if-not-found*. You can declare your replacement function by enclosing the prototype in '`#ifndef HAVE_function`'. If the system has the function, it probably declares it in a header file you should be including, so you shouldn't redeclare it lest your declaration conflict.

5.6 Header Files

The following macros check for the presence of certain C header files. If there is no macro specifically defined to check for a header file you need, and you don't need to check for any special properties of it, then you can use one of the general header-file check macros.

5.6.1 Portability of Headers

This section tries to collect knowledge about common headers, and the problems they cause. By definition, this list always requires additions. Please help us keeping it as complete as possible.

'limits.h'
: C99 says that 'limits.h' defines LLONG_MIN, LLONG_MAX, and ULLONG_MAX, but many almost-C99 environments (e.g., default GCC 4.0.2 + glibc 2.4) do not define them.

'inttypes.h' vs. 'stdint.h'
: The C99 standard says that 'inttypes.h' includes 'stdint.h', so there's no need to include 'stdint.h' separately in a standard environment. Some implementations have 'inttypes.h' but not 'stdint.h' (e.g., Solaris 7), but we don't know of any implementation that has 'stdint.h' but not 'inttypes.h'.

'linux/irda.h'
: It requires 'linux/types.h' and 'sys/socket.h'.

'linux/random.h'
: It requires 'linux/types.h'.

'net/if.h'
: On Darwin, this file requires that 'sys/socket.h' be included beforehand. One should run:

```
AC_CHECK_HEADERS([sys/socket.h])
AC_CHECK_HEADERS([net/if.h], [], [],
[#include <stdio.h>
#ifdef STDC_HEADERS
# include <stdlib.h>
# include <stddef.h>
#else
# ifdef HAVE_STDLIB_H
#  include <stdlib.h>
# endif
#endif
#ifdef HAVE_SYS_SOCKET_H
# include <sys/socket.h>
#endif
])
```

'netinet/if_ether.h'
: On Darwin, this file requires that 'stdio.h' and 'sys/socket.h' be included beforehand. One should run:

```
AC_CHECK_HEADERS([sys/socket.h])
AC_CHECK_HEADERS([netinet/if_ether.h], [], [],
[#include <stdio.h>
#ifdef STDC_HEADERS
# include <stdlib.h>
# include <stddef.h>
#else
# ifdef HAVE_STDLIB_H
#  include <stdlib.h>
# endif
```

```
#endif
#ifdef HAVE_SYS_SOCKET_H
# include <sys/socket.h>
#endif
])
```

'stdint.h'
: See above, item 'inttypes.h' vs. 'stdint.h'.

'stdlib.h'
: On many systems (e.g., Darwin), 'stdio.h' is a prerequisite.

'sys/mount.h'
: On FreeBSD 4.8 on ia32 and using gcc version 2.95.4, 'sys/params.h' is a prerequisite.

'sys/ptem.h'
: On Solaris 8, 'sys/stream.h' is a prerequisite.

'sys/socket.h'
: On Darwin, 'stdlib.h' is a prerequisite.

'sys/ucred.h'
: On Tru64 5.1, 'sys/types.h' is a prerequisite.

'X11/extensions/scrnsaver.h'
: Using XFree86, this header requires 'X11/Xlib.h', which is probably so required that you might not even consider looking for it.

```
AC_CHECK_HEADERS([X11/extensions/scrnsaver.h], [], [],
[[#include <X11/Xlib.h>
]])
```

5.6.2 Particular Header Checks

These macros check for particular system header files—whether they exist, and in some cases whether they declare certain symbols.

AC_HEADER_ASSERT [Macro]

Check whether to enable assertions in the style of 'assert.h'. Assertions are enabled by default, but the user can override this by invoking configure with the '--disable-assert' option.

AC_HEADER_DIRENT [Macro]

Check for the following header files. For the first one that is found and defines 'DIR', define the listed C preprocessor macro:

'dirent.h'	HAVE_DIRENT_H
'sys/ndir.h'	HAVE_SYS_NDIR_H
'sys/dir.h'	HAVE_SYS_DIR_H
'ndir.h'	HAVE_NDIR_H

The directory-library declarations in your source code should look something like the following:

```
#include <sys/types.h>
#ifdef HAVE_DIRENT_H
# include <dirent.h>
# define NAMLEN(dirent) strlen ((dirent)->d_name)
#else
# define dirent direct
# define NAMLEN(dirent) ((dirent)->d_namlen)
# ifdef HAVE_SYS_NDIR_H
#  include <sys/ndir.h>
# endif
# ifdef HAVE_SYS_DIR_H
#  include <sys/dir.h>
# endif
# ifdef HAVE_NDIR_H
#  include <ndir.h>
# endif
#endif
```

Using the above declarations, the program would declare variables to be of type `struct dirent`, not `struct direct`, and would access the length of a directory entry name by passing a pointer to a `struct dirent` to the `NAMLEN` macro.

This macro also checks for the SCO Xenix '`dir`' and '`x`' libraries.

This macro is obsolescent, as all current systems with directory libraries have `<dirent.h>`. New programs need not use this macro.

Also see `AC_STRUCT_DIRENT_D_INO` and `AC_STRUCT_DIRENT_D_TYPE` (see Section 5.8.1 [Particular Structures], page 67).

`AC_HEADER_MAJOR` [Macro]

If '`sys/types.h`' does not define `major`, `minor`, and `makedev`, but '`sys/mkdev.h`' does, define `MAJOR_IN_MKDEV`; otherwise, if '`sys/sysmacros.h`' does, define `MAJOR_IN_SYSMACROS`.

`AC_HEADER_RESOLV` [Macro]

Checks for header '`resolv.h`', checking for prerequisites first. To properly use '`resolv.h`', your code should contain something like the following:

```
#ifdef HAVE_SYS_TYPES_H
#  include <sys/types.h>
#endif
#ifdef HAVE_NETINET_IN_H
#  include <netinet/in.h>   /* inet_ functions / structs */
#endif
#ifdef HAVE_ARPA_NAMESER_H
#  include <arpa/nameser.h> /* DNS HEADER struct */
#endif
#ifdef HAVE_NETDB_H
#  include <netdb.h>
#endif
#include <resolv.h>
```

AC_HEADER_STAT [Macro]

If the macros S_ISDIR, S_ISREG, etc. defined in 'sys/stat.h' do not work properly (returning false positives), define STAT_MACROS_BROKEN. This is the case on Tektronix UTekV, Amdahl UTS and Motorola System V/88.

This macro is obsolescent, as no current systems have the bug. New programs need not use this macro.

AC_HEADER_STDBOOL [Macro]

If 'stdbool.h' exists and conforms to C99, define HAVE_STDBOOL_H to 1; if the type _Bool is defined, define HAVE__BOOL to 1. To fulfill the C99 requirements, your 'system.h' could contain the following code:

```
#ifdef HAVE_STDBOOL_H
# include <stdbool.h>
#else
# ifndef HAVE__BOOL
#  ifdef __cplusplus
typedef bool _Bool;
#  else
#   define _Bool signed char
#  endif
# endif
# define bool _Bool
# define false 0
# define true 1
# define __bool_true_false_are_defined 1
#endif
```

Alternatively you can use the 'stdbool' package of Gnulib (see Section 2.2 [Gnulib], page 3); it packages the above code into a replacement header and contains a few other bells and whistles.

AC_HEADER_STDC [Macro]

Define STDC_HEADERS if the system has C header files conforming to ANSI C89 (ISO C90). Specifically, this macro checks for 'stdlib.h', 'stdarg.h', 'string.h', and 'float.h'; if the system has those, it probably has the rest of the C89 header files. This macro also checks whether 'string.h' declares memchr (and thus presumably the other mem functions), whether 'stdlib.h' declare free (and thus presumably malloc and other related functions), and whether the 'ctype.h' macros work on characters with the high bit set, as the C standard requires.

If you use this macro, your code can refer to STDC_HEADERS to determine whether the system has conforming header files (and probably C library functions).

This macro is obsolescent, as current systems have conforming header files. New programs need not use this macro.

Nowadays 'string.h' is part of the C standard and declares functions like strcpy, and 'strings.h' is standardized by Posix and declares BSD functions like bcopy; but historically, string functions were a major sticking point in this area. If you still want to worry about portability to ancient systems without standard headers, there is so

much variation that it is probably easier to declare the functions you use than to figure out exactly what the system header files declare. Some ancient systems contained a mix of functions from the C standard and from BSD; some were mostly standard but lacked 'memmove'; some defined the BSD functions as macros in 'string.h' or 'strings.h'; some had only the BSD functions but 'string.h'; some declared the memory functions in 'memory.h', some in 'string.h'; etc. It is probably sufficient to check for one string function and one memory function; if the library had the standard versions of those then it probably had most of the others. If you put the following in 'configure.ac':

```
# This example is obsolescent.
# Nowadays you can omit these macro calls.
AC_HEADER_STDC
AC_CHECK_FUNCS([strchr memcpy])
```

then, in your code, you can use declarations like this:

```
/* This example is obsolescent.
   Nowadays you can just #include <string.h>.  */
#ifdef STDC_HEADERS
# include <string.h>
#else
# ifndef HAVE_STRCHR
#  define strchr index
#  define strrchr rindex
# endif
char *strchr (), *strrchr ();
# ifndef HAVE_MEMCPY
#  define memcpy(d, s, n) bcopy ((s), (d), (n))
#  define memmove(d, s, n) bcopy ((s), (d), (n))
# endif
#endif
```

If you use a function like memchr, memset, strtok, or strspn, which have no BSD equivalent, then macros don't suffice to port to ancient hosts; you must provide an implementation of each function. An easy way to incorporate your implementations only when needed (since the ones in system C libraries may be hand optimized) is to, taking memchr for example, put it in 'memchr.c' and use 'AC_REPLACE_FUNCS([memchr])'.

AC_HEADER_SYS_WAIT [Macro]

If 'sys/wait.h' exists and is compatible with Posix, define HAVE_SYS_WAIT_H. Incompatibility can occur if 'sys/wait.h' does not exist, or if it uses the old BSD union wait instead of int to store a status value. If 'sys/wait.h' is not Posix compatible, then instead of including it, define the Posix macros with their usual interpretations. Here is an example:

```
#include <sys/types.h>
#ifdef HAVE_SYS_WAIT_H
# include <sys/wait.h>
#endif
#ifndef WEXITSTATUS
# define WEXITSTATUS(stat_val) ((unsigned int) (stat_val) >> 8)
#endif
#ifndef WIFEXITED
# define WIFEXITED(stat_val) (((stat_val) & 255) == 0)
#endif
```

This macro is obsolescent, as current systems are compatible with Posix. New programs need not use this macro.

`_POSIX_VERSION` is defined when '`unistd.h`' is included on Posix systems. If there is no '`unistd.h`', it is definitely not a Posix system. However, some non-Posix systems do have '`unistd.h`'.

The way to check whether the system supports Posix is:

```
#ifdef HAVE_UNISTD_H
# include <sys/types.h>
# include <unistd.h>
#endif

#ifdef _POSIX_VERSION
/* Code for Posix systems.  */
#endif
```

`AC_HEADER_TIME` [Macro]

If a program may include both '`time.h`' and '`sys/time.h`', define `TIME_WITH_SYS_TIME`. On some ancient systems, '`sys/time.h`' included '`time.h`', but '`time.h`' was not protected against multiple inclusion, so programs could not explicitly include both files. This macro is useful in programs that use, for example, `struct timeval` as well as `struct tm`. It is best used in conjunction with `HAVE_SYS_TIME_H`, which can be checked for using `AC_CHECK_HEADERS([sys/time.h])`.

```
#ifdef TIME_WITH_SYS_TIME
# include <sys/time.h>
# include <time.h>
#else
# ifdef HAVE_SYS_TIME_H
#  include <sys/time.h>
# else
#  include <time.h>
# endif
#endif
```

This macro is obsolescent, as current systems can include both files when they exist. New programs need not use this macro.

AC_HEADER_TIOCGWINSZ [Macro]

If the use of TIOCGWINSZ requires '<sys/ioctl.h>', then define GWINSZ_IN_SYS_IOCTL. Otherwise TIOCGWINSZ can be found in '<termios.h>'.

Use:

```
#ifdef HAVE_TERMIOS_H
# include <termios.h>
#endif

#ifdef GWINSZ_IN_SYS_IOCTL
# include <sys/ioctl.h>
#endif
```

5.6.3 Generic Header Checks

These macros are used to find system header files not covered by the "particular" test macros. If you need to check the contents of a header as well as find out whether it is present, you have to write your own test for it (see Chapter 6 [Writing Tests], page 91).

AC_CHECK_HEADER (*header-file*, [*action-if-found*], [*action-if-not-found*], [*includes* = 'AC_INCLUDES_DEFAULT']) [Macro]

If the system header file *header-file* is compilable, execute shell commands *action-if-found*, otherwise execute *action-if-not-found*. If you just want to define a symbol if the header file is available, consider using AC_CHECK_HEADERS instead.

includes is a series of include directives, defaulting to AC_INCLUDES_DEFAULT (see Section 5.1.2 [Default Includes], page 39), which are used prior to the header under test.

For compatibility issues with older versions of Autoconf, please read below.

AC_CHECK_HEADERS (*header-file* ..., [*action-if-found*], [*action-if-not-found*], [*includes* = 'AC_INCLUDES_DEFAULT']) [Macro]

For each given system header file *header-file* in the blank-separated argument list that exists, define HAVE_*header-file* (in all capitals). If *action-if-found* is given, it is additional shell code to execute when one of the header files is found. You can give it a value of 'break' to break out of the loop on the first match. If *action-if-not-found* is given, it is executed when one of the header files is not found.

includes is a series of include directives, defaulting to AC_INCLUDES_DEFAULT (see Section 5.1.2 [Default Includes], page 39), which are used prior to the headers under test.

For compatibility issues with older versions of Autoconf, please read below.

Previous versions of Autoconf merely checked whether the header was accepted by the preprocessor. This was changed because the old test was inappropriate for typical uses. Headers are typically used to compile, not merely to preprocess, and the old behavior sometimes accepted headers that clashed at compile-time. If you need to check whether a header is preprocessable, you can use AC_PREPROC_IFELSE (see Section 6.3 [Running the Preprocessor], page 96).

This scheme, which improves the robustness of the test, also requires that you make sure that headers that must be included before the *header-file* be part of the *includes*, (see Section 5.1.2 [Default Includes], page 39). If looking for '`bar.h`', which requires that '`foo.h`' be included before if it exists, we suggest the following scheme:

```
AC_CHECK_HEADERS([foo.h])
AC_CHECK_HEADERS([bar.h], [], [],
[#ifdef HAVE_FOO_H
# include <foo.h>
# endif
])
```

The following variant generates smaller, faster `configure` files if you do not need the full power of `AC_CHECK_HEADERS`.

`AC_CHECK_HEADERS_ONCE (header-file...)` [Macro]

For each given system header file *header-file* in the blank-separated argument list that exists, define `HAVE_header-file` (in all capitals). This is a once-only variant of `AC_CHECK_HEADERS`. It generates the checking code at most once, so that `configure` is smaller and faster; but the checks cannot be conditionalized and are always done once, early during the `configure` run.

5.7 Declarations

The following macros check for the declaration of variables and functions. If there is no macro specifically defined to check for a symbol you need, then you can use the general macros (see Section 5.7.2 [Generic Declarations], page 66) or, for more complex tests, you may use `AC_COMPILE_IFELSE` (see Section 6.4 [Running the Compiler], page 97).

5.7.1 Particular Declaration Checks

There are no specific macros for declarations.

5.7.2 Generic Declaration Checks

These macros are used to find declarations not covered by the "particular" test macros.

`AC_CHECK_DECL (symbol, [action-if-found], [action-if-not-found], [includes = 'AC_INCLUDES_DEFAULT'])` [Macro]

If *symbol* (a function, variable, or constant) is not declared in *includes* and a declaration is needed, run the shell commands *action-if-not-found*, otherwise *action-if-found*. *includes* is a series of include directives, defaulting to `AC_INCLUDES_DEFAULT` (see Section 5.1.2 [Default Includes], page 39), which are used prior to the declaration under test.

This macro actually tests whether *symbol* is defined as a macro or can be used as an r-value, not whether it is really declared, because it is much safer to avoid introducing extra declarations when they are not needed.

`AC_CHECK_DECLS (symbols, [action-if-found], [action-if-not-found], [includes = 'AC_INCLUDES_DEFAULT'])` [Macro]

For each of the *symbols* (*comma*-separated list), define `HAVE_DECL_symbol` (in all capitals) to '`1`' if *symbol* is declared, otherwise to '`0`'. If *action-if-not-found* is given,

it is additional shell code to execute when one of the function declarations is needed, otherwise *action-if-found* is executed.

includes is a series of include directives, defaulting to `AC_INCLUDES_DEFAULT` (see Section 5.1.2 [Default Includes], page 39), which are used prior to the declarations under test.

This macro uses an M4 list as first argument:

```
AC_CHECK_DECLS([strdup])
AC_CHECK_DECLS([strlen])
AC_CHECK_DECLS([malloc, realloc, calloc, free])
AC_CHECK_DECLS([j0], [], [], [[#include <math.h>]])
```

Unlike the other '`AC_CHECK_*S`' macros, when a *symbol* is not declared, `HAVE_DECL_`*`symbol`* is defined to '`0`' instead of leaving `HAVE_DECL_`*`symbol`* undeclared. When you are *sure* that the check was performed, use `HAVE_DECL_`*`symbol`* in `#if`:

```
#if !HAVE_DECL_SYMBOL
extern char *symbol;
#endif
```

If the test may have not been performed, however, because it is safer *not* to declare a symbol than to use a declaration that conflicts with the system's one, you should use:

```
#if defined HAVE_DECL_MALLOC && !HAVE_DECL_MALLOC
void *malloc (size_t *s);
#endif
```

You fall into the second category only in extreme situations: either your files may be used without being configured, or they are used during the configuration. In most cases the traditional approach is enough.

`AC_CHECK_DECLS_ONCE (`*`symbols`*`)` [Macro]

For each of the *symbols* (*comma*-separated list), define `HAVE_DECL_`*`symbol`* (in all capitals) to '`1`' if *symbol* is declared in the default include files, otherwise to '`0`'. This is a once-only variant of `AC_CHECK_DECLS`. It generates the checking code at most once, so that `configure` is smaller and faster; but the checks cannot be conditionalized and are always done once, early during the `configure` run.

5.8 Structures

The following macros check for the presence of certain members in C structures. If there is no macro specifically defined to check for a member you need, then you can use the general structure-member macros (see Section 5.8.2 [Generic Structures], page 68) or, for more complex tests, you may use `AC_COMPILE_IFELSE` (see Section 6.4 [Running the Compiler], page 97).

5.8.1 Particular Structure Checks

The following macros check for certain structures or structure members.

AC_STRUCT_DIRENT_D_INO [Macro]

Perform all the actions of AC_HEADER_DIRENT (see Section 5.6.2 [Particular Headers], page 60). Then, if struct dirent contains a d_ino member, define HAVE_STRUCT_DIRENT_D_INO.

HAVE_STRUCT_DIRENT_D_INO indicates only the presence of d_ino, not whether its contents are always reliable. Traditionally, a zero d_ino indicated a deleted directory entry, though current systems hide this detail from the user and never return zero d_ino values. Many current systems report an incorrect d_ino for a directory entry that is a mount point.

AC_STRUCT_DIRENT_D_TYPE [Macro]

Perform all the actions of AC_HEADER_DIRENT (see Section 5.6.2 [Particular Headers], page 60). Then, if struct dirent contains a d_type member, define HAVE_STRUCT_DIRENT_D_TYPE.

AC_STRUCT_ST_BLOCKS [Macro]

If struct stat contains an st_blocks member, define HAVE_STRUCT_STAT_ST_BLOCKS. Otherwise, require an AC_LIBOBJ replacement of 'fileblocks'. The former name, HAVE_ST_BLOCKS is to be avoided, as its support will cease in the future.

AC_STRUCT_TM [Macro]

If 'time.h' does not define struct tm, define TM_IN_SYS_TIME, which means that including 'sys/time.h' had better define struct tm.

This macro is obsolescent, as 'time.h' defines struct tm in current systems. New programs need not use this macro.

AC_STRUCT_TIMEZONE [Macro]

Figure out how to get the current timezone. If struct tm has a tm_zone member, define HAVE_STRUCT_TM_TM_ZONE (and the obsoleted HAVE_TM_ZONE). Otherwise, if the external array tzname is found, define HAVE_TZNAME; if it is declared, define HAVE_DECL_TZNAME.

5.8.2 Generic Structure Checks

These macros are used to find structure members not covered by the "particular" test macros.

AC_CHECK_MEMBER (*aggregate.member*, [*action-if-found*], [*action-if-not-found*], [*includes* = 'AC_INCLUDES_DEFAULT']) [Macro]

Check whether *member* is a member of the aggregate *aggregate*. If no *includes* are specified, the default includes are used (see Section 5.1.2 [Default Includes], page 39).

```
AC_CHECK_MEMBER([struct passwd.pw_gecos], [],
                [AC_MSG_ERROR([We need 'passwd.pw_gecos'!])],
                [[#include <pwd.h>]])
```

You can use this macro for submembers:

```
AC_CHECK_MEMBER(struct top.middle.bot)
```

AC_CHECK_MEMBERS (*members*, [*action-if-found*], [*action-if-not-found*], [*includes* = 'AC_INCLUDES_DEFAULT']) [Macro]

Check for the existence of each '*aggregate.member*' of *members* using the previous macro. When *member* belongs to *aggregate*, define HAVE_*aggregate*_*member* (in all capitals, with spaces and dots replaced by underscores). If *action-if-found* is given, it is executed for each of the found members. If *action-if-not-found* is given, it is executed for each of the members that could not be found.

includes is a series of include directives, defaulting to AC_INCLUDES_DEFAULT (see Section 5.1.2 [Default Includes], page 39), which are used prior to the members under test.

This macro uses M4 lists:

```
AC_CHECK_MEMBERS([struct stat.st_rdev, struct stat.st_blksize])
```

5.9 Types

The following macros check for C types, either builtin or typedefs. If there is no macro specifically defined to check for a type you need, and you don't need to check for any special properties of it, then you can use a general type-check macro.

5.9.1 Particular Type Checks

These macros check for particular C types in 'sys/types.h', 'stdlib.h', 'stdint.h', 'inttypes.h' and others, if they exist.

The Gnulib stdint module is an alternate way to define many of these symbols; it is useful if you prefer your code to assume a C99-or-better environment. See Section 2.2 [Gnulib], page 3.

AC_TYPE_GETGROUPS [Macro]

Define GETGROUPS_T to be whichever of gid_t or int is the base type of the array argument to getgroups.

AC_TYPE_INT8_T [Macro]

If 'stdint.h' or 'inttypes.h' does not define the type int8_t, define int8_t to a signed integer type that is exactly 8 bits wide and that uses two's complement representation, if such a type exists. If you are worried about porting to hosts that lack such a type, you can use the results of this macro in C89-or-later code as follows:

```
#if HAVE_STDINT_H
# include <stdint.h>
#endif
#if defined INT8_MAX || defined int8_t
 code using int8_t
#else
 complicated alternative using >8-bit 'signed char'
#endif
```

AC_TYPE_INT16_T [Macro]

This is like AC_TYPE_INT8_T, except for 16-bit integers.

AC_TYPE_INT32_T [Macro]

This is like AC_TYPE_INT8_T, except for 32-bit integers.

AC_TYPE_INT64_T [Macro]

This is like AC_TYPE_INT8_T, except for 64-bit integers.

AC_TYPE_INTMAX_T [Macro]

If 'stdint.h' or 'inttypes.h' defines the type intmax_t, define HAVE_INTMAX_T. Otherwise, define intmax_t to the widest signed integer type.

AC_TYPE_INTPTR_T [Macro]

If 'stdint.h' or 'inttypes.h' defines the type intptr_t, define HAVE_INTPTR_T. Otherwise, define intptr_t to a signed integer type wide enough to hold a pointer, if such a type exists.

AC_TYPE_LONG_DOUBLE [Macro]

If the C compiler supports a working long double type, define HAVE_LONG_DOUBLE. The long double type might have the same range and precision as double.

This macro is obsolescent, as current C compilers support long double. New programs need not use this macro.

AC_TYPE_LONG_DOUBLE_WIDER [Macro]

If the C compiler supports a working long double type with more range or precision than the double type, define HAVE_LONG_DOUBLE_WIDER.

AC_TYPE_LONG_LONG_INT [Macro]

If the C compiler supports a working long long int type, define HAVE_LONG_LONG_INT. However, this test does not test long long int values in preprocessor #if expressions, because too many compilers mishandle such expressions. See Section 12.3 [Preprocessor Arithmetic], page 216.

AC_TYPE_MBSTATE_T [Macro]

Define HAVE_MBSTATE_T if <wchar.h> declares the mbstate_t type. Also, define mbstate_t to be a type if <wchar.h> does not declare it.

AC_TYPE_MODE_T [Macro]

Define mode_t to a suitable type, if standard headers do not define it.

AC_TYPE_OFF_T [Macro]

Define off_t to a suitable type, if standard headers do not define it.

AC_TYPE_PID_T [Macro]

Define pid_t to a suitable type, if standard headers do not define it.

AC_TYPE_SIGNAL [Macro]

If 'signal.h' declares signal as returning a pointer to a function returning void, define RETSIGTYPE to be void; otherwise, define it to be int.

Define signal handlers as returning type RETSIGTYPE:

```
RETSIGTYPE
hup_handler ()
{
...
}
```

AC_TYPE_SIZE_T [Macro]

Define size_t to a suitable type, if standard headers do not define it.

AC_TYPE_SSIZE_T [Macro]

Define ssize_t to a suitable type, if standard headers do not define it.

AC_TYPE_UID_T [Macro]

Define uid_t and gid_t to suitable types, if standard headers do not define them.

AC_TYPE_UINT8_T [Macro]

If 'stdint.h' or 'inttypes.h' does not define the type uint8_t, define uint8_t to an unsigned integer type that is exactly 8 bits wide, if such a type exists. This is like AC_TYPE_INT8_T, except for unsigned integers.

AC_TYPE_UINT16_T [Macro]

This is like AC_TYPE_UINT8_T, except for 16-bit integers.

AC_TYPE_UINT32_T [Macro]

This is like AC_TYPE_UINT8_T, except for 32-bit integers.

AC_TYPE_UINT64_T [Macro]

This is like AC_TYPE_UINT8_T, except for 64-bit integers.

AC_TYPE_UINTMAX_T [Macro]

If 'stdint.h' or 'inttypes.h' defines the type uintmax_t, define HAVE_UINTMAX_T. Otherwise, define uintmax_t to the widest unsigned integer type.

AC_TYPE_UINTPTR_T [Macro]

If 'stdint.h' or 'inttypes.h' defines the type uintptr_t, define HAVE_UINTPTR_T. Otherwise, define uintptr_t to an unsigned integer type wide enough to hold a pointer, if such a type exists.

AC_TYPE_UNSIGNED_LONG_LONG_INT [Macro]

If the C compiler supports a working unsigned long long int type, define HAVE_UNSIGNED_LONG_LONG_INT. However, this test does not test unsigned long long int values in preprocessor #if expressions, because too many compilers mishandle such expressions. See Section 12.3 [Preprocessor Arithmetic], page 216.

5.9.2 Generic Type Checks

These macros are used to check for types not covered by the "particular" test macros.

AC_CHECK_TYPE (*type*, [*action-if-found*], [*action-if-not-found*], [*includes* = 'AC_INCLUDES_DEFAULT']) [Macro]

Check whether *type* is defined. It may be a compiler builtin type or defined by the *includes*. *includes* is a series of include directives, defaulting to AC_INCLUDES_DEFAULT (see Section 5.1.2 [Default Includes], page 39), which are used prior to the type under test.

In C, *type* must be a type-name, so that the expression 'sizeof (*type*)' is valid (but 'sizeof ((*type*))' is not). The same test is applied when compiling for C++, which means that in C++ *type* should be a type-id and should not be an anonymous 'struct' or 'union'.

AC_CHECK_TYPES (*types*, [*action-if-found*], [*action-if-not-found*], [*includes* = 'AC_INCLUDES_DEFAULT']) [Macro]

For each *type* of the *types* that is defined, define HAVE_*type* (in all capitals). Each *type* must follow the rules of AC_CHECK_TYPE. If no *includes* are specified, the default includes are used (see Section 5.1.2 [Default Includes], page 39). If *action-if-found* is given, it is additional shell code to execute when one of the types is found. If *action-if-not-found* is given, it is executed when one of the types is not found.

This macro uses M4 lists:

```
AC_CHECK_TYPES([ptrdiff_t])
AC_CHECK_TYPES([unsigned long long int, uintmax_t])
AC_CHECK_TYPES([float_t], [], [], [[#include <math.h>]])
```

Autoconf, up to 2.13, used to provide to another version of AC_CHECK_TYPE, broken by design. In order to keep backward compatibility, a simple heuristic, quite safe but not totally, is implemented. In case of doubt, read the documentation of the former AC_CHECK_TYPE, see Section 17.4 [Obsolete Macros], page 243.

5.10 Compilers and Preprocessors

All the tests for compilers (AC_PROG_CC, AC_PROG_CXX, AC_PROG_F77) define the output variable EXEEXT based on the output of the compiler, typically to the empty string if Posix and '.exe' if a DOS variant.

They also define the output variable OBJEXT based on the output of the compiler, after '.c' files have been excluded, typically to 'o' if Posix, 'obj' if a DOS variant.

If the compiler being used does not produce executables, the tests fail. If the executables can't be run, and cross-compilation is not enabled, they fail too. See Chapter 13 [Manual Configuration], page 221, for more on support for cross compiling.

5.10.1 Specific Compiler Characteristics

Some compilers exhibit different behaviors.

Static/Dynamic Expressions

Autoconf relies on a trick to extract one bit of information from the C compiler: using negative array sizes. For instance the following excerpt of a C source demonstrates how to test whether 'int' objects are 4 bytes wide:

```
static int test_array[sizeof (int) == 4 ? 1 : -1];
```

To our knowledge, there is a single compiler that does not support this trick: the HP C compilers (the real ones, not only the "bundled") on HP-UX 11.00. They incorrectly reject the above program with the diagnostic "Variable-length arrays cannot have static storage." This bug comes from HP compilers' mishandling of `sizeof (int)`, not from the `? 1 : -1`, and Autoconf works around this problem by casting `sizeof (int)` to `long int` before comparing it.

5.10.2 Generic Compiler Characteristics

`AC_CHECK_SIZEOF (`*type-or-expr*, [*unused*], [*includes* = '`AC_INCLUDES_DEFAULT`'])` [Macro]

Define `SIZEOF_`*type-or-expr* (see Section 5.1.1 [Standard Symbols], page 39) to be the size in bytes of *type-or-expr*, which may be either a type or an expression returning a value that has a size. If the expression '`sizeof (`*type-or-expr*`)`' is invalid, the result is 0. *includes* is a series of include directives, defaulting to `AC_INCLUDES_DEFAULT` (see Section 5.1.2 [Default Includes], page 39), which are used prior to the expression under test.

This macro now works even when cross-compiling. The *unused* argument was used when cross-compiling.

For example, the call

```
AC_CHECK_SIZEOF([int *])
```

defines `SIZEOF_INT_P` to be 8 on DEC Alpha AXP systems.

`AC_CHECK_ALIGNOF (`*type*, [*includes* = '`AC_INCLUDES_DEFAULT`'])` [Macro]

Define `ALIGNOF_`*type* (see Section 5.1.1 [Standard Symbols], page 39) to be the alignment in bytes of *type*. '*type* `y;`' must be valid as a structure member declaration. If '`type`' is unknown, the result is 0. If no *includes* are specified, the default includes are used (see Section 5.1.2 [Default Includes], page 39).

`AC_COMPUTE_INT (`*var*, *expression*, [*includes* = '`AC_INCLUDES_DEFAULT`'], [*action-if-fails*])` [Macro]

Store into the shell variable *var* the value of the integer *expression*. The value should fit in an initializer in a C variable of type `signed long`. To support cross compilation (in which case, the macro only works on hosts that use twos-complement arithmetic), it should be possible to evaluate the expression at compile-time. If no *includes* are specified, the default includes are used (see Section 5.1.2 [Default Includes], page 39).

Execute *action-if-fails* if the value cannot be determined correctly.

`AC_LANG_WERROR` [Macro]

Normally Autoconf ignores warnings generated by the compiler, linker, and preprocessor. If this macro is used, warnings count as fatal errors for the current language. This macro is useful when the results of configuration are used where warnings are unacceptable; for instance, if parts of a program are built with the GCC '`-Werror`' option. If the whole program is built using '`-Werror`' it is often simpler to put '`-Werror`' in the compiler flags (`CFLAGS`, etc.).

AC_OPENMP [Macro]

OpenMP (http://www.openmp.org/) specifies extensions of C, C++, and Fortran that simplify optimization of shared memory parallelism, which is a common problem on multicore CPUs.

If the current language is C, the macro AC_OPENMP sets the variable OPENMP_CFLAGS to the C compiler flags needed for supporting OpenMP. OPENMP_CFLAGS is set to empty if the compiler already supports OpenMP, if it has no way to activate OpenMP support, or if the user rejects OpenMP support by invoking 'configure' with the '--disable-openmp' option.

OPENMP_CFLAGS needs to be used when compiling programs, when preprocessing program source, and when linking programs. Therefore you need to add $(OPENMP_CFLAGS) to the CFLAGS of C programs that use OpenMP. If you preprocess OpenMP-specific C code, you also need to add $(OPENMP_CFLAGS) to CPPFLAGS. The presence of OpenMP support is revealed at compile time by the preprocessor macro _OPENMP.

Linking a program with OPENMP_CFLAGS typically adds one more shared library to the program's dependencies, so its use is recommended only on programs that actually require OpenMP.

If the current language is C++, AC_OPENMP sets the variable OPENMP_CXXFLAGS, suitably for the C++ compiler. The same remarks hold as for C.

If the current language is Fortran 77 or Fortran, AC_OPENMP sets the variable OPENMP_FFLAGS or OPENMP_FCFLAGS, respectively. Similar remarks as for C hold, except that CPPFLAGS is not used for Fortran, and no preprocessor macro signals OpenMP support.

5.10.3 C Compiler Characteristics

The following macros provide ways to find and exercise a C Compiler. There are a few constructs that ought to be avoided, but do not deserve being checked for, since they can easily be worked around.

Don't use lines containing solitary backslashes

They tickle a bug in the HP-UX C compiler (checked on HP-UX 10.20, 11.00, and 11i). When given the following source:

```
#ifdef __STDC__
/\
* A comment with backslash-newlines in it.  %{ %} *\
\
/
char str[] = "\\
" A string with backslash-newlines in it %{ %} \\
"";
char apostrophe = '\\
\
'\
';
#endif
```

the compiler incorrectly fails with the diagnostics "Non-terminating comment at end of file" and "Missing '`#endif`' at end of file." Removing the lines with solitary backslashes solves the problem.

Don't compile several files at once if output matters to you

Some compilers, such as HP's, report names of files being compiled when given more than one file operand. For instance:

```
$ cc a.c b.c
a.c:
b.c:
```

This can cause problems if you observe the output of the compiler to detect failures. Invoking '`cc -c a.c && cc -c b.c && cc -o c a.o b.o`' solves the issue.

Don't rely on `#error` failing

The IRIX C compiler does not fail when #error is preprocessed; it simply emits a diagnostic and continues, exiting successfully. So, instead of an error directive like `#error "Unsupported word size"` it is more portable to use an invalid directive like `#Unsupported word size` in Autoconf tests. In ordinary source code, `#error` is OK, since installers with inadequate compilers like IRIX can simply examine these compilers' diagnostic output.

Don't rely on correct `#line` support

On Solaris, `c89` (at least Sun C 5.3 through 5.8) diagnoses `#line` directives whose line numbers are greater than 32767. Nothing in Posix makes this invalid. That is why Autoconf stopped issuing `#line` directives.

`AC_PROG_CC` ([*compiler-search-list*]) [Macro]

Determine a C compiler to use. If `CC` is not already set in the environment, check for `gcc` and `cc`, then for other C compilers. Set output variable `CC` to the name of the compiler found.

This macro may, however, be invoked with an optional first argument which, if specified, must be a blank-separated list of C compilers to search for. This just gives the user an opportunity to specify an alternative search list for the C compiler. For example, if you didn't like the default order, then you could invoke `AC_PROG_CC` like this:

```
AC_PROG_CC([gcc cl cc])
```

If the C compiler does not handle function prototypes correctly by default, try to add an option to output variable `CC` to make it so. This macro tries various options that select standard-conformance modes on various systems.

After calling this macro you can check whether the C compiler has been set to accept ANSI C89 (ISO C90); if not, the shell variable `ac_cv_prog_cc_c89` is set to '`no`'. See also `AC_C_PROTOTYPES` below.

If using the GNU C compiler, set shell variable `GCC` to '`yes`'. If output variable `CFLAGS` was not already set, set it to '`-g -O2`' for the GNU C compiler ('`-O2`' on systems where GCC does not accept '`-g`'), or '`-g`' for other compilers.

AC_PROG_CC_C_O [Macro]

If the C compiler does not accept the '-c' and '-o' options simultaneously, define NO_MINUS_C_MINUS_O. This macro actually tests both the compiler found by AC_PROG_CC, and, if different, the first cc in the path. The test fails if one fails. This macro was created for GNU Make to choose the default C compilation rule.

AC_PROG_CPP [Macro]

Set output variable CPP to a command that runs the C preprocessor. If '$CC -E' doesn't work, '/lib/cpp' is used. It is only portable to run CPP on files with a '.c' extension.

Some preprocessors don't indicate missing include files by the error status. For such preprocessors an internal variable is set that causes other macros to check the standard error from the preprocessor and consider the test failed if any warnings have been reported. For most preprocessors, though, warnings do not cause include-file tests to fail unless AC_PROG_CPP_WERROR is also specified.

AC_PROG_CPP_WERROR [Macro]

This acts like AC_PROG_CPP, except it treats warnings from the preprocessor as errors even if the preprocessor exit status indicates success. This is useful for avoiding headers that generate mandatory warnings, such as deprecation notices.

The following macros check for C compiler or machine architecture features. To check for characteristics not listed here, use AC_COMPILE_IFELSE (see Section 6.4 [Running the Compiler], page 97) or AC_RUN_IFELSE (see Section 6.6 [Runtime], page 98).

AC_PROG_CC_STDC [Macro]

If the C compiler cannot compile ISO Standard C (currently C99), try to add an option to output variable CC to make it work. If the compiler does not support C99, fall back to supporting ANSI C89 (ISO C90).

After calling this macro you can check whether the C compiler has been set to accept Standard C; if not, the shell variable ac_cv_prog_cc_stdc is set to 'no'.

AC_PROG_CC_C89 [Macro]

If the C compiler is not in ANSI C89 (ISO C90) mode by default, try to add an option to output variable CC to make it so. This macro tries various options that select ANSI C89 on some system or another. It considers the compiler to be in ANSI C89 mode if it handles function prototypes correctly.

After calling this macro you can check whether the C compiler has been set to accept ANSI C89; if not, the shell variable ac_cv_prog_cc_c89 is set to 'no'.

This macro is called automatically by AC_PROG_CC.

AC_PROG_CC_C99 [Macro]

If the C compiler is not in C99 mode by default, try to add an option to output variable CC to make it so. This macro tries various options that select C99 on some system or another. It considers the compiler to be in C99 mode if it handles _Bool, // comments, flexible array members, inline, signed and unsigned long long int, mixed code and declarations, named initialization of structs, restrict, va_copy, varargs macros, variable declarations in for loops, and variable length arrays.

After calling this macro you can check whether the C compiler has been set to accept C99; if not, the shell variable `ac_cv_prog_cc_c99` is set to '`no`'.

`AC_C_BACKSLASH_A` [Macro]

Define '`HAVE_C_BACKSLASH_A`' to 1 if the C compiler understands '`\a`'.

This macro is obsolescent, as current C compilers understand '`\a`'. New programs need not use this macro.

`AC_C_BIGENDIAN` ([*action-if-true*], [*action-if-false*], [*action-if-unknown*], [*action-if-universal*]) [Macro]

If words are stored with the most significant byte first (like Motorola and SPARC CPUs), execute *action-if-true*. If words are stored with the least significant byte first (like Intel and VAX CPUs), execute *action-if-false*.

This macro runs a test-case if endianness cannot be determined from the system header files. When cross-compiling, the test-case is not run but grep'ed for some magic values. *action-if-unknown* is executed if the latter case fails to determine the byte sex of the host system.

In some cases a single run of a compiler can generate code for multiple architectures. This can happen, for example, when generating Mac OS X universal binary files, which work on both PowerPC and Intel architectures. In this case, the different variants might be for different architectures whose endiannesses differ. If `configure` detects this, it executes *action-if-universal* instead of *action-if-unknown*.

The default for *action-if-true* is to define '`WORDS_BIGENDIAN`'. The default for *action-if-false* is to do nothing. The default for *action-if-unknown* is to abort configure and tell the installer how to bypass this test. And finally, the default for *action-if-universal* is to define '`WORDS_BIGENDIAN`' or not, depending on the architecture that the code is being generated for.

If you use this macro without specifying *action-if-universal*, you should also use `AC_CONFIG_HEADERS`; otherwise '`WORDS_BIGENDIAN`' may be set incorrectly for Mac OS X universal binary files.

`AC_C_CONST` [Macro]

If the C compiler does not fully support the `const` keyword, define `const` to be empty. Some C compilers that do not define `__STDC__` do support `const`; some compilers that define `__STDC__` do not completely support `const`. Programs can simply use `const` as if every C compiler supported it; for those that don't, the makefile or configuration header file defines it as empty.

Occasionally installers use a C++ compiler to compile C code, typically because they lack a C compiler. This causes problems with `const`, because C and C++ treat `const` differently. For example:

```
const int foo;
```

is valid in C but not in C++. These differences unfortunately cannot be papered over by defining `const` to be empty.

If `autoconf` detects this situation, it leaves `const` alone, as this generally yields better results in practice. However, using a C++ compiler to compile C code is not

recommended or supported, and installers who run into trouble in this area should get a C compiler like GCC to compile their C code.

This macro is obsolescent, as current C compilers support `const`. New programs need not use this macro.

`AC_C_RESTRICT` [Macro]

If the C compiler recognizes a variant spelling for the `restrict` keyword (`__restrict`, `__restrict__`, or `_Restrict`), then define `restrict` to that; this is more likely to do the right thing with compilers that support language variants where plain `restrict` is not a keyword. Otherwise, if the C compiler recognizes the `restrict` keyword, don't do anything. Otherwise, define `restrict` to be empty. Thus, programs may simply use `restrict` as if every C compiler supported it; for those that do not, the makefile or configuration header defines it away.

Although support in C++ for the `restrict` keyword is not required, several C++ compilers do accept the keyword. This macro works for them, too.

`AC_C_VOLATILE` [Macro]

If the C compiler does not understand the keyword `volatile`, define `volatile` to be empty. Programs can simply use `volatile` as if every C compiler supported it; for those that do not, the makefile or configuration header defines it as empty.

If the correctness of your program depends on the semantics of `volatile`, simply defining it to be empty does, in a sense, break your code. However, given that the compiler does not support `volatile`, you are at its mercy anyway. At least your program compiles, when it wouldn't before. See Section 12.6 [Volatile Objects], page 217, for more about `volatile`.

In general, the `volatile` keyword is a standard C feature, so you might expect that `volatile` is available only when `__STDC__` is defined. However, Ultrix 4.3's native compiler does support volatile, but does not define `__STDC__`.

This macro is obsolescent, as current C compilers support `volatile`. New programs need not use this macro.

`AC_C_INLINE` [Macro]

If the C compiler supports the keyword `inline`, do nothing. Otherwise define `inline` to `__inline__` or `__inline` if it accepts one of those, otherwise define `inline` to be empty.

`AC_C_CHAR_UNSIGNED` [Macro]

If the C type `char` is unsigned, define `__CHAR_UNSIGNED__`, unless the C compiler predefines it.

`AC_C_STRINGIZE` [Macro]

If the C preprocessor supports the stringizing operator, define `HAVE_STRINGIZE`. The stringizing operator is '`#`' and is found in macros such as this:

```
#define x(y) #y
```

This macro is obsolescent, as current C compilers support the stringizing operator. New programs need not use this macro.

AC_C_FLEXIBLE_ARRAY_MEMBER [Macro]

If the C compiler supports flexible array members, define FLEXIBLE_ARRAY_MEMBER to nothing; otherwise define it to 1. That way, a declaration like this:

```
struct s
  {
    size_t n_vals;
    double val[FLEXIBLE_ARRAY_MEMBER];
  };
```

will let applications use the "struct hack" even with compilers that do not support flexible array members. To allocate and use such an object, you can use code like this:

```
size_t i;
size_t n = compute_value_count ();
struct s *p =
   malloc (offsetof (struct s, val)
           + n * sizeof (double));
p->n_vals = n;
for (i = 0; i < n; i++)
  p->val[i] = compute_value (i);
```

AC_C_VARARRAYS [Macro]

If the C compiler supports variable-length arrays, define HAVE_C_VARARRAYS. A variable-length array is an array of automatic storage duration whose length is determined at run time, when the array is declared.

AC_C_TYPEOF [Macro]

If the C compiler supports GCC's typeof syntax either directly or through a different spelling of the keyword (e.g., __typeof__), define HAVE_TYPEOF. If the support is available only through a different spelling, define typeof to that spelling.

AC_C_PROTOTYPES [Macro]

If function prototypes are understood by the compiler (as determined by AC_PROG_CC), define PROTOTYPES and __PROTOTYPES. Defining __PROTOTYPES is for the benefit of header files that cannot use macros that infringe on user name space.

This macro is obsolescent, as current C compilers support prototypes. New programs need not use this macro.

AC_PROG_GCC_TRADITIONAL [Macro]

Add '-traditional' to output variable CC if using the GNU C compiler and ioctl does not work properly without '-traditional'. That usually happens when the fixed header files have not been installed on an old system.

This macro is obsolescent, since current versions of the GNU C compiler fix the header files automatically when installed.

5.10.4 C++ Compiler Characteristics

AC_PROG_CXX ([*compiler-search-list*]) [Macro]

Determine a C++ compiler to use. Check whether the environment variable CXX or CCC (in that order) is set; if so, then set output variable CXX to its value.

Otherwise, if the macro is invoked without an argument, then search for a C++ compiler under the likely names (first g++ and c++ then other names). If none of those checks succeed, then as a last resort set CXX to g++.

This macro may, however, be invoked with an optional first argument which, if specified, must be a blank-separated list of C++ compilers to search for. This just gives the user an opportunity to specify an alternative search list for the C++ compiler. For example, if you didn't like the default order, then you could invoke AC_PROG_CXX like this:

```
AC_PROG_CXX([gcc cl KCC CC cxx cc++ xlC aCC c++ g++])
```

If using the GNU C++ compiler, set shell variable GXX to 'yes'. If output variable CXXFLAGS was not already set, set it to '-g -O2' for the GNU C++ compiler ('-O2' on systems where G++ does not accept '-g'), or '-g' for other compilers.

AC_PROG_CXXCPP [Macro]

Set output variable CXXCPP to a command that runs the C++ preprocessor. If '$CXX -E' doesn't work, '/lib/cpp' is used. It is portable to run CXXCPP only on files with a '.c', '.C', '.cc', or '.cpp' extension.

Some preprocessors don't indicate missing include files by the error status. For such preprocessors an internal variable is set that causes other macros to check the standard error from the preprocessor and consider the test failed if any warnings have been reported. However, it is not known whether such broken preprocessors exist for C++.

AC_PROG_CXX_C_O [Macro]

Test whether the C++ compiler accepts the options '-c' and '-o' simultaneously, and define CXX_NO_MINUS_C_MINUS_O, if it does not.

5.10.5 Objective C Compiler Characteristics

AC_PROG_OBJC ([*compiler-search-list*]) [Macro]

Determine an Objective C compiler to use. If OBJC is not already set in the environment, check for Objective C compilers. Set output variable OBJC to the name of the compiler found.

This macro may, however, be invoked with an optional first argument which, if specified, must be a blank-separated list of Objective C compilers to search for. This just gives the user an opportunity to specify an alternative search list for the Objective C compiler. For example, if you didn't like the default order, then you could invoke AC_PROG_OBJC like this:

```
AC_PROG_OBJC([gcc objcc objc])
```

If using the GNU Objective C compiler, set shell variable GOBJC to 'yes'. If output variable OBJCFLAGS was not already set, set it to '-g -O2' for the GNU Objective C compiler ('-O2' on systems where gcc does not accept '-g'), or '-g' for other compilers.

AC_PROG_OBJCPP [Macro]

Set output variable OBJCPP to a command that runs the Objective C preprocessor. If '$OBJC -E' doesn't work, '/lib/cpp' is used.

5.10.6 Erlang Compiler and Interpreter Characteristics

Autoconf defines the following macros for determining paths to the essential Erlang/OTP programs:

AC_ERLANG_PATH_ERLC ([*value-if-not-found*], [*path* = '$PATH']) [Macro]

Determine an Erlang compiler to use. If ERLC is not already set in the environment, check for erlc. Set output variable ERLC to the complete path of the compiler command found. In addition, if ERLCFLAGS is not set in the environment, set it to an empty value.

The two optional arguments have the same meaning as the two last arguments of macro AC_PROG_PATH for looking for the erlc program. For example, to look for erlc only in the '/usr/lib/erlang/bin' directory:

```
AC_ERLANG_PATH_ERLC([not found], [/usr/lib/erlang/bin])
```

AC_ERLANG_NEED_ERLC ([*path* = '$PATH']) [Macro]

A simplified variant of the AC_ERLANG_PATH_ERLC macro, that prints an error message and exits the configure script if the erlc program is not found.

AC_ERLANG_PATH_ERL ([*value-if-not-found*], [*path* = '$PATH']) [Macro]

Determine an Erlang interpreter to use. If ERL is not already set in the environment, check for erl. Set output variable ERL to the complete path of the interpreter command found.

The two optional arguments have the same meaning as the two last arguments of macro AC_PROG_PATH for looking for the erl program. For example, to look for erl only in the '/usr/lib/erlang/bin' directory:

```
AC_ERLANG_PATH_ERL([not found], [/usr/lib/erlang/bin])
```

AC_ERLANG_NEED_ERL ([*path* = '$PATH']) [Macro]

A simplified variant of the AC_ERLANG_PATH_ERL macro, that prints an error message and exits the configure script if the erl program is not found.

5.10.7 Fortran Compiler Characteristics

The Autoconf Fortran support is divided into two categories: legacy Fortran 77 macros (F77), and modern Fortran macros (FC). The former are intended for traditional Fortran 77 code, and have output variables like F77, FFLAGS, and FLIBS. The latter are for newer programs that can (or must) compile under the newer Fortran standards, and have output variables like FC, FCFLAGS, and FCLIBS.

Except for two new macros AC_FC_SRCEXT and AC_FC_FREEFORM (see below), the FC and F77 macros behave almost identically, and so they are documented together in this section.

AC_PROG_F77 ([*compiler-search-list*]) [Macro]

Determine a Fortran 77 compiler to use. If F77 is not already set in the environment, then check for g77 and f77, and then some other names. Set the output variable F77 to the name of the compiler found.

This macro may, however, be invoked with an optional first argument which, if specified, must be a blank-separated list of Fortran 77 compilers to search for. This just gives the user an opportunity to specify an alternative search list for the Fortran 77 compiler. For example, if you didn't like the default order, then you could invoke AC_PROG_F77 like this:

```
AC_PROG_F77([fl32 f77 fort77 xlf g77 f90 xlf90])
```

If using g77 (the GNU Fortran 77 compiler), then set the shell variable G77 to 'yes'. If the output variable FFLAGS was not already set in the environment, then set it to '-g -O2' for g77 (or '-O2' where g77 does not accept '-g'). Otherwise, set FFLAGS to '-g' for all other Fortran 77 compilers.

AC_PROG_FC ([*compiler-search-list*], [*dialect*]) [Macro]

Determine a Fortran compiler to use. If FC is not already set in the environment, then dialect is a hint to indicate what Fortran dialect to search for; the default is to search for the newest available dialect. Set the output variable FC to the name of the compiler found.

By default, newer dialects are preferred over older dialects, but if dialect is specified then older dialects are preferred starting with the specified dialect. dialect can currently be one of Fortran 77, Fortran 90, or Fortran 95. However, this is only a hint of which compiler *name* to prefer (e.g., f90 or f95), and no attempt is made to guarantee that a particular language standard is actually supported. Thus, it is preferable that you avoid the dialect option, and use AC_PROG_FC only for code compatible with the latest Fortran standard.

This macro may, alternatively, be invoked with an optional first argument which, if specified, must be a blank-separated list of Fortran compilers to search for, just as in AC_PROG_F77.

If the output variable FCFLAGS was not already set in the environment, then set it to '-g -O2' for GNU g77 (or '-O2' where g77 does not accept '-g'). Otherwise, set FCFLAGS to '-g' for all other Fortran compilers.

AC_PROG_F77_C_O [Macro]
AC_PROG_FC_C_O [Macro]

Test whether the Fortran compiler accepts the options '-c' and '-o' simultaneously, and define F77_NO_MINUS_C_MINUS_O or FC_NO_MINUS_C_MINUS_O, respectively, if it does not.

The following macros check for Fortran compiler characteristics. To check for characteristics not listed here, use AC_COMPILE_IFELSE (see Section 6.4 [Running the Compiler], page 97) or AC_RUN_IFELSE (see Section 6.6 [Runtime], page 98), making sure to first set the current language to Fortran 77 or Fortran via AC_LANG([Fortran 77]) or AC_LANG(Fortran) (see Section 6.1 [Language Choice], page 91).

AC_F77_LIBRARY_LDFLAGS [Macro]
AC_FC_LIBRARY_LDFLAGS [Macro]

Determine the linker flags (e.g., '-L' and '-l') for the *Fortran intrinsic and runtime libraries* that are required to successfully link a Fortran program or shared library.

The output variable FLIBS or FCLIBS is set to these flags (which should be included after LIBS when linking).

This macro is intended to be used in those situations when it is necessary to mix, e.g., C++ and Fortran source code in a single program or shared library (see section "Mixing Fortran 77 With C and C++" in *GNU Automake*).

For example, if object files from a C++ and Fortran compiler must be linked together, then the C++ compiler/linker must be used for linking (since special C++-ish things need to happen at link time like calling global constructors, instantiating templates, enabling exception support, etc.).

However, the Fortran intrinsic and runtime libraries must be linked in as well, but the C++ compiler/linker doesn't know by default how to add these Fortran 77 libraries. Hence, this macro was created to determine these Fortran libraries.

The macros AC_F77_DUMMY_MAIN and AC_FC_DUMMY_MAIN or AC_F77_MAIN and AC_FC_MAIN are probably also necessary to link C/C++ with Fortran; see below.

AC_F77_DUMMY_MAIN ([*action-if-found*], [*action-if-not-found*]) [Macro]
AC_FC_DUMMY_MAIN ([*action-if-found*], [*action-if-not-found*]) [Macro]

With many compilers, the Fortran libraries detected by AC_F77_LIBRARY_LDFLAGS or AC_FC_LIBRARY_LDFLAGS provide their own main entry function that initializes things like Fortran I/O, and which then calls a user-provided entry function named (say) MAIN__ to run the user's program. The AC_F77_DUMMY_MAIN and AC_FC_DUMMY_MAIN or AC_F77_MAIN and AC_FC_MAIN macros figure out how to deal with this interaction.

When using Fortran for purely numerical functions (no I/O, etc.) often one prefers to provide one's own main and skip the Fortran library initializations. In this case, however, one may still need to provide a dummy MAIN__ routine in order to prevent linking errors on some systems. AC_F77_DUMMY_MAIN or AC_FC_DUMMY_MAIN detects whether any such routine is *required* for linking, and what its name is; the shell variable F77_DUMMY_MAIN or FC_DUMMY_MAIN holds this name, unknown when no solution was found, and none when no such dummy main is needed.

By default, *action-if-found* defines F77_DUMMY_MAIN or FC_DUMMY_MAIN to the name of this routine (e.g., MAIN__) *if* it is required. *action-if-not-found* defaults to exiting with an error.

In order to link with Fortran routines, the user's C/C++ program should then include the following code to define the dummy main if it is needed:

```
#ifdef F77_DUMMY_MAIN
#  ifdef __cplusplus
     extern "C"
#  endif
   int F77_DUMMY_MAIN() { return 1; }
#endif
```

(Replace F77 with FC for Fortran instead of Fortran 77.)

Note that this macro is called automatically from AC_F77_WRAPPERS or AC_FC_WRAPPERS; there is generally no need to call it explicitly unless one wants to change the default actions.

AC_F77_MAIN [Macro]
AC_FC_MAIN [Macro]

As discussed above, many Fortran libraries allow you to provide an entry point called (say) MAIN__ instead of the usual main, which is then called by a main function in the Fortran libraries that initializes things like Fortran I/O. The AC_F77_MAIN and AC_FC_MAIN macros detect whether it is *possible* to utilize such an alternate main function, and defines F77_MAIN and FC_MAIN to the name of the function. (If no alternate main function name is found, F77_MAIN and FC_MAIN are simply defined to main.)

Thus, when calling Fortran routines from C that perform things like I/O, one should use this macro and declare the "main" function like so:

```
#ifdef __cplusplus
  extern "C"
#endif
int F77_MAIN(int argc, char *argv[]);
```

(Again, replace F77 with FC for Fortran instead of Fortran 77.)

AC_F77_WRAPPERS [Macro]
AC_FC_WRAPPERS [Macro]

Defines C macros F77_FUNC(name, NAME), FC_FUNC(name, NAME), F77_FUNC_(name, NAME), and FC_FUNC_(name, NAME) to properly mangle the names of C/C++ identifiers, and identifiers with underscores, respectively, so that they match the name-mangling scheme used by the Fortran compiler.

Fortran is case-insensitive, and in order to achieve this the Fortran compiler converts all identifiers into a canonical case and format. To call a Fortran subroutine from C or to write a C function that is callable from Fortran, the C program must explicitly use identifiers in the format expected by the Fortran compiler. In order to do this, one simply wraps all C identifiers in one of the macros provided by AC_F77_WRAPPERS or AC_FC_WRAPPERS. For example, suppose you have the following Fortran 77 subroutine:

```
      subroutine foobar (x, y)
      double precision x, y
      y = 3.14159 * x
      return
      end
```

You would then declare its prototype in C or C++ as:

```
#define FOOBAR_F77 F77_FUNC (foobar, FOOBAR)
#ifdef __cplusplus
extern "C"  /* prevent C++ name mangling */
#endif
void FOOBAR_F77(double *x, double *y);
```

Note that we pass both the lowercase and uppercase versions of the function name to F77_FUNC so that it can select the right one. Note also that all parameters to Fortran 77 routines are passed as pointers (see section "Mixing Fortran 77 With C and C++" in *GNU Automake*).

(Replace F77 with FC for Fortran instead of Fortran 77.)

Although Autoconf tries to be intelligent about detecting the name-mangling scheme of the Fortran compiler, there may be Fortran compilers that it doesn't support yet. In this case, the above code generates a compile-time error, but some other behavior (e.g., disabling Fortran-related features) can be induced by checking whether `F77_FUNC` or `FC_FUNC` is defined.

Now, to call that routine from a C program, we would do something like:

```
{
    double x = 2.7183, y;
    FOOBAR_F77 (&x, &y);
}
```

If the Fortran identifier contains an underscore (e.g., `foo_bar`), you should use `F77_FUNC_` or `FC_FUNC_` instead of `F77_FUNC` or `FC_FUNC` (with the same arguments). This is because some Fortran compilers mangle names differently if they contain an underscore.

`AC_F77_FUNC` (*name*, [*shellvar*]) [Macro]
`AC_FC_FUNC` (*name*, [*shellvar*]) [Macro]

Given an identifier *name*, set the shell variable *shellvar* to hold the mangled version *name* according to the rules of the Fortran linker (see also `AC_F77_WRAPPERS` or `AC_FC_WRAPPERS`). *shellvar* is optional; if it is not supplied, the shell variable is simply *name*. The purpose of this macro is to give the caller a way to access the name-mangling information other than through the C preprocessor as above, for example, to call Fortran routines from some language other than C/C++.

`AC_FC_SRCEXT` (*ext*, [*action-if-success*], [*action-if-failure*]) [Macro]

By default, the `FC` macros perform their tests using a '`.f`' extension for source-code files. Some compilers, however, only enable newer language features for appropriately named files, e.g., Fortran 90 features only for '`.f90`' files. On the other hand, some other compilers expect all source files to end in '`.f`' and require special flags to support other file name extensions. The `AC_FC_SRCEXT` macro deals with both of these issues.

The `AC_FC_SRCEXT` tries to get the `FC` compiler to accept files ending with the extension *.ext* (i.e., *ext* does *not* contain the dot). If any special compiler flags are needed for this, it stores them in the output variable `FCFLAGS_`*ext*. This extension and these flags are then used for all subsequent `FC` tests (until `AC_FC_SRCEXT` is called again).

For example, you would use `AC_FC_SRCEXT(f90)` to employ the '`.f90`' extension in future tests, and it would set a `FCFLAGS_f90` output variable with any extra flags that are needed to compile such files.

The `FCFLAGS_`*ext* can *not* be simply absorbed into `FCFLAGS`, for two reasons based on the limitations of some compilers. First, only one `FCFLAGS_`*ext* can be used at a time, so files with different extensions must be compiled separately. Second, `FCFLAGS_`*ext* must appear *immediately* before the source-code file name when compiling. So, continuing the example above, you might compile a '`foo.f90`' file in your makefile with the command:

```
foo.o: foo.f90
     $(FC) -c $(FCFLAGS) $(FCFLAGS_f90) '$(srcdir)/foo.f90'
```

If AC_FC_SRCEXT succeeds in compiling files with the *ext* extension, it calls *action-if-success* (defaults to nothing). If it fails, and cannot find a way to make the FC compiler accept such files, it calls *action-if-failure* (defaults to exiting with an error message).

AC_FC_FREEFORM ([*action-if-success*], [*action-if-failure*]) [Macro]

The AC_FC_FREEFORM tries to ensure that the Fortran compiler ($FC) allows free-format source code (as opposed to the older fixed-format style from Fortran 77). If necessary, it may add some additional flags to FCFLAGS.

This macro is most important if you are using the default '.f' extension, since many compilers interpret this extension as indicating fixed-format source unless an additional flag is supplied. If you specify a different extension with AC_FC_SRCEXT, such as '.f90' or '.f95', then AC_FC_FREEFORM ordinarily succeeds without modifying FCFLAGS.

If AC_FC_FREEFORM succeeds in compiling free-form source, it calls *action-if-success* (defaults to nothing). If it fails, it calls *action-if-failure* (defaults to exiting with an error message).

5.11 System Services

The following macros check for operating system services or capabilities.

AC_PATH_X [Macro]

Try to locate the X Window System include files and libraries. If the user gave the command line options '--x-includes=*dir*' and '--x-libraries=*dir*', use those directories.

If either or both were not given, get the missing values by running xmkmf (or an executable pointed to by the XMKMF environment variable) on a trivial 'Imakefile' and examining the makefile that it produces. Setting XMKMF to 'false' disables this method.

If this method fails to find the X Window System, configure looks for the files in several directories where they often reside. If either method is successful, set the shell variables x_includes and x_libraries to their locations, unless they are in directories the compiler searches by default.

If both methods fail, or the user gave the command line option '--without-x', set the shell variable no_x to 'yes'; otherwise set it to the empty string.

AC_PATH_XTRA [Macro]

An enhanced version of AC_PATH_X. It adds the C compiler flags that X needs to output variable X_CFLAGS, and the X linker flags to X_LIBS. Define X_DISPLAY_MISSING if X is not available.

This macro also checks for special libraries that some systems need in order to compile X programs. It adds any that the system needs to output variable X_EXTRA_LIBS. And it checks for special X11R6 libraries that need to be linked with before '-lX11', and adds any found to the output variable X_PRE_LIBS.

AC_SYS_INTERPRETER [Macro]

Check whether the system supports starting scripts with a line of the form '#!/bin/sh' to select the interpreter to use for the script. After running this macro, shell code in 'configure.ac' can check the shell variable interpval; it is set to 'yes' if the system supports '#!', 'no' if not.

AC_SYS_LARGEFILE [Macro]

Arrange for large-file support (http://www.unix-systems.org/version2/whatsnew/lfs20mar.html). On some hosts, one must use special compiler options to build programs that can access large files. Append any such options to the output variable CC. Define _FILE_OFFSET_BITS and _LARGE_FILES if necessary.

Large-file support can be disabled by configuring with the '--disable-largefile' option.

If you use this macro, check that your program works even when off_t is wider than long int, since this is common when large-file support is enabled. For example, it is not correct to print an arbitrary off_t value X with printf ("%ld", (long int) X).

The LFS introduced the fseeko and ftello functions to replace their C counterparts fseek and ftell that do not use off_t. Take care to use AC_FUNC_FSEEKO to make their prototypes available when using them and large-file support is enabled.

AC_SYS_LONG_FILE_NAMES [Macro]

If the system supports file names longer than 14 characters, define HAVE_LONG_FILE_NAMES.

AC_SYS_POSIX_TERMIOS [Macro]

Check to see if the Posix termios headers and functions are available on the system. If so, set the shell variable ac_cv_sys_posix_termios to 'yes'. If not, set the variable to 'no'.

5.12 Posix Variants

The following macro makes it possible to use features of Posix that are extensions to C, as well as platform extensions not defined by Posix.

AC_USE_SYSTEM_EXTENSIONS [Macro]

This macro was introduced in Autoconf 2.60. If possible, enable extensions to C or Posix on hosts that normally disable the extensions, typically due to standards-conformance namespace issues. This should be called before any macros that run the C compiler. The following preprocessor macros are defined where appropriate:

_GNU_SOURCE
: Enable extensions on GNU/Linux.

__EXTENSIONS__
: Enable general extensions on Solaris.

_POSIX_PTHREAD_SEMANTICS
: Enable threading extensions on Solaris.

`_TANDEM_SOURCE`
: Enable extensions for the HP NonStop platform.

`_ALL_SOURCE`
: Enable extensions for AIX 3, and for Interix.

`_POSIX_SOURCE`
: Enable Posix functions for Minix.

`_POSIX_1_SOURCE`
: Enable additional Posix functions for Minix.

`_MINIX`
: Identify Minix platform. This particular preprocessor macro is obsolescent, and may be removed in a future release of Autoconf.

5.13 Erlang Libraries

The following macros check for an installation of Erlang/OTP, and for the presence of certain Erlang libraries. All those macros require the configuration of an Erlang interpreter and an Erlang compiler (see Section 5.10.6 [Erlang Compiler and Interpreter], page 81).

`AC_ERLANG_SUBST_ROOT_DIR` [Macro]

Set the output variable `ERLANG_ROOT_DIR` to the path to the base directory in which Erlang/OTP is installed (as returned by Erlang's `code:root_dir/0` function). The result of this test is cached if caching is enabled when running `configure`.

`AC_ERLANG_SUBST_LIB_DIR` [Macro]

Set the output variable `ERLANG_LIB_DIR` to the path of the library directory of Erlang/OTP (as returned by Erlang's `code:lib_dir/0` function), which subdirectories each contain an installed Erlang/OTP library. The result of this test is cached if caching is enabled when running `configure`.

`AC_ERLANG_CHECK_LIB (`*`library`*`, [`*`action-if-found`*`], [`*`action-if-not-found`*`])` [Macro]

Test whether the Erlang/OTP library *library* is installed by calling Erlang's `code:lib_dir/1` function. The result of this test is cached if caching is enabled when running `configure`. *action-if-found* is a list of shell commands to run if the library is installed; *action-if-not-found* is a list of shell commands to run if it is not. Additionally, if the library is installed, the output variable '`ERLANG_LIB_DIR_`*`library`*' is set to the path to the library installation directory, and the output variable '`ERLANG_LIB_VER_`*`library`*' is set to the version number that is part of the subdirectory name, if it is in the standard form (*`library-version`*). If the directory name does not have a version part, '`ERLANG_LIB_VER_`*`library`*' is set to the empty string. If the library is not installed, '`ERLANG_LIB_DIR_`*`library`*' and '`ERLANG_LIB_VER_`*`library`*' are set to `"not found"`. For example, to check if library `stdlib` is installed:

```
AC_ERLANG_CHECK_LIB([stdlib],
  [echo "stdlib version \"$ERLANG_LIB_VER_stdlib\""
   echo "is installed in \"$ERLANG_LIB_DIR_stdlib\""],
  [AC_MSG_ERROR([stdlib was not found!])])
```

In addition to the above macros, which test installed Erlang libraries, the following macros determine the paths to the directories into which newly built Erlang libraries are to be installed:

`AC_ERLANG_SUBST_INSTALL_LIB_DIR` [Macro]

Set the `ERLANG_INSTALL_LIB_DIR` output variable to the directory into which every built Erlang library should be installed in a separate subdirectory. If this variable is not set in the environment when `configure` runs, its default value is `$ERLANG_LIB_DIR`, which value is set by the `AC_ERLANG_SUBST_LIB_DIR` macro.

`AC_ERLANG_SUBST_INSTALL_LIB_SUBDIR (`*`library`*`, `*`version`*`)` [Macro]

Set the '`ERLANG_INSTALL_LIB_DIR_`*`library`*' output variable to the directory into which the built Erlang library *library* version *version* should be installed. If this variable is not set in the environment when `configure` runs, its default value is '`$ERLANG_INSTALL_LIB_DIR/`*`library-version`*', the value of the `ERLANG_INSTALL_LIB_DIR` variable being set by the `AC_ERLANG_SUBST_INSTALL_LIB_DIR` macro.

6 Writing Tests

If the existing feature tests don't do something you need, you have to write new ones. These macros are the building blocks. They provide ways for other macros to check whether various kinds of features are available and report the results.

This chapter contains some suggestions and some of the reasons why the existing tests are written the way they are. You can also learn a lot about how to write Autoconf tests by looking at the existing ones. If something goes wrong in one or more of the Autoconf tests, this information can help you understand the assumptions behind them, which might help you figure out how to best solve the problem.

These macros check the output of the compiler system of the current language (see Section 6.1 [Language Choice], page 91). They do not cache the results of their tests for future use (see Section 7.4 [Caching Results], page 107), because they don't know enough about the information they are checking for to generate a cache variable name. They also do not print any messages, for the same reason. The checks for particular kinds of features call these macros and do cache their results and print messages about what they're checking for.

When you write a feature test that could be applicable to more than one software package, the best thing to do is encapsulate it in a new macro. See Chapter 9 [Writing Autoconf Macros], page 145, for how to do that.

6.1 Language Choice

Autoconf-generated `configure` scripts check for the C compiler and its features by default. Packages that use other programming languages (maybe more than one, e.g., C and C++) need to test features of the compilers for the respective languages. The following macros determine which programming language is used in the subsequent tests in '`configure.ac`'.

`AC_LANG (`*`language`*`)` [Macro]

Do compilation tests using the compiler, preprocessor, and file extensions for the specified *language*.

Supported languages are:

'`C`' Do compilation tests using `CC` and `CPP` and use extension '`.c`' for test programs. Use compilation flags: `CPPFLAGS` with `CPP`, and both `CPPFLAGS` and `CFLAGS` with `CC`.

'`C++`' Do compilation tests using `CXX` and `CXXCPP` and use extension '`.C`' for test programs. Use compilation flags: `CPPFLAGS` with `CXXCPP`, and both `CPPFLAGS` and `CXXFLAGS` with `CXX`.

'`Fortran 77`' Do compilation tests using `F77` and use extension '`.f`' for test programs. Use compilation flags: `FFLAGS`.

'`Fortran`' Do compilation tests using `FC` and use extension '`.f`' (or whatever has been set by `AC_FC_SRCEXT`) for test programs. Use compilation flags: `FCFLAGS`.

'Erlang' Compile and execute tests using ERLC and ERL and use extension '.erl' for test Erlang modules. Use compilation flags: ERLCFLAGS.

'Objective C'
Do compilation tests using OBJC and OBJCPP and use extension '.m' for test programs. Use compilation flags: CPPFLAGS with OBJCPP, and both CPPFLAGS and OBJCFLAGS with OBJC.

AC_LANG_PUSH (*language*) [Macro]

Remember the current language (as set by AC_LANG) on a stack, and then select the *language*. Use this macro and AC_LANG_POP in macros that need to temporarily switch to a particular language.

AC_LANG_POP ([*language*]) [Macro]

Select the language that is saved on the top of the stack, as set by AC_LANG_PUSH, and remove it from the stack.

If given, *language* specifies the language we just *quit*. It is a good idea to specify it when it's known (which should be the case. . .), since Autoconf detects inconsistencies.

```
AC_LANG_PUSH([Fortran 77])
# Perform some tests on Fortran 77.
# ...
AC_LANG_POP([Fortran 77])
```

AC_LANG_ASSERT (*language*) [Macro]

Check statically that the current language is *language*. You should use this in your language specific macros to avoid that they be called with an inappropriate language.

This macro runs only at autoconf time, and incurs no cost at configure time. Sadly enough and because Autoconf is a two layer language[1], the macros AC_LANG_PUSH and AC_LANG_POP cannot be "optimizing", therefore as much as possible you ought to avoid using them to wrap your code, rather, require from the user to run the macro with a correct current language, and check it with AC_LANG_ASSERT. And anyway, that may help the user understand she is running a Fortran macro while expecting a result about her Fortran 77 compiler. . .

AC_REQUIRE_CPP [Macro]

Ensure that whichever preprocessor would currently be used for tests has been found. Calls AC_REQUIRE (see Section 9.4.1 [Prerequisite Macros], page 147) with an argument of either AC_PROG_CPP or AC_PROG_CXXCPP, depending on which language is current.

6.2 Writing Test Programs

Autoconf tests follow a common scheme: feed some program with some input, and most of the time, feed a compiler with some source file. This section is dedicated to these source samples.

[1] Because M4 is not aware of Sh code, especially conditionals, some optimizations that look nice statically may produce incorrect results at runtime.

6.2.1 Guidelines for Test Programs

The most important rule to follow when writing testing samples is:

Look for realism.

This motto means that testing samples must be written with the same strictness as real programs are written. In particular, you should avoid "shortcuts" and simplifications.

Don't just play with the preprocessor if you want to prepare a compilation. For instance, using `cpp` to check whether a header is functional might let your `configure` accept a header which causes some *compiler* error. Do not hesitate to check a header with other headers included before, especially required headers.

Make sure the symbols you use are properly defined, i.e., refrain for simply declaring a function yourself instead of including the proper header.

Test programs should not write to standard output. They should exit with status 0 if the test succeeds, and with status 1 otherwise, so that success can be distinguished easily from a core dump or other failure; segmentation violations and other failures produce a nonzero exit status. Unless you arrange for `exit` to be declared, test programs should `return`, not `exit`, from `main`, because on many systems `exit` is not declared by default.

Test programs can use `#if` or `#ifdef` to check the values of preprocessor macros defined by tests that have already run. For example, if you call `AC_HEADER_STDBOOL`, then later on in '`configure.ac`' you can have a test program that includes '`stdbool.h`' conditionally:

```
#ifdef HAVE_STDBOOL_H
# include <stdbool.h>
#endif
```

Both `#if HAVE_STDBOOL_H` and `#ifdef HAVE_STDBOOL_H` will work with any standard C compiler. Some developers prefer `#if` because it is easier to read, while others prefer `#ifdef` because it avoids diagnostics with picky compilers like GCC with the '`-Wundef`' option.

If a test program needs to use or create a data file, give it a name that starts with '`conftest`', such as '`conftest.data`'. The `configure` script cleans up by running '`rm -f -r conftest*`' after running test programs and if the script is interrupted.

6.2.2 Test Functions

These days it's safe to assume support for function prototypes (introduced in C89).

Functions that test programs declare should also be conditionalized for C++, which requires '`extern "C"`' prototypes. Make sure to not include any header files containing clashing prototypes.

```
#ifdef __cplusplus
extern "C"
#endif
void *valloc (size_t);
```

If a test program calls a function with invalid parameters (just to see whether it exists), organize the program to ensure that it never invokes that function. You can do this by calling it in another function that is never invoked. You can't do it by putting it after a call to `exit`, because GCC version 2 knows that `exit` never returns and optimizes out any code that follows it in the same block.

If you include any header files, be sure to call the functions relevant to them with the correct number of arguments, even if they are just 0, to avoid compilation errors due to prototypes. GCC version 2 has internal prototypes for several functions that it automatically inlines; for example, `memcpy`. To avoid errors when checking for them, either pass them the correct number of arguments or redeclare them with a different return type (such as `char`).

6.2.3 Generating Sources

Autoconf provides a set of macros that can be used to generate test source files. They are written to be language generic, i.e., they actually depend on the current language (see Section 6.1 [Language Choice], page 91) to "format" the output properly.

`AC_LANG_CONFTEST` (*source*) [Macro]

Save the *source* text in the current test source file: '`conftest.`*extension*' where the *extension* depends on the current language.

Note that the *source* is evaluated exactly once, like regular Autoconf macro arguments, and therefore (i) you may pass a macro invocation, (ii) if not, be sure to double quote if needed.

`AC_LANG_SOURCE` (*source*) [Macro]

Expands into the *source*, with the definition of all the `AC_DEFINE` performed so far.

For instance executing (observe the double quotation!):

```
AC_INIT([Hello], [1.0], [bug-hello@example.org])
AC_DEFINE([HELLO_WORLD], ["Hello, World\n"],
  [Greetings string.])
AC_LANG(C)
AC_LANG_CONFTEST(
   [AC_LANG_SOURCE([[const char hw[] = "Hello, World\n";]])])
gcc -E -dD -o - conftest.c
```

results in:

```
...
# 1 "conftest.c"

#define PACKAGE_NAME "Hello"
#define PACKAGE_TARNAME "hello"
#define PACKAGE_VERSION "1.0"
#define PACKAGE_STRING "Hello 1.0"
#define PACKAGE_BUGREPORT "bug-hello@example.org"
#define HELLO_WORLD "Hello, World\n"

const char hw[] = "Hello, World\n";
```

When the test language is Fortran or Erlang, the `AC_DEFINE` definitions are not automatically translated into constants in the source code by this macro.

`AC_LANG_PROGRAM` (*prologue*, *body*) [Macro]

Expands into a source file which consists of the *prologue*, and then *body* as body of the main function (e.g., `main` in C). Since it uses `AC_LANG_SOURCE`, the features of the latter are available.

For instance:

```
AC_INIT([Hello], [1.0], [bug-hello@example.org])
AC_DEFINE([HELLO_WORLD], ["Hello, World\n"],
  [Greetings string.])
AC_LANG_CONFTEST(
[AC_LANG_PROGRAM([[const char hw[] = "Hello, World\n";]],
                 [[fputs (hw, stdout);]])])
gcc -E -dD -o - conftest.c
```

results in:

```
...
# 1 "conftest.c"

#define PACKAGE_NAME "Hello"
#define PACKAGE_TARNAME "hello"
#define PACKAGE_VERSION "1.0"
#define PACKAGE_STRING "Hello 1.0"
#define PACKAGE_BUGREPORT "bug-hello@example.org"
#define HELLO_WORLD "Hello, World\n"

const char hw[] = "Hello, World\n";
int
main ()
{
fputs (hw, stdout);
  ;
  return 0;
}
```

In Erlang tests, the created source file is that of an Erlang module called `conftest` (‘`conftest.erl`’). This module defines and exports at least one `start/0` function, which is called to perform the test. The *prologue* is optional code that is inserted between the module header and the `start/0` function definition. *body* is the body of the `start/0` function without the final period (see Section 6.6 [Runtime], page 98, about constraints on this function’s behavior).

For instance:

```
AC_INIT([Hello], [1.0], [bug-hello@example.org])
AC_LANG(Erlang)
AC_LANG_CONFTEST(
[AC_LANG_PROGRAM([[-define(HELLO_WORLD, "Hello, world!").]],
                 [[io:format("~s~n", [?HELLO_WORLD])]])])
cat conftest.erl
```

results in:

```
-module(conftest).
-export([start/0]).
-define(HELLO_WORLD, "Hello, world!").
start() ->
```

```
io:format("~s~n", [?HELLO_WORLD])
.
```

AC_LANG_CALL (*prologue*, *function*) [Macro]

Expands into a source file which consists of the *prologue*, and then a call to the *function* as body of the main function (e.g., `main` in C). Since it uses `AC_LANG_PROGRAM`, the feature of the latter are available.

This function will probably be replaced in the future by a version which would enable specifying the arguments. The use of this macro is not encouraged, as it violates strongly the typing system.

This macro cannot be used for Erlang tests.

AC_LANG_FUNC_LINK_TRY (*function*) [Macro]

Expands into a source file which uses the *function* in the body of the main function (e.g., `main` in C). Since it uses `AC_LANG_PROGRAM`, the features of the latter are available.

As `AC_LANG_CALL`, this macro is documented only for completeness. It is considered to be severely broken, and in the future will be removed in favor of actual function calls (with properly typed arguments).

This macro cannot be used for Erlang tests.

6.3 Running the Preprocessor

Sometimes one might need to run the preprocessor on some source file. *Usually it is a bad idea*, as you typically need to *compile* your project, not merely run the preprocessor on it; therefore you certainly want to run the compiler, not the preprocessor. Resist the temptation of following the easiest path.

Nevertheless, if you need to run the preprocessor, then use `AC_PREPROC_IFELSE`.

The macros described in this section cannot be used for tests in Erlang or Fortran, since those languages require no preprocessor.

AC_PREPROC_IFELSE (*input*, [*action-if-true*], [*action-if-false*]) [Macro]

Run the preprocessor of the current language (see Section 6.1 [Language Choice], page 91) on the *input*, run the shell commands *action-if-true* on success, *action-if-false* otherwise. The *input* can be made by `AC_LANG_PROGRAM` and friends.

This macro uses `CPPFLAGS`, but not `CFLAGS`, because '`-g`', '`-O`', etc. are not valid options to many C preprocessors.

It is customary to report unexpected failures with `AC_MSG_FAILURE`.

For instance:

```
AC_INIT([Hello], [1.0], [bug-hello@example.org])
AC_DEFINE([HELLO_WORLD], ["Hello, World\n"],
  [Greetings string.])
AC_PREPROC_IFELSE(
   [AC_LANG_PROGRAM([[const char hw[] = "Hello, World\n";]],
                    [[fputs (hw, stdout);]])],
   [AC_MSG_RESULT([OK])],
```

```
        [AC_MSG_FAILURE([unexpected preprocessor failure])])
```

results in:

```
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking how to run the C preprocessor... gcc -E
OK
```

The macro `AC_TRY_CPP` (see Section 17.4 [Obsolete Macros], page 243) used to play the role of `AC_PREPROC_IFELSE`, but double quotes its argument, making it impossible to use it to elaborate sources. You are encouraged to get rid of your old use of the macro `AC_TRY_CPP` in favor of `AC_PREPROC_IFELSE`, but, in the first place, are you sure you need to run the *preprocessor* and not the compiler?

`AC_EGREP_HEADER` (*pattern*, *header-file*, *action-if-found*, [*action-if-not-found*]) [Macro]

If the output of running the preprocessor on the system header file *header-file* matches the extended regular expression *pattern*, execute shell commands *action-if-found*, otherwise execute *action-if-not-found*.

`AC_EGREP_CPP` (*pattern*, *program*, [*action-if-found*], [*action-if-not-found*]) [Macro]

program is the text of a C or C++ program, on which shell variable, back quote, and backslash substitutions are performed. If the output of running the preprocessor on *program* matches the extended regular expression *pattern*, execute shell commands *action-if-found*, otherwise execute *action-if-not-found*.

6.4 Running the Compiler

To check for a syntax feature of the current language's (see Section 6.1 [Language Choice], page 91) compiler, such as whether it recognizes a certain keyword, or simply to try some library feature, use `AC_COMPILE_IFELSE` to try to compile a small program that uses that feature.

`AC_COMPILE_IFELSE` (*input*, [*action-if-true*], [*action-if-false*]) [Macro]

Run the compiler and compilation flags of the current language (see Section 6.1 [Language Choice], page 91) on the *input*, run the shell commands *action-if-true* on success, *action-if-false* otherwise. The *input* can be made by `AC_LANG_PROGRAM` and friends.

It is customary to report unexpected failures with `AC_MSG_FAILURE`. This macro does not try to link; use `AC_LINK_IFELSE` if you need to do that (see Section 6.5 [Running the Linker], page 98).

For tests in Erlang, the *input* must be the source code of a module named `conftest`. `AC_COMPILE_IFELSE` generates a '`conftest.beam`' file that can be interpreted by the Erlang virtual machine (`ERL`). It is recommended to use `AC_LANG_PROGRAM` to specify the test program, to ensure that the Erlang module has the right name.

6.5 Running the Linker

To check for a library, a function, or a global variable, Autoconf `configure` scripts try to compile and link a small program that uses it. This is unlike Metaconfig, which by default uses `nm` or `ar` on the C library to try to figure out which functions are available. Trying to link with the function is usually a more reliable approach because it avoids dealing with the variations in the options and output formats of `nm` and `ar` and in the location of the standard libraries. It also allows configuring for cross-compilation or checking a function's runtime behavior if needed. On the other hand, it can be slower than scanning the libraries once, but accuracy is more important than speed.

`AC_LINK_IFELSE` is used to compile test programs to test for functions and global variables. It is also used by `AC_CHECK_LIB` to check for libraries (see Section 5.4 [Libraries], page 46), by adding the library being checked for to `LIBS` temporarily and trying to link a small program.

`AC_LINK_IFELSE (`*`input`*`, [`*`action-if-true`*`], [`*`action-if-false`*`])` [Macro]

Run the compiler (and compilation flags) and the linker of the current language (see Section 6.1 [Language Choice], page 91) on the *input*, run the shell commands *action-if-true* on success, *action-if-false* otherwise. The *input* can be made by `AC_LANG_PROGRAM` and friends.

`LDFLAGS` and `LIBS` are used for linking, in addition to the current compilation flags.

It is customary to report unexpected failures with `AC_MSG_FAILURE`. This macro does not try to execute the program; use `AC_RUN_IFELSE` if you need to do that (see Section 6.6 [Runtime], page 98).

The `AC_LINK_IFELSE` macro cannot be used for Erlang tests, since Erlang programs are interpreted and do not require linking.

6.6 Checking Runtime Behavior

Sometimes you need to find out how a system performs at runtime, such as whether a given function has a certain capability or bug. If you can, make such checks when your program runs instead of when it is configured. You can check for things like the machine's endianness when your program initializes itself.

If you really need to test for a runtime behavior while configuring, you can write a test program to determine the result, and compile and run it using `AC_RUN_IFELSE`. Avoid running test programs if possible, because this prevents people from configuring your package for cross-compiling.

`AC_RUN_IFELSE (`*`input`*`, [`*`action-if-true`*`], [`*`action-if-false`*`], [`*`action-if-cross-compiling`*`])` [Macro]

If *program* compiles and links successfully and returns an exit status of 0 when executed, run shell commands *action-if-true*. Otherwise, run shell commands *action-if-false*.

The *input* can be made by `AC_LANG_PROGRAM` and friends. `LDFLAGS` and `LIBS` are used for linking, in addition to the compilation flags of the current language (see Section 6.1 [Language Choice], page 91).

If the compiler being used does not produce executables that run on the system where `configure` is being run, then the test program is not run. If the optional shell commands *action-if-cross-compiling* are given, they are run instead. Otherwise, `configure` prints an error message and exits.

In the *action-if-false* section, the failing exit status is available in the shell variable '`$?`'. This exit status might be that of a failed compilation, or it might be that of a failed program execution.

It is customary to report unexpected failures with `AC_MSG_FAILURE`.

Try to provide a pessimistic default value to use when cross-compiling makes runtime tests impossible. You do this by passing the optional last argument to `AC_RUN_IFELSE`. `autoconf` prints a warning message when creating `configure` each time it encounters a call to `AC_RUN_IFELSE` with no *action-if-cross-compiling* argument given. You may ignore the warning, though users cannot configure your package for cross-compiling. A few of the macros distributed with Autoconf produce this warning message.

To configure for cross-compiling you can also choose a value for those parameters based on the canonical system name (see Chapter 13 [Manual Configuration], page 221). Alternatively, set up a test results cache file with the correct values for the host system (see Section 7.4 [Caching Results], page 107).

To provide a default for calls of `AC_RUN_IFELSE` that are embedded in other macros, including a few of the ones that come with Autoconf, you can test whether the shell variable `cross_compiling` is set to '`yes`', and then use an alternate method to get the results instead of calling the macros.

It is also permissible to temporarily assign to `cross_compiling` in order to force tests to behave as though they are in a cross-compilation environment, particularly since this provides a way to test your *action-if-cross-compiling* even when you are not using a cross-compiler.

```
# We temporarily set cross-compile mode to force AC_COMPUTE_INT
# to use the slow link-only method
save_cross_compiling=$cross_compiling
cross_compiling=yes
AC_COMPUTE_INT([...])
cross_compiling=$save_cross_compiling
```

A C or C++ runtime test should be portable. See Chapter 12 [Portable C and C++], page 211.

Erlang tests must exit themselves the Erlang VM by calling the `halt/1` function: the given status code is used to determine the success of the test (status is `0`) or its failure (status is different than `0`), as explained above. It must be noted that data output through the standard output (e.g., using `io:format/2`) may be truncated when halting the VM. Therefore, if a test must output configuration information, it is recommended to create and to output data into the temporary file named '`conftest.out`', using the functions of module `file`. The `conftest.out` file is automatically deleted by the `AC_RUN_IFELSE` macro. For instance, a simplified implementation of Autoconf's `AC_ERLANG_SUBST_LIB_DIR` macro is:

```
AC_INIT([LibdirTest], [1.0], [bug-libdirtest@example.org])
AC_ERLANG_NEED_ERL
AC_LANG(Erlang)
AC_RUN_IFELSE(
  [AC_LANG_PROGRAM([], [dnl
    file:write_file("conftest.out", code:lib_dir()),
    halt(0)])],
  [echo "code:lib_dir() returned: `cat conftest.out`"],
  [AC_MSG_FAILURE([test Erlang program execution failed])])
```

6.7 Systemology

This section aims at presenting some systems and pointers to documentation. It may help you addressing particular problems reported by users.

Posix-conforming systems (`http://www.opengroup.org/susv3`) are derived from the Unix operating system (`http://www.bell-labs.com/history/unix/`).

The Rosetta Stone for Unix (`http://bhami.com/rosetta.html`) contains a table correlating the features of various Posix-conforming systems. Unix History (`http://www.levenez.com/unix/`) is a simplified diagram of how many Unix systems were derived from each other.

The Heirloom Project (`http://heirloom.sourceforge.net/`) provides some variants of traditional implementations of Unix utilities.

Darwin
: Darwin is also known as Mac OS X. Beware that the file system *can* be case-preserving, but case insensitive. This can cause nasty problems, since for instance the installation attempt for a package having an '`INSTALL`' file can result in '`make install`' report that nothing was to be done!

  That's all dependent on whether the file system is a UFS (case sensitive) or HFS+ (case preserving). By default Apple wants you to install the OS on HFS+. Unfortunately, there are some pieces of software which really need to be built on UFS. We may want to rebuild Darwin to have both UFS and HFS+ available (and put the /local/build tree on the UFS).

QNX 4.25
: QNX is a realtime operating system running on Intel architecture meant to be scalable from the small embedded systems to the hundred processor supercomputer. It claims to be Posix certified. More information is available on the QNX home page (`http://www.qnx.com/`).

Tru64
: Documentation of several versions of Tru64 (`http://h30097.www3.hp.com/docs/`) is available in different formats.

Unix version 7
: Officially this was called the "Seventh Edition" of "the UNIX time-sharing system" but we use the more-common name "Unix version 7". Documentation is available in the Unix Seventh Edition Manual (`http://plan9.bell-labs.com/7thEdMan/`). Previous versions of Unix are called "Unix version 6", etc., but they were not as widely used.

6.8 Multiple Cases

Some operations are accomplished in several possible ways, depending on the OS variant. Checking for them essentially requires a "case statement". Autoconf does not directly provide one; however, it is easy to simulate by using a shell variable to keep track of whether a way to perform the operation has been found yet.

Here is an example that uses the shell variable `fstype` to keep track of whether the remaining cases need to be checked.

```
AC_MSG_CHECKING([how to get file system type])
fstype=no
# The order of these tests is important.
AC_COMPILE_IFELSE([AC_LANG_PROGRAM([[#include <sys/statvfs.h>
#include <sys/fstyp.h>]])],
                  [AC_DEFINE([FSTYPE_STATVFS], [1],
                     [Define if statvfs exists.])
                   fstype=SVR4])
if test $fstype = no; then
  AC_COMPILE_IFELSE([AC_LANG_PROGRAM([[#include <sys/statfs.h>
#include <sys/fstyp.h>]])],
                  [AC_DEFINE([FSTYPE_USG_STATFS], [1],
                     [Define if USG statfs.])
                   fstype=SVR3])
fi
if test $fstype = no; then
  AC_COMPILE_IFELSE([AC_LANG_PROGRAM([[#include <sys/statfs.h>
#include <sys/vmount.h>]])]),
                  [AC_DEFINE([FSTYPE_AIX_STATFS], [1],
                     [Define if AIX statfs.])
                   fstype=AIX])
fi
# (more cases omitted here)
AC_MSG_RESULT([$fstype])
```

7 Results of Tests

Once `configure` has determined whether a feature exists, what can it do to record that information? There are four sorts of things it can do: define a C preprocessor symbol, set a variable in the output files, save the result in a cache file for future `configure` runs, and print a message letting the user know the result of the test.

7.1 Defining C Preprocessor Symbols

A common action to take in response to a feature test is to define a C preprocessor symbol indicating the results of the test. That is done by calling `AC_DEFINE` or `AC_DEFINE_UNQUOTED`.

By default, `AC_OUTPUT` places the symbols defined by these macros into the output variable `DEFS`, which contains an option '`-Dsymbol=value`' for each symbol defined. Unlike in Autoconf version 1, there is no variable `DEFS` defined while `configure` is running. To check whether Autoconf macros have already defined a certain C preprocessor symbol, test the value of the appropriate cache variable, as in this example:

```
AC_CHECK_FUNC([vprintf], [AC_DEFINE([HAVE_VPRINTF], [1],
                          [Define if vprintf exists.])])
if test "$ac_cv_func_vprintf" != yes; then
  AC_CHECK_FUNC([_doprnt], [AC_DEFINE([HAVE_DOPRNT], [1],
                            [Define if _doprnt exists.])])
fi
```

If `AC_CONFIG_HEADERS` has been called, then instead of creating `DEFS`, `AC_OUTPUT` creates a header file by substituting the correct values into `#define` statements in a template file. See Section 4.9 [Configuration Headers], page 32, for more information about this kind of output.

`AC_DEFINE` (*variable*, *value*, [*description*]) [Macro]
`AC_DEFINE` (*variable*) [Macro]

Define *variable* to *value* (verbatim), by defining a C preprocessor macro for *variable*. *variable* should be a C identifier, optionally suffixed by a parenthesized argument list to define a C preprocessor macro with arguments. The macro argument list, if present, should be a comma-separated list of C identifiers, possibly terminated by an ellipsis '`...`' if C99 syntax is employed. *variable* should not contain comments, white space, trigraphs, backslash-newlines, universal character names, or non-ASCII characters.

value may contain backslash-escaped newlines, which will be preserved if you use `AC_CONFIG_HEADERS` but flattened if passed via `@DEFS@` (with no effect on the compilation, since the preprocessor sees only one line in the first place). *value* should not contain raw newlines. If you are not using `AC_CONFIG_HEADERS`, *value* should not contain any '`#`' characters, as `make` tends to eat them. To use a shell variable, use `AC_DEFINE_UNQUOTED` instead.

description is only useful if you are using `AC_CONFIG_HEADERS`. In this case, *description* is put into the generated '`config.h.in`' as the comment before the macro define. The following example defines the C preprocessor variable `EQUATION` to be the string constant '`"$a > $b"`':

```
AC_DEFINE([EQUATION], ["$a > $b"],
  [Equation string.])
```

If neither *value* nor *description* are given, then *value* defaults to 1 instead of to the empty string. This is for backwards compatibility with older versions of Autoconf, but this usage is obsolescent and may be withdrawn in future versions of Autoconf.

If the *variable* is a literal string, it is passed to `m4_pattern_allow` (see Section 8.3.9 [Forbidden Patterns], page 141).

If multiple `AC_DEFINE` statements are executed for the same *variable* name (not counting any parenthesized argument list), the last one wins.

`AC_DEFINE_UNQUOTED` (*variable*, *value*, [*description*]) [Macro]
`AC_DEFINE_UNQUOTED` (*variable*) [Macro]

Like `AC_DEFINE`, but three shell expansions are performed—once—on *variable* and *value*: variable expansion ('$'), command substitution ('`'), and backslash escaping ('\'). Single and double quote characters in the value have no special meaning. Use this macro instead of `AC_DEFINE` when *variable* or *value* is a shell variable. Examples:

```
AC_DEFINE_UNQUOTED([config_machfile], ["$machfile"],
  [Configuration machine file.])
AC_DEFINE_UNQUOTED([GETGROUPS_T], [$ac_cv_type_getgroups],
  [getgroups return type.])
AC_DEFINE_UNQUOTED([$ac_tr_hdr], [1],
  [Translated header name.])
```

Due to a syntactical bizarreness of the Bourne shell, do not use semicolons to separate `AC_DEFINE` or `AC_DEFINE_UNQUOTED` calls from other macro calls or shell code; that can cause syntax errors in the resulting `configure` script. Use either blanks or newlines. That is, do this:

```
AC_CHECK_HEADER([elf.h],
  [AC_DEFINE([SVR4], [1], [System V Release 4]) LIBS="-lelf $LIBS"])
```

or this:

```
AC_CHECK_HEADER([elf.h],
  [AC_DEFINE([SVR4], [1], [System V Release 4])
   LIBS="-lelf $LIBS"])
```

instead of this:

```
AC_CHECK_HEADER([elf.h],
  [AC_DEFINE([SVR4], [1], [System V Release 4]); LIBS="-lelf $LIBS"])
```

7.2 Setting Output Variables

Another way to record the results of tests is to set *output variables*, which are shell variables whose values are substituted into files that `configure` outputs. The two macros below create new output variables. See Section 4.8.1 [Preset Output Variables], page 23, for a list of output variables that are always available.

`AC_SUBST` (*variable*, [*value*]) [Macro]

Create an output variable from a shell variable. Make `AC_OUTPUT` substitute the variable *variable* into output files (typically one or more makefiles). This means that

AC_OUTPUT replaces instances of '@*variable*@' in input files with the value that the shell variable *variable* has when AC_OUTPUT is called. The value can contain any non-NUL character, including newline. Variable occurrences should not overlap: e.g., an input file should not contain '@*var1*@*var2*@' if *var1* and *var2* are variable names. The substituted value is not rescanned for more output variables; occurrences of '@*variable*@' in the value are inserted literally into the output file. (The algorithm uses the special marker |#_!!_#| internally, so neither the substituted value nor the output file may contain |#_!!_#|.)

If *value* is given, in addition assign it to *variable*.

The string *variable* is passed to m4_pattern_allow (see Section 8.3.9 [Forbidden Patterns], page 141).

AC_SUBST_FILE (*variable*) [Macro]

Another way to create an output variable from a shell variable. Make AC_OUTPUT insert (without substitutions) the contents of the file named by shell variable *variable* into output files. This means that AC_OUTPUT replaces instances of '@*variable*@' in output files (such as 'Makefile.in') with the contents of the file that the shell variable *variable* names when AC_OUTPUT is called. Set the variable to '/dev/null' for cases that do not have a file to insert. This substitution occurs only when the '@*variable*@' is on a line by itself, optionally surrounded by spaces and tabs. The substitution replaces the whole line, including the spaces, tabs, and the terminating newline.

This macro is useful for inserting makefile fragments containing special dependencies or other make directives for particular host or target types into makefiles. For example, 'configure.ac' could contain:

```
AC_SUBST_FILE([host_frag])
host_frag=$srcdir/conf/sun4.mh
```

and then a 'Makefile.in' could contain:

```
@host_frag@
```

The string *variable* is passed to m4_pattern_allow (see Section 8.3.9 [Forbidden Patterns], page 141).

Running configure in varying environments can be extremely dangerous. If for instance the user runs 'CC=bizarre-cc ./configure', then the cache, 'config.h', and many other output files depend upon bizarre-cc being the C compiler. If for some reason the user runs ./configure again, or if it is run via './config.status --recheck', (See Section 4.8.5 [Automatic Remaking], page 31, and see Chapter 16 [config.status Invocation], page 239), then the configuration can be inconsistent, composed of results depending upon two different compilers.

Environment variables that affect this situation, such as 'CC' above, are called *precious variables*, and can be declared as such by AC_ARG_VAR.

AC_ARG_VAR (*variable*, *description*) [Macro]

Declare *variable* is a precious variable, and include its *description* in the variable section of './configure --help'.

Being precious means that

- *variable* is substituted via `AC_SUBST`.
- The value of *variable* when `configure` was launched is saved in the cache, including if it was not specified on the command line but via the environment. Indeed, while `configure` can notice the definition of `CC` in '`./configure CC=bizarre-cc`', it is impossible to notice it in '`CC=bizarre-cc ./configure`', which, unfortunately, is what most users do.

  We emphasize that it is the *initial* value of *variable* which is saved, not that found during the execution of `configure`. Indeed, specifying '`./configure FOO=foo`' and letting '`./configure`' guess that `FOO` is `foo` can be two different things.
- *variable* is checked for consistency between two `configure` runs. For instance:

```
$ ./configure --silent --config-cache
$ CC=cc ./configure --silent --config-cache
configure: error: 'CC' was not set in the previous run
configure: error: changes in the environment can compromise \
the build
configure: error: run 'make distclean' and/or \
'rm config.cache' and start over
```

  and similarly if the variable is unset, or if its content is changed. If the content has white space changes only, then the error is degraded to a warning only, but the old value is reused.
- *variable* is kept during automatic reconfiguration (see Chapter 16 [config.status Invocation], page 239) as if it had been passed as a command line argument, including when no cache is used:

```
$ CC=/usr/bin/cc ./configure var=raboof --silent
$ ./config.status --recheck
running CONFIG_SHELL=/bin/sh /bin/sh ./configure var=raboof \
  CC=/usr/bin/cc  --no-create --no-recursion
```

7.3 Special Characters in Output Variables

Many output variables are intended to be evaluated both by `make` and by the shell. Some characters are expanded differently in these two contexts, so to avoid confusion these variables' values should not contain any of the following characters:

```
" # $ & ' ( ) * ; < > ? [ \ ^ ` |
```

Also, these variables' values should neither contain newlines, nor start with '`~`', nor contain white space or '`:`' immediately followed by '`~`'. The values can contain nonempty sequences of white space characters like tabs and spaces, but each such sequence might arbitrarily be replaced by a single space during substitution.

These restrictions apply both to the values that `configure` computes, and to the values set directly by the user. For example, the following invocations of `configure` are problematic, since they attempt to use special characters within `CPPFLAGS` and white space within `$(srcdir)`:

```
CPPFLAGS='-DOUCH="&\"#$*?"' '../My Source/ouch-1.0/configure'

'../My Source/ouch-1.0/configure' CPPFLAGS='-DOUCH="&\"#$*?"'
```

7.4 Caching Results

To avoid checking for the same features repeatedly in various `configure` scripts (or in repeated runs of one script), `configure` can optionally save the results of many checks in a *cache file* (see Section 7.4.2 [Cache Files], page 108). If a `configure` script runs with caching enabled and finds a cache file, it reads the results of previous runs from the cache and avoids rerunning those checks. As a result, `configure` can then run much faster than if it had to perform all of the checks every time.

`AC_CACHE_VAL` (*cache-id*, *commands-to-set-it*) [Macro]

Ensure that the results of the check identified by *cache-id* are available. If the results of the check were in the cache file that was read, and `configure` was not given the '`--quiet`' or '`--silent`' option, print a message saying that the result was cached; otherwise, run the shell commands *commands-to-set-it*. If the shell commands are run to determine the value, the value is saved in the cache file just before `configure` creates its output files. See Section 7.4.1 [Cache Variable Names], page 108, for how to choose the name of the *cache-id* variable.

The *commands-to-set-it must have no side effects* except for setting the variable *cache-id*, see below.

`AC_CACHE_CHECK` (*message*, *cache-id*, *commands-to-set-it*) [Macro]

A wrapper for `AC_CACHE_VAL` that takes care of printing the messages. This macro provides a convenient shorthand for the most common way to use these macros. It calls `AC_MSG_CHECKING` for *message*, then `AC_CACHE_VAL` with the *cache-id* and *commands* arguments, and `AC_MSG_RESULT` with *cache-id*.

The *commands-to-set-it must have no side effects* except for setting the variable *cache-id*, see below.

It is common to find buggy macros using `AC_CACHE_VAL` or `AC_CACHE_CHECK`, because people are tempted to call `AC_DEFINE` in the *commands-to-set-it*. Instead, the code that *follows* the call to `AC_CACHE_VAL` should call `AC_DEFINE`, by examining the value of the cache variable. For instance, the following macro is broken:

```
AC_DEFUN([AC_SHELL_TRUE],
[AC_CACHE_CHECK([whether true(1) works], [my_cv_shell_true_works],
                [my_cv_shell_true_works=no
                 (true) 2>/dev/null && my_cv_shell_true_works=yes
                 if test "$my_cv_shell_true_works" = yes; then
                   AC_DEFINE([TRUE_WORKS], [1],
                             [Define if `true(1)' works properly.])
                 fi])
])
```

This fails if the cache is enabled: the second time this macro is run, `TRUE_WORKS` *will not be defined*. The proper implementation is:

```
AC_DEFUN([AC_SHELL_TRUE],
[AC_CACHE_CHECK([whether true(1) works], [my_cv_shell_true_works],
                [my_cv_shell_true_works=no
                 (true) 2>/dev/null && my_cv_shell_true_works=yes])
 if test "$my_cv_shell_true_works" = yes; then
   AC_DEFINE([TRUE_WORKS], [1],
             [Define if `true(1)' works properly.])
 fi
])
```

Also, *commands-to-set-it* should not print any messages, for example with `AC_MSG_CHECKING`; do that before calling `AC_CACHE_VAL`, so the messages are printed regardless of whether the results of the check are retrieved from the cache or determined by running the shell commands.

7.4.1 Cache Variable Names

The names of cache variables should have the following format:

package-prefix`_cv_`*value-type*`_`*specific-value*`_`[*additional-options*]

for example, '`ac_cv_header_stat_broken`' or '`ac_cv_prog_gcc_traditional`'. The parts of the variable name are:

package-prefix
: An abbreviation for your package or organization; the same prefix you begin local Autoconf macros with, except lowercase by convention. For cache values used by the distributed Autoconf macros, this value is '`ac`'.

`_cv_`
: Indicates that this shell variable is a cache value. This string *must* be present in the variable name, including the leading underscore.

value-type
: A convention for classifying cache values, to produce a rational naming system. The values used in Autoconf are listed in Section 9.2 [Macro Names], page 145.

specific-value
: Which member of the class of cache values this test applies to. For example, which function ('`alloca`'), program ('`gcc`'), or output variable ('`INSTALL`').

additional-options
: Any particular behavior of the specific member that this test applies to. For example, '`broken`' or '`set`'. This part of the name may be omitted if it does not apply.

The values assigned to cache variables may not contain newlines. Usually, their values are Boolean ('`yes`' or '`no`') or the names of files or functions; so this is not an important restriction.

7.4.2 Cache Files

A cache file is a shell script that caches the results of configure tests run on one system so they can be shared between configure scripts and configure runs. It is not useful on other systems. If its contents are invalid for some reason, the user may delete or edit it.

By default, `configure` uses no cache file, to avoid problems caused by accidental use of stale cache files.

To enable caching, `configure` accepts '`--config-cache`' (or '`-C`') to cache results in the file '`config.cache`'. Alternatively, '`--cache-file=file`' specifies that *file* be the cache file. The cache file is created if it does not exist already. When `configure` calls `configure` scripts in subdirectories, it uses the '`--cache-file`' argument so that they share the same cache. See Section 4.12 [Subdirectories], page 37, for information on configuring subdirectories with the `AC_CONFIG_SUBDIRS` macro.

'`config.status`' only pays attention to the cache file if it is given the '`--recheck`' option, which makes it rerun `configure`.

It is wrong to try to distribute cache files for particular system types. There is too much room for error in doing that, and too much administrative overhead in maintaining them. For any features that can't be guessed automatically, use the standard method of the canonical system type and linking files (see Chapter 13 [Manual Configuration], page 221).

The site initialization script can specify a site-wide cache file to use, instead of the usual per-program cache. In this case, the cache file gradually accumulates information whenever someone runs a new `configure` script. (Running `configure` merges the new cache results with the existing cache file.) This may cause problems, however, if the system configuration (e.g., the installed libraries or compilers) changes and the stale cache file is not deleted.

7.4.3 Cache Checkpointing

If your configure script, or a macro called from '`configure.ac`', happens to abort the configure process, it may be useful to checkpoint the cache a few times at key points using `AC_CACHE_SAVE`. Doing so reduces the amount of time it takes to rerun the configure script with (hopefully) the error that caused the previous abort corrected.

`AC_CACHE_LOAD` [Macro]

Loads values from existing cache file, or creates a new cache file if a cache file is not found. Called automatically from `AC_INIT`.

`AC_CACHE_SAVE` [Macro]

Flushes all cached values to the cache file. Called automatically from `AC_OUTPUT`, but it can be quite useful to call `AC_CACHE_SAVE` at key points in '`configure.ac`'.

For instance:

```
... AC_INIT, etc. ...
# Checks for programs.
AC_PROG_CC
AC_PROG_AWK
... more program checks ...
AC_CACHE_SAVE

# Checks for libraries.
AC_CHECK_LIB([nsl], [gethostbyname])
AC_CHECK_LIB([socket], [connect])
... more lib checks ...
AC_CACHE_SAVE
```

```
# Might abort...
AM_PATH_GTK([1.0.2], [], [AC_MSG_ERROR([GTK not in path])])
AM_PATH_GTKMM([0.9.5], [], [AC_MSG_ERROR([GTK not in path])])
```
... AC_OUTPUT, etc. ...

7.5 Printing Messages

`configure` scripts need to give users running them several kinds of information. The following macros print messages in ways appropriate for each kind. The arguments to all of them get enclosed in shell double quotes, so the shell performs variable and back-quote substitution on them.

These macros are all wrappers around the `echo` shell command. They direct output to the appropriate file descriptor (see Section 8.5 [File Descriptor Macros], page 143). `configure` scripts should rarely need to run `echo` directly to print messages for the user. Using these macros makes it easy to change how and when each kind of message is printed; such changes need only be made to the macro definitions and all the callers change automatically.

To diagnose static issues, i.e., when `autoconf` is run, see Section 8.3.2 [Diagnostic Macros], page 127.

`AC_MSG_CHECKING (`*`feature-description`*`)` [Macro]

Notify the user that `configure` is checking for a particular feature. This macro prints a message that starts with '`checking` ' and ends with '`...`' and no newline. It must be followed by a call to `AC_MSG_RESULT` to print the result of the check and the newline. The *feature-description* should be something like '`whether the Fortran compiler accepts C++ comments`' or '`for c89`'.

This macro prints nothing if `configure` is run with the '`--quiet`' or '`--silent`' option.

`AC_MSG_RESULT (`*`result-description`*`)` [Macro]

Notify the user of the results of a check. *result-description* is almost always the value of the cache variable for the check, typically '`yes`', '`no`', or a file name. This macro should follow a call to `AC_MSG_CHECKING`, and the *result-description* should be the completion of the message printed by the call to `AC_MSG_CHECKING`.

This macro prints nothing if `configure` is run with the '`--quiet`' or '`--silent`' option.

`AC_MSG_NOTICE (`*`message`*`)` [Macro]

Deliver the *message* to the user. It is useful mainly to print a general description of the overall purpose of a group of feature checks, e.g.,

```
AC_MSG_NOTICE([checking if stack overflow is detectable])
```

This macro prints nothing if `configure` is run with the '`--quiet`' or '`--silent`' option.

`AC_MSG_ERROR` (*`error-description`*, [*`exit-status`*]) [Macro]

Notify the user of an error that prevents `configure` from completing. This macro prints an error message to the standard error output and exits `configure` with *exit-status* (1 by default). *error-description* should be something like '`invalid value $HOME for \$HOME`'.

The *error-description* should start with a lower-case letter, and "cannot" is preferred to "can't".

`AC_MSG_FAILURE` (*`error-description`*, [*`exit-status`*]) [Macro]

This `AC_MSG_ERROR` wrapper notifies the user of an error that prevents `configure` from completing *and* that additional details are provided in '`config.log`'. This is typically used when abnormal results are found during a compilation.

`AC_MSG_WARN` (*`problem-description`*) [Macro]

Notify the `configure` user of a possible problem. This macro prints the message to the standard error output; `configure` continues running afterward, so macros that call `AC_MSG_WARN` should provide a default (back-up) behavior for the situations they warn about. *problem-description* should be something like '`ln -s seems to make hard links`'.

8 Programming in M4

Autoconf is written on top of two layers: *M4sugar*, which provides convenient macros for pure M4 programming, and *M4sh*, which provides macros dedicated to shell script generation.

As of this version of Autoconf, these two layers still contain experimental macros, whose interface might change in the future. As a matter of fact, *anything that is not documented must not be used.*

8.1 M4 Quotation

The most common problem with existing macros is an improper quotation. This section, which users of Autoconf can skip, but which macro writers *must* read, first justifies the quotation scheme that was chosen for Autoconf and then ends with a rule of thumb. Understanding the former helps one to follow the latter.

8.1.1 Active Characters

To fully understand where proper quotation is important, you first need to know what the special characters are in Autoconf: '`#`' introduces a comment inside which no macro expansion is performed, '`,`' separates arguments, '`[`' and '`]`' are the quotes themselves, '`(`' and '`)`' (which M4 tries to match by pairs), and finally '`$`' inside a macro definition.

In order to understand the delicate case of macro calls, we first have to present some obvious failures. Below they are "obvious-ified", but when you find them in real life, they are usually in disguise.

Comments, introduced by a hash and running up to the newline, are opaque tokens to the top level: active characters are turned off, and there is no macro expansion:

```
# define([def], ine)
⇒# define([def], ine)
```

Each time there can be a macro expansion, there is a quotation expansion, i.e., one level of quotes is stripped:

```
int tab[10];
⇒int tab10;
[int tab[10];]
⇒int tab[10];
```

Without this in mind, the reader might try hopelessly to use her macro `array`:

```
define([array], [int tab[10];])
array
⇒int tab10;
[array]
⇒array
```

How can you correctly output the intended results[1]?

[1] Using `defn`.

8.1.2 One Macro Call

Let's proceed on the interaction between active characters and macros with this small macro, which just returns its first argument:

```
define([car], [$1])
```

The two pairs of quotes above are not part of the arguments of `define`; rather, they are understood by the top level when it tries to find the arguments of `define`. Therefore, assuming `car` is not already defined, it is equivalent to write:

```
define(car, $1)
```

But, while it is acceptable for a '`configure.ac`' to avoid unnecessary quotes, it is bad practice for Autoconf macros which must both be more robust and also advocate perfect style.

At the top level, there are only two possibilities: either you quote or you don't:

```
car(foo, bar, baz)
⇒foo
[car(foo, bar, baz)]
⇒car(foo, bar, baz)
```

Let's pay attention to the special characters:

```
car(#)
error EOF in argument list
```

The closing parenthesis is hidden in the comment; with a hypothetical quoting, the top level understood it this way:

```
car([#)]
```

Proper quotation, of course, fixes the problem:

```
car([#])
⇒#
```

Here are more examples:

```
car(foo, bar)
⇒foo
car([foo, bar])
⇒foo, bar
car((foo, bar))
⇒(foo, bar)
car([(foo], [bar)])
⇒(foo
define([a], [b])
⇒
car(a)
⇒b
car([a])
⇒b
car([[a]])
⇒a
car([[[a]]])
⇒[a]
```

8.1.3 Quoting and Parameters

When M4 encounters '$' within a macro definition, followed immediately by a character it recognizes ('0'...'9', '#', '@', or '*'), it will perform M4 parameter expansion. This happens regardless of how many layers of quotes the parameter expansion is nested within, or even if it occurs in text that will be rescanned as a comment.

```
define([none], [$1])
⇒
define([one], [[$1]])
⇒
define([two], [[[$1]]])
⇒
define([comment], [# $1])
⇒
define([active], [ACTIVE])
⇒
none([active])
⇒ACTIVE
one([active])
⇒active
two([active])
⇒[active]
comment([active])
⇒# active
```

On the other hand, since autoconf generates shell code, you often want to output shell variable expansion, rather than performing M4 parameter expansion. To do this, you must use M4 quoting to separate the '$' from the next character in the definition of your macro. If the macro definition occurs in single-quoted text, then insert another level of quoting; if the usage is already inside a double-quoted string, then split it into concatenated strings.

```
define([single], [a single-quoted $[]1 definition])
⇒
define([double], [[a double-quoted $][1 definition]])
⇒
single
⇒a single-quoted $1 definition
double
⇒a double-quoted $1 definition
```

Posix states that M4 implementations are free to provide implementation extensions when '${' is encountered in a macro definition. Autoconf reserves the longer sequence '${{' for use with planned extensions that will be available in the future GNU M4 2.0, but guarantees that all other instances of '${' will be output literally. Therefore, this idiom can also be used to output shell code parameter references:

```
define([first], [${1}])first
⇒${1}
```

Posix also states that '$11' should expand to the first parameter concatenated with a literal '1', although some versions of GNU M4 expand the eleventh parameter instead. For portability, you should only use single-digit M4 parameter expansion.

With this in mind, we can explore the cases where macros invoke macros...

8.1.4 Quotation and Nested Macros

The examples below use the following macros:

```
define([car], [$1])
define([active], [ACT, IVE])
define([array], [int tab[10]])
```

Each additional embedded macro call introduces other possible interesting quotations:

```
car(active)
⇒ACT
car([active])
⇒ACT, IVE
car([[active]])
⇒active
```

In the first case, the top level looks for the arguments of `car`, and finds '`active`'. Because M4 evaluates its arguments before applying the macro, '`active`' is expanded, which results in:

```
car(ACT, IVE)
⇒ACT
```

In the second case, the top level gives '`active`' as first and only argument of `car`, which results in:

```
active
⇒ACT, IVE
```

i.e., the argument is evaluated *after* the macro that invokes it. In the third case, `car` receives '`[active]`', which results in:

```
[active]
⇒active
```

exactly as we already saw above.

The example above, applied to a more realistic example, gives:

```
car(int tab[10];)
⇒int tab10;
car([int tab[10];])
⇒int tab10;
car([[int tab[10];]])
⇒int tab[10];
```

Huh? The first case is easily understood, but why is the second wrong, and the third right? To understand that, you must know that after M4 expands a macro, the resulting text is immediately subjected to macro expansion and quote removal. This means that the quote removal occurs twice—first before the argument is passed to the `car` macro, and second after the `car` macro expands to the first argument.

As the author of the Autoconf macro `car`, you then consider it to be incorrect that your users have to double-quote the arguments of `car`, so you "fix" your macro. Let's call it `qar` for quoted car:

```
define([qar], [[$1]])
```

and check that `qar` is properly fixed:

```
qar([int tab[10];])
⇒int tab[10];
```

Ahhh! That's much better.

But note what you've done: now that the result of `qar` is always a literal string, the only time a user can use nested macros is if she relies on an *unquoted* macro call:

```
qar(active)
⇒ACT
qar([active])
⇒active
```

leaving no way for her to reproduce what she used to do with `car`:

```
car([active])
⇒ACT, IVE
```

Worse yet: she wants to use a macro that produces a set of `cpp` macros:

```
define([my_includes], [#include <stdio.h>])
car([my_includes])
⇒#include <stdio.h>
qar(my_includes)
error EOF in argument list
```

This macro, `qar`, because it double quotes its arguments, forces its users to leave their macro calls unquoted, which is dangerous. Commas and other active symbols are interpreted by M4 before they are given to the macro, often not in the way the users expect. Also, because `qar` behaves differently from the other macros, it's an exception that should be avoided in Autoconf.

8.1.5 `changequote` is Evil

The temptation is often high to bypass proper quotation, in particular when it's late at night. Then, many experienced Autoconf hackers finally surrender to the dark side of the force and use the ultimate weapon: `changequote`.

The M4 builtin `changequote` belongs to a set of primitives that allow one to adjust the syntax of the language to adjust it to one's needs. For instance, by default M4 uses '`‘`' and '`’`' as quotes, but in the context of shell programming (and actually of most programming languages), that's about the worst choice one can make: because of strings and back-quoted expressions in shell code (such as '`’this’`' and '`‘that‘`'), and because of literal characters in usual programming languages (as in '`’0’`'), there are many unbalanced '`‘`' and '`’`'. Proper M4 quotation then becomes a nightmare, if not impossible. In order to make M4 useful in such a context, its designers have equipped it with `changequote`, which makes it possible to choose another pair of quotes. M4sugar, M4sh, Autoconf, and Autotest all have chosen to use '`[`' and '`]`'. Not especially because they are unlikely characters, but *because they are characters unlikely to be unbalanced.*

There are other magic primitives, such as `changecom` to specify what syntactic forms are comments (it is common to see '`changecom(<!--, -->)`' when M4 is used to produce HTML pages), `changeword` and `changesyntax` to change other syntactic details (such as the character to denote the *n*th argument, '`$`' by default, the parentheses around arguments, etc.).

These primitives are really meant to make M4 more useful for specific domains: they should be considered like command line options: '`--quotes`', '`--comments`', '`--words`', and '`--syntax`'. Nevertheless, they are implemented as M4 builtins, as it makes M4 libraries self contained (no need for additional options).

There lies the problem. . .

The problem is that it is then tempting to use them in the middle of an M4 script, as opposed to its initialization. This, if not carefully thought out, can lead to disastrous effects: *you are changing the language in the middle of the execution.* Changing and restoring the syntax is often not enough: if you happened to invoke macros in between, these macros are lost, as the current syntax is probably not the one they were implemented with.

8.1.6 Quadrigraphs

When writing an Autoconf macro you may occasionally need to generate special characters that are difficult to express with the standard Autoconf quoting rules. For example, you may need to output the regular expression '`[^[]`', which matches any character other than '`[`'. This expression contains unbalanced brackets so it cannot be put easily into an M4 macro.

You can work around this problem by using one of the following *quadrigraphs*:

'`@<:@`' '`[`'

'`@:>@`' '`]`'

'`@S|@`' '`$`'

'`@%:@`' '`#`'

'`@&t@`' Expands to nothing.

Quadrigraphs are replaced at a late stage of the translation process, after `m4` is run, so they do not get in the way of M4 quoting. For example, the string '`^@<:@`', independently of its quotation, appears as '`^[`' in the output.

The empty quadrigraph can be used:

- to mark trailing spaces explicitly

  Trailing spaces are smashed by `autom4te`. This is a feature.

- to produce other quadrigraphs

  For instance '`@<@&t@:@`' produces '`@<:@`'.

- to escape *occurrences* of forbidden patterns

  For instance you might want to mention `AC_FOO` in a comment, while still being sure that `autom4te` still catches unexpanded '`AC_*`'. Then write '`AC@&t@_FOO`'.

The name '`@&t@`' was suggested by Paul Eggert:

> I should give some credit to the '`@&t@`' pun. The '`&`' is my own invention, but the '`t`' came from the source code of the ALGOL68C compiler, written by Steve Bourne (of Bourne shell fame), and which used '`mt`' to denote the empty string. In C, it would have looked like something like:
>
> ```
> char const mt[] = "";
> ```
>
> but of course the source code was written in Algol 68.
>
> I don't know where he got '`mt`' from: it could have been his own invention, and I suppose it could have been a common pun around the Cambridge University computer lab at the time.

8.1.7 Quotation Rule Of Thumb

To conclude, the quotation rule of thumb is:

One pair of quotes per pair of parentheses.

Never over-quote, never under-quote, in particular in the definition of macros. In the few places where the macros need to use brackets (usually in C program text or regular expressions), properly quote *the arguments*!

It is common to read Autoconf programs with snippets like:

```
AC_TRY_LINK(
changequote(<<, >>)dnl
<<#include <time.h>
#ifndef tzname /* For SGI.  */
extern char *tzname[]; /* RS6000 and others reject char **tzname.  */
#endif>>,
changequote([, ])dnl
[atoi (*tzname);], ac_cv_var_tzname=yes, ac_cv_var_tzname=no)
```

which is incredibly useless since `AC_TRY_LINK` is *already* double quoting, so you just need:

```
AC_TRY_LINK(
[#include <time.h>
#ifndef tzname /* For SGI.  */
extern char *tzname[]; /* RS6000 and others reject char **tzname.  */
#endif],
            [atoi (*tzname);],
            [ac_cv_var_tzname=yes],
            [ac_cv_var_tzname=no])
```

The M4-fluent reader might note that these two examples are rigorously equivalent, since M4 swallows both the '`changequote(<<, >>)`' and '`<<`' '`>>`' when it *collects* the arguments: these quotes are not part of the arguments!

Simplified, the example above is just doing this:

```
changequote(<<, >>)dnl
<<[]>>
changequote([, ])dnl
```

instead of simply:

```
[[]]
```

With macros that do not double quote their arguments (which is the rule), double-quote the (risky) literals:

```
AC_LINK_IFELSE([AC_LANG_PROGRAM(
[[#include <time.h>
#ifndef tzname /* For SGI.  */
extern char *tzname[]; /* RS6000 and others reject char **tzname.  */
#endif]],
                                [atoi (*tzname);])],
                [ac_cv_var_tzname=yes],
                [ac_cv_var_tzname=no])
```

Please note that the macro `AC_TRY_LINK` is obsolete, so you really should be using `AC_LINK_IFELSE` instead.

See Section 8.1.6 [Quadrigraphs], page 118, for what to do if you run into a hopeless case where quoting does not suffice.

When you create a `configure` script using newly written macros, examine it carefully to check whether you need to add more quotes in your macros. If one or more words have disappeared in the M4 output, you need more quotes. When in doubt, quote.

However, it's also possible to put on too many layers of quotes. If this happens, the resulting `configure` script may contain unexpanded macros. The `autoconf` program checks for this problem by looking for the string '`AC_`' in '`configure`'. However, this heuristic does not work in general: for example, it does not catch overquoting in `AC_DEFINE` descriptions.

8.2 Using `autom4te`

The Autoconf suite, including M4sugar, M4sh, and Autotest, in addition to Autoconf per se, heavily rely on M4. All these different uses revealed common needs factored into a layer over M4: `autom4te`[2].

`autom4te` is a preprocessor that is like `m4`. It supports M4 extensions designed for use in tools like Autoconf.

8.2.1 Invoking `autom4te`

The command line arguments are modeled after M4's:

`autom4te` *`options files`*

where the *files* are directly passed to `m4`. By default, GNU M4 is found during configuration, but the environment variable `M4` can be set to tell `autom4te` where to look. In addition to the regular expansion, it handles the replacement of the quadrigraphs (see Section 8.1.6 [Quadrigraphs], page 118), and of '`__oline__`', the current line in the output. It supports an extended syntax for the *files*:

'*`file`*`.m4f`'
: This file is an M4 frozen file. Note that *all the previous files are ignored*. See the option '`--melt`' for the rationale.

[2] Yet another great name from Lars J. Aas.

'*file*?' If found in the library path, the *file* is included for expansion, otherwise it is ignored instead of triggering a failure.

Of course, it supports the Autoconf common subset of options:

'--help'
'-h' Print a summary of the command line options and exit.

'--version'
'-V' Print the version number of Autoconf and exit.

'--verbose'
'-v' Report processing steps.

'--debug'
'-d' Don't remove the temporary files and be even more verbose.

'--include=*dir*'
'-I *dir*' Also look for input files in *dir*. Multiple invocations accumulate.

'--output=*file*'
'-o *file*' Save output (script or trace) to *file*. The file '-' stands for the standard output.

As an extension of m4, it includes the following options:

'--warnings=*category*'
'-W *category*'
Report the warnings related to *category* (which can actually be a comma separated list). See Section 9.3 [Reporting Messages], page 147, macro AC_DIAGNOSE, for a comprehensive list of categories. Special values include:

'all' report all the warnings

'none' report none

'error' treats warnings as errors

'no-*category*'
disable warnings falling into *category*

Warnings about 'syntax' are enabled by default, and the environment variable WARNINGS, a comma separated list of categories, is honored. 'autom4te -W *category*' actually behaves as if you had run:

```
autom4te --warnings=syntax,$WARNINGS,category
```

For example, if you want to disable defaults and WARNINGS of autom4te, but enable the warnings about obsolete constructs, you would use '-W none,obsolete'.

autom4te displays a back trace for errors, but not for warnings; if you want them, just pass '-W error'.

'--melt'
'-M' Do not use frozen files. Any argument *file*.m4f is replaced by *file*.m4. This helps tracing the macros which are executed only when the files are frozen, typically m4_define. For instance, running:

```
autom4te --melt 1.m4 2.m4f 3.m4 4.m4f input.m4
```

is roughly equivalent to running:

```
m4 1.m4 2.m4 3.m4 4.m4 input.m4
```

while

```
autom4te 1.m4 2.m4f 3.m4 4.m4f input.m4
```

is equivalent to:

```
m4 --reload-state=4.m4f input.m4
```

'`--freeze`'
'`-f`' Produce a frozen state file. `autom4te` freezing is stricter than M4's: it must produce no warnings, and no output other than empty lines (a line with white space is *not* empty) and comments (starting with '`#`'). Unlike `m4`'s similarly-named option, this option takes no argument:

```
autom4te 1.m4 2.m4 3.m4 --freeze --output=3.m4f
```

corresponds to

```
m4 1.m4 2.m4 3.m4 --freeze-state=3.m4f
```

'`--mode=`*`octal-mode`*'
'`-m` *`octal-mode`*'
Set the mode of the non-traces output to *octal-mode*; by default '`0666`'.

As another additional feature over `m4`, `autom4te` caches its results. GNU M4 is able to produce a regular output and traces at the same time. Traces are heavily used in the GNU Build System: `autoheader` uses them to build '`config.h.in`', `autoreconf` to determine what GNU Build System components are used, `automake` to "parse" '`configure.ac`' etc. To avoid recomputation, traces are cached while performing regular expansion, and conversely. This cache is (actually, the caches are) stored in the directory '`autom4te.cache`'. *It can safely be removed* at any moment (especially if for some reason `autom4te` considers it trashed).

'`--cache=`*`directory`*'
'`-C` *`directory`*'
Specify the name of the directory where the result should be cached. Passing an empty value disables caching. Be sure to pass a relative file name, as for the time being, global caches are not supported.

'`--no-cache`'
Don't cache the results.

'`--force`'
'`-f`' If a cache is used, consider it obsolete (but update it anyway).

Because traces are so important to the GNU Build System, `autom4te` provides high level tracing features as compared to M4, and helps exploiting the cache:

'`--trace=`*`macro`*`[:`*`format`*`]`'
'`-t` *`macro`*`[:`*`format`*`]`'
Trace the invocations of *macro* according to the *format*. Multiple '`--trace`' arguments can be used to list several macros. Multiple '`--trace`' arguments

for a single macro are not cumulative; instead, you should just make *format* as long as needed.

The *format* is a regular string, with newlines if desired, and several special escape codes. It defaults to '`$f:$l:$n:$%`'. It can use the following special escapes:

'`$$`' The character '`$`'.

'`$f`' The file name from which *macro* is called.

'`$l`' The line number from which *macro* is called.

'`$d`' The depth of the *macro* call. This is an M4 technical detail that you probably don't want to know about.

'`$n`' The name of the *macro*.

'`$num`' The *num*th argument of the call to *macro*.

'`$@`'
'`$sep@`'
'`${separator}@`'
All the arguments passed to *macro*, separated by the character *sep* or the string *separator* ('`,`' by default). Each argument is quoted, i.e., enclosed in a pair of square brackets.

'`$*`'
'`$sep*`'
'`${separator}*`'
As above, but the arguments are not quoted.

'`$%`'
'`$sep%`'
'`${separator}%`'
As above, but the arguments are not quoted, all new line characters in the arguments are smashed, and the default separator is '`:`'.

The escape '`$%`' produces single-line trace outputs (unless you put newlines in the '`separator`'), while '`$@`' and '`$*`' do not.

See Section 3.4 [autoconf Invocation], page 12, for examples of trace uses.

'`--preselect=macro`'
'`-p macro`'
Cache the traces of *macro*, but do not enable traces. This is especially important to save CPU cycles in the future. For instance, when invoked, `autoconf` preselects all the macros that `autoheader`, `automake`, `autoreconf`, etc., trace, so that running `m4` is not needed to trace them: the cache suffices. This results in a huge speed-up.

Finally, `autom4te` introduces the concept of *Autom4te libraries*. They consists in a powerful yet extremely simple feature: sets of combined command line arguments:

'`--language=language`'
'`-l language`'

Use the *language* Autom4te library. Current languages include:

`M4sugar` create M4sugar output.

`M4sh` create M4sh executable shell scripts.

`Autotest` create Autotest executable test suites.

`Autoconf-without-aclocal-m4`
create Autoconf executable configure scripts without reading '`aclocal.m4`'.

`Autoconf` create Autoconf executable configure scripts. This language inherits all the characteristics of `Autoconf-without-aclocal-m4` and additionally reads '`aclocal.m4`'.

'`--prepend-include=dir`'
'`-B dir`' Prepend directory *dir* to the search path. This is used to include the language-specific files before any third-party macros.

As an example, if Autoconf is installed in its default location, '`/usr/local`', the command '`autom4te -l m4sugar foo.m4`' is strictly equivalent to the command:

```
autom4te --prepend-include /usr/local/share/autoconf \
  m4sugar/m4sugar.m4f --warnings syntax foo.m4
```

Recursive expansion applies here: the command '`autom4te -l m4sh foo.m4`' is the same as '`autom4te --language M4sugar m4sugar/m4sh.m4f foo.m4`', i.e.:

```
autom4te --prepend-include /usr/local/share/autoconf \
  m4sugar/m4sugar.m4f m4sugar/m4sh.m4f --mode 777 foo.m4
```

The definition of the languages is stored in '`autom4te.cfg`'.

8.2.2 Customizing `autom4te`

One can customize `autom4te` via '`~/.autom4te.cfg`' (i.e., as found in the user home directory), and '`./.autom4te.cfg`' (i.e., as found in the directory from which `autom4te` is run). The order is first reading '`autom4te.cfg`', then '`~/.autom4te.cfg`', then '`./.autom4te.cfg`', and finally the command line arguments.

In these text files, comments are introduced with `#`, and empty lines are ignored. Customization is performed on a per-language basis, wrapped in between a '`begin-language: "language"`', '`end-language: "language"`' pair.

Customizing a language stands for appending options (see Section 8.2.1 [autom4te Invocation], page 120) to the current definition of the language. Options, and more generally arguments, are introduced by '`args: arguments`'. You may use the traditional shell syntax to quote the *arguments*.

As an example, to disable Autoconf caches ('`autom4te.cache`') globally, include the following lines in '`~/.autom4te.cfg`':

```
## ------------------ ##
## User Preferences.  ##
## ------------------ ##
```

```
begin-language: "Autoconf-without-aclocal-m4"
args: --no-cache
end-language: "Autoconf-without-aclocal-m4"
```

8.3 Programming in M4sugar

M4 by itself provides only a small, but sufficient, set of all-purpose macros. M4sugar introduces additional generic macros. Its name was coined by Lars J. Aas: "Readability And Greater Understanding Stands 4 M4sugar".

M4sugar reserves the macro namespace '`^_m4_`' for internal use, and the macro namespace '`^m4_`' for M4sugar macros. You should not define your own macros into these namespaces.

8.3.1 Redefined M4 Macros

With a few exceptions, all the M4 native macros are moved in the '`m4_`' pseudo-namespace, e.g., M4sugar renames `define` as `m4_define` etc.

The list of macros unchanged from M4, except for their name, is:

- m4_builtin
- m4_changecom
- m4_changequote
- m4_debugfile
- m4_debugmode
- m4_decr
- m4_define
- m4_divnum
- m4_dumpdef
- m4_errprint
- m4_esyscmd
- m4_eval
- m4_format
- m4_ifdef
- m4_incr
- m4_index
- m4_indir
- m4_len
- m4_pushdef
- m4_shift
- m4_substr
- m4_syscmd
- m4_sysval

- m4_traceoff
- m4_traceon
- m4_translit

Some M4 macros are redefined, and are slightly incompatible with their native equivalent.

`__file__` [Macro]
`__line__` [Macro]

All M4 macros starting with '`__`' retain their original name: for example, no `m4__file__` is defined.

`__oline__` [Macro]

This is not technically a macro, but a feature of Autom4te. The sequence `__oline__` can be used similarly to the other m4sugar location macros, but rather than expanding to the location of the input file, it is translated to the line number where it appears in the output file after all other M4 expansions.

`dnl` [Macro]

This macro kept its original name: no `m4_dnl` is defined.

`m4_bpatsubst (`*`string`*`, `*`regexp`*`, [`*`replacement`*`])` [Macro]

This macro corresponds to `patsubst`. The name `m4_patsubst` is kept for future versions of M4sugar, once GNU M4 2.0 is released and supports extended regular expression syntax.

`m4_bregexp (`*`string`*`, `*`regexp`*`, [`*`replacement`*`])` [Macro]

This macro corresponds to `regexp`. The name `m4_regexp` is kept for future versions of M4sugar, once GNU M4 2.0 is released and supports extended regular expression syntax.

`m4_defn (`*`macro`*`)` [Macro]

Unlike the M4 builtin, this macro fails if *macro* is not defined. Also, while newer M4 can concatenate multiple definitions, this version currently only supports a single *macro*. See `m4_undefine`.

`m4_divert (`*`diversion`*`)` [Macro]

M4sugar relies heavily on diversions, so rather than behaving as a primitive, `m4_divert` behaves like:

```
m4_divert_pop()m4_divert_push([diversion])
```

See Section 8.3.3 [Diversion support], page 128, for more details about the use of the diversion stack.

`m4_exit (`*`exit-status`*`)` [Macro]

This macro corresponds to `m4exit`.

`m4_if (`*`comment`*`)` [Macro]
`m4_if (`*`string-1`*`, `*`string-2`*`, `*`equal`*`, [`*`not-equal`*`])` [Macro]
`m4_if (`*`string-1`*`, `*`string-2`*`, `*`equal`*`, ...)` [Macro]

This macro corresponds to `ifelse`. *string-1* and *string-2* are compared literally, so usually one of the two arguments is passed unquoted. See Section 8.3.4 [Conditional constructs], page 130, for more conditional idioms.

`m4_include (file)` [Macro]
`m4_sinclude (file)` [Macro]

Like the M4 builtins, but warn against multiple inclusions of *file*.

`m4_mkstemp (template)` [Macro]
`m4_maketemp (template)` [Macro]

Posix requires `maketemp` to replace the trailing '`X`' characters in *template* with the process id, without regards to the existence of a file by that name, but this a security hole. When this was pointed out to the Posix folks, they agreed to invent a new macro `mkstemp` that always creates a uniquely named file, but not all versions of GNU M4 support the new macro. In M4sugar, `m4_maketemp` and `m4_mkstemp` are synonyms for each other, and both have the secure semantics regardless of which macro the underlying M4 provides.

`m4_popdef (macro)` [Macro]

Unlike the M4 builtin, this macro fails if *macro* is not defined. Also, while newer M4 can pop multiple definitions at once, this version currently only supports a single *macro*. See `m4_undefine`.

`m4_undefine (macro)` [Macro]

Unlike the M4 builtin, this macro fails if *macro* is not defined. Also, while newer M4 can undefine multiple definitions at once, this version currently only supports a single *macro*. Use

```
m4_ifdef([macro], [m4_undefine([macro])])
```

to recover the behavior of the builtin.

`m4_undivert (diversion)` [Macro]

Unlike the M4 builtin, only one diversion can be undiverted per invocation. Also, since the M4sugar diversion stack prefers named diversions, the use of `m4_undivert` to include files is risky. See Section 8.3.3 [Diversion support], page 128, for more details about the use of the diversion stack.

`m4_wrap (text)` [Macro]
`m4_wrap_lifo (text)` [Macro]

These macros correspond to `m4wrap`. Posix requires arguments of multiple wrap calls to be reprocessed at EOF in the same order as the original calls (first-in, first-out). GNU M4 versions through 1.4.10, however, reprocess them in reverse order (last-in, first-out). Both orders are useful, therefore, you can rely on `m4_wrap` to provide FIFO semantics and `m4_wrap_lifo` for LIFO semantics, regardless of the underlying GNU M4 version.

Unlike the GNU M4 builtin, these macros only recognize one argument, and avoid token pasting between consecutive invocations. On the other hand, nested calls to `m4_wrap` from within wrapped text work just as in the builtin.

8.3.2 Diagnostic messages from M4sugar

When macros statically diagnose abnormal situations, benign or fatal, they should report them using these macros. For issuing dynamic issues, i.e., when `configure` is run, see Section 7.5 [Printing Messages], page 110.

`m4_assert` (*expression*, [*exit-status* = '`1`']) [Macro]

Assert that the arithmetic *expression* evaluates to non-zero. Otherwise, issue a fatal error, and exit `autom4te` with *exit-status*.

`m4_errprintn` (*message*) [Macro]

Similar to the builtin `m4_errprint`, except that a newline is guaranteed after *message*.

`m4_fatal` (*message*) [Macro]

Report a severe error *message* prefixed with the current location, and have `autom4te` die.

`m4_location` [Macro]

Useful as a prefix in a message line. Short for:

```
__file__:__line__
```

`m4_warn` (*category*, *message*) [Macro]

Report *message* as a warning (or as an error if requested by the user) if warnings of the *category* are turned on. If the message is emitted, it is prefixed with the current location, and followed by a call trace of all macros defined via `AC_DEFUN` used to get to the current expansion. You are encouraged to use standard categories, which currently include:

'`all`' messages that don't fall into one of the following categories. Use of an empty *category* is equivalent.

'`cross`' related to cross compilation issues.

'`obsolete`' use of an obsolete construct.

'`syntax`' dubious syntactic constructs, incorrectly ordered macro calls.

8.3.3 Diversion support

M4sugar makes heavy use of diversions, because it is often the case that text that must appear early in the output is not discovered until late in the input. Additionally, some of the topological sorting algorithms used in resolving macro dependencies use diversions. Therefore, most macros should not need to change diversions directly, but rather rely on higher-level M4sugar macros to manage diversions transparently.

To make diversion management easier, M4sugar uses the concept of named diversions. Rather than using diversion numbers directly, it is nicer to associate a name with each diversion; the diversion number associated with a particular diversion name is an implementation detail, so you should only use diversion names. In general, you should not output text to a named diversion until after calling the appropriate initialization routine for your language (`m4_init`, `AS_INIT`, `AT_INIT`, ...), although there are some exceptions documented below.

M4sugar defines two named diversions.

`KILL` Text written to this diversion is discarded. This is the default diversion once M4sugar is initialized.

GROW This diversion is used behind the scenes by topological sorting macros, such as AC_REQUIRE.

M4sh adds several more named diversions.

BINSH This diversion is reserved for the '#!' interpreter line.

HEADER-REVISION
This diversion holds text from AC_REVISION.

HEADER-COMMENT
This diversion holds comments about the purpose of a file.

HEADER-COPYRIGHT
This diversion is managed by AC_COPYRIGHT.

M4SH-SANITIZE
This diversion contains M4sh sanitization code, used to ensure M4sh is executing in a reasonable shell environment.

M4SH-INIT
This diversion contains M4sh initialization code, initializing variables that are required by other M4sh macros.

BODY This diversion contains the body of the shell code, and is the default diversion once M4sh is initialized.

Autotest inherits diversions from M4sh, and changes the default diversion from BODY back to KILL. It also adds several more named diversions, with the following subset designed for developer use.

PREPARE_TESTS
This diversion contains initialization sequences which are executed after 'atconfig' and 'atlocal', and after all command line arguments have been parsed, but prior to running any tests. It can be used to set up state that is required across all tests. This diversion will work even before AT_INIT.

For now, the named diversions of Autoconf and Autoheader, and the remaining diversions of Autotest, are not documented. In other words, intentionally outputting text into an undocumented diversion is subject to breakage in a future release of Autoconf.

m4_divert_once (*diversion*, [*content*]) [Macro]
Similar to m4_divert_text, except that *content* is only output to *diversion* if this is the first time that m4_divert_once has been called with its particular arguments.

m4_divert_pop ([*diversion*]) [Macro]
If provided, check that the current diversion is indeed *diversion*. Then change to the diversion located earlier on the stack, giving an error if an attempt is made to pop beyond the initial m4sugar diversion of KILL.

m4_divert_push (*diversion*) [Macro]
Remember the former diversion on the diversion stack, and output subsequent text into *diversion*. M4sugar maintains a diversion stack, and issues an error if there is not a matching pop for every push.

`m4_divert_text (diversion, [content])` [Macro]

Output *content* and a newline into *diversion*, without affecting the current diversion. Shorthand for:

```
m4_divert_push([diversion])content
m4_divert_pop([diversion])dnl
```

`m4_init` [Macro]

Initialize the M4sugar environment, setting up the default named diversion to be `KILL`.

8.3.4 Conditional constructs

The following macros provide additional conditional contructs, as convenience wrappers around `m4_if`.

`m4_bmatch (string, regex-1, value-1, [regex-2], [value-2], ..., [default])` [Macro]

The string *string* is repeatedly compared against a series of *regex* arguments; if a match is found, the expansion is the corresponding *value*, otherwise, the macro moves on to the next *regex*. If no *regex* match, then the result is the optional *default*, or nothing.

`m4_bpatsubsts (string, regex-1, subst-1, [regex-2], [subst-2], ...)` [Macro]

The string *string* is altered by *regex-1* and *subst-1*, as if by:

```
m4_bpatsubst([[string]], [regex], [subst])
```

The result of the substitution is then passed through the next set of *regex* and *subst*, and so forth. An empty *subst* implies deletion of any matched portions in the current string. Note that this macro over-quotes *string*; this behavior is intentional, so that the result of each step of the recursion remains as a quoted string. However, it means that anchors ('^' and '$' in the *regex* will line up with the extra quotations, and not the characters of the original string.

`m4_case (string, value-1, if-value-1, [value-2], [if-value-2], ..., [default])` [Macro]

Test *string* against multiple *value* possibilities, resulting in the first *if-value* for a match, or in the optional *default*. This is shorthand for:

```
m4_if([string], [value-1], [if-value-1],
      [string], [value-2], [if-value-2], ...,
      [default])
```

`m4_cond (test-1, value-1, if-value-1, [test-2], [value-2], [if-value-2], ..., [default])` [Macro]

This macro was introduced in Autoconf 2.62. Similar to `m4_if`, except that each *test* is expanded only when it is encountered. This is useful for short-circuiting expensive tests; while `m4_if` requires all its strings to be expanded up front before doing comparisons, `m4_cond` only expands a *test* when all earlier tests have failed.

For an example, these two sequences give the same result, but in the case where '$1' does not contain a backslash, the `m4_cond` version only expands `m4_index` once,

instead of five times, for faster computation if this is a common case for '$1'. Notice that every third argument is unquoted for m4_if, and quoted for m4_cond:

```
m4_if(m4_index([$1], [\]), [-1], [$2],
      m4_eval(m4_index([$1], [\\]) >= 0), [1], [$2],
      m4_eval(m4_index([$1], [\$]) >= 0), [1], [$2],
      m4_eval(m4_index([$1], [\`]) >= 0), [1], [$3],
      m4_eval(m4_index([$1], [\"]) >= 0), [1], [$3],
      [$2])
m4_cond([m4_index([$1], [\])], [-1], [$2],
        [m4_eval(m4_index([$1], [\\]) >= 0)], [1], [$2],
        [m4_eval(m4_index([$1], [\$]) >= 0)], [1], [$2],
        [m4_eval(m4_index([$1], [\`]) >= 0)], [1], [$3],
        [m4_eval(m4_index([$1], [\"]) >= 0)], [1], [$3],
        [$2])
```

m4_default (*expr-1*, *expr-2*) [Macro]

If *expr-1* is not empty, use it. Otherwise, expand to *expr-2*. Useful for providing a fixed default if the expression that results in *expr-1* would otherwise be empty.

m4_ifndef (*macro*, *if-not-defined*, [*if-defined*]) [Macro]

This is shorthand for:

```
m4_ifdef([macro], [if-defined], [if-not-defined])
```

m4_ifset (*macro*, [*if-true*], [*if-false*]) [Macro]

If *macro* is undefined, or is defined as the empty string, expand to *if-false*. Otherwise, expands to *if-true*. Similar to:

```
m4_ifval(m4_defn([macro]), [if-true], [if-false])
```

except that it is not an error if *macro* is undefined.

m4_ifval (*cond*, [*if-true*], [*if-false*]) [Macro]

Expands to *if-true* if *cond* is not empty, otherwise to *if-false*. This is shorthand for:

```
m4_if([cond], [], [if-true], [if-false])
```

m4_ifvaln (*cond*, [*if-true*], [*if-false*]) [Macro]

Similar to m4_ifval, except guarantee that a newline is present after any non-empty expansion.

m4_n (*text*) [Macro]

Expand to *text*, and add a newline if *text* is not empty.

8.3.5 Looping constructs

The following macros are useful in implementing recursive algorithms in M4, including loop operations. An M4 list is formed by quoting a list of quoted elements; generally the lists are comma-separated, although m4_foreach_w is whitespace-separated. For example, the list '[[a], [b,c]]' contains two elements: '[a]' and '[b,c]'. It is common to see lists with unquoted elements when those elements are not likely to be macro names, as in '[fputc_unlocked, fgetc_unlocked]'.

`m4_car` (*list*) [Macro]

Expands to the quoted first element of the comma-separated quoted *list*. Often used with `m4_cdr` to recursively iterate through a list. Generally, when using quoted lists of quoted elements, `m4_car` should be called without any extra quotes.

`m4_cdr` (*list*) [Macro]

Expands to a quoted list of all but the first element of the comma-separated quoted *list*, or the empty string if *list* had only one element. Generally, when using quoted lists of quoted elements, `m4_cdr` should be called without any extra quotes.

For example, this is a simple implementation of `m4_map`; note how each iteration checks for the end of recursion, then merely applies the first argument to the first element of the list, then repeats with the rest of the list. (The actual implementation in M4sugar is a bit more involved, to gain some speed and share code with `m4_map_sep`).

```
m4_define([m4_map], [m4_ifval([$2],
  [m4_apply([$1], m4_car($2))[]$0([$1], m4_cdr($2))])])dnl
m4_map([ m4_eval], [[[1]], [[1+1]], [[10],[16]]])
⇒ 1 2 a
```

`m4_for` (*var*, *first*, *last*, [*step*], *expression*) [Macro]

Loop over the numeric values between *first* and *last* including bounds by increments of *step*. For each iteration, expand *expression* with the numeric value assigned to *var*. If *step* is omitted, it defaults to '`1`' or '`-1`' depending on the order of the limits. If given, *step* has to match this order.

`m4_foreach` (*var*, *list*, *expression*) [Macro]

Loop over the comma-separated M4 list *list*, assigning each value to *var*, and expand *expression*. The following example outputs two lines:

```
m4_foreach([myvar], [[foo], [bar, baz]],
           [echo myvar
])dnl
⇒echo foo
⇒echo bar, baz
```

`m4_foreach_w` (*var*, *list*, *expression*) [Macro]

Loop over the white-space-separated list *list*, assigning each value to *var*, and expand *expression*.

The deprecated macro `AC_FOREACH` is an alias of `m4_foreach_w`.

`m4_map` (*macro*, *list*) [Macro]
`m4_map_sep` (*macro*, *separator*, *list*) [Macro]

Loop over the comma separated quoted list of argument descriptions in *list*, and invoke *macro* with the arguments. An argument description is in turn a comma-separated quoted list of quoted elements, suitable for `m4_apply`, making it possible to invoke *macro* without arguments if an argument description is empty. `m4_map_sep` additionally outputs *separator* between macro invocations, with no additional expansion of the separator.

```
m4_map([m4_count], [])
⇒
m4_map([ m4_count], [[],
                     [[1]],
                     [[1], [2]]])
⇒ 0 1 2
m4_map_sep([m4_eval], [,], [[[1+2]],
                            [[10], [16]]])
⇒3,a
```

`m4_shiftn` (*count*, ...) [Macro]
`m4_shift2` (...) [Macro]
`m4_shift3` (...) [Macro]

`m4_shiftn` performs *count* iterations of `m4_shift`, along with validation that enough arguments were passed in to match the shift count, and that the count is positive. `m4_shift2` and `m4_shift3` are specializations of `m4_shiftn`, introduced in Autoconf 2.62, and are more efficient for two and three shifts, respectively.

8.3.6 Evaluation Macros

The following macros give some control over the order of the evaluation by adding or removing levels of quotes.

`m4_apply` (*macro*, *list*) [Macro]

Apply the elements of the quoted, comma-separated *list* as the arguments to *macro*. If *list* is empty, invoke *macro* without arguments. Note the difference between `m4_indir`, which expects its first argument to be a macro name but can use names that are otherwise invalid, and `m4_apply`, where *macro* can contain other text, but must end in a valid macro name.

```
m4_apply([m4_count], [])
⇒0
m4_apply([m4_count], [[]])
⇒1
m4_apply([m4_count], [[1], [2]])
⇒2
m4_apply([m4_join], [[|], [1], [2]])
⇒1|2
```

`m4_count` (*arg*, ...) [Macro]

This macro returns the decimal count of the number of arguments it was passed.

`m4_do` (*arg*, ...) [Macro]

This macro loops over its arguments and expands each *arg* in sequence. Its main use is for readability; it allows the use of indentation and fewer `dnl` to result in the same expansion.

`m4_dquote` (*arg*, ...) [Macro]

Return the arguments as a quoted list of quoted arguments. Conveniently, if there is just one *arg*, this effectively adds a level of quoting.

`m4_dquote_elt` (*arg*, ...) [Macro]

Return the arguments as a series of double-quoted arguments. Whereas `m4_dquote` returns a single argument, `m4_dquote_elt` returns as many arguments as it was passed.

`m4_echo` (*arg*, ...) [Macro]

Return the arguments, with the same level of quoting. Other than discarding whitespace after unquoted commas, this macro is a no-op.

`m4_expand` (*arg*) [Macro]

Return the expansion of *arg* as a quoted string. Whereas `m4_quote` is designed to collect expanded text into a single argument, `m4_expand` is designed to perform one level of expansion on quoted text. The distinction is in the treatment of whitespace following a comma in the original *arg*. Any time multiple arguments are collected into one with `m4_quote`, the M4 argument collection rules discard the whitespace. However, with `m4_expand`, whitespace is preserved, even after the expansion of macros contained in *arg*.

Note that `m4_expand` cannot parse everything. The expansion of *arg* must not contain unbalanced quotes (although quadrigraphs can get around this), nor unbalanced parentheses (portable shell `case` statements are a major culprit here, but creative shell comments can get around this).

```
m4_define([active], [ACT, IVE])dnl
m4_define([active2], [[ACT, IVE]])dnl
m4_quote(active, active)
⇒ACT,IVE,ACT,IVE
m4_expand([active, active])
⇒ACT, IVE, ACT, IVE
m4_quote(active2, active2)
⇒ACT, IVE,ACT, IVE
m4_expand([active2, active2])
⇒ACT, IVE, ACT, IVE
```

`m4_ignore` (...) [Macro]

This macro was introduced in Autoconf 2.62. Expands to nothing, ignoring all of its arguments. By itself, this isn't very useful. However, it can be used to conditionally ignore an arbitrary number of arguments, by deciding which macro name to apply to a list of arguments.

```
dnl foo outputs a message only if [debug] is defined.
m4_define([foo],
[m4_ifdef([debug],[AC_MSG_NOTICE],[m4_ignore])([debug message])])
```

Note that for earlier versions of Autoconf, the macro `__gnu__` can serve the same purpose, although it is less readable.

`m4_make_list` (*arg*, ...) [Macro]

This macro exists to aid debugging of M4sugar algorithms. Its net effect is similar to `m4_dquote`—it produces a quoted list of quoted arguments, for each *arg*. The difference is that this version uses a comma-newline separator instead of just comma, to improve readability of the list; with the result that it is less efficient than `m4_dquote`.

```
m4_define([zero],[0])m4_define([one],[1])m4_define([two],[2])dnl
m4_dquote(zero, [one], [[two]])
⇒[0],[one],[[two]]
m4_make_list(zero, [one], [[two]])
⇒[0],
⇒[one],
⇒[[two]]
m4_foreach([number], m4_dquote(zero, [one], [[two]]), [ number])
⇒ 0 1 two
m4_foreach([number], m4_make_list(zero, [one], [[two]]), [ number])
⇒ 0 1 two
```

`m4_quote` (*arg*, ...) [Macro]

Return the arguments as a single entity, i.e., wrap them into a pair of quotes. This effectively collapses multiple arguments into one, although it loses whitespace after unquoted commas in the process.

`m4_unquote` (*arg*, ...) [Macro]

This macro was introduced in Autoconf 2.62. Expand each argument, separated by commas. For a single *arg*, this effectively removes a layer of quoting, and `m4_unquote([arg])` is more efficient than the equivalent `m4_do([arg])`. For multiple arguments, this results in an unquoted list of expansions. This is commonly used with `m4_split`, in order to convert a single quoted list into a series of quoted elements.

The following example aims at emphasizing the difference between several scenarios: not using these macros, using `m4_defn`, using `m4_quote`, using `m4_dquote`, and using `m4_expand`.

```
$ cat example.m4
dnl Overquote, so that quotes are visible.
m4_define([show], [$[]1 = [$1], $[]@ = [$@]])
m4_define([a], [A])
m4_define([mkargs], [1, 2[,] 3])
m4_define([arg1], [[$1]])
m4_divert([0])dnl
show(a, b)
show([a, b])
show(m4_quote(a, b))
show(m4_dquote(a, b))
show(m4_expand([a, b]))

arg1(mkargs)
arg1([mkargs])
arg1(m4_defn([mkargs]))
arg1(m4_quote(mkargs))
arg1(m4_dquote(mkargs))
arg1(m4_expand([mkargs]))
$ autom4te -l m4sugar example.m4
$1 = A, $@ = [A],[b]
```

```
$1 = a, b, $@ = [a, b]
$1 = A,b, $@ = [A,b]
$1 = [A],[b], $@ = [[A],[b]]
$1 = A, b, $@ = [A, b]

1
mkargs
1, 2[,] 3
1,2, 3
[1],[2, 3]
1, 2, 3
```

8.3.7 String manipulation in M4

The following macros may be used to manipulate strings in M4. Many of the macros in this section intentionally result in quoted strings as output, rather than subjecting the arguments to further expansions. As a result, if you are manipulating text that contains active M4 characters, the arguments are passed with single quoting rather than double.

`m4_append` (*macro-name*, *string*, [*separator*]) [Macro]
`m4_append_uniq` (*macro-name*, *string*, [*separator*] [*if-uniq*], [*if-duplicate*]) [Macro]

Redefine *macro-name* to its former contents with *separator* and *string* added at the end. If *macro-name* was undefined before (but not if it was defined but empty), then no *separator* is added. As of Autoconf 2.62, neither *string* nor *separator* are expanded during this macro; instead, they are expanded when *macro-name* is invoked.

`m4_append` can be used to grow strings, and `m4_append_uniq` to grow strings without duplicating substrings. Additionally, `m4_append_uniq` takes two optional parameters as of Autoconf 2.62; *if-uniq* is expanded if *string* was appended, and *if-duplicate* is expanded if *string* was already present. Also, `m4_append_uniq` warns if *separator* is not empty, but occurs within *string*, since that can lead to duplicates.

```
m4_define([active], [ACTIVE])dnl
m4_append([sentence], [This is an])dnl
m4_append([sentence], [ active ])dnl
m4_append([sentence], [symbol.])dnl
sentence
⇒This is an ACTIVE symbol.
m4_undefine([active])dnl
⇒This is an active symbol.
m4_append_uniq([list], [one], [, ], [new], [existing])
⇒new
m4_append_uniq([list], [one], [, ], [new], [existing])
⇒existing
m4_append_uniq([list], [two], [, ], [new], [existing])
⇒new
m4_append_uniq([list], [three], [, ], [new], [existing])
⇒new
m4_append_uniq([list], [two], [, ], [new], [existing])
```

```
⇒existing
list
⇒one, two, three
m4_dquote(list)
⇒[one],[two],[three]
m4_append([list2], [one], [[, ]])dnl
m4_append_uniq([list2], [two], [[, ]])dnl
m4_append([list2], [three], [[, ]])dnl
list2
⇒one, two, three
m4_dquote(list2)
⇒[one, two, three]
```

`m4_append_uniq_w` (*macro-name*, *strings*) [Macro]

This macro was introduced in Autoconf 2.62. It is similar to `m4_append_uniq`, but treats *strings* as a whitespace separated list of words to append, and only appends unique words. *macro-name* is updated with a single space between new words.

```
m4_append_uniq_w([numbers], [1 1 2])dnl
m4_append_uniq_w([numbers], [ 2 3 ])dnl
numbers
⇒1 2 3
```

`m4_combine` ([*separator*], *prefix-list*, [*infix*], *suffix-1*, [*suffix-2*], ...) [Macro]

This macro produces a quoted string containing the pairwise combination of every element of the quoted, comma-separated *prefix-list*, and every element from the *suffix* arguments. Each pairwise combination is joined with *infix* in the middle, and successive pairs are joined by *separator*. No expansion occurs on any of the arguments. No output occurs if either the *prefix* or *suffix* list is empty, but the lists can contain empty elements.

```
m4_define([a], [oops])dnl
m4_combine([, ], [[a], [b], [c]], [-], [1], [2], [3])
⇒a-1, a-2, a-3, b-1, b-2, b-3, c-1, c-2, c-3
m4_combine([, ], [[a], [b]], [-])
⇒
m4_combine([, ], [[a], [b]], [-], [])
⇒a-, b-
m4_combine([, ], [], [-], [1], [2])
⇒
m4_combine([, ], [[]], [-], [1], [2])
⇒-1, -2
```

`m4_flatten` (*string*) [Macro]

Flatten *string* into a single line. Delete all backslash-newline pairs, and replace all remaining newlines with a space. The result is still a quoted string.

`m4_join` ([*separator*], *args*...) [Macro]

Concatenate each *arg*, separated by *separator*, with the exception that no back-to-back separators are issued for empty arguments. The result is a quoted string.

```
m4_define([active], [ACTIVE])dnl
m4_join([|], [one], [], [active], [two])
⇒one|active|two
```

Note that if all you intend to do is join *args* with commas between them, to form a quoted list suitable for `m4_foreach`, it is more efficient to use `m4_dquote`.

`m4_newline` [Macro]

This macro was introduced in Autoconf 2.62, and expands to a newline. It is primarily useful for maintaining macro formatting, and ensuring that M4 does not discard leading whitespace during argument collection.

`m4_normalize` (*string*) [Macro]

Remove leading and trailing spaces and tabs, sequences of backslash-then-newline, and replace multiple spaces, tabs, and newlines with a single space. This is a combination of `m4_flatten` and `m4_strip`.

`m4_re_escape` (*string*) [Macro]

Backslash-escape all characters in *string* that are active in regexps.

`m4_split` (*string*, [*regexp* = '`[\t ]+`']) [Macro]

Split *string* into an M4 list of elements quoted by '`[`' and '`]`', while keeping white space at the beginning and at the end. If *regexp* is given, use it instead of '`[\t ]+`' for splitting. If *string* is empty, the result is an empty list.

`m4_strip` (*string*) [Macro]

Strip whitespace from *string*. Sequences of spaces and tabs are reduced to a single space, then leading and trailing spaces are removed. The result is still a quoted string. Note that this does not interfere with newlines; if you want newlines stripped as well, consider `m4_flatten`, or do it all at once with `m4_normalize`.

`m4_text_box` (*message*, [*frame* = '`-`']) [Macro]

Add a text box around *message*, using *frame* as the border character above and below the message. The frame correctly accounts for the subsequent expansion of *message*. For example:

```
m4_define([macro], [abc])dnl
m4_text_box([macro])
⇒## --- ##
⇒## abc ##
⇒## --- ##
```

`m4_text_wrap` (*string*, [*prefix*], [*prefix1* = '*prefix*'], [*width* = '79']) [Macro]

Break *string* into a series of whitespace-separated words, then output those words separated by spaces, and wrapping lines any time the output would exceed *width* columns. If given, *prefix1* begins the first line, and *prefix* begins all wrapped lines. If *prefix1* is longer than *prefix*, then the first line consists of just *prefix1*. If *prefix* is

longer than *prefix1*, padding is inserted so that the first word of *string* begins at the same indentation as all wrapped lines. Note that using literal tab characters in any of the arguments will interfere with the calculation of width. No expansions occur on *prefix*, *prefix1*, or the words of *string*, although quadrigraphs are recognized.

For some examples:

```
m4_text_wrap([Short string */], [   ], [/* ], [20])
⇒/* Short string */
m4_text_wrap([Much longer string */], [   ], [/* ], [20])
⇒/* Much longer
⇒   string */
m4_text_wrap([Short doc.], [          ], [  --short ], [30])
⇒  --short Short doc.
m4_text_wrap([Short doc.], [          ], [  --too-wide ], [30])
⇒  --too-wide
⇒          Short doc.
m4_text_wrap([Super long documentation.], [     ],
             [  --too-wide ], 30)
⇒  --too-wide
⇒     Super long
⇒     documentation.
```

`m4_tolower` (*string*) [Macro]
`m4_toupper` (*string*) [Macro]

Return *string* with letters converted to upper or lower case, respectively.

8.3.8 Arithmetic computation in M4

The following macros facilitate integer arithmetic operations. Where a parameter is documented as taking an arithmetic expression, you can use anything that can be parsed by `m4_eval`.

`m4_cmp` (*expr-1*, *expr-2*) [Macro]

Compare the arithmetic expressions *expr-1* and *expr-2*, and expand to '`-1`' if *expr-1* is smaller, '`0`' if they are equal, and '`1`' if *expr-1* is larger.

`m4_list_cmp` (*list-1*, *list-2*) [Macro]

Compare the two M4 lists consisting of comma-separated arithmetic expressions, left to right. Expand to '`-1`' for the first element pairing where the value from *list-1* is smaller, '`1`' where the value from *list-2* is smaller, or '`0`' if both lists have the same values. If one list is shorter than the other, the remaining elements of the longer list are compared against zero.

```
m4_list_cmp([1, 0],       [1])
⇒0
m4_list_cmp([1, [1 * 0]], [1, 0])
⇒0
m4_list_cmp([1, 2],       [1, 0])
⇒1
m4_list_cmp([1, [1+1], 3],[1, 2])
```

```
⇒1
m4_list_cmp([1, 2, -3],   [1, 2])
⇒-1
m4_list_cmp([1, 0],       [1, 2])
⇒-1
m4_list_cmp([1],          [1, 2])
⇒-1
```

`m4_max` (*arg*, ...) [Macro]

This macro was introduced in Autoconf 2.62. Expand to the decimal value of the maximum arithmetic expression among all the arguments.

`m4_min` (*arg*, ...) [Macro]

This macro was introduced in Autoconf 2.62. Expand to the decimal value of the minimum arithmetic expression among all the arguments.

`m4_sign` (*expr*) [Macro]

Expand to '`-1`' if the arithmetic expression *expr* is negative, '`1`' if it is positive, and '`0`' if it is zero.

`m4_version_compare` (*version-1*, *version-2*) [Macro]

This macro was introduced in Autoconf 2.53, but had a number of usability limitations that were not lifted until Autoconf 2.62. Compare the version strings *version-1* and *version-2*, and expand to '`-1`' if *version-1* is smaller, '`0`' if they are the same, or '`1`' *version-2* is smaller. Version strings must be a list of elements separated by '`.`', '`,`' or '`-`', where each element is a number along with optional case-insensitive letters designating beta releases. The comparison stops at the leftmost element that contains a difference, although a 0 element compares equal to a missing element.

It is permissible to include commit identifiers in *version*, such as an abbreviated SHA1 of the commit, provided there is still a monotonically increasing prefix to allow for accurate version-based comparisons. For example, this paragraph was written when the development snapshot of autoconf claimed to be at version '`2.61a-248-dc51`', or 248 commits after the 2.61a release, with an abbreviated commit identification of '`dc51`'.

```
m4_version_compare([1.1], [2.0])
⇒-1
m4_version_compare([2.0b], [2.0a])
⇒1
m4_version_compare([1.1.1], [1.1.1a])
⇒-1
m4_version_compare([1.2], [1.1.1a])
⇒1
m4_version_compare([1.0], [1])
⇒0
m4_version_compare([1.1pre], [1.1PRE])
⇒0
m4_version_compare([1.1a], [1,10])
```

```
⇒-1
m4_version_compare([2.61a], [2.61a-248-dc51])
⇒-1
m4_version_compare([2.61b], [2.61a-248-dc51])
⇒1
```

8.3.9 Forbidden Patterns

M4sugar provides a means to define suspicious patterns, patterns describing tokens which should not be found in the output. For instance, if an Autoconf '`configure`' script includes tokens such as '`AC_DEFINE`', or '`dnl`', then most probably something went wrong (typically a macro was not evaluated because of overquotation).

M4sugar forbids all the tokens matching '`^_?m4_`' and '`^dnl$`'. Additional layers, such as M4sh and Autoconf, add additional forbidden patterns to the list.

`m4_pattern_forbid (`*pattern*`)` [Macro]

Declare that no token matching *pattern* must be found in the output. Comments are not checked; this can be a problem if, for instance, you have some macro left unexpanded after an '`#include`'. No consensus is currently found in the Autoconf community, as some people consider it should be valid to name macros in comments (which doesn't make sense to the authors of this documentation: input, such as macros, should be documented by '`dnl`' comments; reserving '`#`'-comments to document the output).

Of course, you might encounter exceptions to these generic rules, for instance you might have to refer to '`$m4_flags`'.

`m4_pattern_allow (`*pattern*`)` [Macro]

Any token matching *pattern* is allowed, including if it matches an `m4_pattern_forbid` pattern.

8.4 Programming in M4sh

M4sh, pronounced "mash", is aiming at producing portable Bourne shell scripts. This name was coined by Lars J. Aas, who notes that, according to the Webster's Revised Unabridged Dictionary (1913):

> Mash \Mash\, n. [Akin to G. meisch, maisch, meische, maische, mash, wash, and prob. to AS. miscian to mix. See "Mix".]
>
> 1. A mass of mixed ingredients reduced to a soft pulpy state by beating or pressure. . .
> 2. A mixture of meal or bran and water fed to animals.
> 3. A mess; trouble. [Obs.] –Beau. & Fl.

For the time being, it is not mature enough to be widely used.

M4sh reserves the M4 macro namespace '`^_AS_`' for internal use, and the namespace '`^AS_`' for M4sh macros. It also reserves the shell and environment variable namespace '`^as_`', and the here-doc delimiter namespace '`^_AS[A-Z]`' in the output file. You should not define your own macros or output shell code that conflicts with these namespaces.

M4sh provides portable alternatives for some common shell constructs that unfortunately are not portable in practice.

`AS_BOURNE_COMPATIBLE` [Macro]

Set up the shell to be more compatible with the Bourne shell as standardized by Posix, if possible. This may involve setting environment variables, or setting options, or similar implementation-specific actions.

`AS_CASE (`*`word`*`, [`*`pattern1`*`], [`*`if-matched1`*`], ..., [`*`default`*`])` [Macro]

Expand into a shell '`case`' statement, where *word* is matched against one or more patterns. *if-matched* is run if the corresponding pattern matched *word*, else *default* is run.

`AS_DIRNAME (`*`file-name`*`)` [Macro]

Output the directory portion of *file-name*. For example, if `$file` is '`/one/two/three`', the command `dir=`AS_DIRNAME(["$file"])` sets `dir` to '`/one/two`'.

`AS_IF (`*`test1`*`, [`*`run-if-true1`*`], ..., [`*`run-if-false`*`])` [Macro]

Run shell code *test1*. If *test1* exits with a zero status then run shell code *run-if-true1*, else examine further tests. If no test exits with a zero status, run shell code *run-if-false*, with simplifications if either *run-if-true1* or *run-if-false1* is empty. For example,

```
AS_IF([test "$foo" = yes], [HANDLE_FOO([yes])],
      [test "$foo" != no], [HANDLE_FOO([maybe])],
      [echo foo not specified])
```

ensures any required macros of `HANDLE_FOO` are expanded before the first test.

`AS_INIT` [Macro]

Initialize the M4sh environment. This macro calls `m4_init`, then outputs the `#! /bin/sh` line, a notice about where the output was generated from, and code to sanitize the environment for the rest of the script. Finally, it changes the current diversion to `BODY`.

`AS_MKDIR_P (`*`file-name`*`)` [Macro]

Make the directory *file-name*, including intervening directories as necessary. This is equivalent to '`mkdir -p` *`file-name`*', except that it is portable to older versions of `mkdir` that lack support for the '`-p`' option. Also, `AS_MKDIR_P` succeeds if *file-name* is a symbolic link to an existing directory, even though Posix is unclear whether '`mkdir -p`' should succeed in that case. If creation of *file-name* fails, exit the script.

Also see the `AC_PROG_MKDIR_P` macro (see Section 5.2.1 [Particular Programs], page 41).

`AS_SHELL_SANITIZE` [Macro]

Initialize the shell suitably for `configure` scripts. This has the effect of `AS_BOURNE_COMPATIBLE`, and sets some other environment variables for predictable results from configuration tests. For example, it sets `LC_ALL` to change to the default C locale. See Section 10.10 [Special Shell Variables], page 168.

AS_TR_CPP (*expression*) [Macro]

Transform *expression* into a valid right-hand side for a C `#define`. For example:

```
# This outputs "#define HAVE_CHAR_P 1".
type="char *"
echo "#define AS_TR_CPP([HAVE_$type]) 1"
```

AS_TR_SH (*expression*) [Macro]

Transform *expression* into a valid shell variable name. For example:

```
# This outputs "Have it!".
header="sys/some file.h"
AS_TR_SH([HAVE_$header])=yes
if test "$HAVE_sys_some_file_h" = yes; then echo "Have it!"; fi
```

AS_SET_CATFILE (*var*, *dir*, *file*) [Macro]

Set the shell variable *var* to *dir*/*file*, but optimizing the common cases (*dir* or *file* is '.', *file* is absolute, etc.).

8.5 File Descriptor Macros

The following macros define file descriptors used to output messages (or input values) from 'configure' scripts. For example:

```
echo "$wombats found" >&AS_MESSAGE_LOG_FD
echo 'Enter desired kangaroo count:' >&AS_MESSAGE_FD
read kangaroos <&AS_ORIGINAL_STDIN_FD`
```

However doing so is seldom needed, because Autoconf provides higher level macros as described below.

AS_MESSAGE_FD [Macro]

The file descriptor for 'checking for...' messages and results. Normally this directs messages to the standard output, however when `configure` is run with the '-q' option, messages sent to `AS_MESSAGE_FD` are discarded.

If you want to display some messages, consider using one of the printing macros (see Section 7.5 [Printing Messages], page 110) instead. Copies of messages output via these macros are also recorded in 'config.log'.

AS_MESSAGE_LOG_FD [Macro]

The file descriptor for messages logged to 'config.log'. Macros that run tools, like `AC_COMPILE_IFELSE` (see Section 6.4 [Running the Compiler], page 97), redirect all output to this descriptor. You may want to do so if you develop such a low-level macro.

AS_ORIGINAL_STDIN_FD [Macro]

The file descriptor for the original standard input.

When `configure` runs, it may accidentally execute an interactive command that has the same name as the non-interactive meant to be used or checked. If the standard input was the terminal, such interactive programs would cause `configure` to stop, pending some user input. Therefore `configure` redirects its standard input from

'`/dev/null`' during its initialization. This is not normally a problem, since `configure` normally does not need user input.

In the extreme case where your '`configure`' script really needs to obtain some values from the original standard input, you can read them explicitly from `AS_ORIGINAL_STDIN_FD`.

9 Writing Autoconf Macros

When you write a feature test that could be applicable to more than one software package, the best thing to do is encapsulate it in a new macro. Here are some instructions and guidelines for writing Autoconf macros.

9.1 Macro Definitions

Autoconf macros are defined using the `AC_DEFUN` macro, which is similar to the M4 builtin `m4_define` macro. In addition to defining a macro, `AC_DEFUN` adds to it some code that is used to constrain the order in which macros are called (see Section 9.4.1 [Prerequisite Macros], page 147).

An Autoconf macro definition looks like this:

`AC_DEFUN(`*`macro-name, macro-body`*`)`

You can refer to any arguments passed to the macro as '`$1`', '`$2`', etc. See section "How to define new macros" in *GNU M4*, for more complete information on writing M4 macros.

Be sure to properly quote both the *macro-body and* the *macro-name* to avoid any problems if the macro happens to have been previously defined.

Each macro should have a header comment that gives its prototype, and a brief description. When arguments have default values, display them in the prototype. For example:

```
# AC_MSG_ERROR(ERROR, [EXIT-STATUS = 1])
# --------------------------------------
m4_define([AC_MSG_ERROR],
  [{ AS_MESSAGE([error: $1], [2])
     exit m4_default([$2], [1]); }])
```

Comments about the macro should be left in the header comment. Most other comments make their way into '`configure`', so just keep using '`#`' to introduce comments.

If you have some special comments about pure M4 code, comments that make no sense in '`configure`' and in the header comment, then use the builtin `dnl`: it causes M4 to discard the text through the next newline.

Keep in mind that `dnl` is rarely needed to introduce comments; `dnl` is more useful to get rid of the newlines following macros that produce no output, such as `AC_REQUIRE`.

9.2 Macro Names

All of the public Autoconf macros have all-uppercase names in the namespace '`^AC_`' to prevent them from accidentally conflicting with other text; Autoconf also reserves the namespace '`^_AC_`' for internal macros. All shell variables that they use for internal purposes have mostly-lowercase names starting with '`ac_`'. Autoconf also uses here-doc delimiters in the namespace '`^_AC[A-Z]`'. During `configure`, files produced by Autoconf make heavy use of the file system namespace '`^conf`'.

Since Autoconf is built on top of M4sugar (see Section 8.3 [Programming in M4sugar], page 125) and M4sh (see Section 8.4 [Programming in M4sh], page 141), you must also be aware of those namespaces ('`^_?\(m4\|AS\)_`'). And since '`configure.ac`' is also designed to be scanned by Autoheader, Autoscan, Autoupdate, and Automake, you should be aware

of the '^_?A[HNUM]_' namespaces. In general, you *should not use* the namespace of a package that does not own the macro or shell code you are writing.

To ensure that your macros don't conflict with present or future Autoconf macros, you should prefix your own macro names and any shell variables they use with some other sequence. Possibilities include your initials, or an abbreviation for the name of your organization or software package. Historically, people have not always followed the rule of using a namespace appropriate for their package, and this has made it difficult for determining the origin of a macro (and where to report bugs about that macro), as well as difficult for the true namespace owner to add new macros without interference from pre-existing uses of third-party macros. Perhaps the best example of this confusion is the AM_GNU_GETTEXT macro, which belongs, not to Automake, but to Gettext.

Most of the Autoconf macros' names follow a structured naming convention that indicates the kind of feature check by the name. The macro names consist of several words, separated by underscores, going from most general to most specific. The names of their cache variables use the same convention (see Section 7.4.1 [Cache Variable Names], page 108, for more information on them).

The first word of the name after the namepace initials (such as 'AC_') usually tells the category of the feature being tested. Here are the categories used in Autoconf for specific test macros, the kind of macro that you are more likely to write. They are also used for cache variables, in all-lowercase. Use them where applicable; where they're not, invent your own categories.

C	C language builtin features.
DECL	Declarations of C variables in header files.
FUNC	Functions in libraries.
GROUP	Posix group owners of files.
HEADER	Header files.
LIB	C libraries.
PROG	The base names of programs.
MEMBER	Members of aggregates.
SYS	Operating system features.
TYPE	C builtin or declared types.
VAR	C variables in libraries.

After the category comes the name of the particular feature being tested. Any further words in the macro name indicate particular aspects of the feature. For example, AC_PROG_CC_STDC checks whether the C compiler supports ISO Standard C.

An internal macro should have a name that starts with an underscore; Autoconf internals should therefore start with '_AC_'. Additionally, a macro that is an internal subroutine of another macro should have a name that starts with an underscore and the name of that other macro, followed by one or more words saying what the internal macro does. For example, AC_PATH_X has internal macros _AC_PATH_X_XMKMF and _AC_PATH_X_DIRECT.

9.3 Reporting Messages

When macros statically diagnose abnormal situations, benign or fatal, it is possible to make `autoconf` detect the problem, and refuse to create '`configure`' in the case of an error. The macros in this section are considered obsolescent, and new code should use M4sugar macros for this purpose, see Section 8.3.2 [Diagnostic Macros], page 127.

On the other hand, it is possible to want to detect errors when `configure` is run, which are dependent on the environment of the user rather than the maintainer. For dynamic diagnostics, see Section 7.5 [Printing Messages], page 110.

`AC_DIAGNOSE (category, message)` [Macro]

Report *message* as a warning (or as an error if requested by the user) if warnings of the *category* are turned on. This macro is obsolescent; you are encouraged to use:

```
m4_warn([category], [message])
```

instead. See [m4_warn], page 128, for more details, including valid *category* names.

`AC_WARNING (message)` [Macro]

Report *message* as a syntax warning. This macro is obsolescent; you are encouraged to use:

```
m4_warn([syntax], [message])
```

instead. See [m4_warn], page 128, for more details, as well as better finer-grained categories of warnings (not all problems have to do with syntax).

`AC_FATAL (message)` [Macro]

Report a severe error *message*, and have `autoconf` die. This macro is obsolescent; you are encouraged to use:

```
m4_fatal([message])
```

instead. See [m4_fatal], page 128, for more details.

When the user runs '`autoconf -W error`', warnings from `m4_warn` (including those issued through `AC_DIAGNOSE` and `AC_WARNING`) are reported as errors, see Section 3.4 [autoconf Invocation], page 12.

9.4 Dependencies Between Macros

Some Autoconf macros depend on other macros having been called first in order to work correctly. Autoconf provides a way to ensure that certain macros are called if needed and a way to warn the user if macros are called in an order that might cause incorrect operation.

9.4.1 Prerequisite Macros

A macro that you write might need to use values that have previously been computed by other macros. For example, `AC_DECL_YYTEXT` examines the output of `flex` or `lex`, so it depends on `AC_PROG_LEX` having been called first to set the shell variable `LEX`.

Rather than forcing the user of the macros to keep track of the dependencies between them, you can use the `AC_REQUIRE` macro to do it automatically. `AC_REQUIRE` can ensure that a macro is only called if it is needed, and only called once.

AC_REQUIRE (*macro-name*) [Macro]

If the M4 macro *macro-name* has not already been called, call it (without any arguments). Make sure to quote *macro-name* with square brackets. *macro-name* must have been defined using AC_DEFUN or else contain a call to AC_PROVIDE to indicate that it has been called.

AC_REQUIRE must be used inside a macro defined by AC_DEFUN; it must not be called from the top level.

AC_REQUIRE is often misunderstood. It really implements dependencies between macros in the sense that if one macro depends upon another, the latter is expanded *before* the body of the former. To be more precise, the required macro is expanded before the outermost defined macro in the current expansion stack. In particular, 'AC_REQUIRE([FOO])' is not replaced with the body of FOO. For instance, this definition of macros:

```
AC_DEFUN([TRAVOLTA],
[test "$body_temperature_in_celsius" -gt "38" &&
  dance_floor=occupied])
AC_DEFUN([NEWTON_JOHN],
[test "$hair_style" = "curly" &&
  dance_floor=occupied])

AC_DEFUN([RESERVE_DANCE_FLOOR],
[if date | grep '^Sat.*pm' >/dev/null 2>&1; then
  AC_REQUIRE([TRAVOLTA])
  AC_REQUIRE([NEWTON_JOHN])
fi])
```

with this 'configure.ac'

```
AC_INIT([Dance Manager], [1.0], [bug-dance@example.org])
RESERVE_DANCE_FLOOR
if test "$dance_floor" = occupied; then
  AC_MSG_ERROR([cannot pick up here, let's move])
fi
```

does not leave you with a better chance to meet a kindred soul at other times than Saturday night since it expands into:

```
test "$body_temperature_in_Celsius" -gt "38" &&
  dance_floor=occupied
test "$hair_style" = "curly" &&
  dance_floor=occupied
fi
if date | grep '^Sat.*pm' >/dev/null 2>&1; then


fi
```

This behavior was chosen on purpose: (i) it prevents messages in required macros from interrupting the messages in the requiring macros; (ii) it avoids bad surprises when shell conditionals are used, as in:

```
if ...; then
  AC_REQUIRE([SOME_CHECK])
fi
...
SOME_CHECK
```

The helper macros AS_IF and AS_CASE may be used to enforce expansion of required macros outside of shell conditional constructs. You are furthermore encouraged to put all AC_REQUIRE calls at the beginning of a macro. You can use dnl to avoid the empty lines they leave.

9.4.2 Suggested Ordering

Some macros should be run before another macro if both are called, but neither *requires* that the other be called. For example, a macro that changes the behavior of the C compiler should be called before any macros that run the C compiler. Many of these dependencies are noted in the documentation.

Autoconf provides the AC_BEFORE macro to warn users when macros with this kind of dependency appear out of order in a 'configure.ac' file. The warning occurs when creating configure from 'configure.ac', not when running configure.

For example, AC_PROG_CPP checks whether the C compiler can run the C preprocessor when given the '-E' option. It should therefore be called after any macros that change which C compiler is being used, such as AC_PROG_CC. So AC_PROG_CC contains:

```
AC_BEFORE([$0], [AC_PROG_CPP])dnl
```

This warns the user if a call to AC_PROG_CPP has already occurred when AC_PROG_CC is called.

AC_BEFORE (*this-macro-name*, *called-macro-name*) [Macro]

Make M4 print a warning message to the standard error output if *called-macro-name* has already been called. *this-macro-name* should be the name of the macro that is calling AC_BEFORE. The macro *called-macro-name* must have been defined using AC_DEFUN or else contain a call to AC_PROVIDE to indicate that it has been called.

9.4.3 One-Shot Macros

Some macros should be called only once, either because calling them multiple time is unsafe, or because it is bad style. For instance Autoconf ensures that AC_CANONICAL_BUILD and cousins (see Section 13.2 [Canonicalizing], page 222) are evaluated only once, because it makes no sense to run these expensive checks more than once. Such one-shot macros can be defined using AC_DEFUN_ONCE.

AC_DEFUN_ONCE (*macro-name*, *macro-body*) [Macro]

Declare macro *macro-name* like AC_DEFUN would (see Section 9.1 [Macro Definitions], page 145), and emit a warning any time the macro is called more than once.

Obviously it is not sensible to evaluate a macro defined by AC_DEFUN_ONCE in a macro defined by AC_DEFUN. Most of the time you want to use AC_REQUIRE (see Section 9.4.1 [Prerequisite Macros], page 147).

9.5 Obsoleting Macros

Configuration and portability technology has evolved over the years. Often better ways of solving a particular problem are developed, or ad-hoc approaches are systematized. This process has occurred in many parts of Autoconf. One result is that some of the macros are now considered *obsolete*; they still work, but are no longer considered the best thing to do, hence they should be replaced with more modern macros. Ideally, `autoupdate` should replace the old macro calls with their modern implementation.

Autoconf provides a simple means to obsolete a macro.

`AU_DEFUN (old-macro, implementation, [message])` [Macro]

Define *old-macro* as *implementation*. The only difference with `AC_DEFUN` is that the user is warned that *old-macro* is now obsolete.

If she then uses `autoupdate`, the call to *old-macro* is replaced by the modern *implementation*. *message* should include information on what to do after running `autoupdate`; `autoupdate` prints it as a warning, and includes it in the updated '`configure.ac`' file.

The details of this macro are hairy: if `autoconf` encounters an `AU_DEFUN`ed macro, all macros inside its second argument are expanded as usual. However, when `autoupdate` is run, only M4 and M4sugar macros are expanded here, while all other macros are disabled and appear literally in the updated '`configure.ac`'.

`AU_ALIAS (old-name, new-name)` [Macro]

Used if the *old-name* is to be replaced by a call to *new-macro* with the same parameters. This happens for example if the macro was renamed.

9.6 Coding Style

The Autoconf macros follow a strict coding style. You are encouraged to follow this style, especially if you intend to distribute your macro, either by contributing it to Autoconf itself, or via other means.

The first requirement is to pay great attention to the quotation. For more details, see Section 3.1.2 [Autoconf Language], page 9, and Section 8.1 [M4 Quotation], page 113.

Do not try to invent new interfaces. It is likely that there is a macro in Autoconf that resembles the macro you are defining: try to stick to this existing interface (order of arguments, default values, etc.). We *are* conscious that some of these interfaces are not perfect; nevertheless, when harmless, homogeneity should be preferred over creativity.

Be careful about clashes both between M4 symbols and between shell variables.

If you stick to the suggested M4 naming scheme (see Section 9.2 [Macro Names], page 145), you are unlikely to generate conflicts. Nevertheless, when you need to set a special value, *avoid using a regular macro name*; rather, use an "impossible" name. For instance, up to version 2.13, the macro `AC_SUBST` used to remember what *symbol* macros were already defined by setting `AC_SUBST_symbol`, which is a regular macro name. But since there is a macro named `AC_SUBST_FILE`, it was just impossible to '`AC_SUBST(FILE)`'! In this case, `AC_SUBST(symbol)` or `_AC_SUBST(symbol)` should have been used (yes, with the parentheses).

No Autoconf macro should ever enter the user-variable name space; i.e., except for the variables that are the actual result of running the macro, all shell variables should start with `ac_`. In addition, small macros or any macro that is likely to be embedded in other macros should be careful not to use obvious names.

Do not use `dnl` to introduce comments: most of the comments you are likely to write are either header comments which are not output anyway, or comments that should make their way into '`configure`'. There are exceptional cases where you do want to comment special M4 constructs, in which case `dnl` is right, but keep in mind that it is unlikely.

M4 ignores the leading blanks and newlines before each argument. Use this feature to indent in such a way that arguments are (more or less) aligned with the opening parenthesis of the macro being called. For instance, instead of

```
AC_CACHE_CHECK(for EMX OS/2 environment,
ac_cv_emxos2,
[AC_COMPILE_IFELSE([AC_LANG_PROGRAM(, [return __EMX__;])],
[ac_cv_emxos2=yes], [ac_cv_emxos2=no])])
```

write

```
AC_CACHE_CHECK([for EMX OS/2 environment], [ac_cv_emxos2],
[AC_COMPILE_IFELSE([AC_LANG_PROGRAM([], [return __EMX__;])],
                   [ac_cv_emxos2=yes],
                   [ac_cv_emxos2=no])])
```

or even

```
AC_CACHE_CHECK([for EMX OS/2 environment],
               [ac_cv_emxos2],
               [AC_COMPILE_IFELSE([AC_LANG_PROGRAM([],
                                                   [return __EMX__;])],
                                  [ac_cv_emxos2=yes],
                                  [ac_cv_emxos2=no])])
```

When using `AC_RUN_IFELSE` or any macro that cannot work when cross-compiling, provide a pessimistic value (typically '`no`').

Feel free to use various tricks to prevent auxiliary tools, such as syntax-highlighting editors, from behaving improperly. For instance, instead of:

```
m4_bpatsubst([$1], [$"])
```

use

```
m4_bpatsubst([$1], [$""])
```

so that Emacsen do not open an endless "string" at the first quote. For the same reasons, avoid:

```
test $[#] != 0
```

and use:

```
test $[@%:@] != 0
```

Otherwise, the closing bracket would be hidden inside a '`#`'-comment, breaking the bracket-matching highlighting from Emacsen. Note the preferred style to escape from M4: '`$[1]`', '`$[@]`', etc. Do not escape when it is unnecessary. Common examples of useless quotation are '`[$]$1`' (write '`$$1`'), '`[$]var`' (use '`$var`'), etc. If you add portability issues to the

picture, you'll prefer '${1+"$[@]"}' to '"[$]@"', and you'll prefer do something better than hacking Autoconf :-).

When using sed, don't use '-e' except for indenting purposes. With the s and y commands, the preferred separator is '/' unless '/' itself might appear in the pattern or replacement, in which case you should use '|', or optionally ',' if you know the pattern and replacement cannot contain a file name. If none of these characters will do, choose a printable character that cannot appear in the pattern or replacement. Characters from the set '"#$&'()*;<=>¿|~' are good choices if the pattern or replacement might contain a file name, since they have special meaning to the shell and are less likely to occur in file names.

See Section 9.1 [Macro Definitions], page 145, for details on how to define a macro. If a macro doesn't use AC_REQUIRE, is expected to never be the object of an AC_REQUIRE directive, and macros required by other macros inside arguments do not need to be expanded before this macro, then use m4_define. In case of doubt, use AC_DEFUN. All the AC_REQUIRE statements should be at the beginning of the macro, and each statement should be followed by dnl.

You should not rely on the number of arguments: instead of checking whether an argument is missing, test that it is not empty. It provides both a simpler and a more predictable interface to the user, and saves room for further arguments.

Unless the macro is short, try to leave the closing '])' at the beginning of a line, followed by a comment that repeats the name of the macro being defined. This introduces an additional newline in configure; normally, that is not a problem, but if you want to remove it you can use '[]dnl' on the last line. You can similarly use '[]dnl' after a macro call to remove its newline. '[]dnl' is recommended instead of 'dnl' to ensure that M4 does not interpret the 'dnl' as being attached to the preceding text or macro output. For example, instead of:

```
AC_DEFUN([AC_PATH_X],
[AC_MSG_CHECKING([for X])
AC_REQUIRE_CPP()
# ...omitted...
  AC_MSG_RESULT([libraries $x_libraries, headers $x_includes])
fi])
```

you would write:

```
AC_DEFUN([AC_PATH_X],
[AC_REQUIRE_CPP()[]dnl
AC_MSG_CHECKING([for X])
# ...omitted...
  AC_MSG_RESULT([libraries $x_libraries, headers $x_includes])
fi[]dnl
])# AC_PATH_X
```

If the macro is long, try to split it into logical chunks. Typically, macros that check for a bug in a function and prepare its AC_LIBOBJ replacement should have an auxiliary macro to perform this setup. Do not hesitate to introduce auxiliary macros to factor your code.

In order to highlight the recommended coding style, here is a macro written the old way:

```
dnl Check for EMX on OS/2.
dnl _AC_EMXOS2
```

```
AC_DEFUN(_AC_EMXOS2,
[AC_CACHE_CHECK(for EMX OS/2 environment, ac_cv_emxos2,
[AC_COMPILE_IFELSE([AC_LANG_PROGRAM(, return __EMX__;)],
ac_cv_emxos2=yes, ac_cv_emxos2=no)])
test "$ac_cv_emxos2" = yes && EMXOS2=yes])
```

and the new way:

```
# _AC_EMXOS2
# ----------
# Check for EMX on OS/2.
m4_define([_AC_EMXOS2],
[AC_CACHE_CHECK([for EMX OS/2 environment], [ac_cv_emxos2],
[AC_COMPILE_IFELSE([AC_LANG_PROGRAM([], [return __EMX__;])],
                   [ac_cv_emxos2=yes],
                   [ac_cv_emxos2=no])])
test "$ac_cv_emxos2" = yes && EMXOS2=yes[]dnl
])# _AC_EMXOS2
```

10 Portable Shell Programming

When writing your own checks, there are some shell-script programming techniques you should avoid in order to make your code portable. The Bourne shell and upward-compatible shells like the Korn shell and Bash have evolved over the years, but to prevent trouble, do not take advantage of features that were added after Unix version 7, circa 1977 (see Section 6.7 [Systemology], page 100).

You should not use aliases, negated character classes, or other features that are not found in all Bourne-compatible shells; restrict yourself to the lowest common denominator. Even `unset` is not supported by all shells!

Shell functions are considered portable nowadays, though Autoconf still does not use them (Autotest does). However, some pitfalls have to be avoided for portable use of shell functions.

Some ancient systems have quite small limits on the length of the '`#!`' line; for instance, 32 bytes (not including the newline) on SunOS 4. A few ancient 4.2BSD based systems (such as Dynix circa 1984) required a single space between the '`#!`' and the '`/`'. However, these ancient systems are no longer of practical concern.

The set of external programs you should run in a `configure` script is fairly small. See section "Utilities in Makefiles" in *GNU Coding Standards*, for the list. This restriction allows users to start out with a fairly small set of programs and build the rest, avoiding too many interdependencies between packages.

Some of these external utilities have a portable subset of features; see Section 10.13 [Limitations of Usual Tools], page 182.

There are other sources of documentation about shells. The specification for the Posix Shell Command Language (`http://www.opengroup.org/susv3/utilities/xcu_chap02.html`), though more generous than the restrictive shell subset described above, is fairly portable nowadays. Also please see the Shell FAQs (`http://www.faqs.org/faqs/unix-faq/shell/`).

10.1 Shellology

There are several families of shells, most prominently the Bourne family and the C shell family which are deeply incompatible. If you want to write portable shell scripts, avoid members of the C shell family. The the Shell difference FAQ (`http://www.faqs.org/faqs/unix-faq/shell/shell-differences/`) includes a small history of Posix shells, and a comparison between several of them.

Below we describe some of the members of the Bourne shell family.

Ash

Ash is often used on GNU/Linux and BSD systems as a light-weight Bourne-compatible shell. Ash 0.2 has some bugs that are fixed in the 0.3.x series, but portable shell scripts should work around them, since version 0.2 is still shipped with many GNU/Linux distributions.

To be compatible with Ash 0.2:

- don't use '`$?`' after expanding empty or unset variables, or at the start of an `eval`:

```
foo=
false
$foo
echo "Do not use it: $?"
false
eval 'echo "Do not use it: $?"'
```

– don't use command substitution within variable expansion:

```
cat ${FOO=`bar`}
```

– beware that single builtin substitutions are not performed by a subshell, hence their effect applies to the current shell! See Section 10.6 [Shell Substitutions], page 162, item "Command Substitution".

Bash
: To detect whether you are running Bash, test whether `BASH_VERSION` is set. To require Posix compatibility, run '`set -o posix`'. See section "Bash Posix Mode" in *The GNU Bash Reference Manual*, for details.

Bash 2.05 and later
: Versions 2.05 and later of Bash use a different format for the output of the `set` builtin, designed to make evaluating its output easier. However, this output is not compatible with earlier versions of Bash (or with many other shells, probably). So if you use Bash 2.05 or higher to execute `configure`, you'll need to use Bash 2.05 for all other build tasks as well.

Ksh
: The Korn shell is compatible with the Bourne family and it mostly conforms to Posix. It has two major variants commonly called '`ksh88`' and '`ksh93`', named after the years of initial release. It is usually called `ksh`, but is called `sh` on some hosts if you set your path appropriately.

  Solaris systems have three variants: `/usr/bin/ksh` is '`ksh88`'; it is standard on Solaris 2.0 and later. `/usr/xpg4/bin/sh` is a Posix-compliant variant of '`ksh88`'; it is standard on Solaris 9 and later. `/usr/dt/bin/dtksh` is '`ksh93`'. Variants that are not standard may be parts of optional packages. There is no extra charge for these packages, but they are not part of a minimal OS install and therefore some installations may not have it.

  Starting with Tru64 Version 4.0, the Korn shell `/usr/bin/ksh` is also available as `/usr/bin/posix/sh`. If the environment variable `BIN_SH` is set to `xpg4`, subsidiary invocations of the standard shell conform to Posix.

Pdksh
: A public-domain clone of the Korn shell called `pdksh` is widely available: it has most of the '`ksh88`' features along with a few of its own. It usually sets `KSH_VERSION`, except if invoked as `/bin/sh` on OpenBSD, and similarly to Bash you can require Posix compatibility by running '`set -o posix`'. Unfortunately, with `pdksh` 5.2.14 (the latest stable version as of January 2007) Posix mode is buggy and causes `pdksh` to depart from Posix in at least one respect:

```
$ echo "`echo \"hello\"`"
hello
$ set -o posix
$ echo "`echo \"hello\"`"
"hello"
```

The last line of output contains spurious quotes. This is yet another reason why portable shell code should not contain "`...\"...\"...`" constructs (see Section 10.6 [Shell Substitutions], page 162).

Zsh To detect whether you are running `zsh`, test whether `ZSH_VERSION` is set. By default `zsh` is *not* compatible with the Bourne shell: you must execute '`emulate sh`', and for `zsh` versions before 3.1.6-dev-18 you must also set `NULLCMD` to '`:`'. See section "Compatibility" in *The Z Shell Manual*, for details.

The default Mac OS X `sh` was originally Zsh; it was changed to Bash in Mac OS X 10.2.

The following discussion between Russ Allbery and Robert Lipe is worth reading:

Russ Allbery:

> The GNU assumption that `/bin/sh` is the one and only shell leads to a permanent deadlock. Vendors don't want to break users' existing shell scripts, and there are some corner cases in the Bourne shell that are not completely compatible with a Posix shell. Thus, vendors who have taken this route will *never* (OK... "never say never") replace the Bourne shell (as `/bin/sh`) with a Posix shell.

Robert Lipe:

> This is exactly the problem. While most (at least most System V's) do have a Bourne shell that accepts shell functions most vendor `/bin/sh` programs are not the Posix shell.
>
> So while most modern systems do have a shell *somewhere* that meets the Posix standard, the challenge is to find it.

10.2 Here-Documents

Don't rely on '\' being preserved just because it has no special meaning together with the next symbol. In the native `sh` on OpenBSD 2.7 '`\"`' expands to '`"`' in here-documents with unquoted delimiter. As a general rule, if '\\' expands to '\' use '\\' to get '\'.

With OpenBSD 2.7's `sh`

```
$ cat <<EOF
> \" \\
> EOF
" \
```

and with Bash:

```
bash-2.04$ cat <<EOF
> \" \\
> EOF
\" \
```

Some shells mishandle large here-documents: for example, Solaris 10 `dtksh` and the UnixWare 7.1.1 Posix shell, which are derived from Korn shell version M-12/28/93d, mishandle braced variable expansion that crosses a 1024- or 4096-byte buffer boundary within a here-document. Only the part of the variable name after the boundary is used. For example, `${variable}` could be replaced by the expansion of `${ble}`. If the end of the

variable name is aligned with the block boundary, the shell reports an error, as if you used `${}`. Instead of `${variable-default}`, the shell may expand `${riable-default}`, or even `${fault}`. This bug can often be worked around by omitting the braces: `$variable`. The bug was fixed in '`ksh93g`' (1998-04-30) but as of 2006 many operating systems were still shipping older versions with the bug.

Many shells (including the Bourne shell) implement here-documents inefficiently. In particular, some shells can be extremely inefficient when a single statement contains many here-documents. For instance if your '`configure.ac`' includes something like:

```
if <cross_compiling>; then
  assume this and that
else
  check this
  check that
  check something else
  ...
  on and on forever
  ...
fi
```

A shell parses the whole `if/fi` construct, creating temporary files for each here-document in it. Some shells create links for such here-documents on every `fork`, so that the clean-up code they had installed correctly removes them. It is creating the links that can take the shell forever.

Moving the tests out of the `if/fi`, or creating multiple `if/fi` constructs, would improve the performance significantly. Anyway, this kind of construct is not exactly the typical use of Autoconf. In fact, it's even not recommended, because M4 macros can't look into shell conditionals, so we may fail to expand a macro when it was expanded before in a conditional path, and the condition turned out to be false at runtime, and we end up not executing the macro at all.

10.3 File Descriptors

Most shells, if not all (including Bash, Zsh, Ash), output traces on stderr, even for subshells. This might result in undesirable content if you meant to capture the standard-error output of the inner command:

```
$ ash -x -c '(eval "echo foo >&2") 2>stderr'
$ cat stderr
+ eval echo foo >&2
+ echo foo
foo
$ bash -x -c '(eval "echo foo >&2") 2>stderr'
$ cat stderr
+ eval 'echo foo >&2'
++ echo foo
foo
$ zsh -x -c '(eval "echo foo >&2") 2>stderr'
# Traces on startup files deleted here.
```

```
$ cat stderr
+zsh:1> eval echo foo >&2
+zsh:1> echo foo
foo
```

One workaround is to grep out uninteresting lines, hoping not to remove good ones.

If you intend to redirect both standard error and standard output, redirect standard output first. This works better with HP-UX, since its shell mishandles tracing if standard error is redirected first:

```
$ sh -x -c ': 2>err >out'
+ :
+ 2> err $ cat err
1> out
```

Don't try to redirect the standard error of a command substitution. It must be done *inside* the command substitution. When running '`: ` `cd /zorglub` ` 2>/dev/null`' expect the error message to escape, while '`: ` `cd /zorglub 2>/dev/null` `'' works properly.

It is worth noting that Zsh (but not Ash nor Bash) makes it possible in assignments though: '`foo=` `cd /zorglub` ` 2>/dev/null`'.

When catering to old systems, don't redirect the same file descriptor several times, as you are doomed to failure under Ultrix.

```
ULTRIX V4.4 (Rev. 69) System #31: Thu Aug 10 19:42:23 GMT 1995
UWS V4.4 (Rev. 11)
$ eval 'echo matter >fullness' >void
illegal io
$ eval '(echo matter >fullness)' >void
illegal io
$ (eval '(echo matter >fullness)') >void
Ambiguous output redirect.
```

In each case the expected result is of course '`fullness`' containing '`matter`' and '`void`' being empty. However, this bug is probably not of practical concern to modern platforms.

Don't rely on file descriptors 0, 1, and 2 remaining closed in a subsidiary program. If any of these descriptors is closed, the operating system may open an unspecified file for the descriptor in the new process image. Posix says this may be done only if the subsidiary program is set-user-ID or set-group-ID, but HP-UX 11.23 does it even for ordinary programs.

Don't rely on open file descriptors being open in child processes. In `ksh`, file descriptors above 2 which are opened using '`exec` *`n`*`>file`' are closed by a subsequent '`exec`' (such as that involved in the fork-and-exec which runs a program or script). Thus, using `sh`, we have:

```
$ cat ./descrips
#!/bin/sh -
echo hello >&5
$ exec 5>t
$ ./descrips
$ cat t
hello
```

```
$
```

But using ksh:

```
$ exec 5>t
$ ./descrips
hello
$ cat t
$
```

Within the process which runs the '`descrips`' script, file descriptor 5 is closed.

DOS variants cannot rename or remove open files, such as in '`mv foo bar >foo`' or '`rm foo >foo`', even though this is perfectly portable among Posix hosts.

A few ancient systems reserved some file descriptors. By convention, file descriptor 3 was opened to '`/dev/tty`' when you logged into Eighth Edition (1985) through Tenth Edition Unix (1989). File descriptor 4 had a special use on the Stardent/Kubota Titan (circa 1990), though we don't now remember what it was. Both these systems are obsolete, so it's now safe to treat file descriptors 3 and 4 like any other file descriptors.

10.4 File System Conventions

Autoconf uses shell-script processing extensively, so the file names that it processes should not contain characters that are special to the shell. Special characters include space, tab, newline, NUL, and the following:

```
" # $ & ' ( ) * ; < = > ? [ \ ` |
```

Also, file names should not begin with '`~`' or '`-`', and should contain neither '`-`' immediately after '`/`' nor '`~`' immediately after '`:`'. On Posix-like platforms, directory names should not contain '`:`', as this runs afoul of '`:`' used as the path separator.

These restrictions apply not only to the files that you distribute, but also to the absolute file names of your source, build, and destination directories.

On some Posix-like platforms, '`!`' and '`^`' are special too, so they should be avoided.

Posix lets implementations treat leading '`//`' specially, but requires leading '`///`' and beyond to be equivalent to '`/`'. Most Unix variants treat '`//`' like '`/`'. However, some treat '`//`' as a "super-root" that can provide access to files that are not otherwise reachable from '`/`'. The super-root tradition began with Apollo Domain/OS, which died out long ago, but unfortunately Cygwin has revived it.

While `autoconf` and friends are usually run on some Posix variety, they can be used on other systems, most notably DOS variants. This impacts several assumptions regarding file names.

For example, the following code:

```
case $foo_dir in
  /*) # Absolute
     ;;
  *)
     foo_dir=$dots$foo_dir ;;
esac
```

fails to properly detect absolute file names on those systems, because they can use a drivespec, and usually use a backslash as directory separator. If you want to be portable to

DOS variants (at the price of rejecting valid but oddball Posix file names like '`a:\b`'), you can check for absolute file names like this:

```
case $foo_dir in
  [\\/]* | ?:[\\/]* ) # Absolute
     ;;
  *)
     foo_dir=$dots$foo_dir ;;
esac
```

Make sure you quote the brackets if appropriate and keep the backslash as first character (see Section 10.12 [Limitations of Builtins], page 173).

Also, because the colon is used as part of a drivespec, these systems don't use it as path separator. When creating or accessing paths, you can use the `PATH_SEPARATOR` output variable instead. `configure` sets this to the appropriate value for the build system ('`:`' or '`;`') when it starts up.

File names need extra care as well. While DOS variants that are Posixy enough to run `autoconf` (such as DJGPP) are usually able to handle long file names properly, there are still limitations that can seriously break packages. Several of these issues can be easily detected by the doschk (`ftp://ftp.gnu.org/gnu/non-gnu/doschk/doschk-1.1.tar.gz`) package.

A short overview follows; problems are marked with SFN/LFN to indicate where they apply: SFN means the issues are only relevant to plain DOS, not to DOS under Microsoft Windows variants, while LFN identifies problems that exist even under Microsoft Windows variants.

No multiple dots (SFN)

DOS cannot handle multiple dots in file names. This is an especially important thing to remember when building a portable configure script, as `autoconf` uses a .in suffix for template files.

This is perfectly OK on Posix variants:

```
AC_CONFIG_HEADERS([config.h])
AC_CONFIG_FILES([source.c foo.bar])
AC_OUTPUT
```

but it causes problems on DOS, as it requires '`config.h.in`', '`source.c.in`' and '`foo.bar.in`'. To make your package more portable to DOS-based environments, you should use this instead:

```
AC_CONFIG_HEADERS([config.h:config.hin])
AC_CONFIG_FILES([source.c:source.cin foo.bar:foobar.in])
AC_OUTPUT
```

No leading dot (SFN)

DOS cannot handle file names that start with a dot. This is usually not important for `autoconf`.

Case insensitivity (LFN)

DOS is case insensitive, so you cannot, for example, have both a file called '`INSTALL`' and a directory called '`install`'. This also affects `make`; if there's a

file called ‘INSTALL’ in the directory, ‘make install’ does nothing (unless the ‘install’ target is marked as PHONY).

The 8+3 limit (SFN)

Because the DOS file system only stores the first 8 characters of the file name and the first 3 of the extension, those must be unique. That means that ‘foobar-part1.c’, ‘foobar-part2.c’ and ‘foobar-prettybird.c’ all resolve to the same file name (‘FOOBAR-P.C’). The same goes for ‘foo.bar’ and ‘foo.bartender’.

The 8+3 limit is not usually a problem under Microsoft Windows, as it uses numeric tails in the short version of file names to make them unique. However, a registry setting can turn this behavior off. While this makes it possible to share file trees containing long file names between SFN and LFN environments, it also means the above problem applies there as well.

Invalid characters (LFN)

Some characters are invalid in DOS file names, and should therefore be avoided. In a LFN environment, these are ‘/’, ‘\’, ‘?’, ‘*’, ‘:’, ‘<’, ‘>’, ‘|’ and ‘"’. In a SFN environment, other characters are also invalid. These include ‘+’, ‘,’, ‘[’ and ‘]’.

Invalid names (LFN)

Some DOS file names are reserved, and cause problems if you try to use files with those names. These names include ‘CON’, ‘AUX’, ‘COM1’, ‘COM2’, ‘COM3’, ‘COM4’, ‘LPT1’, ‘LPT2’, ‘LPT3’, ‘NUL’, and ‘PRN’. File names are case insensitive, so even names like ‘aux/config.guess’ are disallowed.

10.5 Shell Pattern Matching

Nowadays portable patterns can use negated character classes like ‘[!-aeiou]’. The older syntax ‘[^-aeiou]’ is supported by some shells but not others; hence portable scripts should never use ‘^’ as the first character of a bracket pattern.

Outside the C locale, patterns like ‘[a-z]’ are problematic since they may match characters that are not lower-case letters.

10.6 Shell Substitutions

Contrary to a persistent urban legend, the Bourne shell does not systematically split variables and back-quoted expressions, in particular on the right-hand side of assignments and in the argument of case. For instance, the following code:

```
case "$given_srcdir" in
.)  top_srcdir="`echo "$dots" | sed 's|/$||'`" ;;
*)  top_srcdir="$dots$given_srcdir" ;;
esac
```

is more readable when written as:

```
case $given_srcdir in
.)  top_srcdir=`echo "$dots" | sed 's|/$||'` ;;
*)  top_srcdir=$dots$given_srcdir ;;
```

```
esac
```

and in fact it is even *more* portable: in the first case of the first attempt, the computation of `top_srcdir` is not portable, since not all shells properly understand `"`...`"...`"...`...`"`. Worse yet, not all shells understand `"`...\"...\"...`..."` the same way. There is just no portable way to use double-quoted strings inside double-quoted back-quoted expressions (pfew!).

`$@` One of the most famous shell-portability issues is related to '`"$@"`'. When there are no positional arguments, Posix says that '`"$@"`' is supposed to be equivalent to nothing, but the original Unix version 7 Bourne shell treated it as equivalent to '`""`' instead, and this behavior survives in later implementations like Digital Unix 5.0.

The traditional way to work around this portability problem is to use '`${1+"$@"}`'. Unfortunately this method does not work with Zsh (3.x and 4.x), which is used on Mac OS X. When emulating the Bourne shell, Zsh performs word splitting on '`${1+"$@"}`':

```
zsh $ emulate sh
zsh $ for i in "$@"; do echo $i; done
Hello World
!
zsh $ for i in ${1+"$@"}; do echo $i; done
Hello
World
!
```

Zsh handles plain '`"$@"`' properly, but we can't use plain '`"$@"`' because of the portability problems mentioned above. One workaround relies on Zsh's "global aliases" to convert '`${1+"$@"}`' into '`"$@"`' by itself:

```
test "${ZSH_VERSION+set}" = set && alias -g '${1+"$@"}'='"$@"'
```

Zsh only recognizes this alias when a shell word matches it exactly; '`"foo"${1+"$@"}`' remains subject to word splitting. Since this case always yields at least one shell word, use plain '`"$@"`'.

A more conservative workaround is to avoid '`"$@"`' if it is possible that there may be no positional arguments. For example, instead of:

```
cat conftest.c "$@"
```

you can use this instead:

```
case $# in
0) cat conftest.c;;
*) cat conftest.c "$@";;
esac
```

Autoconf macros often use the `set` command to update '`$@`', so if you are writing shell code intended for `configure` you should not assume that the value of '`$@`' persists for any length of time.

`${10}` The 10th, 11th, ... positional parameters can be accessed only after a `shift`. The 7th Edition shell reported an error if given `${10}`, and Solaris 10 `/bin/sh` still acts that way:

```
$ set 1 2 3 4 5 6 7 8 9 10
$ echo ${10}
bad substitution
```

${*var*:-*value*}

Old BSD shells, including the Ultrix `sh`, don't accept the colon for any shell substitution, and complain and die. Similarly for ${*var*:=*value*}, ${*var*:?*value*}, etc.

${*var*=*literal*}

Be sure to quote:

```
: ${var='Some words'}
```

otherwise some shells, such as on Digital Unix V 5.0, die because of a "bad substitution".

Solaris `/bin/sh` has a frightening bug in its interpretation of this. Imagine you need set a variable to a string containing '`}`'. This '`}`' character confuses Solaris `/bin/sh` when the affected variable was already set. This bug can be exercised by running:

```
$ unset foo
$ foo=${foo='}'}
$ echo $foo
}
$ foo=${foo='}'   # no error; this hints to what the bug is
$ echo $foo
}
$ foo=${foo='}'}
$ echo $foo
}}
 ^ ugh!
```

It seems that '`}`' is interpreted as matching '`${`', even though it is enclosed in single quotes. The problem doesn't happen using double quotes.

${*var*=*expanded-value*}

On Ultrix, running

```
default="yu,yaa"
: ${var="$default"}
```

sets *var* to '`M-yM-uM-,M-yM-aM-a`', i.e., the 8th bit of each char is set. You don't observe the phenomenon using a simple '`echo $var`' since apparently the shell resets the 8th bit when it expands $var. Here are two means to make this shell confess its sins:

```
$ cat -v <<EOF
$var
EOF
```

and

```
$ set | grep '^var=' | cat -v
```

One classic incarnation of this bug is:

```
default="a b c"
: ${list="$default"}
for c in $list; do
  echo $c
done
```

You'll get '`a b c`' on a single line. Why? Because there are no spaces in '`$list`': there are '`M- `', i.e., spaces with the 8th bit set, hence no IFS splitting is performed!!!

One piece of good news is that Ultrix works fine with '`: ${list=$default}`'; i.e., if you *don't* quote. The bad news is then that QNX 4.25 then sets *list* to the *last* item of *default*!

The portable way out consists in using a double assignment, to switch the 8th bit twice on Ultrix:

```
list=${list="$default"}
```

. . . but beware of the '`}`' bug from Solaris (see above). For safety, use:

```
test "${var+set}" = set || var={value}
```

`${#var}`
`${var%word}`
`${var%%word}`
`${var#word}`
`${var##word}`

Posix requires support for these usages, but they do not work with many traditional shells, e.g., Solaris 10 `/bin/sh`.

Also, `pdksh` 5.2.14 mishandles some *word* forms. For example if '`$1`' is '`a/b`' and '`$2`' is '`a`', then '`${1#$2}`' should yield '`/b`', but with `pdksh` it yields the empty string.

`` `commands` ``

Posix requires shells to trim all trailing newlines from command output before substituting it, so assignments like '`dir=`echo "$file" | tr a A``' do not work as expected if '`$file`' ends in a newline.

While in general it makes no sense, do not substitute a single builtin with side effects, because Ash 0.2, trying to optimize, does not fork a subshell to perform the command.

For instance, if you wanted to check that `cd` is silent, do not use '`test -z "`cd /`"`' because the following can happen:

```
$ pwd
/tmp
$ test -z "`cd /`" && pwd
/
```

The result of '`foo=`exit 1``' is left as an exercise to the reader.

The MSYS shell leaves a stray byte in the expansion of a double-quoted command substitution of a native program, if the end of the substitution is not aligned with the end of the double quote. This may be worked around by inserting another pair of quotes:

```
$ echo "`printf 'foo\r\n'` bar" > broken
$ echo "`printf 'foo\r\n'`"" bar" | cmp - broken
- broken differ: char 4, line 1
```

`$(commands)`

This construct is meant to replace ``commands``, and it has most of the problems listed under `commands`.

This construct can be nested while this is impossible to do portably with back quotes. Unfortunately it is not yet universally supported. Most notably, even recent releases of Solaris don't support it:

```
$ showrev -c /bin/sh | grep version
Command version: SunOS 5.10 Generic 121005-03 Oct 2006
$ echo $(echo blah)
syntax error: '(' unexpected
```

nor does IRIX 6.5's Bourne shell:

```
$ uname -a
IRIX firebird-image 6.5 07151432 IP22
$ echo $(echo blah)
$(echo blah)
```

If you do use '`$(commands)`', make sure that the commands do not start with a parenthesis, as that would cause confusion with a different notation '`$((expression))`' that in modern shells is an arithmetic expression not a command. To avoid the confusion, insert a space between the two opening parentheses.

Avoid *commands* that contain unbalanced parentheses in here-documents, comments, or case statement patterns, as many shells mishandle them. For example, Bash 3.1, '`ksh88`', `pdksh` 5.2.14, and Zsh 4.2.6 all mishandle the following valid command:

```
echo $(case x in x) echo hello;; esac)
```

`$((expression))`

Arithmetic expansion is not portable as some shells (most notably Solaris 10 `/bin/sh`) don't support it.

`^`

Always quote '`^`', otherwise traditional shells such as `/bin/sh` on Solaris 10 treat this like '`|`'.

10.7 Assignments

When setting several variables in a row, be aware that the order of the evaluation is undefined. For instance '`foo=1 foo=2; echo $foo`' gives '`1`' with Solaris `/bin/sh`, but '`2`' with Bash. You must use '`;`' to enforce the order: '`foo=1; foo=2; echo $foo`'.

Don't rely on the following to find '`subdir/program`':

```
PATH=subdir$PATH_SEPARATOR$PATH program
```

as this does not work with Zsh 3.0.6. Use something like this instead:

```
(PATH=subdir$PATH_SEPARATOR$PATH; export PATH; exec program)
```

Don't rely on the exit status of an assignment: Ash 0.2 does not change the status and propagates that of the last statement:

```
$ false || foo=bar; echo $?
1
$ false || foo=`:`; echo $?
0
```

and to make things even worse, QNX 4.25 just sets the exit status to 0 in any case:

```
$ foo=`exit 1`; echo $?
0
```

To assign default values, follow this algorithm:

1. If the default value is a literal and does not contain any closing brace, use:

   ```
   : ${var='my literal'}
   ```

2. If the default value contains no closing brace, has to be expanded, and the variable being initialized is not intended to be IFS-split (i.e., it's not a list), then use:

   ```
   : ${var="$default"}
   ```

3. If the default value contains no closing brace, has to be expanded, and the variable being initialized is intended to be IFS-split (i.e., it's a list), then use:

   ```
   var=${var="$default"}
   ```

4. If the default value contains a closing brace, then use:

   ```
   test "${var+set}" = set || var="has a '}'"
   ```

In most cases '`var=${var="$default"}`' is fine, but in case of doubt, just use the last form. See Section 10.6 [Shell Substitutions], page 162, items '`${var:-value}`' and '`${var=value}`' for the rationale.

10.8 Parentheses in Shell Scripts

Beware of two opening parentheses in a row, as many shell implementations treat them specially. Posix requires that the command '`((cat))`' must behave like '`(cat)`', but many shells, including Bash and the Korn shell, treat '`((cat))`' as an arithmetic expression equivalent to '`let "cat"`', and may or may not report an error when they detect that '`cat`' is not a number. As another example, '`pdksh`' 5.2.14 misparses the following code:

```
if ((true) || false); then
  echo ok
fi
```

To work around this problem, insert a space between the two opening parentheses. There is a similar problem and workaround with '`$((`'; see Section 10.6 [Shell Substitutions], page 162.

10.9 Slashes in Shell Scripts

Unpatched Tru64 5.1 `sh` omits the last slash of command-line arguments that contain two trailing slashes:

```
$ echo / // /// //// .// //.
/ / // /// ./ //.
$ x=//
$ eval "echo \$x"
```

```
/
$ set -x
$ echo abc | tr -t ab //
+ echo abc
+ tr -t ab /
/bc
```

Unpatched Tru64 4.0 `sh` adds a slash after '`"$var"`' if the variable is empty and the second double-quote is followed by a word that begins and ends with slash:

```
$ sh -xc 'p=; echo "$p"/ouch/'
p=
+ echo //ouch/
//ouch/
```

However, our understanding is that patches are available, so perhaps it's not worth worrying about working around these horrendous bugs.

10.10 Special Shell Variables

Some shell variables should not be used, since they can have a deep influence on the behavior of the shell. In order to recover a sane behavior from the shell, some variables should be unset, but `unset` is not portable (see Section 10.12 [Limitations of Builtins], page 173) and a fallback value is needed.

As a general rule, shell variable names containing a lower-case letter are safe; you can define and use these variables without worrying about their effect on the underlying system, and without worrying about whether the shell changes them unexpectedly. (The exception is the shell variable `status`, as described below.)

Here is a list of names that are known to cause trouble. This list is not exhaustive, but you should be safe if you avoid the name `status` and names containing only upper-case letters and underscores.

`_` Many shells reserve '`$_`' for various purposes, e.g., the name of the last command executed.

`BIN_SH` In Tru64, if `BIN_SH` is set to `xpg4`, subsidiary invocations of the standard shell conform to Posix.

`CDPATH` When this variable is set it specifies a list of directories to search when invoking `cd` with a relative file name that did not start with '`./`' or '`../`'. Posix 1003.1-2001 says that if a nonempty directory name from `CDPATH` is used successfully, `cd` prints the resulting absolute file name. Unfortunately this output can break idioms like '`abs=`cd src && pwd`'' because `abs` receives the name twice. Also, many shells do not conform to this part of Posix; for example, `zsh` prints the result only if a directory name other than '`.`' was chosen from `CDPATH`.

In practice the shells that have this problem also support `unset`, so you can work around the problem as follows:

```
(unset CDPATH) >/dev/null 2>&1 && unset CDPATH
```

You can also avoid output by ensuring that your directory name is absolute or anchored at '`./`', as in '`abs=`cd ./src && pwd`''.

Autoconf-generated scripts automatically unset `CDPATH` if possible, so you need not worry about this problem in those scripts.

`DUALCASE` In the MKS shell, case statements and file name generation are case-insensitive unless `DUALCASE` is nonzero. Autoconf-generated scripts export this variable when they start up.

`ENV`
`MAIL`
`MAILPATH`
`PS1`
`PS2`
`PS4` These variables should not matter for shell scripts, since they are supposed to affect only interactive shells. However, at least one shell (the pre-3.0 UWIN Korn shell) gets confused about whether it is interactive, which means that (for example) a `PS1` with a side effect can unexpectedly modify '`$?`'. To work around this bug, Autoconf-generated scripts do something like this:

```
(unset ENV) >/dev/null 2>&1 && unset ENV MAIL MAILPATH
PS1='$ '
PS2='> '
PS4='+ '
```

`FPATH` The Korn shell uses `FPATH` to find shell functions, so avoid `FPATH` in portable scripts. `FPATH` is consulted after `PATH`, but you still need to be wary of tests that use `PATH` to find whether a command exists, since they might report the wrong result if `FPATH` is also set.

`IFS` Long ago, shell scripts inherited `IFS` from the environment, but this caused many problems so modern shells ignore any environment settings for `IFS`.

Don't set the first character of `IFS` to backslash. Indeed, Bourne shells use the first character (backslash) when joining the components in '`"$@"`' and some shells then reinterpret (!) the backslash escapes, so you can end up with backspace and other strange characters.

The proper value for `IFS` (in regular code, not when performing splits) is '⟨SPC⟩⟨TAB⟩⟨RET⟩'. The first character is especially important, as it is used to join the arguments in '`$*`'; however, note that traditional shells, but also bash-2.04, fail to adhere to this and join with a space anyway.

`LANG`
`LC_ALL`
`LC_COLLATE`
`LC_CTYPE`
`LC_MESSAGES`
`LC_MONETARY`
`LC_NUMERIC`
`LC_TIME`

Autoconf-generated scripts normally set all these variables to '`C`' because so much configuration code assumes the C locale and Posix requires that locale environment variables be set to '`C`' if the C locale is desired. However, some

older, nonstandard systems (notably SCO) break if locale environment variables are set to 'C', so when running on these systems Autoconf-generated scripts unset the variables instead.

`LANGUAGE`

`LANGUAGE` is not specified by Posix, but it is a GNU extension that overrides `LC_ALL` in some cases, so Autoconf-generated scripts set it too.

`LC_ADDRESS`
`LC_IDENTIFICATION`
`LC_MEASUREMENT`
`LC_NAME`
`LC_PAPER`
`LC_TELEPHONE`

These locale environment variables are GNU extensions. They are treated like their Posix brethren (`LC_COLLATE`, etc.) as described above.

`LINENO` Most modern shells provide the current line number in `LINENO`. Its value is the line number of the beginning of the current command. Autoconf attempts to execute `configure` with a shell that supports `LINENO`. If no such shell is available, it attempts to implement `LINENO` with a Sed prepass that replaces each instance of the string `$LINENO` (not followed by an alphanumeric character) with the line's number.

You should not rely on `LINENO` within `eval`, as the behavior differs in practice. Also, the possibility of the Sed prepass means that you should not rely on `$LINENO` when quoted, when in here-documents, or when in long commands that cross line boundaries. Subshells should be OK, though. In the following example, lines 1, 6, and 9 are portable, but the other instances of `LINENO` are not:

```
$ cat lineno
echo 1. $LINENO
cat <<EOF
3. $LINENO
4. $LINENO
EOF
( echo 6. $LINENO )
eval 'echo 7. $LINENO'
echo 8. '$LINENO'
echo 9. $LINENO '
10.' $LINENO
```

```
$ bash-2.05 lineno
1. 1
3. 2
4. 2
6. 6
7. 1
8. $LINENO
9. 9
10. 9
$ zsh-3.0.6 lineno
1. 1
3. 2
4. 2
6. 6
7. 7
8. $LINENO
9. 9
10. 9
$ pdksh-5.2.14 lineno
1. 1
3. 2
4. 2
6. 6
7. 0
8. $LINENO
9. 9
10. 9
$ sed '=' <lineno |
>   sed '
>     N
>     s,$,-,
>     t loop
>     :loop
>     s,^\([0-9]*\)\(.*\)[$]LINENO\([^a-zA-Z0-9_]\),\1\2\1\3,
>     t loop
>     s,-$,,
>     s,^[0-9]*\n,,
>   ' |
>   sh
1. 1
3. 3
4. 4
6. 6
7. 7
8. 8
9. 9
10. 10
```

`NULLCMD` When executing the command '`>foo`', `zsh` executes '`$NULLCMD >foo`' unless it is operating in Bourne shell compatibility mode and the `zsh` version is newer than 3.1.6-dev-18. If you are using an older `zsh` and forget to set `NULLCMD`, your script might be suspended waiting for data on its standard input.

`PATH_SEPARATOR`
On DJGPP systems, the `PATH_SEPARATOR` environment variable can be set to either '`:`' or '`;`' to control the path separator Bash uses to set up certain environment variables (such as `PATH`). You can set this variable to '`;`' if you want `configure` to use '`;`' as a separator; this might be useful if you plan to use non-Posix shells to execute files. See Section 10.4 [File System Conventions], page 160, for more information about `PATH_SEPARATOR`.

`PWD` Posix 1003.1-2001 requires that `cd` and `pwd` must update the `PWD` environment variable to point to the logical name of the current directory, but traditional shells do not support this. This can cause confusion if one shell instance maintains `PWD` but a subsidiary and different shell does not know about `PWD` and executes `cd`; in this case `PWD` points to the wrong directory. Use '`` `pwd` ``' rather than '`$PWD`'.

`RANDOM` Many shells provide `RANDOM`, a variable that returns a different integer each time it is used. Most of the time, its value does not change when it is not used, but on IRIX 6.5 the value changes all the time. This can be observed by using `set`. It is common practice to use `$RANDOM` as part of a file name, but code shouldn't rely on `$RANDOM` expanding to a nonempty string.

`status` This variable is an alias to '`$?`' for `zsh` (at least 3.1.6), hence read-only. Do not use it.

10.11 Shell Functions

Nowadays, it is difficult to find a shell that does not support shell functions at all. However, some differences should be expected:

Inside a shell function, you should not rely on the error status of a subshell if the last command of that subshell was `exit` or `trap`, as this triggers bugs in zsh 4.x; while Autoconf tries to find a shell that does not exhibit the bug, zsh might be the only shell present on the user's machine.

Shell variables and functions may share the same namespace, for example with Solaris 10 `/bin/sh`:

```
$ f () { :; }; f=; f
f: not found
```

For this reason, Autotest uses the prefix '`at_func_`' for its functions.

Handling of positional parameters and shell options varies among shells. For example, Korn shells reset and restore trace output ('`set -x`') and other options upon function entry and exit. Inside a function, IRIX sh sets '`$0`' to the function name.

Some ancient Bourne shell variants with function support did not reset '`$i, i >= 0`', upon function exit, so effectively the arguments of the script were lost after the first function invocation. It is probably not worth worrying about these shells any more.

With AIX sh, a `trap` on 0 installed in a shell function triggers at function exit rather than at script exit, see See Section 10.12 [Limitations of Builtins], page 173.

10.12 Limitations of Shell Builtins

No, no, we are serious: some shells do have limitations! :)

You should always keep in mind that any builtin or command may support options, and therefore differ in behavior with arguments starting with a dash. For instance, the innocent '`echo "$word"`' can give unexpected results when `word` starts with a dash. It is often possible to avoid this problem using '`echo "x$word"`', taking the '`x`' into account later in the pipe.

`.` Use `.` only with regular files (use '`test -f`'). Bash 2.03, for instance, chokes on '`. /dev/null`'. Remember that `.` uses `PATH` if its argument contains no slashes. Also, some shells, including bash 3.2, implicitly append the current directory to this `PATH` search, even though Posix forbids it. So if you want to use `.` on a file '`foo`' in the current directory, you must use '`. ./foo`'.

`!` The Unix version 7 shell did not support negating the exit status of commands with `!`, and this feature is still absent from some shells (e.g., Solaris `/bin/sh`). Shell code like this:

```
if ! cmp file1 file2 >/dev/null 2>&1; then
  echo files differ or trouble
fi
```

is therefore not portable in practice. Typically it is easy to rewrite such code, e.g.:

```
cmp file1 file2 >/dev/null 2>&1 ||
  echo files differ or trouble
```

More generally, one can always rewrite '`! command`' as:

```
if command; then (exit 1); else :; fi
```

`{...}` Bash 3.2 (and earlier versions) sometimes does not properly set '`$?`' when failing to write redirected output of a compound command. This problem is most commonly observed with '`{...}`'; it does not occur with '`(...)`'. For example:

```
$ bash -c '{ echo foo; } >/bad; echo $?'
bash: line 1: /bad: Permission denied
0
$ bash -c 'while :; do echo; done >/bad; echo $?'
bash: line 1: /bad: Permission denied
0
```

To work around the bug, prepend '`:;`':

```
$ bash -c ':;{ echo foo; } >/bad; echo $?'
bash: line 1: /bad: Permission denied
1
```

`break` The use of '`break 2`' etc. is safe.

`case` You don't need to quote the argument; no splitting is performed.

You don't need the final '`;;`', but you should use it.

Posix requires support for `case` patterns with opening parentheses like this:

```
case $file_name in
(*.c) echo "C source code";;
esac
```

but the `(` in this example is not portable to many Bourne shell implementations. It can be omitted safely.

Zsh handles pattern fragments derived from parameter expansions or command substitutions as though quoted:

```
$ pat=\?; case aa in ?$pat) echo match;; esac
$ pat=\?; case a? in ?$pat) echo match;; esac
match
```

Because of a bug in its `fnmatch`, Bash fails to properly handle backslashes in character classes:

```
bash-2.02$ case /tmp in [/\\]*) echo OK;; esac
bash-2.02$
```

This is extremely unfortunate, since you are likely to use this code to handle Posix or MS-DOS absolute file names. To work around this bug, always put the backslash first:

```
bash-2.02$ case '\TMP' in [\\/]*) echo OK;; esac
OK
bash-2.02$ case /tmp in [\\/]*) echo OK;; esac
OK
```

Many Bourne shells cannot handle closing brackets in character classes correctly.

Some shells also have problems with backslash escaping in case you do not want to match the backslash: both a backslash and the escaped character match this pattern. To work around this, specify the character class in a variable, so that quote removal does not apply afterwards, and the special characters don't have to be backslash-escaped:

```
$ case '\' in [\<]) echo OK;; esac
OK
$ scanset='[<]'; case '\' in $scanset) echo OK;; esac
$
```

Even with this, Solaris `ksh` matches a backslash if the set contains any of the characters '`|`', '`&`', '`(`', or '`)`'.

Conversely, Tru64 `ksh` (circa 2003) erroneously always matches a closing parenthesis if not specified in a character class:

```
$ case foo in *\)*) echo fail ;; esac
fail
$ case foo in *')'*) echo fail ;; esac
fail
```

Some shells, such as Ash 0.3.8, are confused by an empty `case`/`esac`:

```
ash-0.3.8 $ case foo in esac;
```

```
error Syntax error: ";" unexpected (expecting ")")
```

Many shells still do not support parenthesized cases, which is a pity for those of us using tools that rely on balanced parentheses. For instance, Solaris `/bin/sh`:

```
$ case foo in (foo) echo foo;; esac
error syntax error: '(' unexpected
```

`cd` Posix 1003.1-2001 requires that `cd` must support the '`-L`' ("logical") and '`-P`' ("physical") options, with '`-L`' being the default. However, traditional shells do not support these options, and their `cd` command has the '`-P`' behavior.

Portable scripts should assume neither option is supported, and should assume neither behavior is the default. This can be a bit tricky, since the Posix default behavior means that, for example, '`ls ..`' and '`cd ..`' may refer to different directories if the current logical directory is a symbolic link. It is safe to use `cd` *`dir`* if *dir* contains no '`..`' components. Also, Autoconf-generated scripts check for this problem when computing variables like `ac_top_srcdir` (see Section 4.6 [Configuration Actions], page 20), so it is safe to `cd` to these variables.

See See Section 10.10 [Special Shell Variables], page 168, for portability problems involving `cd` and the `CDPATH` environment variable. Also please see the discussion of the `pwd` command.

`echo` The simple `echo` is probably the most surprising source of portability troubles. It is not possible to use '`echo`' portably unless both options and escape sequences are omitted. New applications which are not aiming at portability should use '`printf`' instead of '`echo`'.

Don't expect any option. See Section 4.8.1 [Preset Output Variables], page 23, `ECHO_N` etc. for a means to simulate '`-n`'.

Do not use backslashes in the arguments, as there is no consensus on their handling. For '`echo '\n' | wc -l`', the `sh` of Solaris outputs 2, but Bash and Zsh (in `sh` emulation mode) output 1. The problem is truly `echo`: all the shells understand '`'\n'`' as the string composed of a backslash and an '`n`'.

Because of these problems, do not pass a string containing arbitrary characters to `echo`. For example, '`echo "$foo"`' is safe if you know that *foo*'s value cannot contain backslashes and cannot start with '`-`', but otherwise you should use a here-document like this:

```
cat <<EOF
$foo
EOF
```

`eval` The `eval` command is useful in limited circumstances, e.g., using commands like '`eval table_$key=\$value`' and '`eval value=table_$key`' to simulate a hash table when the key is known to be alphanumeric. However, `eval` is tricky to use on arbitrary arguments, even when it is implemented correctly.

It is obviously unwise to use '`eval $cmd`' if the string value of '`cmd`' was derived from an untrustworthy source. But even if the string value is valid, '`eval $cmd`' might not work as intended, since it causes field splitting and file name expansion to occur twice, once for the `eval` and once for the command itself. It is therefore safer to use '`eval "$cmd"`'. For example, if *cmd* has the value

'`cat test?.c`', '`eval $cmd`' might expand to the equivalent of '`cat test;.c`' if there happens to be a file named '`test;.c`' in the current directory; and this in turn mistakenly attempts to invoke `cat` on the file '`test`' and then execute the command `.c`. To avoid this problem, use '`eval "$cmd"`' rather than '`eval $cmd`'.

However, suppose that you want to output the text of the evaluated command just before executing it. Assuming the previous example, '`echo "Executing: $cmd"`' outputs '`Executing: cat test?.c`', but this output doesn't show the user that '`test;.c`' is the actual name of the copied file. Conversely, '`eval "echo Executing: $cmd"`' works on this example, but it fails with '`cmd='cat foo >bar'`', since it mistakenly replaces the contents of '`bar`' by the string '`cat foo`'. No simple, general, and portable solution to this problem is known.

You should also be wary of common bugs in `eval` implementations. In some shell implementations (e.g., older `ash`, OpenBSD 3.8 `sh`, `pdksh` v5.2.14 99/07/13.2, and `zsh` 4.2.5), the arguments of '`eval`' are evaluated in a context where '`$?`' is 0, so they exhibit behavior like this:

```
$ false; eval 'echo $?'
0
```

The correct behavior here is to output a nonzero value, but portable scripts should not rely on this.

You should not rely on `LINENO` within `eval`. See Section 10.10 [Special Shell Variables], page 168.

`exit` The default value of `exit` is supposed to be `$?`; unfortunately, some shells, such as the DJGPP port of Bash 2.04, just perform '`exit 0`'.

```
bash-2.04$ foo=`exit 1` || echo fail
fail
bash-2.04$ foo=`(exit 1)` || echo fail
fail
bash-2.04$ foo=`(exit 1); exit` || echo fail
bash-2.04$
```

Using '`exit $?`' restores the expected behavior.

Some shell scripts, such as those generated by `autoconf`, use a trap to clean up before exiting. If the last shell command exited with nonzero status, the trap also exits with nonzero status so that the invoker can tell that an error occurred.

Unfortunately, in some shells, such as Solaris `/bin/sh`, an exit trap ignores the `exit` command's argument. In these shells, a trap cannot determine whether it was invoked by plain `exit` or by `exit 1`. Instead of calling `exit` directly, use the `AC_MSG_ERROR` macro that has a workaround for this problem.

`export` The builtin `export` dubs a shell variable *environment variable*. Each update of exported variables corresponds to an update of the environment variables. Conversely, each environment variable received by the shell when it is launched should be imported as a shell variable marked as exported.

Alas, many shells, such as Solaris `/bin/sh`, IRIX 6.3, IRIX 5.2, AIX 4.1.5, and Digital Unix 4.0, forget to `export` the environment variables they receive. As a result, two variables coexist: the environment variable and the shell variable. The following code demonstrates this failure:

```
#!/bin/sh
echo $FOO
FOO=bar
echo $FOO
exec /bin/sh $0
```

when run with '`FOO=foo`' in the environment, these shells print alternately '`foo`' and '`bar`', although they should print only '`foo`' and then a sequence of '`bar`'s.

Therefore you should `export` again each environment variable that you update.

`false` Don't expect `false` to exit with status 1: in native Solaris '`/bin/false`' exits with status 255.

`for` To loop over positional arguments, use:

```
for arg
do
  echo "$arg"
done
```

You may *not* leave the `do` on the same line as `for`, since some shells improperly grok:

```
for arg; do
  echo "$arg"
done
```

If you want to explicitly refer to the positional arguments, given the '`$@`' bug (see Section 10.6 [Shell Substitutions], page 162), use:

```
for arg in ${1+"$@"}; do
  echo "$arg"
done
```

But keep in mind that Zsh, even in Bourne shell emulation mode, performs word splitting on '`${1+"$@"}`'; see Section 10.6 [Shell Substitutions], page 162, item '$@', for more.

`if` Using '`!`' is not portable. Instead of:

```
if ! cmp -s file file.new; then
  mv file.new file
fi
```

use:

```
if cmp -s file file.new; then :; else
  mv file.new file
fi
```

There are shells that do not reset the exit status from an `if`:

```
$ if (exit 42); then true; fi; echo $?
```

```
42
```

whereas a proper shell should have printed '0'. This is especially bad in makefiles since it produces false failures. This is why properly written makefiles, such as Automake's, have such hairy constructs:

```
if test -f "$file"; then
  install "$file" "$dest"
else
  :
fi
```

`printf` A format string starting with a '-' can cause problems. Bash interprets it as an option and gives an error. And '--' to mark the end of options is not good in the NetBSD Almquist shell (e.g., 0.4.6) which takes that literally as the format string. Putting the '-' in a '%c' or '%s' is probably easiest:

```
printf %s -foo
```

Bash 2.03 mishandles an escape sequence that happens to evaluate to '%':

```
$ printf '\045'
bash: printf: '%': missing format character
```

Large outputs may cause trouble. On Solaris 2.5.1 through 10, for example, '/usr/bin/printf' is buggy, so when using /bin/sh the command 'printf %010000x 123' normally dumps core.

`read` Not all shells support '-r' (Solaris /bin/sh for example).

`pwd` With modern shells, plain pwd outputs a "logical" directory name, some of whose components may be symbolic links. These directory names are in contrast to "physical" directory names, whose components are all directories.

Posix 1003.1-2001 requires that pwd must support the '-L' ("logical") and '-P' ("physical") options, with '-L' being the default. However, traditional shells do not support these options, and their pwd command has the '-P' behavior.

Portable scripts should assume neither option is supported, and should assume neither behavior is the default. Also, on many hosts '/bin/pwd' is equivalent to 'pwd -P', but Posix does not require this behavior and portable scripts should not rely on it.

Typically it's best to use plain pwd. On modern hosts this outputs logical directory names, which have the following advantages:

- Logical names are what the user specified.
- Physical names may not be portable from one installation host to another due to network file system gymnastics.
- On modern hosts 'pwd -P' may fail due to lack of permissions to some parent directory, but plain pwd cannot fail for this reason.

Also please see the discussion of the cd command.

`set` With the FreeBSD 6.0 shell, the set command (without any options) does not sort its output.

The `set` builtin faces the usual problem with arguments starting with a dash. Modern shells such as Bash or Zsh understand '`--`' to specify the end of the options (any argument after '`--`' is a parameter, even '`-x`' for instance), but many traditional shells (e.g., Solaris 10 `/bin/sh`) simply stop option processing as soon as a non-option argument is found. Therefore, use '`dummy`' or simply '`x`' to end the option processing, and use `shift` to pop it out:

```
set x $my_list; shift
```

Avoid '`set -`', e.g., '`set - $my_list`'. Posix no longer requires support for this command, and in traditional shells '`set - $my_list`' resets the '`-v`' and '`-x`' options, which makes scripts harder to debug.

Some nonstandard shells do not recognize more than one option (e.g., '`set -e -x`' assigns '`-x`' to the command line). It is better to combine them:

```
set -ex
```

The BSD shell has had several problems with the '`-e`' option, partly because BSD `make` traditionally used '`-e`' even though this was incompatible with Posix (see Section 11.2 [Failure in Make Rules], page 197). Older versions of the BSD shell (circa 1990) mishandled '`&&`', '`||`', '`if`', and '`case`' when '`-e`' was in effect, causing the shell to exit unexpectedly in some cases. This was particularly a problem with makefiles, and led to circumlocutions like '`sh -c 'test -f file || touch file''`', where the seemingly-unnecessary '`sh -c '...''`' wrapper works around the bug.

Even relatively-recent versions of the BSD shell (e.g., OpenBSD 3.4) wrongly exit with '`-e`' if a command within '`&&`' fails inside a compound statement. For example:

```
#! /bin/sh
set -e
foo=''
test -n "$foo" && exit 1
echo one
if :; then
  test -n "$foo" && exit 1
fi
echo two
```

does not print '`two`'. One workaround is to use '`if test -n "$foo"; then exit 1; fi`' rather than '`test -n "$foo" && exit 1`'. Another possibility is to warn BSD users not to use '`sh -e`'.

`shift` Not only is `shift`ing a bad idea when there is nothing left to shift, but in addition it is not portable: the shell of MIPS RISC/OS 4.52 refuses to do it.

Don't use '`shift 2`' etc.; it was not in the 7th Edition Bourne shell, and it is also absent in many pre-Posix shells.

`source` This command is not portable, as Posix does not require it; use `.` instead.

`test` The `test` program is the way to perform many file and string tests. It is often invoked by the alternate name '`[`', but using that name in Autoconf code is asking for trouble since it is an M4 quote character.

The '`-a`', '`-o`', '`(`', and '`)`' operands are not portable and should be avoided. Thus, portable uses of `test` should never have more than four arguments, and scripts should use shell constructs like '`&&`' and '`||`' instead. If you combine '`&&`' and '`||`' in the same statement, keep in mind that they have equal precedence, so it is often better to parenthesize even when this is redundant. For example:

```
# Not portable:
test "X$a" = "X$b" -a \
  '(' "X$c" != "X$d" -o "X$e" = "X$f" ')'

# Portable:
test "X$a" = "X$b" &&
  { test "X$c" != "X$d" || test "X$e" = "X$f"; }
```

`test` does not process options like most other commands do; for example, it does not recognize the '`--`' argument as marking the end of options.

It is safe to use '`!`' as a `test` operator. For example, '`if test ! -d foo; ...`' is portable even though '`if ! test -d foo; ...`' is not.

`test` (files)

To enable `configure` scripts to support cross-compilation, they shouldn't do anything that tests features of the build system instead of the host system. But occasionally you may find it necessary to check whether some arbitrary file exists. To do so, use '`test -f`' or '`test -r`'. Do not use '`test -x`', because 4.3BSD does not have it. Do not use '`test -e`' either, because Solaris `/bin/sh` lacks it. To test for symbolic links on systems that have them, use '`test -h`' rather than '`test -L`'; either form conforms to Posix 1003.1-2001, but older shells like Solaris 8 `/bin/sh` support only '`-h`'.

`test` (strings)

Posix says that '`test "`*`string`*`"`' succeeds if *string* is not null, but this usage is not portable to traditional platforms like Solaris 10 `/bin/sh`, which mishandle strings like '`!`' and '`-n`'.

Posix also says that '`test ! "`*`string`*`"`', '`test -n "`*`string`*`"`' and '`test -z "`*`string`*`"`' work with any string, but many shells (such as Solaris, AIX 3.2, UNICOS 10.0.0.6, Digital Unix 4, etc.) get confused if *string* looks like an operator:

```
$ test -n =
test: argument expected
$ test ! -n
test: argument expected
```

Similarly, Posix says that both '`test "`*`string1`*`" = "`*`string2`*`"`' and '`test "`*`string1`*`" != "`*`string2`*`"`' work for any pairs of strings, but in practice this is not true for troublesome strings that look like operators or parentheses, or that begin with '`-`'.

It is best to protect such strings with a leading '`X`', e.g., '`test "X`*`string`*`" != X`' rather than '`test -n "`*`string`*`"`' or '`test ! "`*`string`*`"`'.

It is common to find variations of the following idiom:

```
test -n "`echo $ac_feature | sed 's/[-a-zA-Z0-9_]//g'`" &&
```

```
  action
```

to take an action when a token matches a given pattern. Such constructs should be avoided by using:

```
case $ac_feature in
  *[!-a-zA-Z0-9_]*) action;;
esac
```

If the pattern is a complicated regular expression that cannot be expressed as a shell pattern, use something like this instead:

```
expr "X$ac_feature" : 'X.*[^-a-zA-Z0-9_]' >/dev/null &&
  action
```

'`expr "Xfoo" : "Xbar"`' is more robust than '`echo "Xfoo" | grep "^Xbar"`', because it avoids problems when '*foo*' contains backslashes.

`trap` It is safe to trap at least the signals 1, 2, 13, and 15. You can also trap 0, i.e., have the `trap` run when the script ends (either via an explicit `exit`, or the end of the script). The trap for 0 should be installed outside of a shell function, or AIX 5.3 `/bin/sh` will invoke the trap at the end of this function.

Posix says that '`trap - 1 2 13 15`' resets the traps for the specified signals to their default values, but many common shells (e.g., Solaris `/bin/sh`) misinterpret this and attempt to execute a "command" named `-` when the specified conditions arise. There is no portable workaround, except for '`trap - 0`', for which '`trap '' 0`' is a portable substitute.

Although Posix is not absolutely clear on this point, it is widely admitted that when entering the trap '`$?`' should be set to the exit status of the last command run before the trap. The ambiguity can be summarized as: "when the trap is launched by an `exit`, what is the *last* command run: that before `exit`, or `exit` itself?"

Bash considers `exit` to be the last command, while Zsh and Solaris `/bin/sh` consider that when the trap is run it is *still* in the `exit`, hence it is the previous exit status that the trap receives:

```
$ cat trap.sh
trap 'echo $?' 0
(exit 42); exit 0
$ zsh trap.sh
42
$ bash trap.sh
0
```

The portable solution is then simple: when you want to '`exit 42`', run '`(exit 42); exit 42`', the first `exit` being used to set the exit status to 42 for Zsh, and the second to trigger the trap and pass 42 as exit status for Bash.

The shell in FreeBSD 4.0 has the following bug: '`$?`' is reset to 0 by empty lines if the code is inside `trap`.

```
$ trap 'false

echo $?' 0
```

```
$ exit
0
```

Fortunately, this bug only affects `trap`.

`true` Don't worry: as far as we know `true` is portable. Nevertheless, it's not always a builtin (e.g., Bash 1.x), and the portable shell community tends to prefer using `:`. This has a funny side effect: when asked whether `false` is more portable than `true` Alexandre Oliva answered:

> In a sense, yes, because if it doesn't exist, the shell will produce an exit status of failure, which is correct for `false`, but not for `true`.

`unset` In some nonconforming shells (e.g., Bash 2.05a), `unset FOO` fails when `FOO` is not set. Also, Bash 2.01 mishandles `unset MAIL` in some cases and dumps core.

A few ancient shells lack `unset` entirely. Nevertheless, because it is extremely useful to disable embarrassing variables such as `PS1`, you can test for its existence and use it *provided* you give a neutralizing value when `unset` is not supported:

```
# "|| exit" suppresses any "Segmentation fault" message.
if ( (MAIL=60; unset MAIL) || exit) >/dev/null 2>&1; then
  unset=unset
else
  unset=false
fi
$unset PS1 || PS1='$ '
```

See Section 10.10 [Special Shell Variables], page 168, for some neutralizing values. Also, see Section 10.12 [Limitations of Builtins], page 173, documentation of `export`, for the case of environment variables.

10.13 Limitations of Usual Tools

The small set of tools you can expect to find on any machine can still include some limitations you should be aware of.

Awk Don't leave white space before the opening parenthesis in a user function call. Posix does not allow this and GNU Awk rejects it:

```
$ gawk 'function die () { print "Aaaaarg!"  }
        BEGIN { die () }'
gawk: cmd. line:2:         BEGIN { die () }
gawk: cmd. line:2:                       ^ parse error
$ gawk 'function die () { print "Aaaaarg!"  }
        BEGIN { die() }'
Aaaaarg!
```

Posix says that if a program contains only '`BEGIN`' actions, and contains no instances of `getline`, then the program merely executes the actions without reading input. However, traditional Awk implementations (such as Solaris 10 `awk`) read and discard input in this case. Portable scripts can redirect input from '`/dev/null`' to work around the problem. For example:

```
awk 'BEGIN {print "hello world"}' </dev/null
```

Posix says that in an 'END' action, '$NF' (and presumably, '$1') retain their value from the last record read, if no intervening 'getline' occurred. However, some implementations (such as Solaris 10 '/usr/bin/awk', 'nawk', or Darwin 'awk') reset these variables. A workaround is to use an intermediate variable prior to the 'END' block. For example:

```
$ cat end.awk
{ tmp = $1 }
END { print "a", $1, $NF, "b", tmp }
$ echo 1 | awk -f end.awk
a   b 1
$ echo 1 | gawk -f end.awk
a 1 1 b 1
```

If you want your program to be deterministic, don't depend on for on arrays:

```
$ cat for.awk
END {
  arr["foo"] = 1
  arr["bar"] = 1
  for (i in arr)
    print i
}
$ gawk -f for.awk </dev/null
foo
bar
$ nawk -f for.awk </dev/null
bar
foo
```

Some Awk implementations, such as HP-UX 11.0's native one, mishandle anchors:

```
$ echo xfoo | $AWK '/foo|^bar/ { print }'
$ echo bar | $AWK '/foo|^bar/ { print }'
bar
$ echo xfoo | $AWK '/^bar|foo/ { print }'
xfoo
$ echo bar | $AWK '/^bar|foo/ { print }'
bar
```

Either do not depend on such patterns (i.e., use '/^(.*foo|bar)/', or use a simple test to reject such implementations.

On 'ia64-hp-hpux11.23', Awk mishandles printf conversions after %u:

```
$ awk 'BEGIN { printf "%u %d\n", 0, -1 }'
0 0
```

AIX version 5.2 has an arbitrary limit of 399 on the length of regular expressions and literal strings in an Awk program.

Traditional Awk implementations derived from Unix version 7, such as Solaris /bin/awk, have many limitations and do not conform to Posix. Nowadays AC_PROG_AWK (see Section 5.2.1 [Particular Programs], page 41) finds you an Awk

that doesn't have these problems, but if for some reason you prefer not to use AC_PROG_AWK you may need to address them.

Traditional Awk does not support multidimensional arrays or user-defined functions.

Traditional Awk does not support the '-v' option. You can use assignments after the program instead, e.g., $AWK '{print v $1}' v=x; however, don't forget that such assignments are not evaluated until they are encountered (e.g., after any BEGIN action).

Traditional Awk does not support the keywords delete or do.

Traditional Awk does not support the expressions a?b:c, !a, a^b, or a^=b.

Traditional Awk does not support the predefined CONVFMT variable.

Traditional Awk supports only the predefined functions exp, index, int, length, log, split, sprintf, sqrt, and substr.

Traditional Awk getline is not at all compatible with Posix; avoid it.

Traditional Awk has for (i in a) ... but no other uses of the in keyword. For example, it lacks if (i in a) ....

In code portable to both traditional and modern Awk, FS must be a string containing just one ordinary character, and similarly for the field-separator argument to split.

Traditional Awk has a limit of 99 fields in a record. Since some Awk implementations, like Tru64's, split the input even if you don't refer to any field in the script, to circumvent this problem, set 'FS' to an unusual character and use split.

Traditional Awk has a limit of at most 99 bytes in a number formatted by OFMT; for example, OFMT="%.300e"; print 0.1; typically dumps core.

The original version of Awk had a limit of at most 99 bytes per split field, 99 bytes per substr substring, and 99 bytes per run of non-special characters in a printf format, but these bugs have been fixed on all practical hosts that we know of.

basename Not all hosts have a working basename. You can use expr instead.

cat Don't rely on any option.

cc The command 'cc -c foo.c' traditionally produces an object file named 'foo.o'. Most compilers allow '-c' to be combined with '-o' to specify a different object file name, but Posix does not require this combination and a few compilers lack support for it. See Section 5.10.3 [C Compiler], page 74, for how GNU Make tests for this feature with AC_PROG_CC_C_O.

When a compilation such as 'cc -o foo foo.c' fails, some compilers (such as CDS on Reliant Unix) leave a 'foo.o'.

HP-UX cc doesn't accept '.S' files to preprocess and assemble. 'cc -c foo.S' appears to succeed, but in fact does nothing.

The default executable, produced by 'cc foo.c', can be

- 'a.out' — usual Posix convention.

- '`b.out`' — i960 compilers (including `gcc`).
- '`a.exe`' — DJGPP port of `gcc`.
- '`a_out.exe`' — GNV `cc` wrapper for DEC C on OpenVMS.
- '`foo.exe`' — various MS-DOS compilers.

The C compiler's traditional name is `cc`, but other names like `gcc` are common. Posix 1003.1-2001 specifies the name `c99`, but older Posix editions specified `c89` and anyway these standard names are rarely used in practice. Typically the C compiler is invoked from makefiles that use '`$(CC)`', so the value of the '`CC`' make variable selects the compiler name.

`chmod` Avoid usages like '`chmod -w file`'; use '`chmod a-w file`' instead, for two reasons. First, plain '`-w`' does not necessarily make the file unwritable, since it does not affect mode bits that correspond to bits in the file mode creation mask. Second, Posix says that the '`-w`' might be interpreted as an implementation-specific option, not as a mode; Posix suggests using '`chmod -- -w file`' to avoid this confusion, but unfortunately '`--`' does not work on some older hosts.

`cmp` `cmp` performs a raw data comparison of two files, while `diff` compares two text files. Therefore, if you might compare DOS files, even if only checking whether two files are different, use `diff` to avoid spurious differences due to differences of newline encoding.

`cp` Avoid the '`-r`' option, since Posix 1003.1-2004 marks it as obsolescent and its behavior on special files is implementation-defined. Use '`-R`' instead. On GNU hosts the two options are equivalent, but on Solaris hosts (for example) `cp -r` reads from pipes instead of replicating them.

Some `cp` implementations (e.g., BSD/OS 4.2) do not allow trailing slashes at the end of nonexistent destination directories. To avoid this problem, omit the trailing slashes. For example, use '`cp -R source /tmp/newdir`' rather than '`cp -R source /tmp/newdir/`' if '`/tmp/newdir`' does not exist.

The ancient SunOS 4 `cp` does not support '`-f`', although its `mv` does.

Traditionally, file timestamps had 1-second resolution, and '`cp -p`' copied the timestamps exactly. However, many modern file systems have timestamps with 1-nanosecond resolution. Unfortunately, '`cp -p`' implementations truncate timestamps when copying files, so this can result in the destination file appearing to be older than the source. The exact amount of truncation depends on the resolution of the system calls that `cp` uses; traditionally this was `utime`, which has 1-second resolution, but some newer `cp` implementations use `utimes`, which has 1-microsecond resolution. These newer implementations include GNU Core Utilities 5.0.91 or later, and Solaris 8 (sparc) patch 109933-02 or later. Unfortunately as of January 2006 there is still no system call to set timestamps to the full nanosecond resolution.

Bob Proulx notes that '`cp -p`' always *tries* to copy ownerships. But whether it actually does copy ownerships or not is a system dependent policy decision implemented by the kernel. If the kernel allows it then it happens. If the kernel does not allow it then it does not happen. It is not something `cp` itself has control over.

In Unix System V any user can chown files to any other user, and System V also has a non-sticky '`/tmp`'. That probably derives from the heritage of System V in a business environment without hostile users. BSD changed this to be a more secure model where only root can `chown` files and a sticky '`/tmp`' is used. That undoubtedly derives from the heritage of BSD in a campus environment.

GNU/Linux and Solaris by default follow BSD, but can be configured to allow a System V style `chown`. On the other hand, HP-UX follows System V, but can be configured to use the modern security model and disallow `chown`. Since it is an administrator-configurable parameter you can't use the name of the kernel as an indicator of the behavior.

`date` Some versions of `date` do not recognize special '`%`' directives, and unfortunately, instead of complaining, they just pass them through, and exit with success:

```
$ uname -a
OSF1 medusa.sis.pasteur.fr V5.1 732 alpha
$ date "+%s"
%s
```

`diff` Option '`-u`' is nonportable.

Some implementations, such as Tru64's, fail when comparing to '`/dev/null`'. Use an empty file instead.

`dirname` Not all hosts have a working `dirname`, and you should instead use `AS_DIRNAME` (see Section 8.4 [Programming in M4sh], page 141). For example:

```
dir=`dirname "$file"`       # This is not portable.
dir=`AS_DIRNAME(["$file"])` # This is more portable.
```

`egrep` Posix 1003.1-2001 no longer requires `egrep`, but many hosts do not yet support the Posix replacement `grep -E`. Also, some traditional implementations do not work on long input lines. To work around these problems, invoke `AC_PROG_EGREP` and then use `$EGREP`.

Portable extended regular expressions should use '`\`' only to escape characters in the string '`$()*+.?[\^{|`'. For example, '`\}`' is not portable, even though it typically matches '`}`'.

The empty alternative is not portable. Use '`?`' instead. For instance with Digital Unix v5.0:

```
> printf "foo\n|foo\n" | $EGREP '^(|foo|bar)$'
|foo
> printf "bar\nbar|\n" | $EGREP '^(foo|bar|)$'
bar|
> printf "foo\nfoo|\n|bar\nbar\n" | $EGREP '^(foo||bar)$'
foo
|bar
```

`$EGREP` also suffers the limitations of `grep`.

`expr` No `expr` keyword starts with '`X`', so use '`expr X"`*word*`" : 'X`*regex*`'`' to keep `expr` from misinterpreting *word*.

Don't use `length`, `substr`, `match` and `index`.

`expr` (‘`|`’) You can use ‘`|`’. Although Posix does require that ‘`expr ''`’ return the empty string, it does not specify the result when you ‘`|`’ together the empty string (or zero) with the empty string. For example:

```
expr '' \| ''
```

Posix 1003.2-1992 returns the empty string for this case, but traditional Unix returns ‘`0`’ (Solaris is one such example). In Posix 1003.1-2001, the specification was changed to match traditional Unix's behavior (which is bizarre, but it's too late to fix this). Please note that the same problem does arise when the empty string results from a computation, as in:

```
expr bar : foo \| foo : bar
```

Avoid this portability problem by avoiding the empty string.

`expr` (‘`:`’) Portable `expr` regular expressions should use ‘`\`’ to escape only characters in the string ‘`$()*.0123456789[\^n{}`’. For example, alternation, ‘`\|`’, is common but Posix does not require its support, so it should be avoided in portable scripts. Similarly, ‘`\+`’ and ‘`\?`’ should be avoided.

Portable `expr` regular expressions should not begin with ‘`^`’. Patterns are automatically anchored so leading ‘`^`’ is not needed anyway.

The Posix standard is ambiguous as to whether ‘`expr 'a' : '\(b\)''`’ outputs ‘`0`’ or the empty string. In practice, it outputs the empty string on most platforms, but portable scripts should not assume this. For instance, the QNX 4.25 native `expr` returns ‘`0`’.

One might think that a way to get a uniform behavior would be to use the empty string as a default value:

```
expr a : '\(b\)' \| ''
```

Unfortunately this behaves exactly as the original expression; see the `expr` (‘`|`’) entry for more information.

Some ancient `expr` implementations (e.g., SunOS 4 `expr` and Solaris 8 `/usr/ucb/expr`) have a silly length limit that causes `expr` to fail if the matched substring is longer than 120 bytes. In this case, you might want to fall back on ‘`echo|sed`’ if `expr` fails. Nowadays this is of practical importance only for the rare installer who mistakenly puts ‘`/usr/ucb`’ before ‘`/usr/bin`’ in `PATH`.

On Mac OS X 10.4, `expr` mishandles the pattern ‘`[^-]`’ in some cases. For example, the command

```
expr Xpowerpc-apple-darwin8.1.0 : 'X[^-]*-[^-]*-\(.*\)'
```

outputs ‘`apple-darwin8.1.0`’ rather than the correct ‘`darwin8.1.0`’. This particular case can be worked around by substituting ‘`[^--]`’ for ‘`[^-]`’.

Don't leave, there is some more!

The QNX 4.25 `expr`, in addition of preferring ‘`0`’ to the empty string, has a funny behavior in its exit status: it's always 1 when parentheses are used!

```
$ val=`expr 'a' : 'a'`; echo "$?: $val"
0: 1
$ val=`expr 'a' : 'b'`; echo "$?: $val"
```

```
1: 0

$ val=`expr 'a' : '\(a\)'`; echo "?: $val"
1: a
$ val=`expr 'a' : '\(b\)'`; echo "?: $val"
1: 0
```

In practice this can be a big problem if you are ready to catch failures of `expr` programs with some other method (such as using `sed`), since you may get twice the result. For instance

```
$ expr 'a' : '\(a\)' || echo 'a' | sed 's/^\(a\)$/\1/'
```

outputs '`a`' on most hosts, but '`aa`' on QNX 4.25. A simple workaround consists of testing `expr` and using a variable set to `expr` or to `false` according to the result.

Tru64 `expr` incorrectly treats the result as a number, if it can be interpreted that way:

```
$ expr 00001 : '.*\(...\)'
1
```

`fgrep` Posix 1003.1-2001 no longer requires `fgrep`, but many hosts do not yet support the Posix replacement `grep -F`. Also, some traditional implementations do not work on long input lines. To work around these problems, invoke `AC_PROG_FGREP` and then use `$FGREP`.

`find` The option '`-maxdepth`' seems to be GNU specific. Tru64 v5.1, NetBSD 1.5 and Solaris `find` commands do not understand it.

The replacement of '`{}`' is guaranteed only if the argument is exactly `{}`, not if it's only a part of an argument. For instance on DU, and HP-UX 10.20 and HP-UX 11:

```
$ touch foo
$ find . -name foo -exec echo "{}-{}" \;
{}-{}
```

while GNU `find` reports '`./foo-./foo`'.

`grep` Portable scripts can rely on the `grep` options '`-c`', '`-l`', '`-n`', and '`-v`', but should avoid other options. For example, don't use '`-w`', as Posix does not require it and Irix 6.5.16m's `grep` does not support it. Also, portable scripts should not combine '`-c`' with '`-l`', as Posix does not allow this.

Some of the options required by Posix are not portable in practice. Don't use '`grep -q`' to suppress output, because many `grep` implementations (e.g., Solaris) do not support '`-q`'. Don't use '`grep -s`' to suppress output either, because Posix says '`-s`' does not suppress output, only some error messages; also, the '`-s`' option of traditional `grep` behaved like '`-q`' does in most modern implementations. Instead, redirect the standard output and standard error (in case the file doesn't exist) of `grep` to '`/dev/null`'. Check the exit status of `grep` to determine whether it found a match.

Some traditional `grep` implementations do not work on long input lines. On AIX the default `grep` silently truncates long lines on the input before matching.

Also, many implementations do not support multiple regexps with '`-e`': they either reject '`-e`' entirely (e.g., Solaris) or honor only the last pattern (e.g., IRIX 6.5 and NeXT). To work around these problems, invoke `AC_PROG_GREP` and then use `$GREP`.

Another possible workaround for the multiple '`-e`' problem is to separate the patterns by newlines, for example:

```
grep 'foo
bar' in.txt
```

except that this fails with traditional `grep` implementations and with OpenBSD 3.8 `grep`.

Traditional `grep` implementations (e.g., Solaris) do not support the '`-E`' or '`-F`' options. To work around these problems, invoke `AC_PROG_EGREP` and then use `$EGREP`, and similarly for `AC_PROG_FGREP` and `$FGREP`. Even if you are willing to require support for Posix `grep`, your script should not use both '`-E`' and '`-F`', since Posix does not allow this combination.

Portable `grep` regular expressions should use '`\`' only to escape characters in the string '`$()*.0123456789[\^{}`'. For example, alternation, '`\|`', is common but Posix does not require its support in basic regular expressions, so it should be avoided in portable scripts. Solaris and HP-UX `grep` do not support it. Similarly, the following escape sequences should also be avoided: '`\<`', '`\>`', '`\+`', '`\?`', '`\‘`', '`\’`', '`\B`', '`\b`', '`\S`', '`\s`', '`\W`', and '`\w`'.

Posix does not specify the behavior of `grep` on binary files. An example where this matters is using BSD `grep` to search text that includes embedded ANSI escape sequences for colored output to terminals ('`\033[m`' is the sequence to restore normal output); the behavior depends on whether input is seekable:

```
$ printf 'esc\033[mape\n' > sample
$ grep . sample
Binary file sample matches
$ cat sample | grep .
escape
```

`join` Solaris 8 `join` has bugs when the second operand is standard input, and when standard input is a pipe. For example, the following shell script causes Solaris 8 `join` to loop forever:

```
cat >file <<'EOF'
1 x
2 y
EOF
cat file | join file -
```

Use '`join - file`' instead.

`ln` Don't rely on `ln` having a '`-f`' option. Symbolic links are not available on old systems; use '`$(LN_S)`' as a portable substitute.

For versions of the DJGPP before 2.04, `ln` emulates symbolic links to executables by generating a stub that in turn calls the real program. This feature also works with nonexistent files like in the Posix spec. So '`ln -s file link`' generates

'`link.exe`', which attempts to call '`file.exe`' if run. But this feature only works for executables, so '`cp -p`' is used instead for these systems. DJGPP versions 2.04 and later have full support for symbolic links.

`ls` The portable options are '`-acdilrtu`'. Current practice is for '`-l`' to output both owner and group, even though ancient versions of `ls` omitted the group.

On ancient hosts, '`ls foo`' sent the diagnostic '`foo not found`' to standard output if '`foo`' did not exist. Hence a shell command like '`sources=`ls *.c 2>/dev/null`'' did not always work, since it was equivalent to '`sources='*.c not found''` in the absence of '`.c`' files. This is no longer a practical problem, since current `ls` implementations send diagnostics to standard error.

`mkdir` No `mkdir` option is portable to older systems. Instead of '`mkdir -p` *file-name*', you should use `AS_MKDIR_P(`*file-name*`)` (see Section 8.4 [Programming in M4sh], page 141) or `AC_PROG_MKDIR_P` (see Section 5.2.1 [Particular Programs], page 41).

Combining the '`-m`' and '`-p`' options, as in '`mkdir -m go-w -p` *dir*', often leads to trouble. FreeBSD `mkdir` incorrectly attempts to change the permissions of *dir* even if it already exists. HP-UX 11.23 and IRIX 6.5 `mkdir` often assign the wrong permissions to any newly-created parents of *dir*.

Posix does not clearly specify whether '`mkdir -p foo`' should succeed when '`foo`' is a symbolic link to an already-existing directory. The GNU Core Utilities 5.1.0 `mkdir` succeeds, but Solaris `mkdir` fails.

Traditional `mkdir -p` implementations suffer from race conditions. For example, if you invoke `mkdir -p a/b` and `mkdir -p a/c` at the same time, both processes might detect that '`a`' is missing, one might create '`a`', then the other might try to create '`a`' and fail with a `File exists` diagnostic. The GNU Core Utilities ('`fileutils`' version 4.1), FreeBSD 5.0, NetBSD 2.0.2, and OpenBSD 2.4 are known to be race-free when two processes invoke `mkdir -p` simultaneously, but earlier versions are vulnerable. Solaris `mkdir` is still vulnerable as of Solaris 10, and other traditional Unix systems are probably vulnerable too. This possible race is harmful in parallel builds when several Make rules call `mkdir -p` to construct directories. You may use `install-sh -d` as a safe replacement, provided this script is recent enough; the copy shipped with Autoconf 2.60 and Automake 1.10 is OK, but copies from older versions are vulnerable.

`mktemp` Shell scripts can use temporary files safely with `mktemp`, but it does not exist on all systems. A portable way to create a safe temporary file name is to create a temporary directory with mode 700 and use a file inside this directory. Both methods prevent attackers from gaining control, though `mktemp` is far less likely to fail gratuitously under attack.

Here is sample code to create a new temporary directory safely:

```
# Create a temporary directory $tmp in $TMPDIR (default /tmp).
# Use mktemp if possible; otherwise fall back on mkdir,
# with $RANDOM to make collisions less likely.
: ${TMPDIR=/tmp}
{
```

```
    tmp=`
      (umask 077 && mktemp -d "$TMPDIR/fooXXXXXX") 2>/dev/null
    ` &&
    test -n "$tmp" && test -d "$tmp"
  } || {
    tmp=$TMPDIR/foo$$-$RANDOM
    (umask 077 && mkdir "$tmp")
  } || exit $?
```

`mv` The only portable options are '`-f`' and '`-i`'.

Moving individual files between file systems is portable (it was in Unix version 6), but it is not always atomic: when doing '`mv new existing`', there's a critical section where neither the old nor the new version of '`existing`' actually exists.

On some systems moving files from '`/tmp`' can sometimes cause undesirable (but perfectly valid) warnings, even if you created these files. This is because '`/tmp`' belongs to a group that ordinary users are not members of, and files created in '`/tmp`' inherit the group of '`/tmp`'. When the file is copied, `mv` issues a diagnostic without failing:

```
$ touch /tmp/foo
$ mv /tmp/foo .
error mv: ./foo: set owner/group (was: 100/0): Operation not permitted
$ echo $?
0
$ ls foo
foo
```

This annoying behavior conforms to Posix, unfortunately.

Moving directories across mount points is not portable, use `cp` and `rm`.

DOS variants cannot rename or remove open files, and do not support commands like '`mv foo bar >foo`', even though this is perfectly portable among Posix hosts.

`od`

In Mac OS X 10.3, `od` does not support the standard Posix options '`-A`', '`-j`', '`-N`', or '`-t`', or the XSI option '`-s`'. The only supported Posix option is '`-v`', and the only supported XSI options are those in '`-bcdox`'. The BSD `hexdump` program can be used instead.

This problem no longer exists in Mac OS X 10.4.3.

`rm` The '`-f`' and '`-r`' options are portable.

It is not portable to invoke `rm` without operands. For example, on many systems '`rm -f -r`' (with no other arguments) silently succeeds without doing anything, but it fails with a diagnostic on NetBSD 2.0.2.

A file might not be removed even if its parent directory is writable and searchable. Many Posix hosts cannot remove a mount point, a named stream, a working directory, or a last link to a file that is being executed.

DOS variants cannot rename or remove open files, and do not support commands like '`rm foo >foo`', even though this is perfectly portable among Posix hosts.

`sed`

Patterns should not include the separator (unless escaped), even as part of a character class. In conformance with Posix, the Cray `sed` rejects '`s/[^/]*$//`': use '`s,[^/]*$,,`'.

Avoid empty patterns within parentheses (i.e., '`\(\)`'). Posix does not require support for empty patterns, and Unicos 9 `sed` rejects them.

Unicos 9 `sed` loops endlessly on patterns like '`.*\n.*`'.

Sed scripts should not use branch labels longer than 7 characters and should not contain comments. HP-UX sed has a limit of 99 commands (not counting '`:`' commands) and 48 labels, which can not be circumvented by using more than one script file. It can execute up to 19 reads with the '`r`' command per cycle. Solaris `/usr/ucb/sed` rejects usages that exceed an limit of about 6000 bytes for the internal representation of commands.

Avoid redundant '`;`', as some `sed` implementations, such as NetBSD 1.4.2's, incorrectly try to interpret the second '`;`' as a command:

```
$ echo a | sed 's/x/x/;;s/x/x/'
sed: 1: "s/x/x/;;s/x/x/": invalid command code ;
```

Input should not have unreasonably long lines, since some `sed` implementations have an input buffer limited to 4000 bytes.

Portable `sed` regular expressions should use '`\`' only to escape characters in the string '`$()*.0123456789[\^n{}`'. For example, alternation, '`\|`', is common but Posix does not require its support, so it should be avoided in portable scripts. Solaris `sed` does not support alternation; e.g., '`sed '/a\|b/d'`' deletes only lines that contain the literal string '`a|b`'. Similarly, '`\+`' and '`\?`' should be avoided.

Anchors ('`^`' and '`$`') inside groups are not portable.

Nested parentheses in patterns (e.g., '`\(\(a*\)b*)\)`') are quite portable to current hosts, but was not supported by some ancient `sed` implementations like SVR3.

Some `sed` implementations, e.g., Solaris, restrict the special role of the asterisk to one-character regular expressions. This may lead to unexpected behavior:

```
$ echo '1*23*4' | /usr/bin/sed 's/\(.\)*/x/g'
x2x4
$ echo '1*23*4' | /usr/xpg4/bin/sed 's/\(.\)*/x/g'
x
```

The '`-e`' option is mostly portable. However, its argument cannot start with '`a`', '`c`', or '`i`', as this runs afoul of a Tru64 5.1 bug. Also, its argument cannot be empty, as this fails on AIX 5.3. Some people prefer to use '`-e`':

```
sed -e 'command-1' \
    -e 'command-2'
```

as opposed to the equivalent:

```
sed '
  command-1
  command-2
'
```

The following usage is sometimes equivalent:

```
sed 'command-1;command-2'
```

but Posix says that this use of a semicolon has undefined effect if *command-1*'s verb is '`{`', '`a`', '`b`', '`c`', '`i`', '`r`', '`t`', '`w`', '`:`', or '`#`', so you should use semicolon only with simple scripts that do not use these verbs.

Commands inside `{ }` brackets are further restricted. Posix says that they cannot be preceded by addresses, '`!`', or '`;`', and that each command must be followed immediately by a newline, without any intervening blanks or semicolons. The closing bracket must be alone on a line, other than white space preceding or following it.

Contrary to yet another urban legend, you may portably use '`&`' in the replacement part of the `s` command to mean "what was matched". All descendants of Unix version 7 `sed` (at least; we don't have first hand experience with older `sed` implementations) have supported it.

Posix requires that you must not have any white space between '`!`' and the following command. It is OK to have blanks between the address and the '`!`'. For instance, on Solaris:

```
$ echo "foo" | sed -n '/bar/ ! p'
error Unrecognized command: /bar/ ! p
$ echo "foo" | sed -n '/bar/! p'
error Unrecognized command: /bar/! p
$ echo "foo" | sed -n '/bar/ !p'
foo
```

Posix also says that you should not combine '`!`' and '`;`'. If you use '`!`', it is best to put it on a command that is delimited by newlines rather than '`;`'.

Also note that Posix requires that the '`b`', '`t`', '`r`', and '`w`' commands be followed by exactly one space before their argument. On the other hand, no white space is allowed between '`:`' and the subsequent label name.

If a sed script is specified on the command line and ends in an '`a`', '`c`', or '`i`' command, the last line of inserted text should be followed by a newline. Otherwise some `sed` implementations (e.g., OpenBSD 3.9) do not append a newline to the inserted text.

Many `sed` implementations (e.g., MacOS X 10.4, OpenBSD 3.9, Solaris 10 `/usr/ucb/sed`) strip leading white space from the text of '`a`', '`c`', and '`i`' commands. Prepend a backslash to work around this incompatibility with Posix:

```
$ echo flushleft | sed 'a\
>    indented
> '
flushleft
indented
$ echo foo | sed 'a\
> \   indented
> '
flushleft
   indented
```

Posix requires that with an empty regular expression, the last non-empty regular expression from either an address specification or substitution command is applied. However, busybox 1.6.1 complains when using a substitution command with a replacement containing a back-reference to an empty regular expression; the workaround is repeating the regular expression.

```
$ echo abc | busybox sed '/a\(b\)c/ s//\1/'
sed: No previous regexp.
$ echo abc | busybox sed '/a\(b\)c/ s/a\(b\)c/\1/'
b
```

`sed` (‘`t`’) Some old systems have `sed` that “forget” to reset their ‘`t`’ flag when starting a new cycle. For instance on MIPS RISC/OS, and on IRIX 5.3, if you run the following `sed` script (the line numbers are not actual part of the texts):

```
s/keep me/kept/g  # a
t end             # b
s/.*/deleted/g    # c
:end              # d
```

on

```
delete me         # 1
delete me         # 2
keep me           # 3
delete me         # 4
```

you get

```
deleted
delete me
kept
deleted
```

instead of

```
deleted
deleted
kept
deleted
```

Why? When processing line 1, (c) matches, therefore sets the ‘`t`’ flag, and the output is produced. When processing line 2, the ‘`t`’ flag is still set (this is the bug). Command (a) fails to match, but `sed` is not supposed to clear the ‘`t`’ flag when a substitution fails. Command (b) sees that the flag is set, therefore it clears it, and jumps to (d), hence you get ‘`delete me`’ instead of ‘`deleted`’. When processing line (3), ‘`t`’ is clear, (a) matches, so the flag is set, hence (b) clears the flags and jumps. Finally, since the flag is clear, line 4 is processed properly.

There are two things one should remember about ‘`t`’ in `sed`. Firstly, always remember that ‘`t`’ jumps if *some* substitution succeeded, not only the immediately preceding substitution. Therefore, always use a fake ‘`t clear`’ followed by a ‘`:clear`’ on the next line, to reset the ‘`t`’ flag where needed.

Secondly, you cannot rely on `sed` to clear the flag at each new cycle.

One portable implementation of the script above is:

```
t clear
:clear
s/keep me/kept/g
t end
s/.*/deleted/g
:end
```

`touch` If you specify the desired timestamp (e.g., with the '`-r`' option), `touch` typically uses the `utime` or `utimes` system call, which can result in the same kind of timestamp truncation problems that '`cp -p`' has.

On ancient BSD systems, `touch` or any command that results in an empty file does not update the timestamps, so use a command like `echo` as a workaround. Also, GNU `touch` 3.16r (and presumably all before that) fails to work on SunOS 4.1.3 when the empty file is on an NFS-mounted 4.2 volume. However, these problems are no longer of practical concern.

11 Portable Make Programming

Writing portable makefiles is an art. Since a makefile's commands are executed by the shell, you must consider the shell portability issues already mentioned. However, other issues are specific to `make` itself.

11.1 $< in Ordinary Make Rules

Posix says that the '`$<`' construct in makefiles can be used only in inference rules and in the '`.DEFAULT`' rule; its meaning in ordinary rules is unspecified. Solaris `make` for instance replaces it with the empty string. OpenBSD (3.0 and later) `make` diagnoses these uses and errors out.

11.2 Failure in Make Rules

Since 1992 Posix has required that `make` must invoke each command with the equivalent of a '`sh -c`' subshell. However, many `make` implementations, including BSD make through 2004, use '`sh -e -c`' instead, and the '`-e`' option causes the subshell to exit immediately if a subsidiary simple-command fails. For example, the command '`touch T; rm -f U`' always attempts to remove '`U`' with Posix make, but incompatible `make` implementations skip the `rm` if the `touch` fails. One way to work around this is to reword the affected simple-commands so that they always succeed, e.g., '`touch T || :; rm -f U`'. However, even this approach can run into common bugs in BSD implementations of the '`-e`' option of `sh` and `set` (see Section 10.12 [Limitations of Builtins], page 173), so if you are worried about porting to buggy BSD shells it may be simpler to migrate complicated `make` actions into separate scripts.

11.3 Special Characters in Make Macro Names

Posix limits macro names to nonempty strings containing only ASCII letters and digits, '`.`', and '`_`'. Many `make` implementations allow a wider variety of characters, but portable makefiles should avoid them. It is portable to start a name with a special character, e.g., '`$(.FOO)`'.

Some ancient `make` implementations don't support leading underscores in macro names. An example is NEWS-OS 4.2R.

```
$ cat Makefile
_am_include = #
_am_quote =
all:; @echo this is test
$ make
Make: Must be a separator on rules line 2.  Stop.
$ cat Makefile2
am_include = #
am_quote =
all:; @echo this is test
$ make -f Makefile2
this is test
```

However, this problem is no longer of practical concern.

11.4 Backslash-Newline-Newline in Make Macro Values

On some versions of HP-UX, `make` reads multiple newlines following a backslash, continuing to the next non-empty line. For example,

```
FOO = one \

BAR = two

test:
        : FOO is "$(FOO)"
        : BAR is "$(BAR)"
```

shows `FOO` equal to `one BAR = two`. Other implementations sensibly let a backslash continue only to the immediately following line.

11.5 Backslash-Newline in Make Comments

According to Posix, Make comments start with `#` and continue until an unescaped newline is reached.

```
$ cat Makefile
# A = foo \
      bar \
      baz

all:
        @echo ok
$ make   # GNU make
ok
```

However this is not always the case. Some implementations discard everything from `#` through the end of the line, ignoring any trailing backslash.

```
$ pmake  # BSD make
"Makefile", line 3: Need an operator
Fatal errors encountered -- cannot continue
```

Therefore, if you want to comment out a multi-line definition, prefix each line with `#`, not only the first.

```
# A = foo \
#     bar \
#     baz
```

11.6 Long Lines in Makefiles

Tru64 5.1's `make` has been reported to crash when given a makefile with lines longer than around 20 kB. Earlier versions are reported to exit with `Line too long` diagnostics.

11.7 `make macro=value` and Submakes

A command-line variable definition such as `foo=bar` overrides any definition of `foo` in a makefile. Some `make` implementations (such as GNU `make`) propagate this override to

subsidiary invocations of `make`. Some other implementations do not pass the substitution along to submakes.

```
$ cat Makefile
foo = foo
one:
        @echo $(foo)
        $(MAKE) two
two:
        @echo $(foo)
$ make foo=bar            # GNU make 3.79.1
bar
make two
make[1]: Entering directory '/home/adl'
bar
make[1]: Leaving directory '/home/adl'
$ pmake foo=bar           # BSD make
bar
pmake two
foo
```

You have a few possibilities if you do want the `foo=bar` override to propagate to submakes. One is to use the '`-e`' option, which causes all environment variables to have precedence over the makefile macro definitions, and declare foo as an environment variable:

```
$ env foo=bar make -e
```

The '`-e`' option is propagated to submakes automatically, and since the environment is inherited between `make` invocations, the `foo` macro is overridden in submakes as expected.

This syntax (`foo=bar make -e`) is portable only when used outside of a makefile, for instance from a script or from the command line. When run inside a `make` rule, GNU `make` 3.80 and prior versions forget to propagate the '`-e`' option to submakes.

Moreover, using '`-e`' could have unexpected side effects if your environment contains some other macros usually defined by the makefile. (See also the note about `make -e` and `SHELL` below.)

Another way to propagate overrides to submakes is to do it manually, from your makefile:

```
foo = foo
one:
        @echo $(foo)
        $(MAKE) foo=$(foo) two
two:
        @echo $(foo)
```

You need to foresee all macros that a user might want to override if you do that.

11.8 The Make Macro MAKEFLAGS

Posix requires `make` to use `MAKEFLAGS` to affect the current and recursive invocations of make, but allows implementations several formats for the variable. It is tricky to parse `$MAKEFLAGS` to determine whether '`-s`' for silent execution or '`-k`' for continued execution are

in effect. For example, you cannot assume that the first space-separated word in `$MAKEFLAGS` contains single-letter options, since in the Cygwin version of GNU `make` it is either '`--unix`' or '`--win32`' with the second word containing single-letter options.

```
$ cat Makefile
all:
        @echo MAKEFLAGS = $(MAKEFLAGS)
$ make
MAKEFLAGS = --unix
$ make -k
MAKEFLAGS = --unix -k
```

11.9 The Make Macro SHELL

Posix-compliant `make` internally uses the `$(SHELL)` macro to spawn shell processes and execute Make rules. This is a builtin macro supplied by `make`, but it can be modified by a makefile or by a command-line argument.

Not all `make` implementations define this `SHELL` macro. Tru64 `make` is an example; this implementation always uses `/bin/sh`. So it's a good idea to always define `SHELL` in your makefiles. If you use Autoconf, do

```
SHELL = @SHELL@
```

Do not force `SHELL = /bin/sh` because that is not correct everywhere. For instance DJGPP lacks `/bin/sh`, and when its GNU `make` port sees such a setting it enters a special emulation mode where features like pipes and redirections are emulated on top of DOS's `command.com`. Unfortunately this emulation is incomplete; for instance it does not handle command substitutions. On DJGPP `SHELL` should point to Bash.

Posix-compliant `make` should never acquire the value of $(SHELL) from the environment, even when `make -e` is used (otherwise, think about what would happen to your rules if `SHELL=/bin/tcsh`).

However not all `make` implementations have this exception. For instance it's not surprising that Tru64 `make` doesn't protect `SHELL`, since it doesn't use it.

```
$ cat Makefile
SHELL = /bin/sh
FOO = foo
all:
        @echo $(SHELL)
        @echo $(FOO)
$ env SHELL=/bin/tcsh FOO=bar make -e   # Tru64 Make
/bin/tcsh
bar
$ env SHELL=/bin/tcsh FOO=bar gmake -e  # GNU make
/bin/sh
bar
```

11.10 Comments in Make Rules

Never put comments in a rule.

Some `make` treat anything starting with a tab as a command for the current rule, even if the tab is immediately followed by a `#`. The `make` from Tru64 Unix V5.1 is one of them. The following makefile runs `# foo` through the shell.

```
all:
        # foo
```

11.11 The '`obj/`' Subdirectory and Make

Never name one of your subdirectories '`obj/`' if you don't like surprises.

If an '`obj/`' directory exists, BSD `make` enters it before reading the makefile. Hence the makefile in the current directory is not read.

```
$ cat Makefile
all:
        echo Hello
$ cat obj/Makefile
all:
        echo World
$ make      # GNU make
echo Hello
Hello
$ pmake     # BSD make
echo World
World
```

11.12 Exit Status of `make -k`

Do not rely on the exit status of `make -k`. Some implementations reflect whether they encountered an error in their exit status; other implementations always succeed.

```
$ cat Makefile
all:
        false
$ make -k; echo exit status: $?    # GNU make
false
make: *** [all] Error 1
exit status: 2
$ pmake -k; echo exit status: $?   # BSD make
false
*** Error code 1 (continuing)
exit status: 0
```

11.13 `VPATH` and Make

Posix does not specify the semantics of `VPATH`. Typically, `make` supports `VPATH`, but its implementation is not consistent.

Autoconf and Automake support makefiles whose usages of `VPATH` are portable to recent-enough popular implementations of `make`, but to keep the resulting makefiles portable, a package's makefile prototypes must take the following issues into account. These issues are

complicated and are often poorly understood, and installers who use VPATH should expect to find many bugs in this area. If you use VPATH, the simplest way to avoid these portability bugs is to stick with GNU make, since it is the most commonly-used make among Autoconf users.

Here are some known issues with some VPATH implementations.

11.13.1 VPATH and Double-colon Rules

With ancient versions of Sun make, any assignment to VPATH causes make to execute only the first set of double-colon rules. However, this problem is no longer of practical concern.

11.13.2 $< Not Supported in Explicit Rules

Using $< in explicit rules is not portable. The prerequisite file must be named explicitly in the rule. If you want to find the prerequisite via a VPATH search, you have to code the whole thing manually. See Section 4.8.4 [Build Directories], page 30.

11.13.3 Automatic Rule Rewriting

Some make implementations, such as Solaris and Tru64, search for prerequisites in VPATH and then rewrite each occurrence as a plain word in the rule. For instance:

```
# This isn't portable to GNU make.
VPATH = ../pkg/src
f.c: if.c
        cp if.c f.c
```

executes cp ../pkg/src/if.c f.c if 'if.c' is found in '../pkg/src'.

However, this rule leads to real problems in practice. For example, if the source directory contains an ordinary file named 'test' that is used in a dependency, Solaris make rewrites commands like 'if test -r foo; ...' to 'if ../pkg/src/test -r foo; ...', which is typically undesirable. To avoid this problem, portable makefiles should never mention a source file whose name is that of a shell keyword like 'until' or a shell command like cat or gcc or test.

Because of these problems GNU make and many other make implementations do not rewrite commands, so portable makefiles should search VPATH manually. It is tempting to write this:

```
# This isn't portable to Solaris make.
VPATH = ../pkg/src
f.c: if.c
        cp `test -f if.c || echo $(VPATH)/`if.c f.c
```

However, the "prerequisite rewriting" still applies here. So if 'if.c' is in '../pkg/src', Solaris and Tru64 make execute

```
cp `test -f ../pkg/src/if.c || echo ../pkg/src/`if.c f.c
```

which reduces to

```
cp if.c f.c
```

and thus fails. Oops.

A simple workaround, and good practice anyway, is to use '$?' and '$@' when possible:

```
VPATH = ../pkg/src
f.c: if.c
```

```
        cp $? $@
```

but this does not generalize well to commands with multiple prerequisites. A more general workaround is to rewrite the rule so that the prerequisite '`if.c`' never appears as a plain word. For example, these three rules would be safe, assuming '`if.c`' is in '`../pkg/src`' and the other files are in the working directory:

```
VPATH = ../pkg/src
f.c: if.c f1.c
        cat `test -f ./if.c || echo $(VPATH)/`if.c f1.c >$@
g.c: if.c g1.c
        cat `test -f 'if.c' || echo $(VPATH)/`if.c g1.c >$@
h.c: if.c h1.c
        cat `test -f "if.c" || echo $(VPATH)/`if.c h1.c >$@
```

Things get worse when your prerequisites are in a macro.

```
VPATH = ../pkg/src
HEADERS = f.h g.h h.h
install-HEADERS: $(HEADERS)
        for i in $(HEADERS); do \
          $(INSTALL) -m 644 \
            `test -f $$i || echo $(VPATH)/`$$i \
            $(DESTDIR)$(includedir)/$$i; \
        done
```

The above `install-HEADERS` rule is not Solaris-proof because `for i in $(HEADERS);` is expanded to `for i in f.h g.h h.h;` where `f.h` and `g.h` are plain words and are hence subject to `VPATH` adjustments.

If the three files are in '`../pkg/src`', the rule is run as:

```
for i in ../pkg/src/f.h ../pkg/src/g.h h.h; do \
  install -m 644 \
     `test -f $i || echo ../pkg/src/`$i \
     /usr/local/include/$i; \
done
```

where the two first `install` calls fail. For instance, consider the `f.h` installation:

```
install -m 644 \
  `test -f ../pkg/src/f.h || \
    echo ../pkg/src/ \
  `../pkg/src/f.h \
  /usr/local/include/../pkg/src/f.h;
```

It reduces to:

```
install -m 644 \
  ../pkg/src/f.h \
  /usr/local/include/../pkg/src/f.h;
```

Note that the manual `VPATH` search did not cause any problems here; however this command installs '`f.h`' in an incorrect directory.

Trying to quote `$(HEADERS)` in some way, as we did for `foo.c` a few makefiles ago, does not help:

```
install-HEADERS: $(HEADERS)
        headers='$(HEADERS)'; \
        for i in $$headers; do \
          $(INSTALL) -m 644 \
            `test -f $$i || echo $(VPATH)/`$$i \
            $(DESTDIR)$(includedir)/$$i; \
        done
```

Now, `headers='$(HEADERS)'` macro-expands to:

```
headers='f.h g.h h.h'
```

but `g.h` is still a plain word. (As an aside, the idiom `headers='$(HEADERS)'; for i in $$headers;` is a good idea if `$(HEADERS)` can be empty, because some shells diagnose a syntax error on `for i in;`.)

One workaround is to strip this unwanted '`../pkg/src/`' prefix manually:

```
VPATH = ../pkg/src
HEADERS = f.h g.h h.h
install-HEADERS: $(HEADERS)
        headers='$(HEADERS)'; \
        for i in $$headers; do \
          i=`expr "$$i" : '$(VPATH)/\(.*\)'`; \
          $(INSTALL) -m 644 \
            `test -f $$i || echo $(VPATH)/`$$i \
            $(DESTDIR)$(includedir)/$$i; \
        done
```

Automake does something similar. However the above hack works only if the files listed in `HEADERS` are in the current directory or a subdirectory; they should not be in an enclosing directory. If we had `HEADERS = ../f.h`, the above fragment would fail in a VPATH build with Tru64 `make`. The reason is that not only does Tru64 `make` rewrite dependencies, but it also simplifies them. Hence `../f.h` becomes `../pkg/f.h` instead of `../pkg/src/../f.h`. This obviously defeats any attempt to strip a leading '`../pkg/src/`' component.

The following example makes the behavior of Tru64 `make` more apparent.

```
$ cat Makefile
VPATH = sub
all: ../foo
        echo ../foo
$ ls
Makefile foo
$ make
echo foo
foo
```

Dependency '`../foo`' was found in '`sub/../foo`', but Tru64 `make` simplified it as '`foo`'. (Note that the '`sub/`' directory does not even exist, this just means that the simplification occurred before the file was checked for.)

For the record here is how SunOS 4 `make` behaves on this example.

```
$ make
make: Fatal error: Don't know how to make target `../foo'
```

```
$ mkdir sub
$ make
echo sub/../foo
sub/../foo
```

11.13.4 Tru64 make Creates Prerequisite Directories Magically

When a prerequisite is a subdirectory of VPATH, Tru64 make creates it in the current directory.

```
$ mkdir -p foo/bar build
$ cd build
$ cat >Makefile <<END
VPATH = ..
all: foo/bar
END
$ make
mkdir foo
mkdir foo/bar
```

This can yield unexpected results if a rule uses a manual VPATH search as presented before.

```
VPATH = ..
all : foo/bar
        command `test -d foo/bar || echo ../`foo/bar
```

The above command is run on the empty 'foo/bar' directory that was created in the current directory.

11.13.5 Make Target Lookup

GNU make uses a complex algorithm to decide when it should use files found via a VPATH search. See section "How Directory Searches are Performed" in *The GNU Make Manual*.

If a target needs to be rebuilt, GNU make discards the file name found during the VPATH search for this target, and builds the file locally using the file name given in the makefile. If a target does not need to be rebuilt, GNU make uses the file name found during the VPATH search.

Other make implementations, like NetBSD make, are easier to describe: the file name found during the VPATH search is used whether the target needs to be rebuilt or not. Therefore new files are created locally, but existing files are updated at their VPATH location.

OpenBSD and FreeBSD make, however, never perform a VPATH search for a dependency that has an explicit rule. This is extremely annoying.

When attempting a VPATH build for an autoconfiscated package (e.g., mkdir build && cd build && ../configure), this means GNU make builds everything locally in the 'build' directory, while BSD make builds new files locally and updates existing files in the source directory.

```
$ cat Makefile
VPATH = ..
all: foo.x bar.x
foo.x bar.x: newer.x
```

```
        @echo Building $@
$ touch ../bar.x
$ touch ../newer.x
$ make        # GNU make
Building foo.x
Building bar.x
$ pmake       # NetBSD make
Building foo.x
Building ../bar.x
$ fmake       # FreeBSD make, OpenBSD make
Building foo.x
Building bar.x
$ tmake       # Tru64 make
Building foo.x
Building bar.x
$ touch ../bar.x
$ make        # GNU make
Building foo.x
$ pmake       # NetBSD make
Building foo.x
$ fmake       # FreeBSD make, OpenBSD make
Building foo.x
Building bar.x
$ tmake       # Tru64 make
Building foo.x
Building bar.x
```

Note how NetBSD `make` updates '`../bar.x`' in its VPATH location, and how FreeBSD, OpenBSD, and Tru64 `make` always update '`bar.x`', even when '`../bar.x`' is up to date.

Another point worth mentioning is that once GNU `make` has decided to ignore a `VPATH` file name (e.g., it ignored '`../bar.x`' in the above example) it continues to ignore it when the target occurs as a prerequisite of another rule.

The following example shows that GNU `make` does not look up '`bar.x`' in `VPATH` before performing the `.x.y` rule, because it ignored the `VPATH` result of '`bar.x`' while running the `bar.x: newer.x` rule.

```
$ cat Makefile
VPATH = ..
all: bar.y
bar.x: newer.x
        @echo Building $@
.SUFFIXES: .x .y
.x.y:
        cp $< $@
$ touch ../bar.x
$ touch ../newer.x
$ make        # GNU make
Building bar.x
```

```
cp bar.x bar.y
cp: cannot stat ‘bar.x’: No such file or directory
make: *** [bar.y] Error 1
$ pmake       # NetBSD make
Building ../bar.x
cp ../bar.x bar.y
$ rm bar.y
$ fmake       # FreeBSD make, OpenBSD make
echo Building bar.x
cp bar.x bar.y
cp: cannot stat ‘bar.x’: No such file or directory
*** Error code 1
$ tmake       # Tru64 make
Building bar.x
cp: bar.x: No such file or directory
*** Exit 1
```

Note that if you drop away the command from the `bar.x: newer.x` rule, GNU `make` magically starts to work: it knows that `bar.x` hasn't been updated, therefore it doesn't discard the result from `VPATH` (‘`../bar.x`’) in succeeding uses. Tru64 also works, but FreeBSD and OpenBSD still don't.

```
$ cat Makefile
VPATH = ..
all: bar.y
bar.x: newer.x
.SUFFIXES: .x .y
.x.y:
        cp $< $@
$ touch ../bar.x
$ touch ../newer.x
$ make        # GNU make
cp ../bar.x bar.y
$ rm bar.y
$ pmake       # NetBSD make
cp ../bar.x bar.y
$ rm bar.y
$ fmake       # FreeBSD make, OpenBSD make
cp bar.x bar.y
cp: cannot stat ‘bar.x’: No such file or directory
*** Error code 1
$ tmake       # Tru64 make
cp ../bar.x bar.y
```

It seems the sole solution that would please every `make` implementation is to never rely on `VPATH` searches for targets. In other words, `VPATH` should be reserved to unbuilt sources.

11.14 Single Suffix Rules and Separated Dependencies

A *Single Suffix Rule* is basically a usual suffix (inference) rule ('`.from.to:`'), but which *destination* suffix is empty ('`.from:`').

Separated dependencies simply refers to listing the prerequisite of a target, without defining a rule. Usually one can list on the one hand side, the rules, and on the other hand side, the dependencies.

Solaris `make` does not support separated dependencies for targets defined by single suffix rules:

```
$ cat Makefile
.SUFFIXES: .in
foo: foo.in
.in:
        cp $< $@
$ touch foo.in
$ make
$ ls
Makefile  foo.in
```

while GNU Make does:

```
$ gmake
cp foo.in foo
$ ls
Makefile  foo       foo.in
```

Note it works without the '`foo: foo.in`' dependency.

```
$ cat Makefile
.SUFFIXES: .in
.in:
        cp $< $@
$ make foo
cp foo.in foo
```

and it works with double suffix inference rules:

```
$ cat Makefile
foo.out: foo.in
.SUFFIXES: .in .out
.in.out:
        cp $< $@
$ make
cp foo.in foo.out
```

As a result, in such a case, you have to write target rules.

11.15 Timestamp Resolution and Make

Traditionally, file timestamps had 1-second resolution, and `make` used those timestamps to determine whether one file was newer than the other. However, many modern file systems have timestamps with 1-nanosecond resolution. Some `make` implementations look at the entire timestamp; others ignore the fractional part, which can lead to incorrect results.

Normally this is not a problem, but in some extreme cases you may need to use tricks like '`sleep 1`' to work around timestamp truncation bugs.

Commands like '`cp -p`' and '`touch -r`' typically do not copy file timestamps to their full resolutions (see Section 10.13 [Limitations of Usual Tools], page 182). Hence you should be wary of rules like this:

```
dest: src
        cp -p src dest
```

as '`dest`' often appears to be older than '`src`' after the timestamp is truncated, and this can cause `make` to do needless rework the next time it is invoked. To work around this problem, you can use a timestamp file, e.g.:

```
dest-stamp: src
        cp -p src dest
        date >dest-stamp
```

12 Portable C and C++ Programming

C and C++ programs often use low-level features of the underlying system, and therefore are often more difficult to make portable to other platforms.

Several standards have been developed to help make your programs more portable. If you write programs with these standards in mind, you can have greater confidence that your programs work on a wide variety of systems. See section "Language Standards Supported by GCC" in *Using the GNU Compiler Collection (GCC)*, for a list of C-related standards. Many programs also assume the Posix standard (`http://www.opengroup.org/susv3`).

Some old code is written to be portable to K&R C, which predates any C standard. K&R C compilers are no longer of practical interest, though, and the rest of section assumes at least C89, the first C standard.

Program portability is a huge topic, and this section can only briefly introduce common pitfalls. See section "Portability between System Types" in *GNU Coding Standards*, for more information.

12.1 Varieties of Unportability

Autoconf tests and ordinary programs often need to test what is allowed on a system, and therefore they may need to deliberately exceed the boundaries of what the standards allow, if only to see whether an optional feature is present. When you write such a program, you should keep in mind the difference between constraints, unspecified behavior, and undefined behavior.

In C, a *constraint* is a rule that the compiler must enforce. An example constraint is that C programs must not declare a bit-field with negative width. Tests can therefore reliably assume that programs with negative-width bit-fields are rejected by a compiler that conforms to the standard.

Unspecified behavior is valid behavior, where the standard allows multiple possibilities. For example, the order of evaluation of function arguments is unspecified. Some unspecified behavior is *implementation-defined*, i.e., documented by the implementation, but since Autoconf tests cannot read the documentation they cannot distinguish between implementation-defined and other unspecified behavior. It is common for Autoconf tests to probe implementations to determine otherwise-unspecified behavior.

Undefined behavior is invalid behavior, where the standard allows the implementation to do anything it pleases. For example, dereferencing a null pointer leads to undefined behavior. If possible, test programs should avoid undefined behavior, since a program with undefined behavior might succeed on a test that should fail.

The above rules apply to programs that are intended to conform to the standard. However, strictly-conforming programs are quite rare, since the standards are so limiting. A major goal of Autoconf is to support programs that use implementation features not described by the standard, and it is fairly common for test programs to violate the above rules, if the programs work well enough in practice.

12.2 Integer Overflow

In practice many portable C programs assume that signed integer overflow wraps around reliably using two's complement arithmetic. Yet the C standard says that program behavior is undefined on overflow, and in a few cases C programs do not work on some modern implementations because their overflows do not wrap around as their authors expected. Conversely, in signed integer remainder, the C standard requires overflow behavior that is commonly not implemented.

12.2.1 Basics of Integer Overflow

In languages like C, unsigned integer overflow reliably wraps around; e.g., `UINT_MAX + 1` yields zero. This is guaranteed by the C standard and is portable in practice, unless you specify aggressive, nonstandard optimization options suitable only for special applications.

In contrast, the C standard says that signed integer overflow leads to undefined behavior where a program can do anything, including dumping core or overrunning a buffer. The misbehavior can even precede the overflow. Such an overflow can occur during addition, subtraction, multiplication, division, and left shift.

Despite this requirement of the standard, many C programs and Autoconf tests assume that signed integer overflow silently wraps around modulo a power of two, using two's complement arithmetic, so long as you cast the resulting value to a signed integer type or store it into a signed integer variable. If you use conservative optimization flags, such programs are generally portable to the vast majority of modern platforms, with a few exceptions discussed later.

For historical reasons the C standard also allows implementations with ones' complement or signed magnitude arithmetic, but it is safe to assume two's complement nowadays.

Also, overflow can occur when converting an out-of-range value to a signed integer type. Here a standard implementation must define what happens, but this might include raising an exception. In practice all known implementations support silent wraparound in this case, so you need not worry about other possibilities.

12.2.2 Examples of Code Assuming Wraparound Overflow

There has long been a tension between what the C standard requires for signed integer overflow, and what C programs commonly assume. The standard allows aggressive optimizations based on assumptions that overflow never occurs, but many practical C programs rely on overflow wrapping around. These programs do not conform to the standard, but they commonly work in practice because compiler writers are understandably reluctant to implement optimizations that would break many programs, unless perhaps a user specifies aggressive optimization.

The C Standard says that if a program has signed integer overflow its behavior is undefined, and the undefined behavior can even precede the overflow. To take an extreme example:

```
if (password == expected_password)
  allow_superuser_privileges ();
else if (counter++ == INT_MAX)
  abort ();
else
```

```
printf ("%d password mismatches\n", counter);
```

If the `int` variable `counter` equals `INT_MAX`, `counter++` must overflow and the behavior is undefined, so the C standard allows the compiler to optimize away the test against `INT_MAX` and the `abort` call. Worse, if an earlier bug in the program lets the compiler deduce that `counter == INT_MAX` or that `counter` previously overflowed, the C standard allows the compiler to optimize away the password test and generate code that allows superuser privileges unconditionally.

Despite this requirement by the standard, it has long been common for C code to assume wraparound arithmetic after signed overflow, and all known practical C implementations support some C idioms that assume wraparound signed arithmetic, even if the idioms do not conform strictly to the standard. If your code looks like the following examples it will almost surely work with real-world compilers.

Here is an example derived from the 7th Edition Unix implementation of `atoi` (1979-01-10):

```
char *p;
int f, n;
...
while (*p >= '0' && *p <= '9')
  n = n * 10 + *p++ - '0';
return (f ? -n : n);
```

Even if the input string is in range, on most modern machines this has signed overflow when computing the most negative integer (the `-n` overflows) or a value near an extreme integer (the first `+` overflows).

Here is another example, derived from the 7th Edition implementation of `rand` (1979-01-10). Here the programmer expects both multiplication and addition to wrap on overflow:

```
static long int randx = 1;
...
randx = randx * 1103515245 + 12345;
return (randx >> 16) & 077777;
```

In the following example, derived from the GNU C Library 2.5 implementation of `mktime` (2006-09-09), the code assumes wraparound arithmetic in `+` to detect signed overflow:

```
time_t t, t1, t2;
int sec_requested, sec_adjustment;
...
t1 = t + sec_requested;
t2 = t1 + sec_adjustment;
if (((t1 < t) != (sec_requested < 0))
    | ((t2 < t1) != (sec_adjustment < 0)))
  return -1;
```

If your code looks like these examples, it is probably safe even though it does not strictly conform to the C standard. This might lead one to believe that one can generally assume wraparound on overflow, but that is not always true, as can be seen in the next section.

12.2.3 Optimizations That Break Wraparound Arithmetic

Compilers sometimes generate code that is incompatible with wraparound integer arithmetic. A simple example is an algebraic simplification: a compiler might translate `(i * 2000) / 1000` to `i * 2` because it assumes that `i * 2000` does not overflow. The translation is not equivalent to the original when overflow occurs: e.g., in the typical case of 32-bit signed two's complement wraparound `int`, if `i` has type `int` and value `1073742`, the original expression returns −2147483 but the optimized version returns the mathematically correct value 2147484.

More subtly, loop induction optimizations often exploit the undefined behavior of signed overflow. Consider the following contrived function `sumc`:

```
int
sumc (int lo, int hi)
{
  int sum = 0;
  int i;
  for (i = lo; i <= hi; i++)
    sum ^= i * 53;
  return sum;
}
```

To avoid multiplying by 53 each time through the loop, an optimizing compiler might internally transform `sumc` to the equivalent of the following:

```
int
transformed_sumc (int lo, int hi)
{
  int sum = 0;
  int hic = hi * 53;
  int ic;
  for (ic = lo * 53; ic <= hic; ic += 53)
    sum ^= ic;
  return sum;
}
```

This transformation is allowed by the C standard, but it is invalid for wraparound arithmetic when `INT_MAX / 53 < hi`, because then the overflow in computing expressions like `hi * 53` can cause the expression `i <= hi` to yield a different value from the transformed expression `ic <= hic`.

For this reason, compilers that use loop induction and similar techniques often do not support reliable wraparound arithmetic when a loop induction variable like `ic` is involved. Since loop induction variables are generated by the compiler, and are not visible in the source code, it is not always trivial to say whether the problem affects your code.

Hardly any code actually depends on wraparound arithmetic in cases like these, so in practice these loop induction optimizations are almost always useful. However, edge cases in this area can cause problems. For example:

```
int j;
for (j = 1; 0 < j; j *= 2)
  test (j);
```

Here, the loop attempts to iterate through all powers of 2 that `int` can represent, but the C standard allows a compiler to optimize away the comparison and generate an infinite loop, under the argument that behavior is undefined on overflow. As of this writing this optimization is not done by any production version of GCC with '`-O2`', but it might be performed by other compilers, or by more aggressive GCC optimization options, and the GCC developers have not decided whether it will continue to work with GCC and '`-O2`'.

12.2.4 Practical Advice for Signed Overflow Issues

Ideally the safest approach is to avoid signed integer overflow entirely. For example, instead of multiplying two signed integers, you can convert them to unsigned integers, multiply the unsigned values, then test whether the result is in signed range.

Rewriting code in this way will be inconvenient, though, particularly if the signed values might be negative. Also, it may hurt performance. Using unsigned arithmetic to check for overflow is particularly painful to do portably and efficiently when dealing with an integer type like `uid_t` whose width and signedness vary from platform to platform.

Furthermore, many C applications pervasively assume wraparound behavior and typically it is not easy to find and remove all these assumptions. Hence it is often useful to maintain nonstandard code that assumes wraparound on overflow, instead of rewriting the code. The rest of this section attempts to give practical advice for this situation.

If your code wants to detect signed integer overflow in `sum = a + b`, it is generally safe to use an expression like `(sum < a) != (b < 0)`.

If your code uses a signed loop index, make sure that the index cannot overflow, along with all signed expressions derived from the index. Here is a contrived example of problematic code with two instances of overflow.

```
for (i = INT_MAX - 10; i <= INT_MAX; i++)
  if (i + 1 < 0)
    {
      report_overflow ();
      break;
    }
```

Because of the two overflows, a compiler might optimize away or transform the two comparisons in a way that is incompatible with the wraparound assumption.

If your code uses an expression like `(i * 2000) / 1000` and you actually want the multiplication to wrap around on overflow, use unsigned arithmetic to do it, e.g., `((int) (i * 2000u)) / 1000`.

If your code assumes wraparound behavior and you want to insulate it against any GCC optimizations that would fail to support that behavior, you should use GCC's '`-fwrapv`' option, which causes signed overflow to wrap around reliably (except for division and remainder, as discussed in the next section).

If you need to port to platforms where signed integer overflow does not reliably wrap around (e.g., due to hardware overflow checking, or to highly aggressive optimizations), you should consider debugging with GCC's '`-ftrapv`' option, which causes signed overflow to raise an exception.

12.2.5 Signed Integer Division and Integer Overflow

Overflow in signed integer division is not always harmless: for example, on CPUs of the i386 family, dividing `INT_MIN` by `-1` yields a SIGFPE signal which by default terminates the program. Worse, taking the remainder of these two values typically yields the same signal on these CPUs, even though the C standard requires `INT_MIN % -1` to yield zero because the expression does not overflow.

12.3 Preprocessor Arithmetic

In C99, preprocessor arithmetic, used for `#if` expressions, must be evaluated as if all signed values are of type `intmax_t` and all unsigned values of type `uintmax_t`. Many compilers are buggy in this area, though. For example, as of 2007, Sun C mishandles `#if LLONG_MIN < 0` on a platform with 32-bit `long int` and 64-bit `long long int`. Also, some older preprocessors mishandle constants ending in `LL`. To work around these problems, you can compute the value of expressions like `LONG_MAX < LLONG_MAX` at `configure`-time rather than at `#if`-time.

12.4 Properties of Null Pointers

Most modern hosts reliably fail when you attempt to dereference a null pointer.

On almost all modern hosts, null pointers use an all-bits-zero internal representation, so you can reliably use `memset` with 0 to set all the pointers in an array to null values.

If `p` is a null pointer to an object type, the C expression `p + 0` always evaluates to `p` on modern hosts, even though the standard says that it has undefined behavior.

12.5 Buffer Overruns and Subscript Errors

Buffer overruns and subscript errors are the most common dangerous errors in C programs. They result in undefined behavior because storing outside an array typically modifies storage that is used by some other object, and most modern systems lack runtime checks to catch these errors. Programs should not rely on buffer overruns being caught.

There is one exception to the usual rule that a portable program cannot address outside an array. In C, it is valid to compute the address just past an object, e.g., `&a[N]` where `a` has `N` elements, so long as you do not dereference the resulting pointer. But it is not valid to compute the address just before an object, e.g., `&a[-1]`; nor is it valid to compute two past the end, e.g., `&a[N+1]`. On most platforms `&a[-1] < &a[0] && &a[N] < &a[N+1]`, but this is not reliable in general, and it is usually easy enough to avoid the potential portability problem, e.g., by allocating an extra unused array element at the start or end.

Valgrind (`http://valgrind.org/`) can catch many overruns. GCC users might also consider using the '`-fmudflap`' option to catch overruns.

Buffer overruns are usually caused by off-by-one errors, but there are more subtle ways to get them.

Using `int` values to index into an array or compute array sizes causes problems on typical 64-bit hosts where an array index might be 2^31 or larger. Index values of type `size_t` avoid this problem, but cannot be negative. Index values of type `ptrdiff_t` are signed, and are wide enough in practice.

If you add or multiply two numbers to calculate an array size, e.g., `malloc (x * sizeof y + z)`, havoc ensues if the addition or multiplication overflows.

Many implementations of the `alloca` function silently misbehave and can generate buffer overflows if given sizes that are too large. The size limits are implementation dependent, but are at least 4000 bytes on all platforms that we know about.

The standard functions `asctime`, `asctime_r`, `ctime`, `ctime_r`, and `gets` are prone to buffer overflows, and portable code should not use them unless the inputs are known to be within certain limits. The time-related functions can overflow their buffers if given timestamps out of range (e.g., a year less than -999 or greater than 9999). Time-related buffer overflows cannot happen with recent-enough versions of the GNU C library, but are possible with other implementations. The `gets` function is the worst, since it almost invariably overflows its buffer when presented with an input line larger than the buffer.

12.6 Volatile Objects

The keyword `volatile` is often misunderstood in portable code. Its use inhibits some memory-access optimizations, but programmers often wish that it had a different meaning than it actually does.

`volatile` was designed for code that accesses special objects like memory-mapped device registers whose contents spontaneously change. Such code is inherently low-level, and it is difficult to specify portably what `volatile` means in these cases. The C standard says, "What constitutes an access to an object that has volatile-qualified type is implementation-defined," so in theory each implementation is supposed to fill in the gap by documenting what `volatile` means for that implementation. In practice, though, this documentation is usually absent or incomplete.

One area of confusion is the distinction between objects defined with volatile types, and volatile lvalues. From the C standard's point of view, an object defined with a volatile type has externally visible behavior. You can think of such objects as having little oscilloscope probes attached to them, so that the user can observe some properties of accesses to them, just as the user can observe data written to output files. However, the standard does not make it clear whether users can observe accesses by volatile lvalues to ordinary objects. For example:

```
/* Declare and access a volatile object.
   Accesses to X are "visible" to users.  */
static int volatile x;
x = 1;

/* Access two ordinary objects via a volatile lvalue.
   It's not clear whether accesses to *P are "visible".  */
int y;
int *z = malloc (sizeof (int));
int volatile *p;
p = &y;
*p = 1;
p = z;
*p = 1;
```

Programmers often wish that `volatile` meant "Perform the memory access here and now, without merging several memory accesses, without changing the memory word size, and without reordering." But the C standard does not require this. For objects defined with a volatile type, accesses must be done before the next sequence point; but otherwise merging, reordering, and word-size change is allowed. Worse, it is not clear from the standard whether volatile lvalues provide more guarantees in general than nonvolatile lvalues, if the underlying objects are ordinary.

Even when accessing objects defined with a volatile type, the C standard allows only extremely limited signal handlers: the behavior is undefined if a signal handler reads any nonlocal object, or writes to any nonlocal object whose type is not `sig_atomic_t volatile`, or calls any standard library function other than `abort`, `signal`, and (if C99) `_Exit`. Hence C compilers need not worry about a signal handler disturbing ordinary computation, unless the computation accesses a `sig_atomic_t volatile` lvalue that is not a local variable. (There is an obscure exception for accesses via a pointer to a volatile character, since it may point into part of a `sig_atomic_t volatile` object.) Posix adds to the list of library functions callable from a portable signal handler, but otherwise is like the C standard in this area.

Some C implementations allow memory-access optimizations within each translation unit, such that actual behavior agrees with the behavior required by the standard only when calling a function in some other translation unit, and a signal handler acts like it was called from a different translation unit. The C standard hints that in these implementations, objects referred to by signal handlers "would require explicit specification of `volatile` storage, as well as other implementation-defined restrictions." But unfortunately even for this special case these other restrictions are often not documented well. See section "When is a Volatile Object Accessed?" in *Using the GNU Compiler Collection (GCC)*, for some restrictions imposed by GCC. See section "Defining Signal Handlers" in *The GNU C Library*, for some restrictions imposed by the GNU C library. Restrictions differ on other platforms.

If possible, it is best to use a signal handler that fits within the limits imposed by the C and Posix standards.

If this is not practical, you can try the following rules of thumb. A signal handler should access only volatile lvalues, preferably lvalues that refer to objects defined with a volatile type, and should not assume that the accessed objects have an internally consistent state if they are larger than a machine word. Furthermore, installers should employ compilers and compiler options that are commonly used for building operating system kernels, because kernels often need more from `volatile` than the C Standard requires, and installers who compile an application in a similar environment can sometimes benefit from the extra constraints imposed by kernels on compilers. Admittedly we are handwaving somewhat here, as there are few guarantees in this area; the rules of thumb may help to fix some bugs but there is a good chance that they will not fix them all.

For `volatile`, C++ has the same problems that C does. Multithreaded applications have even more problems with `volatile`, but they are beyond the scope of this section.

The bottom line is that using `volatile` typically hurts performance but should not hurt correctness. In some cases its use does help correctness, but these cases are often so poorly understood that all too often adding `volatile` to a data structure merely alleviates some symptoms of a bug while not fixing the bug in general.

12.7 Floating Point Portability

Almost all modern systems use IEEE-754 floating point, and it is safe to assume IEEE-754 in most portable code these days. For more information, please see David Goldberg's classic paper What Every Computer Scientist Should Know About Floating-Point Arithmetic (`http://www.validlab.com/goldberg/paper.pdf`).

12.8 Exiting Portably

A C or C++ program can exit with status N by returning N from the `main` function. Portable programs are supposed to exit either with status 0 or `EXIT_SUCCESS` to succeed, or with status `EXIT_FAILURE` to fail, but in practice it is portable to fail by exiting with status 1, and test programs that assume Posix can fail by exiting with status values from 1 through 255. Programs on SunOS 2.0 (1985) through 3.5.2 (1988) incorrectly exited with zero status when `main` returned nonzero, but ancient systems like these are no longer of practical concern.

A program can also exit with status N by passing N to the `exit` function, and a program can fail by calling the `abort` function. If a program is specialized to just some platforms, it can fail by calling functions specific to those platforms, e.g., `_exit` (Posix) and `_Exit` (C99). However, like other functions, an exit function should be declared, typically by including a header. For example, if a C program calls `exit`, it should include '`stdlib.h`' either directly or via the default includes (see Section 5.1.2 [Default Includes], page 39).

A program can fail due to undefined behavior such as dereferencing a null pointer, but this is not recommended as undefined behavior allows an implementation to do whatever it pleases and this includes exiting successfully.

13 Manual Configuration

A few kinds of features can't be guessed automatically by running test programs. For example, the details of the object-file format, or special options that need to be passed to the compiler or linker. You can check for such features using ad-hoc means, such as having `configure` check the output of the `uname` program, or looking for libraries that are unique to particular systems. However, Autoconf provides a uniform method for handling unguessable features.

13.1 Specifying the System Type

Autoconf-generated `configure` scripts can make decisions based on a canonical name for the system type, which has the form: '*cpu-vendor-os*', where *os* can be '*system*' or '*kernel-system*'

`configure` can usually guess the canonical name for the type of system it's running on. To do so it runs a script called `config.guess`, which infers the name using the `uname` command or symbols predefined by the C preprocessor.

Alternately, the user can specify the system type with command line arguments to `configure`. Doing so is necessary when cross-compiling. In the most complex case of cross-compiling, three system types are involved. The options to specify them are:

'`--build=`*build-type*'
: the type of system on which the package is being configured and compiled. It defaults to the result of running `config.guess`.

'`--host=`*host-type*'
: the type of system on which the package runs. By default it is the same as the build machine. Specifying it enables the cross-compilation mode.

'`--target=`*target-type*'
: the type of system for which any compiler tools in the package produce code (rarely needed). By default, it is the same as host.

If you mean to override the result of `config.guess`, use '`--build`', not '`--host`', since the latter enables cross-compilation. For historical reasons, whenever you specify '`--host`', be sure to specify '`--build`' too; this will be fixed in the future. So, to enter cross-compilation mode, use a command like this

```
./configure --build=i686-pc-linux-gnu --host=m68k-coff
```

Note that if you do not specify '`--host`', `configure` fails if it can't run the code generated by the specified compiler. For example, configuring as follows fails:

```
./configure CC=m68k-coff-gcc
```

In the future, when cross-compiling Autoconf will *not* accept tools (compilers, linkers, assemblers) whose name is not prefixed with the host type. The only case when this may be useful is when you really are not cross-compiling, but only building for a least-common-denominator architecture: an example is building for `i386-pc-linux-gnu` while running on an `i686-pc-linux-gnu` architecture. In this case, some particular pairs might be similar enough to let you get away with the system compilers, but in general the compiler might

make bogus assumptions on the host: if you know what you are doing, please create symbolic links from the host compiler to the build compiler.

`configure` recognizes short aliases for many system types; for example, '`decstation`' can be used instead of '`mips-dec-ultrix4.2`'. `configure` runs a script called `config.sub` to canonicalize system type aliases.

This section deliberately omits the description of the obsolete interface; see Section 17.6.3 [Hosts and Cross-Compilation], page 260.

13.2 Getting the Canonical System Type

The following macros make the system type available to `configure` scripts.

The variables '`build_alias`', '`host_alias`', and '`target_alias`' are always exactly the arguments of '`--build`', '`--host`', and '`--target`'; in particular, they are left empty if the user did not use them, even if the corresponding `AC_CANONICAL` macro was run. Any configure script may use these variables anywhere. These are the variables that should be used when in interaction with the user.

If you need to recognize some special environments based on their system type, run the following macros to get canonical system names. These variables are not set before the macro call.

If you use these macros, you must distribute `config.guess` and `config.sub` along with your source code. See Section 4.5 [Output], page 20, for information about the `AC_CONFIG_AUX_DIR` macro which you can use to control in which directory `configure` looks for those scripts.

`AC_CANONICAL_BUILD` [Macro]

Compute the canonical build-system type variable, `build`, and its three individual parts `build_cpu`, `build_vendor`, and `build_os`.

If '`--build`' was specified, then `build` is the canonicalization of `build_alias` by `config.sub`, otherwise it is determined by the shell script `config.guess`.

`AC_CANONICAL_HOST` [Macro]

Compute the canonical host-system type variable, `host`, and its three individual parts `host_cpu`, `host_vendor`, and `host_os`.

If '`--host`' was specified, then `host` is the canonicalization of `host_alias` by `config.sub`, otherwise it defaults to `build`.

`AC_CANONICAL_TARGET` [Macro]

Compute the canonical target-system type variable, `target`, and its three individual parts `target_cpu`, `target_vendor`, and `target_os`.

If '`--target`' was specified, then `target` is the canonicalization of `target_alias` by `config.sub`, otherwise it defaults to `host`.

Note that there can be artifacts due to the backward compatibility code. See See Section 17.6.3 [Hosts and Cross-Compilation], page 260, for more.

13.3 Using the System Type

In '`configure.ac`' the system type is generally used by one or more `case` statements to select system-specifics. Shell wildcards can be used to match a group of system types.

For example, an extra assembler code object file could be chosen, giving access to a CPU cycle counter register. `$(CYCLE_OBJ)` in the following would be used in a makefile to add the object to a program or library.

```
case $host in
  alpha*-*-*) CYCLE_OBJ=rpcc.o ;;
  i?86-*-*)   CYCLE_OBJ=rdtsc.o ;;
  *)          CYCLE_OBJ= ;;
esac
AC_SUBST([CYCLE_OBJ])
```

`AC_CONFIG_LINKS` (see Section 4.11 [Configuration Links], page 36) is another good way to select variant source files, for example optimized code for some CPUs. The configured CPU type doesn't always indicate exact CPU types, so some runtime capability checks may be necessary too.

```
case $host in
  alpha*-*-*)   AC_CONFIG_LINKS([dither.c:alpha/dither.c]) ;;
  powerpc*-*-*) AC_CONFIG_LINKS([dither.c:powerpc/dither.c]) ;;
  *-*-*)        AC_CONFIG_LINKS([dither.c:generic/dither.c]) ;;
esac
```

The host system type can also be used to find cross-compilation tools with `AC_CHECK_TOOL` (see Section 5.2.2 [Generic Programs], page 43).

The above examples all show '`$host`', since this is where the code is going to run. Only rarely is it necessary to test '`$build`' (which is where the build is being done).

Whenever you're tempted to use '`$host`' it's worth considering whether some sort of probe would be better. New system types come along periodically or previously missing features are added. Well-written probes can adapt themselves to such things, but hard-coded lists of names can't. Here are some guidelines,

- Availability of libraries and library functions should always be checked by probing.
- Variant behavior of system calls is best identified with runtime tests if possible, but bug workarounds or obscure difficulties might have to be driven from '`$host`'.
- Assembler code is inevitably highly CPU-specific and is best selected according to '`$host_cpu`'.
- Assembler variations like underscore prefix on globals or ELF versus COFF type directives are however best determined by probing, perhaps even examining the compiler output.

'`$target`' is for use by a package creating a compiler or similar. For ordinary packages it's meaningless and should not be used. It indicates what the created compiler should generate code for, if it can cross-compile. '`$target`' generally selects various hard-coded CPU and system conventions, since usually the compiler or tools under construction themselves determine how the target works.

14 Site Configuration

`configure` scripts support several kinds of local configuration decisions. There are ways for users to specify where external software packages are, include or exclude optional features, install programs under modified names, and set default values for `configure` options.

14.1 Controlling Help Output

Users consult '`configure --help`' to learn of configuration decisions specific to your package. By default, `configure` breaks this output into sections for each type of option; within each section, help strings appear in the order '`configure.ac`' defines them:

```
Optional Features:
  ...
  --enable-bar            include bar

Optional Packages:
  ...
  --with-foo              use foo
```

`AC_PRESERVE_HELP_ORDER` [Macro]

Request an alternate '`--help`' format, in which options of all types appear together, in the order defined. Call this macro before any `AC_ARG_ENABLE` or `AC_ARG_WITH`.

```
Optional Features and Packages:
  ...
  --enable-bar            include bar
  --with-foo              use foo
```

14.2 Working With External Software

Some packages require, or can optionally use, other software packages that are already installed. The user can give `configure` command line options to specify which such external software to use. The options have one of these forms:

`--with-`*`package`*`[=`*`arg`*`]`
`--without-`*`package`*

For example, '`--with-gnu-ld`' means work with the GNU linker instead of some other linker. '`--with-x`' means work with The X Window System.

The user can give an argument by following the package name with '`=`' and the argument. Giving an argument of '`no`' is for packages that are used by default; it says to *not* use the package. An argument that is neither '`yes`' nor '`no`' could include a name or number of a version of the other package, to specify more precisely which other package this program is supposed to work with. If no argument is given, it defaults to '`yes`'. '`--without-`*`package`*' is equivalent to '`--with-`*`package`*`=no`'.

Normally `configure` scripts complain about '`--with-`*`package`*' options that they do not support. See Section 14.5 [Option Checking], page 229, for details, and for how to override the defaults.

For each external software package that may be used, 'configure.ac' should call AC_ARG_WITH to detect whether the configure user asked to use it. Whether each package is used or not by default, and which arguments are valid, is up to you.

AC_ARG_WITH (*package*, *help-string*, [*action-if-given*], [*action-if-not-given*]) [Macro]

If the user gave configure the option '--with-*package*' or '--without-*package*', run shell commands *action-if-given*. If neither option was given, run shell commands *action-if-not-given*. The name *package* indicates another software package that this program should work with. It should consist only of alphanumeric characters, dashes, and dots.

The option's argument is available to the shell commands *action-if-given* in the shell variable withval, which is actually just the value of the shell variable named with_*package*, with any non-alphanumeric characters in *package* changed into '_'. You may use that variable instead, if you wish.

The argument *help-string* is a description of the option that looks like this:

```
--with-readline         support fancy command line editing
```

help-string may be more than one line long, if more detail is needed. Just make sure the columns line up in 'configure --help'. Avoid tabs in the help string. You'll need to enclose the help string in '[' and ']' in order to produce the leading blanks.

You should format your *help-string* with the macro AS_HELP_STRING (see Section 14.4 [Pretty Help Strings], page 228).

The following example shows how to use the AC_ARG_WITH macro in a common situation. You want to let the user decide whether to enable support for an external library (e.g., the readline library); if the user specified neither '--with-readline' nor '--without-readline', you want to enable support for readline only if the library is available on the system.

```
AC_ARG_WITH([readline],
  [AS_HELP_STRING([--with-readline],
    [support fancy command line editing @<:@default=check@:>@])],
  [],
  [with_readline=check])

LIBREADLINE=
AS_IF([test "x$with_readline" != xno],
  [AC_CHECK_LIB([readline], [main],
    [AC_SUBST([LIBREADLINE], ["-lreadline -lncurses"])
     AC_DEFINE([HAVE_LIBREADLINE], [1],
               [Define if you have libreadline])
    ],
    [if test "x$with_readline" != xcheck; then
       AC_MSG_FAILURE(
         [--with-readline was given, but test for readline failed])
     fi
    ], -lncurses)])
```

The next example shows how to use AC_ARG_WITH to give the user the possibility to enable support for the readline library, in case it is still experimental and not well tested, and is therefore disabled by default.

```
AC_ARG_WITH([readline],
  [AS_HELP_STRING([--with-readline],
    [enable experimental support for readline])],
  [],
  [with_readline=no])

LIBREADLINE=
AS_IF([test "x$with_readline" != xno],
  [AC_CHECK_LIB([readline], [main],
    [AC_SUBST([LIBREADLINE], ["-lreadline -lncurses"])
     AC_DEFINE([HAVE_LIBREADLINE], [1],
               [Define if you have libreadline])
    ],
    [AC_MSG_FAILURE(
       [--with-readline was given, but test for readline failed])],
    [-lncurses])])
```

The last example shows how to use AC_ARG_WITH to give the user the possibility to disable support for the readline library, given that it is an important feature and that it should be enabled by default.

```
AC_ARG_WITH([readline],
  [AS_HELP_STRING([--without-readline],
    [disable support for readline])],
  [],
  [with_readline=yes])

LIBREADLINE=
AS_IF([test "x$with_readline" != xno],
  [AC_CHECK_LIB([readline], [main],
    [AC_SUBST([LIBREADLINE], ["-lreadline -lncurses"])
     AC_DEFINE([HAVE_LIBREADLINE], [1],
               [Define if you have libreadline])
    ],
    [AC_MSG_FAILURE(
       [readline test failed (--without-readline to disable)])],
    [-lncurses])])
```

These three examples can be easily adapted to the case where AC_ARG_ENABLE should be preferred to AC_ARG_WITH (see Section 14.3 [Package Options], page 227).

14.3 Choosing Package Options

If a software package has optional compile-time features, the user can give configure command line options to specify whether to compile them. The options have one of these forms:

`--enable-feature[=arg]`
`--disable-feature`

These options allow users to choose which optional features to build and install. '`--enable-feature`' options should never make a feature behave differently or cause one feature to replace another. They should only cause parts of the program to be built rather than left out.

The user can give an argument by following the feature name with '`=`' and the argument. Giving an argument of '`no`' requests that the feature *not* be made available. A feature with an argument looks like '`--enable-debug=stabs`'. If no argument is given, it defaults to '`yes`'. '`--disable-feature`' is equivalent to '`--enable-feature=no`'.

Normally `configure` scripts complain about '`--enable-package`' options that they do not support. See Section 14.5 [Option Checking], page 229, for details, and for how to override the defaults.

For each optional feature, '`configure.ac`' should call `AC_ARG_ENABLE` to detect whether the `configure` user asked to include it. Whether each feature is included or not by default, and which arguments are valid, is up to you.

`AC_ARG_ENABLE (feature, help-string, [action-if-given], [action-if-not-given])` [Macro]

If the user gave `configure` the option '`--enable-feature`' or '`--disable-feature`', run shell commands *action-if-given*. If neither option was given, run shell commands *action-if-not-given*. The name *feature* indicates an optional user-level facility. It should consist only of alphanumeric characters, dashes, and dots.

The option's argument is available to the shell commands *action-if-given* in the shell variable `enableval`, which is actually just the value of the shell variable named `enable_feature`, with any non-alphanumeric characters in *feature* changed into '`_`'. You may use that variable instead, if you wish. The *help-string* argument is like that of `AC_ARG_WITH` (see Section 14.2 [External Software], page 225).

You should format your *help-string* with the macro `AS_HELP_STRING` (see Section 14.4 [Pretty Help Strings], page 228).

See the examples suggested with the definition of `AC_ARG_WITH` (see Section 14.2 [External Software], page 225) to get an idea of possible applications of `AC_ARG_ENABLE`.

14.4 Making Your Help Strings Look Pretty

Properly formatting the '`help strings`' which are used in `AC_ARG_WITH` (see Section 14.2 [External Software], page 225) and `AC_ARG_ENABLE` (see Section 14.3 [Package Options], page 227) can be challenging. Specifically, you want your own '`help strings`' to line up in the appropriate columns of '`configure --help`' just like the standard Autoconf '`help strings`' do. This is the purpose of the `AS_HELP_STRING` macro.

`AS_HELP_STRING (left-hand-side, right-hand-side [indent-column = '26'], [wrap-column = '79'])` [Macro]

Expands into an help string that looks pretty when the user executes '`configure --help`'. It is typically used in `AC_ARG_WITH` (see Section 14.2 [External Software],

page 225) or AC_ARG_ENABLE (see Section 14.3 [Package Options], page 227). The following example makes this clearer.

```
AC_ARG_WITH([foo],
  [AS_HELP_STRING([--with-foo],
     [use foo (default is no)])],
  [use_foo=$withval],
  [use_foo=no])
```

Then the last few lines of '`configure --help`' appear like this:

```
--enable and --with options recognized:
  --with-foo              use foo (default is no)
```

Macro expansion is performed on the first argument. However, the second argument of AS_HELP_STRING is treated as a whitespace separated list of text to be reformatted, and is not subject to macro expansion. Since it is not expanded, it should not be double quoted. See Section 3.1.2 [Autoconf Language], page 9, for a more detailed explanation.

The AS_HELP_STRING macro is particularly helpful when the *left-hand-side* and/or *right-hand-side* are composed of macro arguments, as shown in the following example. Be aware that *left-hand-side* may not contain unbalanced quotes or parentheses.

```
AC_DEFUN([MY_ARG_WITH],
  [AC_ARG_WITH(m4_translit([[$1]], [_], [-]),
     [AS_HELP_STRING([--with-m4_translit([$1], [_], [-])],
                     [use $1 (default is $2)])],
     [use_[]$1=$withval],
     [use_[]$1=$2])])
MY_ARG_WITH([a_b], [no])
```

Here, the last few lines of '`configure --help`' will include:

```
--enable and --with options recognized:
  --with-a-b              use a_b (default is no)
```

The parameters *indent-column* and *wrap-column* were introduced in Autoconf 2.62. Generally, they should not be specified; they exist for fine-tuning of the wrapping.

```
AS_HELP_STRING([--option], [description of option])
⇒  --option               description of option
AS_HELP_STRING([--option], [description of option], [15], [30])
⇒  --option     description of
⇒               option
```

14.5 Controlling Checking of configure Options

The configure script checks its command-line options against a list of known options, like '`--help`' or '`--config-cache`'. An unknown option ordinarily indicates a mistake by the user and configure halts with an error. However, by default unknown '`--with-`*package*' and '`--enable-`*feature*' options elicit only a warning, to support configuring entire source trees.

Source trees often contain multiple packages with a top-level configure script that uses the AC_CONFIG_SUBDIRS macro (see Section 4.12 [Subdirectories], page 37). Because the

packages generally support different '`--with-package`' and '`--enable-feature`' options, the GNU Coding Standards say they must accept unrecognized options without halting. Even a warning message is undesirable here, so `AC_CONFIG_SUBDIRS` automatically disables the warnings.

This default behavior may be modified in two ways. First, the installer can invoke `configure --disable-option-checking` to disable these warnings, or invoke `configure --enable-option-checking=fatal` options to turn them into fatal errors, respectively. Second, the maintainer can use `AC_DISABLE_OPTION_CHECKING`.

`AC_DISABLE_OPTION_CHECKING` [Macro]

By default, disable warnings related to any unrecognized '`--with-package`' or '`--enable-feature`' options. This is implied by `AC_CONFIG_SUBDIRS`.

The installer can override this behavior by passing '`--enable-option-checking`' (enable warnings) or '`--enable-option-checking=fatal`' (enable errors) to `configure`.

14.6 Configuring Site Details

Some software packages require complex site-specific information. Some examples are host names to use for certain services, company names, and email addresses to contact. Since some configuration scripts generated by Metaconfig ask for such information interactively, people sometimes wonder how to get that information in Autoconf-generated configuration scripts, which aren't interactive.

Such site configuration information should be put in a file that is edited *only by users*, not by programs. The location of the file can either be based on the `prefix` variable, or be a standard location such as the user's home directory. It could even be specified by an environment variable. The programs should examine that file at runtime, rather than at compile time. Runtime configuration is more convenient for users and makes the configuration process simpler than getting the information while configuring. See section "Variables for Installation Directories" in *GNU Coding Standards*, for more information on where to put data files.

14.7 Transforming Program Names When Installing

Autoconf supports changing the names of programs when installing them. In order to use these transformations, '`configure.ac`' must call the macro `AC_ARG_PROGRAM`.

`AC_ARG_PROGRAM` [Macro]

Place in output variable `program_transform_name` a sequence of `sed` commands for changing the names of installed programs.

If any of the options described below are given to `configure`, program names are transformed accordingly. Otherwise, if `AC_CANONICAL_TARGET` has been called and a '`--target`' value is given, the target type followed by a dash is used as a prefix. Otherwise, no program name transformation is done.

14.7.1 Transformation Options

You can specify name transformations by giving `configure` these command line options:

'`--program-prefix=prefix`'
: prepend *prefix* to the names;

'`--program-suffix=suffix`'
: append *suffix* to the names;

'`--program-transform-name=expression`'
: perform `sed` substitution *expression* on the names.

14.7.2 Transformation Examples

These transformations are useful with programs that can be part of a cross-compilation development environment. For example, a cross-assembler running on a Sun 4 configured with '`--target=i960-vxworks`' is normally installed as '`i960-vxworks-as`', rather than '`as`', which could be confused with a native Sun 4 assembler.

You can force a program name to begin with '`g`', if you don't want GNU programs installed on your system to shadow other programs with the same name. For example, if you configure GNU `diff` with '`--program-prefix=g`', then when you run '`make install`' it is installed as '`/usr/local/bin/gdiff`'.

As a more sophisticated example, you could use

```
--program-transform-name='s/^/g/; s/^gg/g/; s/^gless/less/'
```

to prepend '`g`' to most of the program names in a source tree, excepting those like `gdb` that already have one and those like `less` and `lesskey` that aren't GNU programs. (That is assuming that you have a source tree containing those programs that is set up to use this feature.)

One way to install multiple versions of some programs simultaneously is to append a version number to the name of one or both. For example, if you want to keep Autoconf version 1 around for awhile, you can configure Autoconf version 2 using '`--program-suffix=2`' to install the programs as '`/usr/local/bin/autoconf2`', '`/usr/local/bin/autoheader2`', etc. Nevertheless, pay attention that only the binaries are renamed, therefore you'd have problems with the library files which might overlap.

14.7.3 Transformation Rules

Here is how to use the variable `program_transform_name` in a '`Makefile.in`':

```
PROGRAMS = cp ls rm
transform = @program_transform_name@
install:
        for p in $(PROGRAMS); do \
          $(INSTALL_PROGRAM) $$p $(DESTDIR)$(bindir)/`echo $$p | \
                                          sed '$(transform)'`; \
        done

uninstall:
        for p in $(PROGRAMS); do \
          rm -f $(DESTDIR)$(bindir)/`echo $$p | sed '$(transform)'`; \
        done
```

It is guaranteed that `program_transform_name` is never empty, and that there are no useless separators. Therefore you may safely embed `program_transform_name` within a sed program using '`;`':

```
transform = @program_transform_name@
transform_exe = s/$(EXEEXT)$$//;$(transform);s/$$/$(EXEEXT)/
```

Whether to do the transformations on documentation files (Texinfo or `man`) is a tricky question; there seems to be no perfect answer, due to the several reasons for name transforming. Documentation is not usually particular to a specific architecture, and Texinfo files do not conflict with system documentation. But they might conflict with earlier versions of the same files, and `man` pages sometimes do conflict with system documentation. As a compromise, it is probably best to do name transformations on `man` pages but not on Texinfo manuals.

14.8 Setting Site Defaults

Autoconf-generated `configure` scripts allow your site to provide default values for some configuration values. You do this by creating site- and system-wide initialization files.

If the environment variable `CONFIG_SITE` is set, `configure` uses its value as the name of a shell script to read. Otherwise, it reads the shell script '*prefix*`/share/config.site`' if it exists, then '*prefix*`/etc/config.site`' if it exists. Thus, settings in machine-specific files override those in machine-independent ones in case of conflict.

Site files can be arbitrary shell scripts, but only certain kinds of code are really appropriate to be in them. Because `configure` reads any cache file after it has read any site files, a site file can define a default cache file to be shared between all Autoconf-generated `configure` scripts run on that system (see Section 7.4.2 [Cache Files], page 108). If you set a default cache file in a site file, it is a good idea to also set the output variable `CC` in that site file, because the cache file is only valid for a particular compiler, but many systems have several available.

You can examine or override the value set by a command line option to `configure` in a site file; options set shell variables that have the same names as the options, with any dashes turned into underscores. The exceptions are that '`--without-`' and '`--disable-`' options are like giving the corresponding '`--with-`' or '`--enable-`' option and the value '`no`'. Thus, '`--cache-file=localcache`' sets the variable `cache_file` to the value '`localcache`'; '`--enable-warnings=no`' or '`--disable-warnings`' sets the variable `enable_warnings` to the value '`no`'; '`--prefix=/usr`' sets the variable `prefix` to the value '`/usr`'; etc.

Site files are also good places to set default values for other output variables, such as `CFLAGS`, if you need to give them non-default values: anything you would normally do, repetitively, on the command line. If you use non-default values for *prefix* or *exec_prefix* (wherever you locate the site file), you can set them in the site file if you specify it with the `CONFIG_SITE` environment variable.

You can set some cache values in the site file itself. Doing this is useful if you are cross-compiling, where it is impossible to check features that require running a test program. You could "prime the cache" by setting those values correctly for that system in '*prefix*`/etc/config.site`'. To find out the names of the cache variables you need to set, look for shell variables with '`_cv_`' in their names in the affected `configure` scripts, or in the Autoconf M4 source code for those macros.

The cache file is careful to not override any variables set in the site files. Similarly, you should not override command-line options in the site files. Your code should check that

variables such as `prefix` and `cache_file` have their default values (as set near the top of `configure`) before changing them.

Here is a sample file '`/usr/share/local/gnu/share/config.site`'. The command '`configure --prefix=/usr/share/local/gnu`' would read this file (if `CONFIG_SITE` is not set to a different file).

```
# config.site for configure
#
# Change some defaults.
test "$prefix" = NONE && prefix=/usr/share/local/gnu
test "$exec_prefix" = NONE && exec_prefix=/usr/local/gnu
test "$sharedstatedir" = '${prefix}/com' && sharedstatedir=/var
test "$localstatedir" = '${prefix}/var' && localstatedir=/var

# Give Autoconf 2.x generated configure scripts a shared default
# cache file for feature test results, architecture-specific.
if test "$cache_file" = /dev/null; then
  cache_file="$prefix/var/config.cache"
  # A cache file is only valid for one C compiler.
  CC=gcc
fi
```

Another use of '`config.site`' is for priming the directory variables in a manner consistent with the Filesystem Hierarchy Standard (FHS). Once the following file is installed at '`/usr/share/config.site`', a user can execute simply `./configure --prefix=/usr` to get all the directories chosen in the locations recommended by FHS.

```
# /usr/local/config.site for FHS defaults when installing below /usr,
# and the respective settings were not changed on the command line.
if test "$prefix" = /usr; then
  test "$sysconfdir" = '${prefix}/etc' && sysconfdir=/etc
  test "$sharedstatedir" = '${prefix}/com' && sharedstatedir=/var
  test "$localstatedir" = '${prefix}/var' && localstatedir=/var
fi
```

15 Running configure Scripts

Below are instructions on how to configure a package that uses a configure script, suitable for inclusion as an 'INSTALL' file in the package. A plain-text version of 'INSTALL' which you may use comes with Autoconf.

15.1 Basic Installation

Briefly, the shell commands './configure; make; make install' should configure, build, and install this package. The following more-detailed instructions are generic; see the 'README' file for instructions specific to this package.

The configure shell script attempts to guess correct values for various system-dependent variables used during compilation. It uses those values to create a 'Makefile' in each directory of the package. It may also create one or more '.h' files containing system-dependent definitions. Finally, it creates a shell script 'config.status' that you can run in the future to recreate the current configuration, and a file 'config.log' containing compiler output (useful mainly for debugging configure).

It can also use an optional file (typically called 'config.cache' and enabled with '--cache-file=config.cache' or simply '-C') that saves the results of its tests to speed up reconfiguring. Caching is disabled by default to prevent problems with accidental use of stale cache files.

If you need to do unusual things to compile the package, please try to figure out how configure could check whether to do them, and mail diffs or instructions to the address given in the 'README' so they can be considered for the next release. If you are using the cache, and at some point 'config.cache' contains results you don't want to keep, you may remove or edit it.

The file 'configure.ac' (or 'configure.in') is used to create 'configure' by a program called autoconf. You need 'configure.ac' if you want to change it or regenerate 'configure' using a newer version of autoconf.

The simplest way to compile this package is:

1. cd to the directory containing the package's source code and type './configure' to configure the package for your system.

   Running configure might take a while. While running, it prints some messages telling which features it is checking for.
2. Type 'make' to compile the package.
3. Optionally, type 'make check' to run any self-tests that come with the package.
4. Type 'make install' to install the programs and any data files and documentation.
5. You can remove the program binaries and object files from the source code directory by typing 'make clean'. To also remove the files that configure created (so you can compile the package for a different kind of computer), type 'make distclean'. There is also a 'make maintainer-clean' target, but that is intended mainly for the package's developers. If you use it, you may have to get all sorts of other programs in order to regenerate files that came with the distribution.
6. Often, you can also type 'make uninstall' to remove the installed files again.

15.2 Compilers and Options

Some systems require unusual options for compilation or linking that the `configure` script does not know about. Run '`./configure --help`' for details on some of the pertinent environment variables.

You can give `configure` initial values for configuration parameters by setting variables in the command line or in the environment. Here is an example:

```
./configure CC=c99 CFLAGS=-g LIBS=-lposix
```

See Section 15.8 [Defining Variables], page 237, for more details.

15.3 Compiling For Multiple Architectures

You can compile the package for more than one kind of computer at the same time, by placing the object files for each architecture in their own directory. To do this, you can use GNU `make`. `cd` to the directory where you want the object files and executables to go and run the `configure` script. `configure` automatically checks for the source code in the directory that `configure` is in and in '`..`'.

With a non-GNU `make`, it is safer to compile the package for one architecture at a time in the source code directory. After you have installed the package for one architecture, use '`make distclean`' before reconfiguring for another architecture.

15.4 Installation Names

By default, '`make install`' installs the package's commands under '`/usr/local/bin`', include files under '`/usr/local/include`', etc. You can specify an installation prefix other than '`/usr/local`' by giving `configure` the option '`--prefix=`*`prefix`*'.

You can specify separate installation prefixes for architecture-specific files and architecture-independent files. If you pass the option '`--exec-prefix=`*`prefix`*' to `configure`, the package uses *prefix* as the prefix for installing programs and libraries. Documentation and other data files still use the regular prefix.

In addition, if you use an unusual directory layout you can give options like '`--bindir=`*`dir`*' to specify different values for particular kinds of files. Run '`configure --help`' for a list of the directories you can set and what kinds of files go in them.

If the package supports it, you can cause programs to be installed with an extra prefix or suffix on their names by giving `configure` the option '`--program-prefix=`*`PREFIX`*' or '`--program-suffix=`*`SUFFIX`*'.

15.5 Optional Features

Some packages pay attention to '`--enable-`*`feature`*' options to `configure`, where *feature* indicates an optional part of the package. They may also pay attention to '`--with-`*`package`*' options, where *package* is something like '`gnu-as`' or '`x`' (for the X Window System). The '`README`' should mention any '`--enable-`' and '`--with-`' options that the package recognizes.

For packages that use the X Window System, `configure` can usually find the X include and library files automatically, but if it doesn't, you can use the `configure` options '`--x-includes=`*`dir`*' and '`--x-libraries=`*`dir`*' to specify their locations.

15.6 Specifying the System Type

There may be some features configure cannot figure out automatically, but needs to determine by the type of machine the package will run on. Usually, assuming the package is built to be run on the *same* architectures, configure can figure that out, but if it prints a message saying it cannot guess the machine type, give it the '--build=*type*' option. *type* can either be a short name for the system type, such as 'sun4', or a canonical name which has the form:

cpu-company-system

where *system* can have one of these forms:

os kernel-os

See the file 'config.sub' for the possible values of each field. If 'config.sub' isn't included in this package, then this package doesn't need to know the machine type.

If you are *building* compiler tools for cross-compiling, you should use the option '--target=*type*' to select the type of system they will produce code for.

If you want to *use* a cross compiler, that generates code for a platform different from the build platform, you should specify the *host* platform (i.e., that on which the generated programs will eventually be run) with '--host=*type*'.

15.7 Sharing Defaults

If you want to set default values for configure scripts to share, you can create a site shell script called 'config.site' that gives default values for variables like CC, cache_file, and prefix. configure looks for '*prefix*/share/config.site' if it exists, then '*prefix*/etc/config.site' if it exists. Or, you can set the CONFIG_SITE environment variable to the location of the site script. A warning: not all configure scripts look for a site script.

15.8 Defining Variables

Variables not defined in a site shell script can be set in the environment passed to configure. However, some packages may run configure again during the build, and the customized values of these variables may be lost. In order to avoid this problem, you should set them in the configure command line, using 'VAR=value'. For example:

```
./configure CC=/usr/local2/bin/gcc
```

causes the specified gcc to be used as the C compiler (unless it is overridden in the site shell script).

Unfortunately, this technique does not work for CONFIG_SHELL due to an Autoconf bug. Until the bug is fixed you can use this workaround:

```
CONFIG_SHELL=/bin/bash /bin/bash ./configure CONFIG_SHELL=/bin/bash
```

15.9 configure Invocation

configure recognizes the following options to control how it operates.

'--help'
'-h' Print a summary of the options to configure, and exit.

‘`--version`’
‘`-V`’ Print the version of Autoconf used to generate the `configure` script, and exit.

‘`--cache-file=`*`file`*’
Enable the cache: use and save the results of the tests in *file*, traditionally ‘`config.cache`’. *file* defaults to ‘`/dev/null`’ to disable caching.

‘`--config-cache`’
‘`-C`’ Alias for ‘`--cache-file=config.cache`’.

‘`--quiet`’
‘`--silent`’
‘`-q`’ Do not print messages saying which checks are being made. To suppress all normal output, redirect it to ‘`/dev/null`’ (any error messages will still be shown).

‘`--srcdir=`*`dir`*’
Look for the package’s source code in directory *dir*. Usually `configure` can determine that directory automatically.

`configure` also accepts some other, not widely useful, options. Run ‘`configure --help`’ for more details.

16 config.status Invocation

The `configure` script creates a file named '`config.status`', which actually configures, *instantiates*, the template files. It also records the configuration options that were specified when the package was last configured in case reconfiguring is needed.

Synopsis:

```
./config.status option... [file...]
```

It configures the *files*; if none are specified, all the templates are instantiated. The files must be specified without their dependencies, as in

```
./config.status foobar
```

not

```
./config.status foobar:foo.in:bar.in
```

The supported options are:

'`--help`'
'`-h`' Print a summary of the command line options, the list of the template files, and exit.

'`--version`'
'`-V`' Print the version number of Autoconf and the configuration settings, and exit.

'`--silent`'
'`--quiet`'
'`-q`' Do not print progress messages.

'`--debug`'
'`-d`' Don't remove the temporary files.

'`--file=file[:template]`'
Require that *file* be instantiated as if '`AC_CONFIG_FILES(file:template)`' was used. Both *file* and *template* may be '`-`' in which case the standard output and/or standard input, respectively, is used. If a *template* file name is relative, it is first looked for in the build tree, and then in the source tree. See Section 4.6 [Configuration Actions], page 20, for more details.

This option and the following ones provide one way for separately distributed packages to share the values computed by `configure`. Doing so can be useful if some of the packages need a superset of the features that one of them, perhaps a common library, does. These options allow a '`config.status`' file to create files other than the ones that its '`configure.ac`' specifies, so it can be used for a different package.

'`--header=file[:template]`'
Same as '`--file`' above, but with '`AC_CONFIG_HEADERS`'.

'`--recheck`'
Ask '`config.status`' to update itself and exit (no instantiation). This option is useful if you change `configure`, so that the results of some tests might be different from the previous run. The '`--recheck`' option reruns `configure` with the same arguments you used before, plus the '`--no-create`' option, which

prevents `configure` from running '`config.status`' and creating '`Makefile`' and other files, and the '`--no-recursion`' option, which prevents `configure` from running other `configure` scripts in subdirectories. (This is so other Make rules can run '`config.status`' when it changes; see Section 4.8.5 [Automatic Remaking], page 31, for an example).

'`config.status`' checks several optional environment variables that can alter its behavior:

`CONFIG_SHELL` [Variable]

The shell with which to run `configure` for the '`--recheck`' option. It must be Bourne-compatible. The default is a shell that supports `LINENO` if available, and '`/bin/sh`' otherwise. Invoking `configure` by hand bypasses this setting, so you may need to use a command like '`CONFIG_SHELL=/bin/bash /bin/bash ./configure`' to insure that the same shell is used everywhere. The absolute name of the shell should be passed.

`CONFIG_STATUS` [Variable]

The file name to use for the shell script that records the configuration. The default is '`./config.status`'. This variable is useful when one package uses parts of another and the `configure` scripts shouldn't be merged because they are maintained separately.

You can use '`./config.status`' in your makefiles. For example, in the dependencies given above (see Section 4.8.5 [Automatic Remaking], page 31), '`config.status`' is run twice when '`configure.ac`' has changed. If that bothers you, you can make each run only regenerate the files for that rule:

```
config.h: stamp-h
stamp-h: config.h.in config.status
        ./config.status config.h
        echo > stamp-h

Makefile: Makefile.in config.status
        ./config.status Makefile
```

The calling convention of '`config.status`' has changed; see Section 17.1 [Obsolete config.status Use], page 241, for details.

17 Obsolete Constructs

Autoconf changes, and throughout the years some constructs have been obsoleted. Most of the changes involve the macros, but in some cases the tools themselves, or even some concepts, are now considered obsolete.

You may completely skip this chapter if you are new to Autoconf. Its intention is mainly to help maintainers updating their packages by understanding how to move to more modern constructs.

17.1 Obsolete 'config.status' Invocation

'config.status' now supports arguments to specify the files to instantiate; see Chapter 16 [config.status Invocation], page 239, for more details. Before, environment variables had to be used.

CONFIG_COMMANDS [Variable]

The tags of the commands to execute. The default is the arguments given to AC_OUTPUT and AC_CONFIG_COMMANDS in 'configure.ac'.

CONFIG_FILES [Variable]

The files in which to perform '@*variable*@' substitutions. The default is the arguments given to AC_OUTPUT and AC_CONFIG_FILES in 'configure.ac'.

CONFIG_HEADERS [Variable]

The files in which to substitute C #define statements. The default is the arguments given to AC_CONFIG_HEADERS; if that macro was not called, 'config.status' ignores this variable.

CONFIG_LINKS [Variable]

The symbolic links to establish. The default is the arguments given to AC_CONFIG_LINKS; if that macro was not called, 'config.status' ignores this variable.

In Chapter 16 [config.status Invocation], page 239, using this old interface, the example would be:

```
config.h: stamp-h
stamp-h: config.h.in config.status
        CONFIG_COMMANDS= CONFIG_LINKS= CONFIG_FILES= \
          CONFIG_HEADERS=config.h ./config.status
        echo > stamp-h

Makefile: Makefile.in config.status
        CONFIG_COMMANDS= CONFIG_LINKS= CONFIG_HEADERS= \
          CONFIG_FILES=Makefile ./config.status
```

(If 'configure.ac' does not call AC_CONFIG_HEADERS, there is no need to set CONFIG_HEADERS in the make rules. Equally for CONFIG_COMMANDS, etc.)

17.2 'acconfig.h'

In order to produce 'config.h.in', autoheader needs to build or to find templates for each symbol. Modern releases of Autoconf use AH_VERBATIM and AH_TEMPLATE (see Section 4.9.3 [Autoheader Macros], page 35), but in older releases a file, 'acconfig.h', contained the list of needed templates. autoheader copied comments and #define and #undef statements from 'acconfig.h' in the current directory, if present. This file used to be mandatory if you AC_DEFINE any additional symbols.

Modern releases of Autoconf also provide AH_TOP and AH_BOTTOM if you need to prepend/append some information to 'config.h.in'. Ancient versions of Autoconf had a similar feature: if './acconfig.h' contains the string '@TOP@', autoheader copies the lines before the line containing '@TOP@' into the top of the file that it generates. Similarly, if './acconfig.h' contains the string '@BOTTOM@', autoheader copies the lines after that line to the end of the file it generates. Either or both of those strings may be omitted. An even older alternate way to produce the same effect in ancient versions of Autoconf is to create the files '*file*.top' (typically 'config.h.top') and/or '*file*.bot' in the current directory. If they exist, autoheader copies them to the beginning and end, respectively, of its output.

In former versions of Autoconf, the files used in preparing a software package for distribution were:

```
configure.ac --.   .------> autoconf* -----> configure
               +---+
[aclocal.m4] --+   `---.
[acsite.m4] ---'       |
                       +--> [autoheader*] -> [config.h.in]
[acconfig.h] ----.     |
                 +-----'
[config.h.top] --+
[config.h.bot] --'
```

Using only the AH_ macros, 'configure.ac' should be self-contained, and should not depend upon 'acconfig.h' etc.

17.3 Using autoupdate to Modernize 'configure.ac'

The autoupdate program updates a 'configure.ac' file that calls Autoconf macros by their old names to use the current macro names. In version 2 of Autoconf, most of the macros were renamed to use a more uniform and descriptive naming scheme. See Section 9.2 [Macro Names], page 145, for a description of the new scheme. Although the old names still work (see Section 17.4 [Obsolete Macros], page 243, for a list of the old macros and the corresponding new names), you can make your 'configure.ac' files more readable and make it easier to use the current Autoconf documentation if you update them to use the new macro names.

If given no arguments, autoupdate updates 'configure.ac', backing up the original version with the suffix '~' (or the value of the environment variable SIMPLE_BACKUP_SUFFIX, if that is set). If you give autoupdate an argument, it reads that file instead of 'configure.ac' and writes the updated file to the standard output.

autoupdate accepts the following options:

'`--help`'
'`-h`' Print a summary of the command line options and exit.

'`--version`'
'`-V`' Print the version number of Autoconf and exit.

'`--verbose`'
'`-v`' Report processing steps.

'`--debug`'
'`-d`' Don't remove the temporary files.

'`--force`'
'`-f`' Force the update even if the file has not changed. Disregard the cache.

'`--include=dir`'
'`-I dir`' Also look for input files in *dir*. Multiple invocations accumulate. Directories are browsed from last to first.

17.4 Obsolete Macros

Several macros are obsoleted in Autoconf, for various reasons (typically they failed to quote properly, couldn't be extended for more recent issues, etc.). They are still supported, but deprecated: their use should be avoided.

During the jump from Autoconf version 1 to version 2, most of the macros were renamed to use a more uniform and descriptive naming scheme, but their signature did not change. See Section 9.2 [Macro Names], page 145, for a description of the new naming scheme. Below, if there is just the mapping from old names to new names for these macros, the reader is invited to refer to the definition of the new macro for the signature and the description.

`AC_AIX` [Macro]
This macro is a platform-specific subset of `AC_USE_SYSTEM_EXTENSIONS` (see [AC_USE_SYSTEM_EXTENSIONS], page 87).

`AC_ALLOCA` [Macro]
Replaced by `AC_FUNC_ALLOCA` (see [AC_FUNC_ALLOCA], page 50).

`AC_ARG_ARRAY` [Macro]
Removed because of limited usefulness.

`AC_C_CROSS` [Macro]
This macro is obsolete; it does nothing.

`AC_C_LONG_DOUBLE` [Macro]
If the C compiler supports a working `long double` type with more range or precision than the `double` type, define `HAVE_LONG_DOUBLE`.

You should use `AC_TYPE_LONG_DOUBLE` or `AC_TYPE_LONG_DOUBLE_WIDER` instead. See Section 5.9.1 [Particular Types], page 69.

AC_CANONICAL_SYSTEM [Macro]

Determine the system type and set output variables to the names of the canonical system types. See Section 13.2 [Canonicalizing], page 222, for details about the variables this macro sets.

The user is encouraged to use either AC_CANONICAL_BUILD, or AC_CANONICAL_HOST, or AC_CANONICAL_TARGET, depending on the needs. Using AC_CANONICAL_TARGET is enough to run the two other macros (see Section 13.2 [Canonicalizing], page 222).

AC_CHAR_UNSIGNED [Macro]

Replaced by AC_C_CHAR_UNSIGNED (see [AC_C_CHAR_UNSIGNED], page 78).

AC_CHECK_TYPE (*type*, *default*) [Macro]

Autoconf, up to 2.13, used to provide this version of AC_CHECK_TYPE, deprecated because of its flaws. First, although it is a member of the CHECK clan, it does more than just checking. Secondly, missing types are defined using #define, not typedef, and this can lead to problems in the case of pointer types.

This use of AC_CHECK_TYPE is obsolete and discouraged; see Section 5.9.2 [Generic Types], page 71, for the description of the current macro.

If the type *type* is not defined, define it to be the C (or C++) builtin type *default*, e.g., 'short int' or 'unsigned int'.

This macro is equivalent to:

```
AC_CHECK_TYPE([type], [],
  [AC_DEFINE_UNQUOTED([type], [default],
     [Define to 'default'
      if <sys/types.h> does not define.])])
```

In order to keep backward compatibility, the two versions of AC_CHECK_TYPE are implemented, selected using these heuristics:

1. If there are three or four arguments, the modern version is used.
2. If the second argument appears to be a C or C++ type, then the obsolete version is used. This happens if the argument is a C or C++ *builtin* type or a C identifier ending in '_t', optionally followed by one of '[(* ' and then by a string of zero or more characters taken from the set '[]()* _a-zA-Z0-9'.
3. If the second argument is spelled with the alphabet of valid C and C++ types, the user is warned and the modern version is used.
4. Otherwise, the modern version is used.

You are encouraged either to use a valid builtin type, or to use the equivalent modern code (see above), or better yet, to use AC_CHECK_TYPES together with

```
#ifndef HAVE_LOFF_T
typedef loff_t off_t;
#endif
```

AC_CHECKING (*feature-description*) [Macro]

Same as

```
AC_MSG_NOTICE([checking feature-description...]
```

See [AC_MSG_NOTICE], page 110.

AC_COMPILE_CHECK (*echo-text*, *includes*, *function-body*, *action-if-true*, [*action-if-false*]) [Macro]

This is an obsolete version of AC_TRY_COMPILE itself replaced by AC_COMPILE_IFELSE (see Section 6.4 [Running the Compiler], page 97), with the addition that it prints 'checking for *echo-text*' to the standard output first, if *echo-text* is non-empty. Use AC_MSG_CHECKING and AC_MSG_RESULT instead to print messages (see Section 7.5 [Printing Messages], page 110).

AC_CONST [Macro]

Replaced by AC_C_CONST (see [AC_C_CONST], page 77).

AC_CROSS_CHECK [Macro]

Same as AC_C_CROSS, which is obsolete too, and does nothing :-).

AC_CYGWIN [Macro]

Check for the Cygwin environment in which case the shell variable CYGWIN is set to 'yes'. Don't use this macro, the dignified means to check the nature of the host is using AC_CANONICAL_HOST (see Section 13.2 [Canonicalizing], page 222). As a matter of fact this macro is defined as:

```
AC_REQUIRE([AC_CANONICAL_HOST])[]dnl
case $host_os in
  *cygwin* ) CYGWIN=yes;;
         * ) CYGWIN=no;;
esac
```

Beware that the variable CYGWIN has a special meaning when running Cygwin, and should not be changed. That's yet another reason not to use this macro.

AC_DECL_SYS_SIGLIST [Macro]

Same as:

```
AC_CHECK_DECLS([sys_siglist], [], [],
[#include <signal.h>
/* NetBSD declares sys_siglist in unistd.h.  */
#ifdef HAVE_UNISTD_H
# include <unistd.h>
#endif
])
```

See [AC_CHECK_DECLS], page 66.

AC_DECL_YYTEXT [Macro]

Does nothing, now integrated in AC_PROG_LEX (see [AC_PROG_LEX], page 42).

AC_DIR_HEADER [Macro]

Like calling AC_FUNC_CLOSEDIR_VOID (see [AC_FUNC_CLOSEDIR_VOID], page 51) and AC_HEADER_DIRENT (see [AC_HEADER_DIRENT], page 60), but defines a different set of C preprocessor macros to indicate which header file is found:

Header	Old Symbol	New Symbol
'dirent.h'	DIRENT	HAVE_DIRENT_H
'sys/ndir.h'	SYSNDIR	HAVE_SYS_NDIR_H

'sys/dir.h'	SYSDIR	HAVE_SYS_DIR_H
'ndir.h'	NDIR	HAVE_NDIR_H

AC_DYNIX_SEQ [Macro]

If on DYNIX/ptx, add '-lseq' to output variable LIBS. This macro used to be defined as

```
AC_CHECK_LIB([seq], [getmntent], [LIBS="-lseq $LIBS"])
```

now it is just AC_FUNC_GETMNTENT (see [AC_FUNC_GETMNTENT], page 53).

AC_EXEEXT [Macro]

Defined the output variable EXEEXT based on the output of the compiler, which is now done automatically. Typically set to empty string if Posix and '.exe' if a DOS variant.

AC_EMXOS2 [Macro]

Similar to AC_CYGWIN but checks for the EMX environment on OS/2 and sets EMXOS2. Don't use this macro, the dignified means to check the nature of the host is using AC_CANONICAL_HOST (see Section 13.2 [Canonicalizing], page 222).

AC_ENABLE (*feature*, *action-if-given*, [*action-if-not-given*]) [Macro]

This is an obsolete version of AC_ARG_ENABLE that does not support providing a help string (see [AC_ARG_ENABLE], page 228).

AC_ERROR [Macro]

Replaced by AC_MSG_ERROR (see [AC_MSG_ERROR], page 110).

AC_FIND_X [Macro]

Replaced by AC_PATH_X (see [AC_PATH_X], page 86).

AC_FIND_XTRA [Macro]

Replaced by AC_PATH_XTRA (see [AC_PATH_XTRA], page 86).

AC_FOREACH [Macro]

Replaced by m4_foreach_w (see [m4_foreach_w], page 132).

AC_FUNC_CHECK [Macro]

Replaced by AC_CHECK_FUNC (see [AC_CHECK_FUNC], page 56).

AC_FUNC_SETVBUF_REVERSED [Macro]

Do nothing. Formerly, this macro checked whether setvbuf takes the buffering type as its second argument and the buffer pointer as the third, instead of the other way around, and defined SETVBUF_REVERSED. However, the last systems to have the problem were those based on SVR2, which became obsolete in 1987, and the macro is no longer needed.

AC_FUNC_WAIT3 [Macro]

If wait3 is found and fills in the contents of its third argument (a 'struct rusage *'), which HP-UX does not do, define HAVE_WAIT3.

These days portable programs should use waitpid, not wait3, as wait3 has been removed from Posix.

`AC_GCC_TRADITIONAL` [Macro]
Replaced by `AC_PROG_GCC_TRADITIONAL` (see [AC_PROG_GCC_TRADITIONAL], page 79).

`AC_GETGROUPS_T` [Macro]
Replaced by `AC_TYPE_GETGROUPS` (see [AC_TYPE_GETGROUPS], page 69).

`AC_GETLOADAVG` [Macro]
Replaced by `AC_FUNC_GETLOADAVG` (see [AC_FUNC_GETLOADAVG], page 52).

`AC_GNU_SOURCE` [Macro]
This macro is a platform-specific subset of `AC_USE_SYSTEM_EXTENSIONS` (see [AC_USE_SYSTEM_EXTENSIONS], page 87).

`AC_HAVE_FUNCS` [Macro]
Replaced by `AC_CHECK_FUNCS` (see [AC_CHECK_FUNCS], page 57).

`AC_HAVE_HEADERS` [Macro]
Replaced by `AC_CHECK_HEADERS` (see [AC_CHECK_HEADERS], page 65).

`AC_HAVE_LIBRARY (`*`library`*`, [`*`action-if-found`*`], [`*`action-if-not-found`*`], [`*`other-libraries`*`])` [Macro]
This macro is equivalent to calling `AC_CHECK_LIB` with a *function* argument of `main`. In addition, *library* can be written as any of '`foo`', '`-lfoo`', or '`libfoo.a`'. In all of those cases, the compiler is passed '`-lfoo`'. However, *library* cannot be a shell variable; it must be a literal name. See [AC_CHECK_LIB], page 46.

`AC_HAVE_POUNDBANG` [Macro]
Replaced by `AC_SYS_INTERPRETER` (see [AC_SYS_INTERPRETER], page 86).

`AC_HEADER_CHECK` [Macro]
Replaced by `AC_CHECK_HEADER` (see [AC_CHECK_HEADER], page 65).

`AC_HEADER_EGREP` [Macro]
Replaced by `AC_EGREP_HEADER` (see [AC_EGREP_HEADER], page 97).

`AC_HELP_STRING` [Macro]
Replaced by `AS_HELP_STRING` (see [AS_HELP_STRING], page 228).

`AC_INIT (`*`unique-file-in-source-dir`*`)` [Macro]
Formerly `AC_INIT` used to have a single argument, and was equivalent to:

```
AC_INIT
AC_CONFIG_SRCDIR(unique-file-in-source-dir)
```

See [AC_INIT], page 17 and [AC_CONFIG_SRCDIR], page 19.

`AC_INLINE` [Macro]
Replaced by `AC_C_INLINE` (see [AC_C_INLINE], page 78).

`AC_INT_16_BITS` [Macro]
If the C type `int` is 16 bits wide, define `INT_16_BITS`. Use '`AC_CHECK_SIZEOF(int)`' instead (see [AC_CHECK_SIZEOF], page 73).

AC_IRIX_SUN [Macro]

If on IRIX (Silicon Graphics Unix), add '-lsun' to output LIBS. If you were using it to get getmntent, use AC_FUNC_GETMNTENT instead. If you used it for the NIS versions of the password and group functions, use 'AC_CHECK_LIB(sun, getpwnam)'. Up to Autoconf 2.13, it used to be

```
AC_CHECK_LIB([sun], [getmntent], [LIBS="-lsun $LIBS"])
```

now it is defined as

```
AC_FUNC_GETMNTENT
AC_CHECK_LIB([sun], [getpwnam])
```

See [AC_FUNC_GETMNTENT], page 53 and [AC_CHECK_LIB], page 46.

AC_ISC_POSIX [Macro]

This macro adds '-lcposix' to output variable LIBS if necessary for Posix facilities. Sun dropped support for the obsolete INTERACTIVE Systems Corporation Unix on 2006-07-23. New programs need not use this macro. It is implemented as AC_SEARCH_LIBS([strerror], [cposix]) (see [AC_SEARCH_LIBS], page 47).

AC_LANG_C [Macro]

Same as 'AC_LANG([C])' (see [AC_LANG], page 91).

AC_LANG_CPLUSPLUS [Macro]

Same as 'AC_LANG([C++])' (see [AC_LANG], page 91).

AC_LANG_FORTRAN77 [Macro]

Same as 'AC_LANG([Fortran 77])' (see [AC_LANG], page 91).

AC_LANG_RESTORE [Macro]

Select the *language* that is saved on the top of the stack, as set by AC_LANG_SAVE, remove it from the stack, and call AC_LANG(*language*). See Section 6.1 [Language Choice], page 91, for the preferred way to change languages.

AC_LANG_SAVE [Macro]

Remember the current language (as set by AC_LANG) on a stack. The current language does not change. AC_LANG_PUSH is preferred (see [AC_LANG_PUSH], page 92).

AC_LINK_FILES (*source*..., *dest*...) [Macro]

This is an obsolete version of AC_CONFIG_LINKS (see [AC_CONFIG_LINKS], page 36. An updated version of:

```
AC_LINK_FILES(config/$machine.h config/$obj_format.h,
              host.h            object.h)
```

is:

```
AC_CONFIG_LINKS([host.h:config/$machine.h
                object.h:config/$obj_format.h])
```

AC_LN_S [Macro]

Replaced by AC_PROG_LN_S (see [AC_PROG_LN_S], page 43).

`AC_LONG_64_BITS` [Macro]

Define `LONG_64_BITS` if the C type `long int` is 64 bits wide. Use the generic macro '`AC_CHECK_SIZEOF([long int])`' instead (see [AC_CHECK_SIZEOF], page 73).

`AC_LONG_DOUBLE` [Macro]

If the C compiler supports a working `long double` type with more range or precision than the `double` type, define `HAVE_LONG_DOUBLE`.

You should use `AC_TYPE_LONG_DOUBLE` or `AC_TYPE_LONG_DOUBLE_WIDER` instead. See Section 5.9.1 [Particular Types], page 69.

`AC_LONG_FILE_NAMES` [Macro]

Replaced by

```
AC_SYS_LONG_FILE_NAMES
```

See [AC_SYS_LONG_FILE_NAMES], page 87.

`AC_MAJOR_HEADER` [Macro]

Replaced by `AC_HEADER_MAJOR` (see [AC_HEADER_MAJOR], page 61).

`AC_MEMORY_H` [Macro]

Used to define `NEED_MEMORY_H` if the `mem` functions were defined in '`memory.h`'. Today it is equivalent to '`AC_CHECK_HEADERS([memory.h])`' (see [AC_CHECK_HEADERS], page 65). Adjust your code to depend upon `HAVE_MEMORY_H`, not `NEED_MEMORY_H`; see Section 5.1.1 [Standard Symbols], page 39.

`AC_MINGW32` [Macro]

Similar to `AC_CYGWIN` but checks for the MinGW compiler environment and sets `MINGW32`. Don't use this macro, the dignified means to check the nature of the host is using `AC_CANONICAL_HOST` (see Section 13.2 [Canonicalizing], page 222).

`AC_MINIX` [Macro]

This macro is a platform-specific subset of `AC_USE_SYSTEM_EXTENSIONS` (see [AC_USE_SYSTEM_EXTENSIONS], page 87).

`AC_MINUS_C_MINUS_O` [Macro]

Replaced by `AC_PROG_CC_C_O` (see [AC_PROG_CC_C_O], page 75).

`AC_MMAP` [Macro]

Replaced by `AC_FUNC_MMAP` (see [AC_FUNC_MMAP], page 54).

`AC_MODE_T` [Macro]

Replaced by `AC_TYPE_MODE_T` (see [AC_TYPE_MODE_T], page 70).

`AC_OBJEXT` [Macro]

Defined the output variable `OBJEXT` based on the output of the compiler, after .c files have been excluded. Typically set to '`o`' if Posix, '`obj`' if a DOS variant. Now the compiler checking macros handle this automatically.

`AC_OBSOLETE (`*`this-macro-name`*`, [`*`suggestion`*`])` [Macro]

Make M4 print a message to the standard error output warning that *this-macro-name* is obsolete, and giving the file and line number where it was called. *this-macro-name*

should be the name of the macro that is calling AC_OBSOLETE. If *suggestion* is given, it is printed at the end of the warning message; for example, it can be a suggestion for what to use instead of *this-macro-name*.

For instance

```
AC_OBSOLETE([$0], [; use AC_CHECK_HEADERS(unistd.h) instead])dnl
```

You are encouraged to use AU_DEFUN instead, since it gives better services to the user (see [AU_DEFUN], page 150).

AC_OFF_T [Macro]

Replaced by AC_TYPE_OFF_T (see [AC_TYPE_OFF_T], page 70).

AC_OUTPUT ([*file*]..., [*extra-cmds*], [*init-cmds*]) [Macro]

The use of AC_OUTPUT with arguments is deprecated. This obsoleted interface is equivalent to:

```
AC_CONFIG_FILES(file...)
AC_CONFIG_COMMANDS([default],
                   extra-cmds, init-cmds)
AC_OUTPUT
```

See [AC_CONFIG_FILES], page 22, [AC_CONFIG_COMMANDS], page 35, and [AC_OUTPUT], page 20.

AC_OUTPUT_COMMANDS (*extra-cmds*, [*init-cmds*]) [Macro]

Specify additional shell commands to run at the end of 'config.status', and shell commands to initialize any variables from configure. This macro may be called multiple times. It is obsolete, replaced by AC_CONFIG_COMMANDS (see [AC_CONFIG_COMMANDS], page 35).

Here is an unrealistic example:

```
fubar=27
AC_OUTPUT_COMMANDS([echo this is extra $fubar, and so on.],
                   [fubar=$fubar])
AC_OUTPUT_COMMANDS([echo this is another, extra, bit],
                   [echo init bit])
```

Aside from the fact that AC_CONFIG_COMMANDS requires an additional key, an important difference is that AC_OUTPUT_COMMANDS is quoting its arguments twice, unlike AC_CONFIG_COMMANDS. This means that AC_CONFIG_COMMANDS can safely be given macro calls as arguments:

```
AC_CONFIG_COMMANDS(foo, [my_FOO()])
```

Conversely, where one level of quoting was enough for literal strings with AC_OUTPUT_COMMANDS, you need two with AC_CONFIG_COMMANDS. The following lines are equivalent:

```
AC_OUTPUT_COMMANDS([echo "Square brackets: []"])
AC_CONFIG_COMMANDS([default], [[echo "Square brackets: []"]])
```

AC_PID_T [Macro]

Replaced by AC_TYPE_PID_T (see [AC_TYPE_PID_T], page 70).

AC_PREFIX [Macro]

Replaced by AC_PREFIX_PROGRAM (see [AC_PREFIX_PROGRAM], page 38).

AC_PROGRAMS_CHECK [Macro]

Replaced by AC_CHECK_PROGS (see [AC_CHECK_PROGS], page 44).

AC_PROGRAMS_PATH [Macro]

Replaced by AC_PATH_PROGS (see [AC_PATH_PROGS], page 45).

AC_PROGRAM_CHECK [Macro]

Replaced by AC_CHECK_PROG (see [AC_CHECK_PROG], page 44).

AC_PROGRAM_EGREP [Macro]

Replaced by AC_EGREP_CPP (see [AC_EGREP_CPP], page 97).

AC_PROGRAM_PATH [Macro]

Replaced by AC_PATH_PROG (see [AC_PATH_PROG], page 45).

AC_REMOTE_TAPE [Macro]

Removed because of limited usefulness.

AC_RESTARTABLE_SYSCALLS [Macro]

This macro was renamed AC_SYS_RESTARTABLE_SYSCALLS. However, these days portable programs should use sigaction with SA_RESTART if they want restartable system calls. They should not rely on HAVE_RESTARTABLE_SYSCALLS, since nowadays whether a system call is restartable is a dynamic issue, not a configuration-time issue.

AC_RETSIGTYPE [Macro]

Replaced by AC_TYPE_SIGNAL (see [AC_TYPE_SIGNAL], page 70).

AC_RSH [Macro]

Removed because of limited usefulness.

AC_SCO_INTL [Macro]

If on SCO Unix, add '-lintl' to output variable LIBS. This macro used to do this:

```
AC_CHECK_LIB([intl], [strftime], [LIBS="-lintl $LIBS"])
```

Now it just calls AC_FUNC_STRFTIME instead (see [AC_FUNC_STRFTIME], page 55).

AC_SETVBUF_REVERSED [Macro]

Replaced by

```
AC_FUNC_SETVBUF_REVERSED
```

See [AC_FUNC_SETVBUF_REVERSED], page 246.

AC_SET_MAKE [Macro]

Replaced by AC_PROG_MAKE_SET (see [AC_PROG_MAKE_SET], page 20).

AC_SIZEOF_TYPE [Macro]

Replaced by AC_CHECK_SIZEOF (see [AC_CHECK_SIZEOF], page 73).

AC_SIZE_T [Macro]

Replaced by AC_TYPE_SIZE_T (see [AC_TYPE_SIZE_T], page 71).

AC_STAT_MACROS_BROKEN [Macro]

Replaced by AC_HEADER_STAT (see [AC_HEADER_STAT], page 62).

AC_STDC_HEADERS [Macro]

Replaced by AC_HEADER_STDC (see [AC_HEADER_STDC], page 62).

AC_STRCOLL [Macro]

Replaced by AC_FUNC_STRCOLL (see [AC_FUNC_STRCOLL], page 55).

AC_STRUCT_ST_BLKSIZE [Macro]

If struct stat contains an st_blksize member, define HAVE_STRUCT_STAT_ST_BLKSIZE. The former name, HAVE_ST_BLKSIZE is to be avoided, as its support will cease in the future. This macro is obsoleted, and should be replaced by

```
AC_CHECK_MEMBERS([struct stat.st_blksize])
```

See [AC_CHECK_MEMBERS], page 68.

AC_STRUCT_ST_RDEV [Macro]

If struct stat contains an st_rdev member, define HAVE_STRUCT_STAT_ST_RDEV. The former name for this macro, HAVE_ST_RDEV, is to be avoided as it will cease to be supported in the future. Actually, even the new macro is obsolete and should be replaced by:

```
AC_CHECK_MEMBERS([struct stat.st_rdev])
```

See [AC_CHECK_MEMBERS], page 68.

AC_ST_BLKSIZE [Macro]

Replaced by AC_CHECK_MEMBERS (see [AC_CHECK_MEMBERS], page 68).

AC_ST_BLOCKS [Macro]

Replaced by AC_STRUCT_ST_BLOCKS (see [AC_STRUCT_ST_BLOCKS], page 68).

AC_ST_RDEV [Macro]

Replaced by AC_CHECK_MEMBERS (see [AC_CHECK_MEMBERS], page 68).

AC_SYS_RESTARTABLE_SYSCALLS [Macro]

If the system automatically restarts a system call that is interrupted by a signal, define HAVE_RESTARTABLE_SYSCALLS. This macro does not check whether system calls are restarted in general—it checks whether a signal handler installed with signal (but not sigaction) causes system calls to be restarted. It does not check whether system calls can be restarted when interrupted by signals that have no handler.

These days portable programs should use sigaction with SA_RESTART if they want restartable system calls. They should not rely on HAVE_RESTARTABLE_SYSCALLS, since nowadays whether a system call is restartable is a dynamic issue, not a configuration-time issue.

AC_SYS_SIGLIST_DECLARED [Macro]

This macro was renamed AC_DECL_SYS_SIGLIST. However, even that name is obsolete, as the same functionality is now acheived via AC_CHECK_DECLS (see [AC_CHECK_DECLS], page 66).

`AC_TEST_CPP` [Macro]

This macro was renamed `AC_TRY_CPP`, which in turn was replaced by `AC_PREPROC_IFELSE` (see [AC_PREPROC_IFELSE], page 96).

`AC_TEST_PROGRAM` [Macro]

This macro was renamed `AC_TRY_RUN`, which in turn was replaced by `AC_RUN_IFELSE` (see [AC_RUN_IFELSE], page 98).

`AC_TIMEZONE` [Macro]

Replaced by `AC_STRUCT_TIMEZONE` (see [AC_STRUCT_TIMEZONE], page 68).

`AC_TIME_WITH_SYS_TIME` [Macro]

Replaced by `AC_HEADER_TIME` (see [AC_HEADER_TIME], page 64).

`AC_TRY_COMPILE (`*`includes`*`, `*`function-body`*`, [`*`action-if-true`*`], [`*`action-if-false`*`])` [Macro]

Same as:

```
AC_COMPILE_IFELSE(
  [AC_LANG_PROGRAM([[includes]],
     [[function-body]])],
  [action-if-true],
  [action-if-false])
```

See Section 6.4 [Running the Compiler], page 97.

This macro double quotes both *includes* and *function-body*.

For C and C++, *includes* is any `#include` statements needed by the code in *function-body* (*includes* is ignored if the currently selected language is Fortran or Fortran 77). The compiler and compilation flags are determined by the current language (see Section 6.1 [Language Choice], page 91).

`AC_TRY_CPP (`*`input`*`, [`*`action-if-true`*`], [`*`action-if-false`*`])` [Macro]

Same as:

```
AC_PREPROC_IFELSE(
  [AC_LANG_SOURCE([[input]])],
  [action-if-true],
  [action-if-false])
```

See Section 6.3 [Running the Preprocessor], page 96.

This macro double quotes the *input*.

`AC_TRY_LINK (`*`includes`*`, `*`function-body`*`, [`*`action-if-true`*`], [`*`action-if-false`*`])` [Macro]

Same as:

```
AC_LINK_IFELSE(
  [AC_LANG_PROGRAM([[includes]],
     [[function-body]])],
  [action-if-true],
  [action-if-false])
```

See Section 6.4 [Running the Compiler], page 97.

This macro double quotes both *includes* and *function-body*.

Depending on the current language (see Section 6.1 [Language Choice], page 91), create a test program to see whether a function whose body consists of *function-body* can be compiled and linked. If the file compiles and links successfully, run shell commands *action-if-found*, otherwise run *action-if-not-found*.

This macro double quotes both *includes* and *function-body*.

For C and C++, *includes* is any `#include` statements needed by the code in *function-body* (*includes* is ignored if the currently selected language is Fortran or Fortran 77). The compiler and compilation flags are determined by the current language (see Section 6.1 [Language Choice], page 91), and in addition `LDFLAGS` and `LIBS` are used for linking.

`AC_TRY_LINK_FUNC` (*function*, [*action-if-found*], [*action-if-not-found*]) [Macro]

This macro is equivalent to

```
AC_LINK_IFELSE([AC_LANG_CALL([], [function])],
  [action-if-found], [action-if-not-found])
```

See [AC_LINK_IFELSE], page 98.

`AC_TRY_RUN` (*program*, [*action-if-true*], [*action-if-false*], [*action-if-cross-compiling*]) [Macro]

Same as:

```
AC_RUN_IFELSE(
  [AC_LANG_SOURCE([[program]])],
  [action-if-true],
  [action-if-false],
  [action-if-cross-compiling])
```

See Section 6.6 [Runtime], page 98.

`AC_UID_T` [Macro]

Replaced by `AC_TYPE_UID_T` (see [AC_TYPE_UID_T], page 71).

`AC_UNISTD_H` [Macro]

Same as '`AC_CHECK_HEADERS([unistd.h])`' (see [AC_CHECK_HEADERS], page 65).

`AC_USG` [Macro]

Define `USG` if the BSD string functions are defined in '`strings.h`'. You should no longer depend upon `USG`, but on `HAVE_STRING_H`; see Section 5.1.1 [Standard Symbols], page 39.

`AC_UTIME_NULL` [Macro]

Replaced by `AC_FUNC_UTIME_NULL` (see [AC_FUNC_UTIME_NULL], page 56).

`AC_VALIDATE_CACHED_SYSTEM_TUPLE` ([*cmd*]) [Macro]

If the cache file is inconsistent with the current host, target and build system types, it used to execute *cmd* or print a default error message. This is now handled by default.

`AC_VERBOSE` (*result-description*) [Macro]

Replaced by `AC_MSG_RESULT` (see [AC_MSG_RESULT], page 110).

AC_VFORK [Macro]
Replaced by AC_FUNC_FORK (see [AC_FUNC_FORK], page 52).

AC_VPRINTF [Macro]
Replaced by AC_FUNC_VPRINTF (see [AC_FUNC_VPRINTF], page 56).

AC_WAIT3 [Macro]
This macro was renamed AC_FUNC_WAIT3. However, these days portable programs should use waitpid, not wait3, as wait3 has been removed from Posix.

AC_WARN [Macro]
Replaced by AC_MSG_WARN (see [AC_MSG_WARN], page 111).

AC_WITH (*package*, *action-if-given*, [*action-if-not-given*]) [Macro]
This is an obsolete version of AC_ARG_WITH that does not support providing a help string (see [AC_ARG_WITH], page 226).

AC_WORDS_BIGENDIAN [Macro]
Replaced by AC_C_BIGENDIAN (see [AC_C_BIGENDIAN], page 77).

AC_XENIX_DIR [Macro]
This macro used to add '-lx' to output variable LIBS if on Xenix. Also, if 'dirent.h' is being checked for, added '-ldir' to LIBS. Now it is merely an alias of AC_HEADER_DIRENT instead, plus some code to detect whether running XENIX on which you should not depend:

```
AC_MSG_CHECKING([for Xenix])
AC_EGREP_CPP([yes],
[#if defined M_XENIX && !defined M_UNIX
  yes
#endif],
             [AC_MSG_RESULT([yes]); XENIX=yes],
             [AC_MSG_RESULT([no]); XENIX=])
```

Don't use this macro, the dignified means to check the nature of the host is using AC_CANONICAL_HOST (see Section 13.2 [Canonicalizing], page 222).

AC_YYTEXT_POINTER [Macro]
This macro was renamed AC_DECL_YYTEXT, which in turn was integrated into AC_PROG_LEX (see [AC_PROG_LEX], page 42).

17.5 Upgrading From Version 1

Autoconf version 2 is mostly backward compatible with version 1. However, it introduces better ways to do some things, and doesn't support some of the ugly things in version 1. So, depending on how sophisticated your 'configure.ac' files are, you might have to do some manual work in order to upgrade to version 2. This chapter points out some problems to watch for when upgrading. Also, perhaps your configure scripts could benefit from some of the new features in version 2; the changes are summarized in the file 'NEWS' in the Autoconf distribution.

17.5.1 Changed File Names

If you have an 'aclocal.m4' installed with Autoconf (as opposed to in a particular package's source directory), you must rename it to 'acsite.m4'. See Section 3.4 [autoconf Invocation], page 12.

If you distribute 'install.sh' with your package, rename it to 'install-sh' so make builtin rules don't inadvertently create a file called 'install' from it. AC_PROG_INSTALL looks for the script under both names, but it is best to use the new name.

If you were using 'config.h.top', 'config.h.bot', or 'acconfig.h', you still can, but you have less clutter if you use the AH_ macros. See Section 4.9.3 [Autoheader Macros], page 35.

17.5.2 Changed Makefiles

Add '@CFLAGS@', '@CPPFLAGS@', and '@LDFLAGS@' in your 'Makefile.in' files, so they can take advantage of the values of those variables in the environment when configure is run. Doing this isn't necessary, but it's a convenience for users.

Also add '@configure_input@' in a comment to each input file for AC_OUTPUT, so that the output files contain a comment saying they were produced by configure. Automatically selecting the right comment syntax for all the kinds of files that people call AC_OUTPUT on became too much work.

Add 'config.log' and 'config.cache' to the list of files you remove in distclean targets.

If you have the following in 'Makefile.in':

```
prefix = /usr/local
exec_prefix = $(prefix)
```

you must change it to:

```
prefix = @prefix@
exec_prefix = @exec_prefix@
```

The old behavior of replacing those variables without '@' characters around them has been removed.

17.5.3 Changed Macros

Many of the macros were renamed in Autoconf version 2. You can still use the old names, but the new ones are clearer, and it's easier to find the documentation for them. See Section 17.4 [Obsolete Macros], page 243, for a table showing the new names for the old macros. Use the autoupdate program to convert your 'configure.ac' to using the new macro names. See Section 17.3 [autoupdate Invocation], page 242.

Some macros have been superseded by similar ones that do the job better, but are not call-compatible. If you get warnings about calling obsolete macros while running autoconf, you may safely ignore them, but your configure script generally works better if you follow the advice that is printed about what to replace the obsolete macros with. In particular, the mechanism for reporting the results of tests has changed. If you were using echo or AC_VERBOSE (perhaps via AC_COMPILE_CHECK), your configure script's output looks better if you switch to AC_MSG_CHECKING and AC_MSG_RESULT. See Section 7.5 [Printing Messages], page 110. Those macros work best in conjunction with cache variables. See Section 7.4 [Caching Results], page 107.

17.5.4 Changed Results

If you were checking the results of previous tests by examining the shell variable DEFS, you need to switch to checking the values of the cache variables for those tests. DEFS no longer exists while configure is running; it is only created when generating output files. This difference from version 1 is because properly quoting the contents of that variable turned out to be too cumbersome and inefficient to do every time AC_DEFINE is called. See Section 7.4.1 [Cache Variable Names], page 108.

For example, here is a 'configure.ac' fragment written for Autoconf version 1:

```
AC_HAVE_FUNCS(syslog)
case "$DEFS" in
*-DHAVE_SYSLOG*) ;;
*) # syslog is not in the default libraries.  See if it's in some other.
  saved_LIBS="$LIBS"
  for lib in bsd socket inet; do
    AC_CHECKING(for syslog in -l$lib)
    LIBS="-l$lib $saved_LIBS"
    AC_HAVE_FUNCS(syslog)
    case "$DEFS" in
    *-DHAVE_SYSLOG*) break ;;
    *) ;;
    esac
    LIBS="$saved_LIBS"
  done ;;
esac
```

Here is a way to write it for version 2:

```
AC_CHECK_FUNCS([syslog])
if test $ac_cv_func_syslog = no; then
  # syslog is not in the default libraries.  See if it's in some other.
  for lib in bsd socket inet; do
    AC_CHECK_LIB([$lib], [syslog], [AC_DEFINE([HAVE_SYSLOG])
      LIBS="-l$lib $LIBS"; break])
  done
fi
```

If you were working around bugs in AC_DEFINE_UNQUOTED by adding backslashes before quotes, you need to remove them. It now works predictably, and does not treat quotes (except back quotes) specially. See Section 7.2 [Setting Output Variables], page 104.

All of the Boolean shell variables set by Autoconf macros now use 'yes' for the true value. Most of them use 'no' for false, though for backward compatibility some use the empty string instead. If you were relying on a shell variable being set to something like 1 or 't' for true, you need to change your tests.

17.5.5 Changed Macro Writing

When defining your own macros, you should now use AC_DEFUN instead of define. AC_DEFUN automatically calls AC_PROVIDE and ensures that macros called via AC_REQUIRE do not interrupt other macros, to prevent nested 'checking...' messages on the screen. There's

no actual harm in continuing to use the older way, but it's less convenient and attractive. See Section 9.1 [Macro Definitions], page 145.

You probably looked at the macros that came with Autoconf as a guide for how to do things. It would be a good idea to take a look at the new versions of them, as the style is somewhat improved and they take advantage of some new features.

If you were doing tricky things with undocumented Autoconf internals (macros, variables, diversions), check whether you need to change anything to account for changes that have been made. Perhaps you can even use an officially supported technique in version 2 instead of kludging. Or perhaps not.

To speed up your locally written feature tests, add caching to them. See whether any of your tests are of general enough usefulness to encapsulate them into macros that you can share.

17.6 Upgrading From Version 2.13

The introduction of the previous section (see Section 17.5 [Autoconf 1], page 255) perfectly suits this section. . .

> Autoconf version 2.50 is mostly backward compatible with version 2.13. However, it introduces better ways to do some things, and doesn't support some of the ugly things in version 2.13. So, depending on how sophisticated your '`configure.ac`' files are, you might have to do some manual work in order to upgrade to version 2.50. This chapter points out some problems to watch for when upgrading. Also, perhaps your `configure` scripts could benefit from some of the new features in version 2.50; the changes are summarized in the file '`NEWS`' in the Autoconf distribution.

17.6.1 Changed Quotation

The most important changes are invisible to you: the implementation of most macros have completely changed. This allowed more factorization of the code, better error messages, a higher uniformity of the user's interface etc. Unfortunately, as a side effect, some construct which used to (miraculously) work might break starting with Autoconf 2.50. The most common culprit is bad quotation.

For instance, in the following example, the message is not properly quoted:

```
AC_INIT
AC_CHECK_HEADERS(foo.h, ,
  AC_MSG_ERROR(cannot find foo.h, bailing out))
AC_OUTPUT
```

Autoconf 2.13 simply ignores it:

```
$ autoconf-2.13; ./configure --silent
creating cache ./config.cache
configure: error: cannot find foo.h
$
```

while Autoconf 2.50 produces a broken '`configure`':

```
$ autoconf-2.50; ./configure --silent
configure: error: cannot find foo.h
```

```
./configure: exit: bad non-numeric arg ‘bailing’
./configure: exit: bad non-numeric arg ‘bailing’
$
```

The message needs to be quoted, and the AC_MSG_ERROR invocation too!

```
AC_INIT([Example], [1.0], [bug-example@example.org])
AC_CHECK_HEADERS([foo.h], [],
  [AC_MSG_ERROR([cannot find foo.h, bailing out])])
AC_OUTPUT
```

Many many (and many more) Autoconf macros were lacking proper quotation, including no less than... AC_DEFUN itself!

```
$ cat configure.in
AC_DEFUN([AC_PROG_INSTALL],
[# My own much better version
])
AC_INIT
AC_PROG_INSTALL
AC_OUTPUT
$ autoconf-2.13
autoconf: Undefined macros:
***BUG in Autoconf--please report*** AC_FD_MSG
***BUG in Autoconf--please report*** AC_EPI
configure.in:1:AC_DEFUN([AC_PROG_INSTALL],
configure.in:5:AC_PROG_INSTALL
$ autoconf-2.50
$
```

17.6.2 New Macros

While Autoconf was relatively dormant in the late 1990s, Automake provided Autoconf-like macros for a while. Starting with Autoconf 2.50 in 2001, Autoconf provided versions of these macros, integrated in the AC_ namespace, instead of AM_. But in order to ease the upgrading via autoupdate, bindings to such AM_ macros are provided.

Unfortunately older versions of Automake (e.g., Automake 1.4) did not quote the names of these macros. Therefore, when m4 finds something like ‘AC_DEFUN(AM_TYPE_PTRDIFF_T, ...)’ in ‘aclocal.m4’, AM_TYPE_PTRDIFF_T is expanded, replaced with its Autoconf definition.

Fortunately Autoconf catches pre-AC_INIT expansions, and complains, in its own words:

```
$ cat configure.ac
AC_INIT([Example], [1.0], [bug-example@example.org])
AM_TYPE_PTRDIFF_T
$ aclocal-1.4
$ autoconf
aclocal.m4:17: error: m4_defn: undefined macro: _m4_divert_diversion
aclocal.m4:17: the top level
autom4te: m4 failed with exit status: 1
$
```

Modern versions of Automake no longer define most of these macros, and properly quote the names of the remaining macros. If you must use an old Automake, do not depend upon macros from Automake as it is simply not its job to provide macros (but the one it requires itself):

```
$ cat configure.ac
AC_INIT([Example], [1.0], [bug-example@example.org])
AM_TYPE_PTRDIFF_T
$ rm aclocal.m4
$ autoupdate
autoupdate: ‘configure.ac’ is updated
$ cat configure.ac
AC_INIT([Example], [1.0], [bug-example@example.org])
AC_CHECK_TYPES([ptrdiff_t])
$ aclocal-1.4
$ autoconf
$
```

17.6.3 Hosts and Cross-Compilation

Based on the experience of compiler writers, and after long public debates, many aspects of the cross-compilation chain have changed:

- the relationship between the build, host, and target architecture types,
- the command line interface for specifying them to `configure`,
- the variables defined in `configure`,
- the enabling of cross-compilation mode.

The relationship between build, host, and target have been cleaned up: the chain of default is now simply: target defaults to host, host to build, and build to the result of `config.guess`. Nevertheless, in order to ease the transition from 2.13 to 2.50, the following transition scheme is implemented. *Do not rely on it*, as it will be completely disabled in a couple of releases (we cannot keep it, as it proves to cause more problems than it cures).

They all default to the result of running `config.guess`, unless you specify either ‘`--build`’ or ‘`--host`’. In this case, the default becomes the system type you specified. If you specify both, and they’re different, `configure` enters cross compilation mode, so it doesn’t run any tests that require execution.

Hint: if you mean to override the result of `config.guess`, prefer ‘`--build`’ over ‘`--host`’. In the future, ‘`--host`’ will not override the name of the build system type. Whenever you specify ‘`--host`’, be sure to specify ‘`--build`’ too.

For backward compatibility, `configure` accepts a system type as an option by itself. Such an option overrides the defaults for build, host, and target system types. The following configure statement configures a cross toolchain that runs on NetBSD/alpha but generates code for GNU Hurd/sparc, which is also the build platform.

```
./configure --host=alpha-netbsd sparc-gnu
```

In Autoconf 2.13 and before, the variables `build`, `host`, and `target` had a different semantics before and after the invocation of `AC_CANONICAL_BUILD` etc. Now, the argument of '`--build`' is strictly copied into `build_alias`, and is left empty otherwise. After the `AC_CANONICAL_BUILD`, `build` is set to the canonicalized build type. To ease the transition, before, its contents is the same as that of `build_alias`. Do *not* rely on this broken feature.

For consistency with the backward compatibility scheme exposed above, when '`--host`' is specified but '`--build`' isn't, the build system is assumed to be the same as '`--host`', and '`build_alias`' is set to that value. Eventually, this historically incorrect behavior will go away.

The former scheme to enable cross-compilation proved to cause more harm than good, in particular, it used to be triggered too easily, leaving regular end users puzzled in front of cryptic error messages. `configure` could even enter cross-compilation mode only because the compiler was not functional. This is mainly because `configure` used to try to detect cross-compilation, instead of waiting for an explicit flag from the user.

Now, `configure` enters cross-compilation mode if and only if '`--host`' is passed.

That's the short documentation. To ease the transition between 2.13 and its successors, a more complicated scheme is implemented. *Do not rely on the following*, as it will be removed in the near future.

If you specify '`--host`', but not '`--build`', when `configure` performs the first compiler test it tries to run an executable produced by the compiler. If the execution fails, it enters cross-compilation mode. This is fragile. Moreover, by the time the compiler test is performed, it may be too late to modify the build-system type: other tests may have already been performed. Therefore, whenever you specify '`--host`', be sure to specify '`--build`' too.

```
./configure --build=i686-pc-linux-gnu --host=m68k-coff
```

enters cross-compilation mode. The former interface, which consisted in setting the compiler to a cross-compiler without informing `configure` is obsolete. For instance, `configure` fails if it can't run the code generated by the specified compiler if you configure as follows:

```
./configure CC=m68k-coff-gcc
```

17.6.4 `AC_LIBOBJ` vs. `LIBOBJS`

Up to Autoconf 2.13, the replacement of functions was triggered via the variable `LIBOBJS`. Since Autoconf 2.50, the macro `AC_LIBOBJ` should be used instead (see Section 5.5.3 [Generic Functions], page 56). Starting at Autoconf 2.53, the use of `LIBOBJS` is an error.

This change is mandated by the unification of the GNU Build System components. In particular, the various fragile techniques used to parse a '`configure.ac`' are all replaced with the use of traces. As a consequence, any action must be traceable, which obsoletes critical variable assignments. Fortunately, `LIBOBJS` was the only problem, and it can even be handled gracefully (read, "without your having to change something").

There were two typical uses of `LIBOBJS`: asking for a replacement function, and adjusting `LIBOBJS` for Automake and/or Libtool.

As for function replacement, the fix is immediate: use `AC_LIBOBJ`. For instance:

```
LIBOBJS="$LIBOBJS fnmatch.o"
LIBOBJS="$LIBOBJS malloc.$ac_objext"
```

should be replaced with:

```
AC_LIBOBJ([fnmatch])
AC_LIBOBJ([malloc])
```

When used with Automake 1.10 or newer, a suitable value for `LIBOBJDIR` is set so that the `LIBOBJS` and `LTLIBOBJS` can be referenced from any '`Makefile.am`'. Even without Automake, arranging for `LIBOBJDIR` to be set correctly enables referencing `LIBOBJS` and `LTLIBOBJS` in another directory. The `LIBOBJDIR` feature is experimental.

17.6.5 `AC_FOO_IFELSE` vs. `AC_TRY_FOO`

Since Autoconf 2.50, internal codes uses `AC_PREPROC_IFELSE`, `AC_COMPILE_IFELSE`, `AC_LINK_IFELSE`, and `AC_RUN_IFELSE` on one hand and `AC_LANG_SOURCES`, and `AC_LANG_PROGRAM` on the other hand instead of the deprecated `AC_TRY_CPP`, `AC_TRY_COMPILE`, `AC_TRY_LINK`, and `AC_TRY_RUN`. The motivations where:

- a more consistent interface: `AC_TRY_COMPILE` etc. were double quoting their arguments;
- the combinatoric explosion is solved by decomposing on the one hand the generation of sources, and on the other hand executing the program;
- this scheme helps supporting more languages than plain C and C++.

In addition to the change of syntax, the philosophy has changed too: while emphasis was put on speed at the expense of accuracy, today's Autoconf promotes accuracy of the testing framework at, ahem. . . , the expense of speed.

As a perfect example of what is *not* to be done, here is how to find out whether a header file contains a particular declaration, such as a typedef, a structure, a structure member, or a function. Use `AC_EGREP_HEADER` instead of running `grep` directly on the header file; on some systems the symbol might be defined in another header file that the file you are checking includes.

As a (bad) example, here is how you should not check for C preprocessor symbols, either defined by header files or predefined by the C preprocessor: using `AC_EGREP_CPP`:

```
AC_EGREP_CPP(yes,
[#ifdef _AIX
  yes
#endif
], is_aix=yes, is_aix=no)
```

The above example, properly written would (i) use `AC_LANG_PROGRAM`, and (ii) run the compiler:

```
AC_COMPILE_IFELSE([AC_LANG_PROGRAM(
[[#ifndef _AIX
 error: This isn't AIX!
#endif
]])],
                   [is_aix=yes],
                   [is_aix=no])
```

18 Generating Test Suites with Autotest

N.B.: This section describes an experimental feature which will be part of Autoconf in a forthcoming release. Although we believe Autotest is stabilizing, this documentation describes an interface which might change in the future: do not depend upon Autotest without subscribing to the Autoconf mailing lists.

It is paradoxical that portable projects depend on nonportable tools to run their test suite. Autoconf by itself is the paragon of this problem: although it aims at perfectly portability, up to 2.13 its test suite was using DejaGNU, a rich and complex testing framework, but which is far from being standard on Posix systems. Worse yet, it was likely to be missing on the most fragile platforms, the very platforms that are most likely to torture Autoconf and exhibit deficiencies.

To circumvent this problem, many package maintainers have developed their own testing framework, based on simple shell scripts whose sole outputs are exit status values describing whether the test succeeded. Most of these tests share common patterns, and this can result in lots of duplicated code and tedious maintenance.

Following exactly the same reasoning that yielded to the inception of Autoconf, Autotest provides a test suite generation framework, based on M4 macros building a portable shell script. The suite itself is equipped with automatic logging and tracing facilities which greatly diminish the interaction with bug reporters, and simple timing reports.

Autoconf itself has been using Autotest for years, and we do attest that it has considerably improved the strength of the test suite and the quality of bug reports. Other projects are known to use some generation of Autotest, such as Bison, Free Recode, Free Wdiff, GNU Tar, each of them with different needs, and this usage has validated Autotest as a general testing framework.

Nonetheless, compared to DejaGNU, Autotest is inadequate for interactive tool testing, which is probably its main limitation.

18.1 Using an Autotest Test Suite

18.1.1 `testsuite` Scripts

Generating testing or validation suites using Autotest is rather easy. The whole validation suite is held in a file to be processed through `autom4te`, itself using GNU M4 under the scene, to produce a stand-alone Bourne shell script which then gets distributed. Neither `autom4te` nor GNU M4 are needed at the installer's end.

Each test of the validation suite should be part of some test group. A *test group* is a sequence of interwoven tests that ought to be executed together, usually because one test in the group creates data files than a later test in the same group needs to read. Complex test groups make later debugging more tedious. It is much better to keep only a few tests per test group. Ideally there is only one test per test group.

For all but the simplest packages, some file such as '`testsuite.at`' does not fully hold all test sources, as these are often easier to maintain in separate files. Each of these separate files holds a single test group, or a sequence of test groups all addressing some common functionality in the package. In such cases, '`testsuite.at`' merely initializes the validation

suite, and sometimes does elementary health checking, before listing include statements for all other test files. The special file '`package.m4`', containing the identification of the package, is automatically included if found.

A convenient alternative consists in moving all the global issues (local Autotest macros, elementary health checking, and `AT_INIT` invocation) into the file `local.at`, and making '`testsuite.at`' be a simple list of `m4_include` of sub test suites. In such case, generating the whole test suite or pieces of it is only a matter of choosing the `autom4te` command line arguments.

The validation scripts that Autotest produces are by convention called `testsuite`. When run, `testsuite` executes each test group in turn, producing only one summary line per test to say if that particular test succeeded or failed. At end of all tests, summarizing counters get printed. One debugging directory is left for each test group which failed, if any: such directories are named '`testsuite.dir/`*nn*', where *nn* is the sequence number of the test group, and they include:

- a debugging script named '`run`' which reruns the test in *debug mode* (see Section 18.3 [testsuite Invocation], page 267). The automatic generation of debugging scripts has the purpose of easing the chase for bugs.
- all the files created with `AT_DATA`
- a log of the run, named '`testsuite.log`'

In the ideal situation, none of the tests fail, and consequently no debugging directory is left behind for validation.

It often happens in practice that individual tests in the validation suite need to get information coming out of the configuration process. Some of this information, common for all validation suites, is provided through the file '`atconfig`', automatically created by `AC_CONFIG_TESTDIR`. For configuration informations which your testing environment specifically needs, you might prepare an optional file named '`atlocal.in`', instantiated by `AC_CONFIG_FILES`. The configuration process produces '`atconfig`' and '`atlocal`' out of these two input files, and these two produced files are automatically read by the '`testsuite`' script.

Here is a diagram showing the relationship between files.

Files used in preparing a software package for distribution:

```
                    [package.m4] -->.
                                     \
subfile-1.at ->.  [local.at] ---->+
    ...         \                  \
subfile-i.at ---->-- testsuite.at -->-- autom4te* -->testsuite
    ...         /
subfile-n.at ->'
```

Files used in configuring a software package:

```
                                        .--> atconfig
                                       /
[atlocal.in] -->  config.status* --<
                                       \
                                        `--> [atlocal]
```

Files created during the test suite execution:

```
atconfig -->.                    .--> testsuite.log
            \                   /
             >-- testsuite* --<
            /                   \
[atlocal] ->'                    '--> [testsuite.dir]
```

18.1.2 Autotest Logs

When run, the test suite creates a log file named after itself, e.g., a test suite named `testsuite` creates '`testsuite.log`'. It contains a lot of information, usually more than maintainers actually need, but therefore most of the time it contains all that is needed:

command line arguments
: A bad but unfortunately widespread habit consists of setting environment variables before the command, such as in '`CC=my-home-grown-cc ./testsuite`'. The test suite does not know this change, hence (i) it cannot report it to you, and (ii) it cannot preserve the value of `CC` for subsequent runs. Autoconf faced exactly the same problem, and solved it by asking users to pass the variable definitions as command line arguments. Autotest requires this rule, too, but has no means to enforce it; the log then contains a trace of the variables that were changed by the user.

'`ChangeLog`' excerpts
: The topmost lines of all the '`ChangeLog`' files found in the source hierarchy. This is especially useful when bugs are reported against development versions of the package, since the version string does not provide sufficient information to know the exact state of the sources the user compiled. Of course, this relies on the use of a '`ChangeLog`'.

build machine
: Running a test suite in a cross-compile environment is not an easy task, since it would mean having the test suite run on a machine *build*, while running programs on a machine *host*. It is much simpler to run both the test suite and the programs on *host*, but then, from the point of view of the test suite, there remains a single environment, *host* = *build*. The log contains relevant information on the state of the build machine, including some important environment variables.

tested programs
: The absolute file name and answers to '`--version`' of the tested programs (see Section 18.2 [Writing Testsuites], page 265, `AT_TESTED`).

configuration log
: The contents of '`config.log`', as created by `configure`, are appended. It contains the configuration flags and a detailed report on the configuration itself.

18.2 Writing '`testsuite.at`'

The '`testsuite.at`' is a Bourne shell script making use of special Autotest M4 macros. It often contains a call to `AT_INIT` near its beginning followed by one call to `m4_include` per

source file for tests. Each such included file, or the remainder of '`testsuite.at`' if include files are not used, contain a sequence of test groups. Each test group begins with a call to `AT_SETUP`, then an arbitrary number of shell commands or calls to `AT_CHECK`, and then completes with a call to `AT_CLEANUP`. Multiple test groups can be categorized by a call to `AT_BANNER`.

`AT_INIT` ([*name*]) [Macro]

Initialize Autotest. Giving a *name* to the test suite is encouraged if your package includes several test suites. In any case, the test suite always displays the package name and version. It also inherits the package bug report address.

`AT_COPYRIGHT` (*copyright-notice*) [Macro]

State that, in addition to the Free Software Foundation's copyright on the Autotest macros, parts of your test suite are covered by *copyright-notice*.

The *copyright-notice* shows up in both the head of `testsuite` and in '`testsuite --version`'.

`AT_TESTED` (*executables*) [Macro]

Log the file name and answer to '`--version`' of each program in space-separated list *executables*. Several invocations register new executables, in other words, don't fear registering one program several times.

Autotest test suites rely on `PATH` to find the tested program. This avoids the need to generate absolute names of the various tools, and makes it possible to test installed programs. Therefore, knowing which programs are being exercised is crucial to understanding problems in the test suite itself, or its occasional misuses. It is a good idea to also subscribe foreign programs you depend upon, to avoid incompatible diagnostics.

`AT_BANNER` (*test-category-name*) [Macro]

This macro identifies the start of a category of related test groups. When the resulting '`testsuite`' is invoked with more than one test group to run, its output will include a banner containing *test-category-name* prior to any tests run from that category. The banner should be no more than about 40 or 50 characters. A blank banner will not print, effectively ending a category and letting subsequent test groups behave as though they are uncategorized when run in isolation.

`AT_SETUP` (*test-group-name*) [Macro]

This macro starts a group of related tests, all to be executed in the same subshell. It accepts a single argument, which holds a few words (no more than about 30 or 40 characters) quickly describing the purpose of the test group being started. *test-group-name* must not contain unbalanced quotes or parentheses.

`AT_KEYWORDS` (*keywords*) [Macro]

Associate the space-separated list of *keywords* to the enclosing test group. This makes it possible to run "slices" of the test suite. For instance, if some of your test groups exercise some '`foo`' feature, then using '`AT_KEYWORDS(foo)`' lets you run '`./testsuite -k foo`' to run exclusively these test groups. The *title* of the test group is automatically recorded to `AT_KEYWORDS`.

Several invocations within a test group accumulate new keywords. In other words, don't fear registering the same keyword several times in a test group.

`AT_CAPTURE_FILE (file)` [Macro]

If the current test group fails, log the contents of *file*. Several identical calls within one test group have no additional effect.

`AT_XFAIL_IF (shell-condition)` [Macro]

Determine whether the test is expected to fail because it is a known bug (for unsupported features, you should skip the test). *shell-condition* is a shell expression such as a `test` command; you can instantiate this macro many times from within the same test group, and one of the conditions is enough to turn the test into an expected failure.

`AT_CLEANUP` [Macro]

End the current test group.

`AT_DATA (file, contents)` [Macro]

Initialize an input data *file* with given *contents*. Of course, the *contents* have to be properly quoted between square brackets to protect against included commas or spurious M4 expansion. The contents must end with an end of line. *file* must be a single shell word that expands into a single file name.

`AT_CHECK (commands, [status = '0'], [stdout = ''], [stderr = ''], [run-if-fail], [run-if-pass])` [Macro]

Execute a test by performing given shell *commands*. These commands should normally exit with *status*, while producing expected *stdout* and *stderr* contents. If *commands* exit with status 77, then the whole test group is skipped. Otherwise, if this test fails, run shell commands *run-if-fail* or, if this test passes, run shell commands *run-if-pass*.

This macro must be invoked in between `AT_SETUP` and `AT_CLEANUP`.

If *status*, or *stdout*, or *stderr* is '`ignore`', then the corresponding value is not checked.

The special value '`expout`' for *stdout* means the expected output of the *commands* is the content of the file '`expout`'. If *stdout* is '`stdout`', then the standard output of the *commands* is available for further tests in the file '`stdout`'. Similarly for *stderr* with '`experr`' and '`stderr`'.

18.3 Running `testsuite` Scripts

Autotest test suites support the following arguments:

'`--help`'
'`-h`' Display the list of options and exit successfully.

'`--version`'
'`-V`' Display the version of the test suite and exit successfully.

'`--directory=dir`'
'`-C dir`' Change the current directory to *dir* before creating any files. Useful for running the testsuite in a subdirectory from a top-level Makefile.

'`--clean`'
'`-c`' Remove all the files the test suite might have created and exit. Meant for `clean` Make targets.

'`--list`'
'`-l`' List all the tests (or only the selection), including their possible keywords.

By default all tests are performed (or described with '`--list`') in the default environment first silently, then verbosely, but the environment, set of tests, and verbosity level can be tuned:

'*`variable=value`*'
Set the environment *variable* to *value*. Use this rather than '`FOO=foo ./testsuite`' as debugging scripts would then run in a different environment.

The variable `AUTOTEST_PATH` specifies the testing path to prepend to `PATH`. Relative directory names (not starting with '`/`') are considered to be relative to the top level of the package being built. All directories are made absolute, first starting from the top level *build* tree, then from the *source* tree. For instance '`./testsuite AUTOTEST_PATH=tests:bin`' for a '`/src/foo-1.0`' source package built in '`/tmp/foo`' results in '`/tmp/foo/tests:/tmp/foo/bin`' and then '`/src/foo-1.0/tests:/src/foo-1.0/bin`' being prepended to `PATH`.

'*`number`*'
'*`number-number`*'
'*`number-`*'
'*`-number`*' Add the corresponding test groups, with obvious semantics, to the selection.

'`--keywords=`*`keywords`*'
'`-k` *`keywords`*'
Add to the selection the test groups with title or keywords (arguments to `AT_SETUP` or `AT_KEYWORDS`) that match *all* keywords of the comma separated list *keywords*, case-insensitively. Use '`!`' immediately before the keyword to invert the selection for this keyword. By default, the keywords match whole words; enclose them in '`.*`' to also match parts of words.

For example, running

```
./testsuite -k 'autoupdate,.*FUNC.*'
```

selects all tests tagged '`autoupdate`' *and* with tags containing '`FUNC`' (as in '`AC_CHECK_FUNC`', '`AC_FUNC_ALLOCA`', etc.), while

```
./testsuite -k '!autoupdate' -k '.*FUNC.*'
```

selects all tests not tagged '`autoupdate`' *or* with tags containing '`FUNC`'.

'`--errexit`'
'`-e`' If any test fails, immediately abort testing. It implies '`--debug`': post test group clean up, and top-level logging are inhibited. This option is meant for the full test suite, it is not really useful for generated debugging scripts.

'`--verbose`'
'`-v`' Force more verbosity in the detailed output of what is being done. This is the default for debugging scripts.

'--debug'
'-d' Do not remove the files after a test group was performed —but they are still removed *before*, therefore using this option is sane when running several test groups. Create debugging scripts. Do not overwrite the top-level log (in order to preserve supposedly existing full log file). This is the default for debugging scripts, but it can also be useful to debug the testsuite itself.

'--trace'
'-x' Trigger shell tracing of the test groups.

18.4 Making testsuite Scripts

For putting Autotest into movement, you need some configuration and makefile machinery. We recommend, at least if your package uses deep or shallow hierarchies, that you use 'tests/' as the name of the directory holding all your tests and their makefile. Here is a check list of things to do.

- Make sure to create the file 'package.m4', which defines the identity of the package. It must define AT_PACKAGE_STRING, the full signature of the package, and AT_PACKAGE_BUGREPORT, the address to which bug reports should be sent. For sake of completeness, we suggest that you also define AT_PACKAGE_NAME, AT_PACKAGE_TARNAME, and AT_PACKAGE_VERSION. See Section 4.1 [Initializing configure], page 17, for a description of these variables. We suggest the following makefile excerpt:

```
# The ':;' works around a Bash 3.2 bug when the output is not writeable.
$(srcdir)/package.m4: $(top_srcdir)/configure.ac
        :;{ \
          echo '# Signature of the current package.' && \
          echo 'm4_define([AT_PACKAGE_NAME],      [@PACKAGE_NAME@])' && \
          echo 'm4_define([AT_PACKAGE_TARNAME],   [@PACKAGE_TARNAME@])' && \
          echo 'm4_define([AT_PACKAGE_VERSION],   [@PACKAGE_VERSION@])' && \
          echo 'm4_define([AT_PACKAGE_STRING],    [@PACKAGE_STRING@])' && \
          echo 'm4_define([AT_PACKAGE_BUGREPORT], [@PACKAGE_BUGREPORT@])'; \
        } >'$(srcdir)/package.m4'
```

  Be sure to distribute 'package.m4' and to put it into the source hierarchy: the test suite ought to be shipped!

- Invoke AC_CONFIG_TESTDIR.

  AC_CONFIG_TESTDIR (*directory*, [*test-path* = 'directory']) [Macro]
  An Autotest test suite is to be configured in *directory*. This macro requires the instantiation of '*directory*/atconfig' from '*directory*/atconfig.in', and sets the default AUTOTEST_PATH to *test-path* (see Section 18.3 [testsuite Invocation], page 267).

- Still within 'configure.ac', as appropriate, ensure that some AC_CONFIG_FILES command includes substitution for 'tests/atlocal'.
- The 'tests/Makefile.in' should be modified so the validation in your package is triggered by 'make check'. An example is provided below.

With Automake, here is a minimal example about how to link 'make check' with a validation suite.

```
EXTRA_DIST = testsuite.at $(TESTSUITE) atlocal.in
```

```
TESTSUITE = $(srcdir)/testsuite

check-local: atconfig atlocal $(TESTSUITE)
        $(SHELL) '$(TESTSUITE)' $(TESTSUITEFLAGS)

installcheck-local: atconfig atlocal $(TESTSUITE)
        $(SHELL) '$(TESTSUITE)' AUTOTEST_PATH='$(bindir)' \
          $(TESTSUITEFLAGS)

clean-local:
        test ! -f '$(TESTSUITE)' || \
         $(SHELL) '$(TESTSUITE)' --clean

AUTOTEST = $(AUTOM4TE) --language=autotest
$(TESTSUITE): $(srcdir)/testsuite.at
        $(AUTOTEST) -I '$(srcdir)' -o $@.tmp $@.at
        mv $@.tmp $@
```

You might want to list explicitly the dependencies, i.e., the list of the files '`testsuite.at`' includes.

If you don't use Automake, you might need to add lines inspired from the following:

```
subdir = tests

atconfig: $(top_builddir)/config.status
        cd $(top_builddir) && \
           $(SHELL) ./config.status $(subdir)/$@

atlocal: $(srcdir)/atlocal.in $(top_builddir)/config.status
        cd $(top_builddir) && \
           $(SHELL) ./config.status $(subdir)/$@
```

and manage to have `$(EXTRA_DIST)` distributed.

If you use Automake, however, you don't need to add a rule to generate '`atlocal`'.

With all this in place, and if you have not initialized '`TESTSUITEFLAGS`' within your makefile, you can fine-tune test suite execution with this variable, for example:

```
make check TESTSUITEFLAGS='-v -d -x 75 -k AC_PROG_CC CFLAGS=-g'
```

19 Frequent Autoconf Questions, with answers

Several questions about Autoconf come up occasionally. Here some of them are addressed.

19.1 Distributing `configure` Scripts

> What are the restrictions on distributing `configure` scripts that Autoconf generates? How does that affect my programs that use them?

There are no restrictions on how the configuration scripts that Autoconf produces may be distributed or used. In Autoconf version 1, they were covered by the GNU General Public License. We still encourage software authors to distribute their work under terms like those of the GPL, but doing so is not required to use Autoconf.

Of the other files that might be used with `configure`, '`config.h.in`' is under whatever copyright you use for your '`configure.ac`'. '`config.sub`' and '`config.guess`' have an exception to the GPL when they are used with an Autoconf-generated `configure` script, which permits you to distribute them under the same terms as the rest of your package. '`install-sh`' is from the X Consortium and is not copyrighted.

19.2 Why Require GNU M4?

> Why does Autoconf require GNU M4?

Many M4 implementations have hard-coded limitations on the size and number of macros that Autoconf exceeds. They also lack several builtin macros that it would be difficult to get along without in a sophisticated application like Autoconf, including:

```
m4_builtin
m4_indir
m4_bpatsubst
__file__
__line__
```

Autoconf requires version 1.4.5 or later of GNU M4.

Since only software maintainers need to use Autoconf, and since GNU M4 is simple to configure and install, it seems reasonable to require GNU M4 to be installed also. Many maintainers of GNU and other free software already have most of the GNU utilities installed, since they prefer them.

19.3 How Can I Bootstrap?

> If Autoconf requires GNU M4 and GNU M4 has an Autoconf `configure` script, how do I bootstrap? It seems like a chicken and egg problem!

This is a misunderstanding. Although GNU M4 does come with a `configure` script produced by Autoconf, Autoconf is not required in order to run the script and install GNU M4. Autoconf is only required if you want to change the M4 `configure` script, which few people have to do (mainly its maintainer).

19.4 Why Not Imake?

Why not use Imake instead of `configure` scripts?

Several people have written addressing this question, so I include adaptations of their explanations here.

The following answer is based on one written by Richard Pixley:

> Autoconf generated scripts frequently work on machines that it has never been set up to handle before. That is, it does a good job of inferring a configuration for a new system. Imake cannot do this.
>
> Imake uses a common database of host specific data. For X11, this makes sense because the distribution is made as a collection of tools, by one central authority who has control over the database.
>
> GNU tools are not released this way. Each GNU tool has a maintainer; these maintainers are scattered across the world. Using a common database would be a maintenance nightmare. Autoconf may appear to be this kind of database, but in fact it is not. Instead of listing host dependencies, it lists program requirements.
>
> If you view the GNU suite as a collection of native tools, then the problems are similar. But the GNU development tools can be configured as cross tools in almost any host+target permutation. All of these configurations can be installed concurrently. They can even be configured to share host independent files across hosts. Imake doesn't address these issues.
>
> Imake templates are a form of standardization. The GNU coding standards address the same issues without necessarily imposing the same restrictions.

Here is some further explanation, written by Per Bothner:

> One of the advantages of Imake is that it easy to generate large makefiles using the '`#include`' and macro mechanisms of `cpp`. However, `cpp` is not programmable: it has limited conditional facilities, and no looping. And `cpp` cannot inspect its environment.
>
> All of these problems are solved by using `sh` instead of `cpp`. The shell is fully programmable, has macro substitution, can execute (or source) other shell scripts, and can inspect its environment.

Paul Eggert elaborates more:

> With Autoconf, installers need not assume that Imake itself is already installed and working well. This may not seem like much of an advantage to people who are accustomed to Imake. But on many hosts Imake is not installed or the default installation is not working well, and requiring Imake to install a package hinders the acceptance of that package on those hosts. For example, the Imake template and configuration files might not be installed properly on a host, or the Imake build procedure might wrongly assume that all source files are in one big directory tree, or the Imake configuration might assume one compiler whereas the package or the installer needs to use another, or there might be a version mismatch between the Imake expected by the package and the Imake supported by the host. These problems are much rarer with Autoconf, where each package comes with its own independent configuration processor.

> Also, Imake often suffers from unexpected interactions between `make` and the installer's C preprocessor. The fundamental problem here is that the C preprocessor was designed to preprocess C programs, not makefiles. This is much less of a problem with Autoconf, which uses the general-purpose preprocessor M4, and where the package's author (rather than the installer) does the preprocessing in a standard way.

Finally, Mark Eichin notes:

> Imake isn't all that extensible, either. In order to add new features to Imake, you need to provide your own project template, and duplicate most of the features of the existing one. This means that for a sophisticated project, using the vendor-provided Imake templates fails to provide any leverage—since they don't cover anything that your own project needs (unless it is an X11 program).
>
> On the other side, though:
>
> The one advantage that Imake has over `configure`: '`Imakefile`' files tend to be much shorter (likewise, less redundant) than '`Makefile.in`' files. There is a fix to this, however—at least for the Kerberos V5 tree, we've modified things to call in common '`post.in`' and '`pre.in`' makefile fragments for the entire tree. This means that a lot of common things don't have to be duplicated, even though they normally are in `configure` setups.

19.5 How Do I `#define` Installation Directories?

My program needs library files, installed in `datadir` and similar. If I use

```
AC_DEFINE_UNQUOTED([DATADIR], [$datadir],
  [Define to the read-only architecture-independent
   data directory.])
```

I get

```
#define DATADIR "${prefix}/share"
```

As already explained, this behavior is on purpose, mandated by the GNU Coding Standards, see Section 4.8.2 [Installation Directory Variables], page 26. There are several means to achieve a similar goal:

- Do not use `AC_DEFINE` but use your makefile to pass the actual value of `datadir` via compilation flags. See Section 4.8.2 [Installation Directory Variables], page 26, for the details.
- This solution can be simplified when compiling a program: you may either extend the `CPPFLAGS`:

  ```
  CPPFLAGS = -DDATADIR='"$(datadir)"' @CPPFLAGS@
  ```

  If you are using Automake, you should use `AM_CPPFLAGS` instead:

  ```
  AM_CPPFLAGS = -DDATADIR='"$(datadir)"'
  ```

  Alternatively, create a dedicated header file:

```
DISTCLEANFILES = myprog-paths.h
myprog-paths.h: Makefile
        echo '#define DATADIR "$(datadir)"' >$@
```

– Use AC_DEFINE but have configure compute the literal value of datadir and others. Many people have wrapped macros to automate this task. For instance, the macro AC_DEFINE_DIR from the Autoconf Macro Archive (http://autoconf-archive.cryp.to/).

  This solution does not conform to the GNU Coding Standards.

– Note that all the previous solutions hard wire the absolute name of these directories in the executables, which is not a good property. You may try to compute the names relative to prefix, and try to find prefix at runtime, this way your package is relocatable.

19.6 What is 'autom4te.cache'?

What is this directory 'autom4te.cache'? Can I safely remove it?

In the GNU Build System, 'configure.ac' plays a central role and is read by many tools: autoconf to create 'configure', autoheader to create 'config.h.in', automake to create 'Makefile.in', autoscan to check the completeness of 'configure.ac', autoreconf to check the GNU Build System components that are used. To "read 'configure.ac'" actually means to compile it with M4, which can be a long process for complex 'configure.ac'.

This is why all these tools, instead of running directly M4, invoke autom4te (see Section 8.2.1 [autom4te Invocation], page 120) which, while answering to a specific demand, stores additional information in 'autom4te.cache' for future runs. For instance, if you run autoconf, behind the scenes, autom4te also stores information for the other tools, so that when you invoke autoheader or automake etc., reprocessing 'configure.ac' is not needed. The speed up is frequently 30%, and is increasing with the size of 'configure.ac'.

But it is and remains being simply a cache: you can safely remove it.

Can I permanently get rid of it?

The creation of this cache can be disabled from '~/.autom4te.cfg', see Section 8.2.2 [Customizing autom4te], page 124, for more details. You should be aware that disabling the cache slows down the Autoconf test suite by 40%. The more GNU Build System components are used, the more the cache is useful; for instance running 'autoreconf -f' on the Core Utilities is twice slower without the cache *although '--force' implies that the cache is not fully exploited*, and eight times slower than without '--force'.

19.7 Header Present But Cannot Be Compiled

The most important guideline to bear in mind when checking for features is to mimic as much as possible the intended use. Unfortunately, old versions of AC_CHECK_HEADER and AC_CHECK_HEADERS failed to follow this idea, and called the preprocessor, instead of the compiler, to check for headers. As a result, incompatibilities between headers went unnoticed during configuration, and maintainers finally had to deal with this issue elsewhere.

As of Autoconf 2.56 both checks are performed, and configure complains loudly if the compiler and the preprocessor do not agree. For the time being the result used is that of the

preprocessor, to give maintainers time to adjust their '`configure.ac`', but in the future, only the compiler will be considered.

Consider the following example:

```
$ cat number.h
typedef int number;
$ cat pi.h
const number pi = 3;
$ cat configure.ac
AC_INIT([Example], [1.0], [bug-example@example.org])
AC_CHECK_HEADERS([pi.h])
$ autoconf -Wall
$ ./configure
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking how to run the C preprocessor... gcc -E
checking for grep that handles long lines and -e... grep
checking for egrep... grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking pi.h usability... no
checking pi.h presence... yes
configure: WARNING: pi.h: present but cannot be compiled
configure: WARNING: pi.h:     check for missing prerequisite headers?
configure: WARNING: pi.h: see the Autoconf documentation
configure: WARNING: pi.h:     section "Present But Cannot Be Compiled"
configure: WARNING: pi.h: proceeding with the preprocessor's result
configure: WARNING: pi.h: in the future, the compiler will take precedence
configure: WARNING:     ## ------------------------------------- ##
configure: WARNING:     ## Report this to bug-example@example.org ##
configure: WARNING:     ## ------------------------------------- ##
checking for pi.h... yes
```

The proper way the handle this case is using the fourth argument (see Section 5.6.3 [Generic Headers], page 65):

```
$ cat configure.ac
AC_INIT([Example], [1.0], [bug-example@example.org])
AC_CHECK_HEADERS([number.h pi.h], [], [],
[[#ifdef HAVE_NUMBER_H
# include <number.h>
#endif
]])
```

```
$ autoconf -Wall
$ ./configure
checking for gcc... gcc
checking for C compiler default output... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ANSI C... none needed
checking for number.h... yes
checking for pi.h... yes
```

See Section 5.6.2 [Particular Headers], page 60, for a list of headers with their prerequisite.

20 History of Autoconf

You may be wondering, Why was Autoconf originally written? How did it get into its present form? (Why does it look like gorilla spit?) If you're not wondering, then this chapter contains no information useful to you, and you might as well skip it. If you *are* wondering, then let there be light...

20.1 Genesis

In June 1991 I was maintaining many of the GNU utilities for the Free Software Foundation. As they were ported to more platforms and more programs were added, the number of '`-D`' options that users had to select in the makefile (around 20) became burdensome. Especially for me—I had to test each new release on a bunch of different systems. So I wrote a little shell script to guess some of the correct settings for the fileutils package, and released it as part of fileutils 2.0. That `configure` script worked well enough that the next month I adapted it (by hand) to create similar `configure` scripts for several other GNU utilities packages. Brian Berliner also adapted one of my scripts for his CVS revision control system.

Later that summer, I learned that Richard Stallman and Richard Pixley were developing similar scripts to use in the GNU compiler tools; so I adapted my `configure` scripts to support their evolving interface: using the file name '`Makefile.in`' as the templates; adding '`+srcdir`', the first option (of many); and creating '`config.status`' files.

20.2 Exodus

As I got feedback from users, I incorporated many improvements, using Emacs to search and replace, cut and paste, similar changes in each of the scripts. As I adapted more GNU utilities packages to use `configure` scripts, updating them all by hand became impractical. Rich Murphey, the maintainer of the GNU graphics utilities, sent me mail saying that the `configure` scripts were great, and asking if I had a tool for generating them that I could send him. No, I thought, but I should! So I started to work out how to generate them. And the journey from the slavery of hand-written `configure` scripts to the abundance and ease of Autoconf began.

Cygnus `configure`, which was being developed at around that time, is table driven; it is meant to deal mainly with a discrete number of system types with a small number of mainly unguessable features (such as details of the object file format). The automatic configuration system that Brian Fox had developed for Bash takes a similar approach. For general use, it seems to me a hopeless cause to try to maintain an up-to-date database of which features each variant of each operating system has. It's easier and more reliable to check for most features on the fly—especially on hybrid systems that people have hacked on locally or that have patches from vendors installed.

I considered using an architecture similar to that of Cygnus `configure`, where there is a single `configure` script that reads pieces of '`configure.in`' when run. But I didn't want to have to distribute all of the feature tests with every package, so I settled on having a different `configure` made from each '`configure.in`' by a preprocessor. That approach also offered more control and flexibility.

I looked briefly into using the Metaconfig package, by Larry Wall, Harlan Stenn, and Raphael Manfredi, but I decided not to for several reasons. The `Configure` scripts it

produces are interactive, which I find quite inconvenient; I didn't like the ways it checked for some features (such as library functions); I didn't know that it was still being maintained, and the `Configure` scripts I had seen didn't work on many modern systems (such as System V R4 and NeXT); it wasn't flexible in what it could do in response to a feature's presence or absence; I found it confusing to learn; and it was too big and complex for my needs (I didn't realize then how much Autoconf would eventually have to grow).

I considered using Perl to generate my style of `configure` scripts, but decided that M4 was better suited to the job of simple textual substitutions: it gets in the way less, because output is implicit. Plus, everyone already has it. (Initially I didn't rely on the GNU extensions to M4.) Also, some of my friends at the University of Maryland had recently been putting M4 front ends on several programs, including `tvtwm`, and I was interested in trying out a new language.

20.3 Leviticus

Since my `configure` scripts determine the system's capabilities automatically, with no interactive user intervention, I decided to call the program that generates them Autoconfig. But with a version number tacked on, that name would be too long for old Unix file systems, so I shortened it to Autoconf.

In the fall of 1991 I called together a group of fellow questers after the Holy Grail of portability (er, that is, alpha testers) to give me feedback as I encapsulated pieces of my handwritten scripts in M4 macros and continued to add features and improve the techniques used in the checks. Prominent among the testers were François Pinard, who came up with the idea of making an Autoconf shell script to run M4 and check for unresolved macro calls; Richard Pixley, who suggested running the compiler instead of searching the file system to find include files and symbols, for more accurate results; Karl Berry, who got Autoconf to configure TEX and added the macro index to the documentation; and Ian Lance Taylor, who added support for creating a C header file as an alternative to putting '`-D`' options in a makefile, so he could use Autoconf for his UUCP package. The alpha testers cheerfully adjusted their files again and again as the names and calling conventions of the Autoconf macros changed from release to release. They all contributed many specific checks, great ideas, and bug fixes.

20.4 Numbers

In July 1992, after months of alpha testing, I released Autoconf 1.0, and converted many GNU packages to use it. I was surprised by how positive the reaction to it was. More people started using it than I could keep track of, including people working on software that wasn't part of the GNU Project (such as TCL, FSP, and Kerberos V5). Autoconf continued to improve rapidly, as many people using the `configure` scripts reported problems they encountered.

Autoconf turned out to be a good torture test for M4 implementations. Unix M4 started to dump core because of the length of the macros that Autoconf defined, and several bugs showed up in GNU M4 as well. Eventually, we realized that we needed to use some features that only GNU M4 has. 4.3BSD M4, in particular, has an impoverished set of builtin macros; the System V version is better, but still doesn't provide everything we need.

More development occurred as people put Autoconf under more stresses (and to uses I hadn't anticipated). Karl Berry added checks for X11. david zuhn contributed C++ support. François Pinard made it diagnose invalid arguments. Jim Blandy bravely coerced it into configuring GNU Emacs, laying the groundwork for several later improvements. Roland McGrath got it to configure the GNU C Library, wrote the `autoheader` script to automate the creation of C header file templates, and added a '`--verbose`' option to `configure`. Noah Friedman added the '`--autoconf-dir`' option and `AC_MACRODIR` environment variable. (He also coined the term *autoconfiscate* to mean "adapt a software package to use Autoconf".) Roland and Noah improved the quoting protection in `AC_DEFINE` and fixed many bugs, especially when I got sick of dealing with portability problems from February through June, 1993.

20.5 Deuteronomy

A long wish list for major features had accumulated, and the effect of several years of patching by various people had left some residual cruft. In April 1994, while working for Cygnus Support, I began a major revision of Autoconf. I added most of the features of the Cygnus `configure` that Autoconf had lacked, largely by adapting the relevant parts of Cygnus `configure` with the help of david zuhn and Ken Raeburn. These features include support for using '`config.sub`', '`config.guess`', '`--host`', and '`--target`'; making links to files; and running `configure` scripts in subdirectories. Adding these features enabled Ken to convert GNU `as`, and Rob Savoye to convert DejaGNU, to using Autoconf.

I added more features in response to other peoples' requests. Many people had asked for `configure` scripts to share the results of the checks between runs, because (particularly when configuring a large source tree, like Cygnus does) they were frustratingly slow. Mike Haertel suggested adding site-specific initialization scripts. People distributing software that had to unpack on MS-DOS asked for a way to override the '`.in`' extension on the file names, which produced file names like '`config.h.in`' containing two dots. Jim Avera did an extensive examination of the problems with quoting in `AC_DEFINE` and `AC_SUBST`; his insights led to significant improvements. Richard Stallman asked that compiler output be sent to '`config.log`' instead of '`/dev/null`', to help people debug the Emacs `configure` script.

I made some other changes because of my dissatisfaction with the quality of the program. I made the messages showing results of the checks less ambiguous, always printing a result. I regularized the names of the macros and cleaned up coding style inconsistencies. I added some auxiliary utilities that I had developed to help convert source code packages to use Autoconf. With the help of François Pinard, I made the macros not interrupt each others' messages. (That feature revealed some performance bottlenecks in GNU M4, which he hastily corrected!) I reorganized the documentation around problems people want to solve. And I began a test suite, because experience had shown that Autoconf has a pronounced tendency to regress when we change it.

Again, several alpha testers gave invaluable feedback, especially François Pinard, Jim Meyering, Karl Berry, Rob Savoye, Ken Raeburn, and Mark Eichin.

Finally, version 2.0 was ready. And there was much rejoicing. (And I have free time again. I think. Yeah, right.)

Appendix A GNU Free Documentation License

Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released

under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

   You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and

that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

   If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

   If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

   If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

   It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

   You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

   A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.

E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

H. Include an unaltered copy of this License.

I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.

N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.

O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

   You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

   The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

   In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements."

6. COLLECTIONS OF DOCUMENTS

   You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

   You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

   A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called

an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

   Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

   If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

   You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

    The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See `http://www.gnu.org/copyleft/`.

    Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with. . . Texts." line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Appendix B Indices

B.1 Environment Variable Index

This is an alphabetical list of the environment variables that Autoconf checks.

B

BIN_SH ... 168

C

CDPATH ... 168
CONFIG_COMMANDS ... 241
CONFIG_FILES ... 241
CONFIG_HEADERS ... 241
CONFIG_LINKS ... 241
CONFIG_SHELL ... 240
CONFIG_SITE ... 232
CONFIG_STATUS ... 240
CYGWIN ... 245

D

DUALCASE ... 169

E

ENV ... 169

I

IFS ... 169

L

LANG ... 169
LANGUAGE ... 170
LC_ADDRESS ... 170
LC_ALL ... 169
LC_COLLATE ... 169
LC_CTYPE ... 169
LC_IDENTIFICATION ... 170
LC_MEASUREMENT ... 170
LC_MESSAGES ... 169
LC_MONETARY ... 169
LC_NAME ... 170
LC_NUMERIC ... 169
LC_PAPER ... 170
LC_TELEPHONE ... 170
LC_TIME ... 169

M

M4 ... 120
MAIL ... 169
MAILPATH ... 169

N

NULLCMD ... 172

P

PATH_SEPARATOR ... 172
PS1 ... 169
PS2 ... 169
PS4 ... 169
PWD ... 172

S

SIMPLE_BACKUP_SUFFIX ... 242

W

WARNINGS ... 13, 16, 34, 121

X

XMKMF ... 86

B.2 Output Variable Index

This is an alphabetical list of the variables that Autoconf can substitute into files that it creates, typically one or more makefiles. See Section 7.2 [Setting Output Variables], page 104, for more information on how this is done.

A

abs_builddir ... 25
abs_srcdir ... 26
abs_top_builddir ... 25
abs_top_srcdir ... 26
ALLOCA ... 50
AWK ... 41

B

bindir . . . 26
build . . . 222
build_alias . . . 222
build_cpu . . . 222
build_os . . . 222
build_vendor . . . 222
builddir . . . 25

C

CC . . . 75, 79, 87
CFLAGS . . . 23, 75
configure_input . . . 23
CPP . . . 76
CPPFLAGS . . . 24
cross_compiling . . . 99
CXX . . . 80
CXXCPP . . . 80
CXXFLAGS . . . 24, 80

D

datadir . . . 26
datarootdir . . . 26
DEFS . . . 24
docdir . . . 26
dvidir . . . 26

E

ECHO_C . . . 24
ECHO_N . . . 24
ECHO_T . . . 24
EGREP . . . 41
ERL . . . 81, 92, 98
ERLANG_INSTALL_LIB_DIR . . . 29, 89
ERLANG_INSTALL_LIB_DIR_*library* . . . 29, 89
ERLANG_LIB_DIR . . . 88
ERLANG_LIB_DIR_*library* . . . 88
ERLANG_LIB_VER_*library* . . . 88
ERLANG_ROOT_DIR . . . 88
ERLC . . . 81, 92
ERLCFLAGS . . . 24, 81, 92
exec_prefix . . . 26
EXEEXT . . . 72, 246

F

F77 . . . 81
FC . . . 82
FCFLAGS . . . 25, 82
FCLIBS . . . 82
FFLAGS . . . 25, 81
FGREP . . . 41
FLIBS . . . 82

G

GETGROUPS_LIBS . . . 52
GETLOADAVG_LIBS . . . 52
GREP . . . 41

H

host . . . 222
host_alias . . . 222
host_cpu . . . 222
host_os . . . 222
host_vendor . . . 222
htmldir . . . 26

I

includedir . . . 26
infodir . . . 26
INSTALL . . . 41
INSTALL_DATA . . . 41
INSTALL_PROGRAM . . . 41
INSTALL_SCRIPT . . . 41

K

KMEM_GROUP . . . 52

L

LDFLAGS . . . 25
LEX . . . 42
LEX_OUTPUT_ROOT . . . 42
LEXLIB . . . 42
libdir . . . 26
libexecdir . . . 27
LIBOBJDIR . . . 262
LIBOBJS . . . 52, 54, 57, 58, 68
LIBS . . . 25, 248, 251, 255
LN_S . . . 43
localedir . . . 27
localstatedir . . . 27

M

mandir . . . 27
MKDIR_P . . . 42

N

NEED_SETGID . . . 52

O

OBJC . . . 80
OBJCFLAGS . . . 25, 80
OBJCPP . . . 81
OBJEXT . . . 72, 249
oldincludedir . . . 27

OPENMP_CFLAGS 74
OPENMP_CXXFLAGS 74
OPENMP_FCFLAGS 74
OPENMP_FFLAGS 74

P

PACKAGE_BUGREPORT 17
PACKAGE_NAME 17
PACKAGE_STRING 17
PACKAGE_TARNAME 17
PACKAGE_VERSION 17
pdfdir 27
POW_LIB 56
prefix 27
program_transform_name 230
psdir 27

R

RANLIB 43

S

sbindir 27
SED 43
SET_MAKE 20
sharedstatedir 27
srcdir 26
subdirs 37
sysconfdir 27

T

target 222
target_alias 222
target_cpu 222
target_os 222
target_vendor 222
top_build_prefix 25
top_builddir 25
top_srcdir 26

X

X_CFLAGS 86
X_EXTRA_LIBS 86
X_LIBS 86
X_PRE_LIBS 86

Y

YACC 43

B.3 Preprocessor Symbol Index

This is an alphabetical list of the C preprocessor symbols that the Autoconf macros define. To work with Autoconf, C source code needs to use these names in `#if` or `#ifdef` directives.

_

__CHAR_UNSIGNED__ 78
__EXTENSIONS__ 87
__PROTOTYPES 79
_ALL_SOURCE 87, 243
_FILE_OFFSET_BITS 87
_GNU_SOURCE 87, 247
_LARGE_FILES 87
_LARGEFILE_SOURCE 52
_MINIX 87, 249
_OPENMP 74
_POSIX_1_SOURCE 87, 249
_POSIX_PTHREAD_SEMANTICS 87
_POSIX_SOURCE 87, 249
_POSIX_VERSION 64
_TANDEM_SOURCE 87

A

ALIGNOF_*type* 73

C

C_ALLOCA 50
C_GETLOADAVG 52
CLOSEDIR_VOID 51
const 77
CXX_NO_MINUS_C_MINUS_O 80

D

DGUX 52
DIRENT 245

F

F77_DUMMY_MAIN 83
F77_FUNC 84
F77_FUNC_ 84
F77_MAIN 84
F77_NO_MINUS_C_MINUS_O 82
FC_FUNC 84
FC_FUNC_ 84
FC_MAIN 84
FC_NO_MINUS_C_MINUS_O 82

FLEXIBLE_ARRAY_MEMBER 79

G

GETGROUPS_T 69
GETLOADAVG_PRIVILEGED 52
GETPGRP_VOID 53
gid_t 71
GWINSZ_IN_SYS_IOCTL 65

H

HAVE__BOOL 62
HAVE_*aggregate_member* 69
HAVE_ALLOCA_H 50
HAVE_C_BACKSLASH_A 77
HAVE_C_VARARRAYS 79
HAVE_CHOWN 51
HAVE_CONFIG_H 32
HAVE_DECL_STRERROR_R 55
HAVE_DECL_*symbol* 66, 67
HAVE_DECL_TZNAME 68
HAVE_DIRENT_H 60
HAVE_DOPRNT 56
HAVE_FSEEKO 52
HAVE_*function* 57, 58
HAVE_GETGROUPS 52
HAVE_GETMNTENT 53
HAVE_*header* 65, 66
HAVE_INT16_T 69
HAVE_INT32_T 70
HAVE_INT64_T 70
HAVE_INT8_T 69
HAVE_INTMAX_T 70
HAVE_INTPTR_T 70
HAVE_LONG_DOUBLE 70, 243
HAVE_LONG_DOUBLE_WIDER 70
HAVE_LONG_FILE_NAMES 87
HAVE_LONG_LONG_INT 70
HAVE_LSTAT_EMPTY_STRING_BUG 55
HAVE_MALLOC 54
HAVE_MBRTOWC 54
HAVE_MMAP 54
HAVE_NDIR_H 60
HAVE_NLIST_H 52
HAVE_OBSTACK 54
HAVE_REALLOC 55
HAVE_RESOLV_H 61
HAVE_RESTARTABLE_SYSCALLS 252
HAVE_ST_BLKSIZE 252
HAVE_ST_BLOCKS 68
HAVE_ST_RDEV 252
HAVE_STAT_EMPTY_STRING_BUG 55
HAVE_STDBOOL_H 62
HAVE_STRCOLL 55
HAVE_STRERROR_R 55
HAVE_STRFTIME 56
HAVE_STRINGIZE 78
HAVE_STRNLEN 56
HAVE_STRTOLD 56
HAVE_STRUCT_DIRENT_D_INO 68
HAVE_STRUCT_DIRENT_D_TYPE 68
HAVE_STRUCT_STAT_ST_BLKSIZE 252
HAVE_STRUCT_STAT_ST_BLOCKS 68
HAVE_STRUCT_STAT_ST_RDEV 252
HAVE_STRUCT_TM_TM_ZONE 68
HAVE_SYS_DIR_H 60
HAVE_SYS_NDIR_H 60
HAVE_SYS_WAIT_H 63
HAVE_TM_ZONE 68
HAVE_*type* 72
HAVE_TYPEOF 79
HAVE_TZNAME 68
HAVE_UINT16_T 71
HAVE_UINT32_T 71
HAVE_UINT64_T 71
HAVE_UINT8_T 71
HAVE_UINTMAX_T 71
HAVE_UINTPTR_T 71
HAVE_UNSIGNED_LONG_LONG_INT 71
HAVE_UTIME_NULL 56
HAVE_VFORK_H 52
HAVE_VPRINTF 56
HAVE_WAIT3 246
HAVE_WORKING_FORK 52
HAVE_WORKING_VFORK 52

I

inline 78
INT_16_BITS 247
int16_t 69
int32_t 70
int64_t 70
int8_t 69
intmax_t 70
intptr_t 70

L

LONG_64_BITS 249
LSTAT_FOLLOWS_SLASHED_SYMLINK 53

M

MAJOR_IN_MKDEV 61
MAJOR_IN_SYSMACROS 61
malloc 54
mbstate_t 70
mode_t 70

N

NDEBUG 60
NDIR 245
NEED_MEMORY_H 249

NEED_SETGID ... 52
NLIST_NAME_UNION ... 52
NO_MINUS_C_MINUS_O ... 76

O

off_t ... 70

P

PACKAGE_BUGREPORT ... 17
PACKAGE_NAME ... 17
PACKAGE_STRING ... 17
PACKAGE_TARNAME ... 17
PACKAGE_VERSION ... 17
PARAMS ... 79
pid_t ... 70
PROTOTYPES ... 79

R

realloc ... 55
restrict ... 78
RETSIGTYPE ... 70

S

SELECT_TYPE_ARG1 ... 55
SELECT_TYPE_ARG234 ... 55
SELECT_TYPE_ARG5 ... 55
SETPGRP_VOID ... 55
SETVBUF_REVERSED ... 246
size_t ... 71
SIZEOF_*type-or-expr* ... 73
ssize_t ... 71
STAT_MACROS_BROKEN ... 62
STDC_HEADERS ... 62
STRERROR_R_CHAR_P ... 55
SVR4 ... 52
SYS_SIGLIST_DECLARED ... 245
SYSDIR ... 245
SYSNDIR ... 245

T

TIME_WITH_SYS_TIME ... 64
TM_IN_SYS_TIME ... 68
typeof ... 79

U

uid_t ... 71
uint16_t ... 71
uint32_t ... 71
uint64_t ... 71
uint8_t ... 71
uintmax_t ... 71
uintptr_t ... 71
UMAX ... 52
UMAX4_3 ... 52
USG ... 254

V

variable ... 103, 104
vfork ... 52
volatile ... 78

W

WORDS_BIGENDIAN ... 77

X

X_DISPLAY_MISSING ... 86

Y

YYTEXT_POINTER ... 42

B.4 Autoconf Macro Index

This is an alphabetical list of the Autoconf macros. To make the list easier to use, the macros are listed without their preceding 'AC_'.

A

AH_BOTTOM ... 35
AH_HEADER ... 32
AH_TEMPLATE ... 35
AH_TOP ... 35
AH_VERBATIM ... 35
AIX ... 243
ALLOCA ... 243
ARG_ARRAY ... 243
ARG_ENABLE ... 228
ARG_PROGRAM ... 230
ARG_VAR ... 105
ARG_WITH ... 226
AU_ALIAS ... 150
AU_DEFUN ... 150
AUTOCONF_VERSION ... 18

B

BEFORE ... 149

C

C_BACKSLASH_A ... 77
C_BIGENDIAN ... 77
C_CHAR_UNSIGNED ... 78
C_CONST ... 77
C_CROSS ... 243
C_FLEXIBLE_ARRAY_MEMBER ... 79
C_INLINE ... 78
C_LONG_DOUBLE ... 243
C_PROTOTYPES ... 79
C_RESTRICT ... 78
C_STRINGIZE ... 78
C_TYPEOF ... 79
C_VARARRAYS ... 79
C_VOLATILE ... 78
CACHE_CHECK ... 107
CACHE_LOAD ... 109
CACHE_SAVE ... 109
CACHE_VAL ... 107
CANONICAL_BUILD ... 222
CANONICAL_HOST ... 222
CANONICAL_SYSTEM ... 244
CANONICAL_TARGET ... 222
CHAR_UNSIGNED ... 244
CHECK_ALIGNOF ... 73
CHECK_DECL ... 66
CHECK_DECLS ... 66
CHECK_DECLS_ONCE ... 67
CHECK_FILE ... 46
CHECK_FILES ... 46
CHECK_FUNC ... 57
CHECK_FUNCS ... 57
CHECK_FUNCS_ONCE ... 57
CHECK_HEADER ... 65
CHECK_HEADERS ... 65
CHECK_HEADERS_ONCE ... 66
CHECK_LIB ... 46
CHECK_MEMBER ... 68
CHECK_MEMBERS ... 69
CHECK_PROG ... 44
CHECK_PROGS ... 44
CHECK_SIZEOF ... 73
CHECK_TARGET_TOOL ... 44
CHECK_TARGET_TOOLS ... 45
CHECK_TOOL ... 44
CHECK_TOOLS ... 45
CHECK_TYPE ... 72, 244
CHECK_TYPES ... 72
CHECKING ... 244
COMPILE_CHECK ... 245
COMPILE_IFELSE ... 97
COMPUTE_INT ... 73
CONFIG_AUX_DIR ... 19
CONFIG_COMMANDS ... 36
CONFIG_COMMANDS_POST ... 36
CONFIG_COMMANDS_PRE ... 36
CONFIG_FILES ... 22
CONFIG_HEADERS ... 32
CONFIG_LIBOBJ_DIR ... 58
CONFIG_LINKS ... 36
CONFIG_MACRO_DIR ... 19
CONFIG_SRCDIR ... 19
CONFIG_SUBDIRS ... 37
CONFIG_TESTDIR ... 269
CONST ... 245
COPYRIGHT ... 18
CROSS_CHECK ... 245
CYGWIN ... 245

D

DATAROOTDIR_CHECKED ... 30
DECL_SYS_SIGLIST ... 245
DECL_YYTEXT ... 245
DEFINE ... 103
DEFINE_UNQUOTED ... 104
DEFUN ... 145
DEFUN_ONCE ... 149
DIAGNOSE ... 147
DIR_HEADER ... 245
DISABLE_OPTION_CHECKING ... 230
DYNIX_SEQ ... 246

E

EGREP_CPP ... 97
EGREP_HEADER ... 97
EMXOS2 ... 246
ENABLE ... 246
ERLANG_CHECK_LIB ... 88
ERLANG_NEED_ERL ... 81
ERLANG_NEED_ERLC ... 81
ERLANG_PATH_ERL ... 81
ERLANG_PATH_ERLC ... 81
ERLANG_SUBST_INSTALL_LIB_DIR ... 29, 89
ERLANG_SUBST_INSTALL_LIB_SUBDIR ... 29, 89
ERLANG_SUBST_LIB_DIR ... 88
ERLANG_SUBST_ROOT_DIR ... 88
ERROR ... 246
EXEEXT ... 246

F

F77_DUMMY_MAIN ... 83
F77_FUNC ... 85
F77_LIBRARY_LDFLAGS ... 82
F77_MAIN ... 84
F77_WRAPPERS ... 84
FATAL ... 147
FC_FREEFORM ... 86
FC_FUNC ... 85
FC_LIBRARY_LDFLAGS ... 82
FC_MAIN ... 84
FC_SRCEXT ... 85
FC_WRAPPERS ... 84
FIND_X ... 246

FIND_XTRA ... 246
FOREACH ... 246
FUNC_ALLOCA ... 50
FUNC_CHECK ... 246
FUNC_CHOWN ... 51
FUNC_CLOSEDIR_VOID ... 51
FUNC_ERROR_AT_LINE ... 51
FUNC_FNMATCH ... 52
FUNC_FNMATCH_GNU ... 52
FUNC_FORK ... 52
FUNC_FSEEKO ... 52
FUNC_GETGROUPS ... 52
FUNC_GETLOADAVG ... 52
FUNC_GETMNTENT ... 53
FUNC_GETPGRP ... 53
FUNC_LSTAT ... 55
FUNC_LSTAT_FOLLOWS_SLASHED_SYMLINK ... 53
FUNC_MALLOC ... 54
FUNC_MBRTOWC ... 54
FUNC_MEMCMP ... 54
FUNC_MKTIME ... 54
FUNC_MMAP ... 54
FUNC_OBSTACK ... 54
FUNC_REALLOC ... 55
FUNC_SELECT_ARGTYPES ... 55
FUNC_SETPGRP ... 55
FUNC_SETVBUF_REVERSED ... 246
FUNC_STAT ... 55
FUNC_STRCOLL ... 55
FUNC_STRERROR_R ... 55
FUNC_STRFTIME ... 56
FUNC_STRNLEN ... 56
FUNC_STRTOD ... 56
FUNC_STRTOLD ... 56
FUNC_UTIME_NULL ... 56
FUNC_VPRINTF ... 56
FUNC_WAIT3 ... 246

G

GCC_TRADITIONAL ... 247
GETGROUPS_T ... 247
GETLOADAVG ... 247
GNU_SOURCE ... 247

H

HAVE_FUNCS ... 247
HAVE_HEADERS ... 247
HAVE_LIBRARY ... 247
HAVE_POUNDBANG ... 247
HEADER_ASSERT ... 60
HEADER_CHECK ... 247
HEADER_DIRENT ... 60
HEADER_EGREP ... 247
HEADER_MAJOR ... 61
HEADER_RESOLV ... 61
HEADER_STAT ... 62
HEADER_STDBOOL ... 62
HEADER_STDC ... 62
HEADER_SYS_WAIT ... 63
HEADER_TIME ... 64
HEADER_TIOCGWINSZ ... 65
HELP_STRING ... 247

I

INCLUDES_DEFAULT ... 40
INIT ... 17, 247
INLINE ... 247
INT_16_BITS ... 247
IRIX_SUN ... 248
ISC_POSIX ... 248

L

LANG_ASSERT ... 92
LANG_C ... 248
LANG_CALL ... 96
LANG_CONFTEST ... 94
LANG_CPLUSPLUS ... 248
LANG_FORTRAN77 ... 248
LANG_FUNC_LINK_TRY ... 96
LANG_POP ... 92
LANG_PROGRAM ... 94
LANG_PUSH ... 92
LANG_RESTORE ... 248
LANG_SAVE ... 248
LANG_SOURCE ... 94
LANG_WERROR ... 73
LIBOBJ ... 57
LIBSOURCE ... 57
LIBSOURCES ... 58
LINK_FILES ... 248
LINK_IFELSE ... 98
LN_S ... 248
LONG_64_BITS ... 249
LONG_DOUBLE ... 249
LONG_FILE_NAMES ... 249

M

MAJOR_HEADER ... 249
MEMORY_H ... 249
MINGW32 ... 249
MINIX ... 249
MINUS_C_MINUS_O ... 249
MMAP ... 249
MODE_T ... 249
MSG_CHECKING ... 110
MSG_ERROR ... 111
MSG_FAILURE ... 111
MSG_NOTICE ... 110
MSG_RESULT ... 110
MSG_WARN ... 111

O

OBJEXT . . . 249
OBSOLETE . . . 249
OFF_T . . . 250
OPENMP . . . 74
OUTPUT . . . 20, 250
OUTPUT_COMMANDS . . . 250

P

PACKAGE_BUGREPORT . . . 17
PACKAGE_NAME . . . 17
PACKAGE_STRING . . . 17
PACKAGE_TARNAME . . . 17
PACKAGE_VERSION . . . 17
PATH_PROG . . . 45
PATH_PROGS . . . 45
PATH_PROGS_FEATURE_CHECK . . . 45
PATH_TARGET_TOOL . . . 46
PATH_TOOL . . . 46
PATH_X . . . 86
PATH_XTRA . . . 86
PID_T . . . 250
PREFIX . . . 251
PREFIX_DEFAULT . . . 38
PREFIX_PROGRAM . . . 38
PREPROC_IFELSE . . . 96
PREREQ . . . 18
PRESERVE_HELP_ORDER . . . 225
PROG_AWK . . . 41
PROG_CC . . . 75
PROG_CC_C_O . . . 76
PROG_CC_C89 . . . 76
PROG_CC_C99 . . . 76
PROG_CC_STDC . . . 76
PROG_CPP . . . 76
PROG_CPP_WERROR . . . 76
PROG_CXX . . . 80
PROG_CXX_C_O . . . 80
PROG_CXXCPP . . . 80
PROG_EGREP . . . 41
PROG_F77 . . . 81
PROG_F77_C_O . . . 82
PROG_FC . . . 82
PROG_FC_C_O . . . 82
PROG_FGREP . . . 41
PROG_GCC_TRADITIONAL . . . 79
PROG_GREP . . . 41
PROG_INSTALL . . . 41
PROG_LEX . . . 42
PROG_LN_S . . . 43
PROG_MAKE_SET . . . 20
PROG_MKDIR_P . . . 42
PROG_OBJC . . . 80
PROG_OBJCPP . . . 81
PROG_RANLIB . . . 43
PROG_SED . . . 43
PROG_YACC . . . 43
PROGRAM_CHECK . . . 251
PROGRAM_EGREP . . . 251
PROGRAM_PATH . . . 251
PROGRAMS_CHECK . . . 251
PROGRAMS_PATH . . . 251

R

REMOTE_TAPE . . . 251
REPLACE_FNMATCH . . . 56
REPLACE_FUNCS . . . 58
REQUIRE . . . 148
REQUIRE_AUX_FILE . . . 19
REQUIRE_CPP . . . 92
RESTARTABLE_SYSCALLS . . . 251
RETSIGTYPE . . . 251
REVISION . . . 18
RSH . . . 251
RUN_IFELSE . . . 98

S

SCO_INTL . . . 251
SEARCH_LIBS . . . 47
SET_MAKE . . . 251
SETVBUF_REVERSED . . . 251
SIZE_T . . . 252
SIZEOF_TYPE . . . 251
ST_BLKSIZE . . . 252
ST_BLOCKS . . . 252
ST_RDEV . . . 252
STAT_MACROS_BROKEN . . . 252
STDC_HEADERS . . . 252
STRCOLL . . . 252
STRUCT_DIRENT_D_INO . . . 68
STRUCT_DIRENT_D_TYPE . . . 68
STRUCT_ST_BLKSIZE . . . 252
STRUCT_ST_BLOCKS . . . 68
STRUCT_ST_RDEV . . . 252
STRUCT_TIMEZONE . . . 68
STRUCT_TM . . . 68
SUBST . . . 104
SUBST_FILE . . . 105
SYS_INTERPRETER . . . 87
SYS_LARGEFILE . . . 87
SYS_LONG_FILE_NAMES . . . 87
SYS_POSIX_TERMIOS . . . 87
SYS_RESTARTABLE_SYSCALLS . . . 252
SYS_SIGLIST_DECLARED . . . 252

T

TEST_CPP . . . 253
TEST_PROGRAM . . . 253
TIME_WITH_SYS_TIME . . . 253
TIMEZONE . . . 253
TRY_COMPILE . . . 253
TRY_CPP . . . 253

TRY_LINK ... 253
TRY_LINK_FUNC ... 254
TRY_RUN ... 254
TYPE_GETGROUPS ... 69
TYPE_INT16_T ... 69
TYPE_INT32_T ... 70
TYPE_INT64_T ... 70
TYPE_INT8_T ... 69
TYPE_INTMAX_T ... 70
TYPE_INTPTR_T ... 70
TYPE_LONG_DOUBLE ... 70
TYPE_LONG_DOUBLE_WIDER ... 70
TYPE_LONG_LONG_INT ... 70
TYPE_MBSTATE_T ... 70
TYPE_MODE_T ... 70
TYPE_OFF_T ... 70
TYPE_PID_T ... 70
TYPE_SIGNAL ... 70
TYPE_SIZE_T ... 71
TYPE_SSIZE_T ... 71
TYPE_UID_T ... 71
TYPE_UINT16_T ... 71
TYPE_UINT32_T ... 71
TYPE_UINT64_T ... 71
TYPE_UINT8_T ... 71
TYPE_UINTMAX_T ... 71
TYPE_UINTPTR_T ... 71
TYPE_UNSIGNED_LONG_LONG_INT ... 71

U

UID_T ... 254
UNISTD_H ... 254
USE_SYSTEM_EXTENSIONS ... 87
USG ... 254
UTIME_NULL ... 254

V

VALIDATE_CACHED_SYSTEM_TUPLE ... 254
VERBOSE ... 254
VFORK ... 255
VPRINTF ... 255

W

WAIT3 ... 255
WARN ... 255
WARNING ... 147
WITH ... 255
WORDS_BIGENDIAN ... 255

X

XENIX_DIR ... 255

Y

YYTEXT_POINTER ... 255

B.5 M4 Macro Index

This is an alphabetical list of the M4, M4sugar, and M4sh macros. To make the list easier to use, the macros are listed without their preceding ‘m4_’ or ‘AS_’.

_

__file__ ... 126
__line__ ... 126
__oline__ ... 126

A

append ... 136
append_uniq ... 136
append_uniq_w ... 137
apply ... 133
assert ... 128

B

bmatch ... 130
BOURNE_COMPATIBLE ... 142
bpatsubst ... 126
bpatsubsts ... 130
bregexp ... 126
builtin ... 125

C

car ... 132
case ... 130
CASE ... 142
cdr ... 132
changecom ... 125
changequote ... 125
cmp ... 139
combine ... 137
cond ... 130
count ... 133

D

debugfile ... 125
debugmode ... 125
decr ... 125
default ... 131
define ... 125
defn ... 126
DIRNAME ... 142

divert ... 126
divert_once ... 129
divert_pop ... 129
divert_push ... 129
divert_text ... 130
divnum ... 125
dnl ... 126
do ... 133
dquote ... 133
dquote_elt ... 134
dumpdef ... 125

E

echo ... 134
errprint ... 125
errprintn ... 128
esyscmd ... 125
eval ... 125
exit ... 126
expand ... 134

F

fatal ... 128
flatten ... 137
for ... 132
foreach ... 132
foreach_w ... 132
format ... 125

H

HELP_STRING ... 228

I

if ... 126
IF ... 142
ifdef ... 125
ifndef ... 131
ifset ... 131
ifval ... 131
ifvaln ... 131
ignore ... 134
include ... 127
incr ... 125
index ... 125
indir ... 125
init ... 130
INIT ... 142

J

join ... 138

L

len ... 125
list_cmp ... 139
location ... 128

M

make_list ... 134
maketemp ... 127
max ... 140
MESSAGE_FD ... 143
MESSAGE_LOG_FD ... 143
min ... 140
MKDIR_P ... 142
mkstemp ... 127

N

n ... 131
newline ... 138
normalize ... 138

O

ORIGINAL_STDIN_FD ... 143

P

pattern_allow ... 141
pattern_forbid ... 141
popdef ... 127
pushdef ... 125

Q

quote ... 135

R

re_escape ... 138

S

SET_CATFILE ... 143
SHELL_SANITIZE ... 142
shift ... 125
shift2 ... 133
shift3 ... 133
shiftn ... 133
sign ... 140
sinclude ... 127
split ... 138
strip ... 138
substr ... 125
syscmd ... 125
sysval ... 125

T

text_box ... 138
text_wrap ... 138
tolower ... 139
toupper ... 139
TR_CPP ... 143
TR_SH ... 143
traceoff ... 125
traceon ... 125
translit ... 125

U

undefine ... 127
undivert ... 127
unquote ... 135

V

version_compare ... 140

W

warn ... 128
wrap ... 127
wrap_lifo ... 127

B.6 Autotest Macro Index

This is an alphabetical list of the Autotest macros. To make the list easier to use, the macros are listed without their preceding 'AT_'.

B

BANNER ... 266

C

CAPTURE_FILE ... 267
CHECK ... 267
CLEANUP ... 267
COPYRIGHT ... 266

D

DATA ... 267

I

INIT ... 266

K

KEYWORDS ... 266

S

SETUP ... 266

T

TESTED ... 266

X

XFAIL_IF ... 267

B.7 Program and Function Index

This is an alphabetical list of the programs and functions whose portability is discussed in this document.

!

! ... 173

.

. ... 173

/

/usr/bin/ksh on Solaris ... 156
/usr/dt/bin/dtksh on Solaris ... 156
/usr/xpg4/bin/sh on Solaris ... 156

{

{...} ... 173

A

alloca ... 50
'alloca.h' ... 50
'assert.h' ... 60
Awk ... 182

B

basename ... 184
break ... 173

C

case ... 173
cat ... 184
cc ... 184
cd ... 175
chmod ... 185
chown ... 51
closedir ... 51
cmp ... 185
cp ... 185
‘ctype.h’ ... 62

D

date ... 186
diff ... 186
‘dirent.h’ ... 60
dirname ... 186

E

echo ... 175
egrep ... 186
error_at_line ... 51
eval ... 175
exit ... 48
exit ... 176
export ... 176
expr ... 186, 187
expr (‘|’) ... 187

F

false ... 177
fgrep ... 188
find ... 188
‘float.h’ ... 62
fnmatch ... 52, 56
‘fnmatch.h’ ... 56
for ... 177
fork ... 52
free ... 48
fseeko ... 52

G

getgroups ... 52
getloadavg ... 52
getmntent ... 53
getpgid ... 53
getpgrp ... 53
grep ... 188

I

if ... 177
‘inttypes.h’ ... 59, 69
isinf ... 48
isnan ... 48

J

join ... 189

K

‘ksh’ ... 156
‘ksh88’ ... 156
‘ksh93’ ... 156

L

‘linux/irda.h’ ... 59
‘linux/random.h’ ... 59
ln ... 189
ls ... 190
lstat ... 53, 55

M

make ... 197
malloc ... 48, 54
mbrtowc ... 54
memcmp ... 54
mkdir ... 190
mktemp ... 190
mktime ... 54
mmap ... 54
mv ... 191

N

‘ndir.h’ ... 60
‘net/if.h’ ... 59
‘netinet/if_ether.h’ ... 59
‘nlist.h’ ... 53

O

od ... 191

P

‘pdksh’ ... 156
printf ... 178
putenv ... 49
pwd ... 178

R

read ... 178

realloc ... 49, 55
'resolv.h' ... 61
rm ... 191

S

sed ... 192
sed ('t') ... 194
select ... 55
set ... 178
setpgrp ... 55
setvbuf ... 246
shift ... 179
signal ... 49
'signal.h' ... 70
snprintf ... 49
source ... 179
sprintf ... 49
sscanf ... 49
stat ... 55
'stdarg.h' ... 62
'stdbool.h' ... 62
'stdint.h' ... 59, 69
'stdlib.h' ... 60, 62, 69
strcoll ... 55
strerror_r ... 49, 55
strftime ... 56
'string.h' ... 62
'strings.h' ... 62
strnlen ... 49, 56
strtod ... 56
strtold ... 56
'sys/dir.h' ... 60
'sys/ioctl.h' ... 65
'sys/mkdev.h' ... 61
'sys/mount.h' ... 60
'sys/ndir.h' ... 60
'sys/ptem.h' ... 60
'sys/socket.h' ... 60
'sys/stat.h' ... 62
'sys/sysmacros.h' ... 61
'sys/time.h' ... 64, 68
'sys/types.h' ... 69
'sys/ucred.h' ... 60
'sys/wait.h' ... 63
sysconf ... 50
'system.h' ... 62

T

'termios.h' ... 65
test ... 179
'time.h' ... 64, 68
touch ... 195
trap ... 181
true ... 182

U

'unistd.h' ... 64
unlink ... 50
unset ... 182
unsetenv ... 50
utime ... 56

V

va_copy ... 50
va_list ... 50
vfork ... 52
'vfork.h' ... 52
vprintf ... 56
vsnprintf ... 49
vsprintf ... 49

W

'wchar.h' ... 70

X

'X11/extensions/scrnsaver.h' ... 60

B.8 Concept Index

This is an alphabetical list of the files, tools, and concepts introduced in this document.

"

'"$@"' ... 163

$

$((*expression*)) ... 166
$(*commands*) ... 166
$<, explicit rules, and VPATH ... 202
${#*var*} ... 165
${*var*##*word*} ... 165
${*var*#*word*} ... 165
${*var*%%*word*} ... 165
${*var*%*word*} ... 165
${*var*=*expanded-value*} ... 164
${*var*=*literal*} ... 164

@

'@&t@' ... 118
'@S|@' ... 118

^

^ quoting 166

_

_m4_divert_diversion 259

‘

‘*commands*‘ 165

A

absolute file names, detect 161
‘acconfig.h’ 242
‘aclocal.m4’ 7
Ash 155
autoconf 12
Autoconf upgrading 255, 258
Autoconf version 18
autoheader 33
Autoheader macros 35
Autom4te Library 123
‘autom4te.cache’ 122
‘autom4te.cfg’ 124
Automake 3
Automatic remaking 31
automatic rule rewriting and VPATH 202
autopoint 15
autoreconf 15
autoscan 11
Autotest 263
AUTOTEST_PATH 268
autoupdate 242

B

Back trace 13, 121
Bash 156
Bash 2.05 and later 156
Bootstrap 271
BSD make and ‘obj/’ 201
buffer overruns 216
Build directories 30

C

C function portability 47
C types 69
Cache 107
Cache variable 108
Cache, enabling 238
Canonical system type 222
changequote 117
Coding style 150
Command Substitution 165
Commands for configuration 35
Comments in ‘Makefile’ rules 200
Common autoconf behavior 39
Compilers 72
‘config.h’ 32
‘config.h.bot’ 242
‘config.h.in’ 33
‘config.h.top’ 242
config.status 239
config.sub 222
Configuration actions 20
Configuration commands 35
Configuration file creation 22
Configuration Header 32
Configuration Header Template 33
Configuration links 36
configure 7, 235
Configure subdirectories 37
‘configure.ac’ 7
‘configure.in’ 7
Copyright Notice 18, 266
Creating configuration files 22
Creating temporary files 190
Cross compilation 260

D

Darwin 100
‘datarootdir’ 29
Declaration, checking 66
Default includes 39
Dependencies between macros 147
descriptors 143
Descriptors 158
Directories, build 30
Directories, installation 26
division, integer 216
dnl 145, 151
double-colon rules and VPATH 202

E

Endianness 77
Erlang 81
Erlang, Library, checking 88
exiting portably 219
explicit rules, $<, and VPATH 202
External software 225

F

F77 81
FHS 233
file descriptors 143
File descriptors 158
File system conventions 160
File, checking 46
Filesystem Hierarchy Standard 233
floating point 219
Forbidden patterns 141

Fortran 81
Function, checking 50

G

Gettext 15
GNU build system 3
Gnulib 3

H

Header portability 58
Header templates 33
Header, checking 58
Help strings 228
Here-documents 157
History of autoconf 277

I

`ifnames` 12
Imake 272
Includes, default 39
input 143
Install prefix 37
Installation directories 26
Instantiation 20
integer overflow 212, 215
Introduction 1

K

Korn shell 156
Ksh 156

L

Language 91
Large file support 87
LFS 87
Library, checking 46
Libtool 4
License 271
Limitations of `make` 197
Limitations of shell builtins 173
Limitations of usual tools 182
Links 36
Links for configuration 36
Listing directories 190
loop induction 214
low-level output 143

M

M4 113
M4 quotation 113
M4sugar 125
Macro invocation stack 13, 121
Macros, called once 149
Macros, obsoleting 150
Macros, ordering 149
Macros, prerequisites 147
`make -k` 201
`make` and `MAKEFLAGS` 199
`make` and `SHELL` 200
'`Makefile`' rules and comments 200
Makefile substitutions 23
`MAKEFLAGS` and `make` 199
Making directories 190
Messages, from `autoconf` 147
Messages, from `configure` 110
Messages, from `M4sugar` 127
Moving open files 191

N

Notices in `configure` 18
null pointers 216

O

'`obj/`', subdirectory 201
Obsolete constructs 241
Obsoleting macros 150
obstack 54
One-shot macros 149
Options, package 227
Options, Package 229
Ordering macros 149
Output variables 23, 104
Output variables, special characters in 106
output, low-level 143
Outputting files 20
overflow, signed integer 212, 215

P

Package options 227
'`package.m4`' 269
Patterns, forbidden 141
portability 211
Portability of C functions 47
Portability of headers 58
Portable C and C++ programming 211
Portable shell programming 155
positional parameters 163
Posix termios headers 87
Precious Variable 105
Prefix for install 37
preprocessor arithmetic 216
Preprocessors 72
prerequisite directories and `VPATH` 205
Prerequisite macros 147
Program names, transforming 230
Programs, checking 41

Q

QNX 4.25 100
quadrigraphs 118
quotation 9, 113

R

Remaking automatically 31
Revision 18
Rule, Single Suffix Inference 208

S

Separated Dependencies 208
`SHELL` and `make` 200
Shell assignments 166
Shell builtins 173
Shell file descriptors 158
Shell Functions 172
Shell here-documents 157
Shell parentheses 167
Shell pattern matching 162
Shell slashes 167
Shell substitutions 162
Shell variables 168
Shellology 155
signed integer overflow 212, 215
Single Suffix Inference Rule 208
Site defaults 232
Site details 230
Special shell variables 168
standard input 143
Standard symbols 39
Structure, checking 67
Subdirectory configure 37
Substitutions in makefiles 23
Symbolic links 189
System type 221, 222
Systemology 100

T

termios Posix headers 87
test group 263
`testsuite` 263, 267
timestamp resolution 185, 195, 208
Transforming program names 230
Tru64 100
Types 69

U

undefined macro 259
Unix version 7 100
Upgrading autoconf 255, 258

V

V7 100
Variable, Precious 105
Version 18
version, Autoconf 18
volatile objects 217
`VPATH` 201
`VPATH` and automatic rule rewriting 202
`VPATH` and double-colon rules 202
`VPATH` and prerequisite directories 205
`VPATH`, explicit rules, and `$<` 202
`VPATH`, resolving target pathnames 205

W

wraparound arithmetic 212, 215

X

X Window System 86

Z

Zsh 157