

GNU Grep: Print lines that match patterns

version 3.4, 2 January 2020

Alain Magloire et al.

This manual is for **grep**, a pattern matching engine.

Copyright © 1999–2002, 2005, 2008–2020 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.

Table of Contents

1	Introduction	1
2	Invoking grep	2
2.1	Command-line Options	2
2.1.1	Generic Program Information	2
2.1.2	Matching Control	2
2.1.3	General Output Control	3
2.1.4	Output Line Prefix Control	5
2.1.5	Context Line Control	6
2.1.6	File and Directory Selection	7
2.1.7	Other Options	9
2.2	Environment Variables	9
2.3	Exit Status	13
2.4	grep Programs	13
3	Regular Expressions	14
3.1	Fundamental Structure	14
3.2	Character Classes and Bracket Expressions	15
3.3	The Backslash Character and Special Expressions	16
3.4	Anchoring	17
3.5	Back-references and Subexpressions	17
3.6	Basic vs Extended Regular Expressions	17
4	Usage	18
5	Performance	21
6	Reporting bugs	23
6.1	Known Bugs	23
7	Copying	24
7.1	GNU Free Documentation License	24
	Index	33

1 Introduction

Given one or more patterns, `grep` searches input files for matches to the patterns. When it finds a match in a line, it copies the line to standard output (by default), or produces whatever other sort of output you have requested with options.

Though `grep` expects to do the matching on text, it has no limits on input line length other than available memory, and it can match arbitrary characters within a line. If the final byte of an input file is not a newline, `grep` silently supplies one. Since newline is also a separator for the list of patterns, there is no way to match newline characters in a text.

2 Invoking grep

The general synopsis of the `grep` command line is

```
grep [option...] [patterns] [file...]
```

There can be zero or more *option* arguments, and zero or more *file* arguments. The *patterns* argument contains one or more patterns separated by newlines, and is omitted when patterns are given via the ‘`-e patterns`’ or ‘`-f file`’ options. Typically *patterns* should be quoted when `grep` is used in a shell command.

2.1 Command-line Options

`grep` comes with a rich set of options: some from POSIX and some being GNU extensions. Long option names are always a GNU extension, even for options that are from POSIX specifications. Options that are specified by POSIX, under their short names, are explicitly marked as such to facilitate POSIX-portable programming. A few option names are provided for compatibility with older or more exotic implementations.

Several additional options control which variant of the `grep` matching engine is used. See Section 2.4 [grep Programs], page 13.

2.1.1 Generic Program Information

`--help` Print a usage message briefly summarizing the command-line options and the bug-reporting address, then exit.

`-V`

`--version`

Print the version number of `grep` to the standard output stream. This version number should be included in all bug reports.

2.1.2 Matching Control

`-e patterns`

`--regexp=patterns`

Use *patterns* as one or more patterns; newlines within *patterns* separate each pattern from the next. If this option is used multiple times or is combined with the `-f (--file)` option, search for all patterns given. Typically *patterns* should be quoted when `grep` is used in a shell command. (`-e` is specified by POSIX.)

`-f file`

`--file=file`

Obtain patterns from *file*, one per line. If this option is used multiple times or is combined with the `-e (--regexp)` option, search for all patterns given. The empty file contains zero patterns, and therefore matches nothing. (`-f` is specified by POSIX.)

`-i`

`-y`

`--ignore-case`

Ignore case distinctions in patterns and input data, so that characters that differ only in case match each other. Although this is straightforward when letters

differ in case only via lowercase-uppercase pairs, the behavior is unspecified in other situations. For example, uppercase “S” has an unusual lowercase counterpart “ſ” (Unicode character U+017F, LATIN SMALL LETTER LONG S) in many locales, and it is unspecified whether this unusual character matches “S” or “s” even though uppercasing it yields “S”. Another example: the lowercase German letter “ß” (U+00DF, LATIN SMALL LETTER SHARP S) is normally capitalized as the two-character string “SS” but it does not match “SS”, and it might not match the uppercase letter “Š” (U+1E9E, LATIN CAPITAL LETTER SHARP S) even though lowercasing the latter yields the former.

`-y` is an obsolete synonym that is provided for compatibility. (`-i` is specified by POSIX.)

`--no-ignore-case`

Do not ignore case distinctions in patterns and input data. This is the default. This option is useful for passing to shell scripts that already use `-i`, in order to cancel its effects because the two options override each other.

`-v`

`--invert-match`

Invert the sense of matching, to select non-matching lines. (`-v` is specified by POSIX.)

`-w`

`--word-regexp`

Select only those lines containing matches that form whole words. The test is that the matching substring must either be at the beginning of the line, or preceded by a non-word constituent character. Similarly, it must be either at the end of the line or followed by a non-word constituent character. Word constituent characters are letters, digits, and the underscore. This option has no effect if `-x` is also specified.

Because the `-w` option can match a substring that does not begin and end with word constituents, it differs from surrounding a regular expression with ‘\<’ and ‘\>’. For example, although ‘`grep -w @`’ matches a line containing only ‘@’, ‘`grep '\<@\>'`’ cannot match any line because ‘@’ is not a word constituent. See Section 3.3 [The Backslash Character and Special Expressions], page 16.

`-x`

`--line-regexp`

Select only those matches that exactly match the whole line. For regular expression patterns, this is like parenthesizing each pattern and then surrounding it with ‘^’ and ‘\$’. (`-x` is specified by POSIX.)

2.1.3 General Output Control

`-c`

`--count`

Suppress normal output; instead print a count of matching lines for each input file. With the `-v` (`--invert-match`) option, count non-matching lines. (`-c` is specified by POSIX.)

`--color [=WHEN]`

`--colour [=WHEN]`

Surround the matched (non-empty) strings, matching lines, context lines, file names, line numbers, byte offsets, and separators (for fields and groups of context lines) with escape sequences to display them in color on the terminal. The colors are defined by the environment variable `GREP_COLORS` and default to `'ms=01;31:mc=01;31:sl=:cx=:fn=35:ln=32:bn=32:se=36'` for bold red matched text, magenta file names, green line numbers, green byte offsets, cyan separators, and default terminal colors otherwise. The deprecated environment variable `GREP_COLOR` is still supported, but its setting does not have priority; it defaults to `'01;31'` (bold red) which only covers the color for matched text. *WHEN* is `'never'`, `'always'`, or `'auto'`.

`-L`

`--files-without-match`

Suppress normal output; instead print the name of each input file from which no output would normally have been printed. The scanning of each file stops on the first match.

`-l`

`--files-with-matches`

Suppress normal output; instead print the name of each input file from which output would normally have been printed. The scanning of each file stops on the first match. (`-l` is specified by POSIX.)

`-m num`

`--max-count=num`

Stop after the first *num* selected lines. If the input is standard input from a regular file, and *num* selected lines are output, `grep` ensures that the standard input is positioned just after the last selected line before exiting, regardless of the presence of trailing context lines. This enables a calling process to resume a search. For example, the following shell script makes use of it:

```
while grep -m 1 'PATTERN'
do
    echo xxxx
done < FILE
```

But the following probably will not work because a pipe is not a regular file:

```
# This probably will not work.
cat FILE |
while grep -m 1 'PATTERN'
do
    echo xxxx
done
```

When `grep` stops after *num* selected lines, it outputs any trailing context lines. When the `-c` or `--count` option is also used, `grep` does not output a count greater than *num*. When the `-v` or `--invert-match` option is also used, `grep` stops after outputting *num* non-matching lines.

`-o`
`--only-matching`
 Print only the matched (non-empty) parts of matching lines, with each such part on a separate output line. Output lines use the same delimiters as input, and delimiters are null bytes if `-z` (`--null-data`) is also used (see Section 2.1.7 [Other Options], page 9).

`-q`
`--quiet`
`--silent` Quiet; do not write anything to standard output. Exit immediately with zero status if any match is found, even if an error was detected. Also see the `-s` or `--no-messages` option. (`-q` is specified by POSIX.)

`-s`
`--no-messages`
 Suppress error messages about nonexistent or unreadable files. Portability note: unlike GNU `grep`, 7th Edition Unix `grep` did not conform to POSIX, because it lacked `-q` and its `-s` option behaved like GNU `grep`'s `-q` option.¹ USG-style `grep` also lacked `-q` but its `-s` option behaved like GNU `grep`'s. Portable shell scripts should avoid both `-q` and `-s` and should redirect standard and error output to `/dev/null` instead. (`-s` is specified by POSIX.)

2.1.4 Output Line Prefix Control

When several prefix fields are to be output, the order is always file name, line number, and byte offset, regardless of the order in which these options were specified.

`-b`
`--byte-offset`
 Print the 0-based byte offset within the input file before each line of output. If `-o` (`--only-matching`) is specified, print the offset of the matching part itself.

`-H`
`--with-filename`
 Print the file name for each match. This is the default when there is more than one file to search.

`-h`
`--no-filename`
 Suppress the prefixing of file names on output. This is the default when there is only one file (or only standard input) to search.

`--label=LABEL`
 Display input actually coming from standard input as input coming from file *LABEL*. This can be useful for commands that transform a file's contents before searching; e.g.:

```
gzip -cd foo.gz | grep --label=foo -H 'some pattern'
```

¹ Of course, 7th Edition Unix predated POSIX by several years!

`-n`
`--line-number`
 Prefix each line of output with the 1-based line number within its input file. (`-n` is specified by POSIX.)

`-T`
`--initial-tab`
 Make sure that the first character of actual line content lies on a tab stop, so that the alignment of tabs looks normal. This is useful with options that prefix their output to the actual content: `-H`, `-n`, and `-b`. This may also prepend spaces to output line numbers and byte offsets so that lines from a single file all start at the same column.

`-Z`
`--null`
 Output a zero byte (the ASCII NUL character) instead of the character that normally follows a file name. For example, `'grep -lZ'` outputs a zero byte after each file name instead of the usual newline. This option makes the output unambiguous, even in the presence of file names containing unusual characters like newlines. This option can be used with commands like `'find -print0'`, `'perl -0'`, `'sort -z'`, and `'xargs -0'` to process arbitrary file names, even those that contain newline characters.

2.1.5 Context Line Control

Context lines are non-matching lines that are near a matching line. They are output only if one of the following options are used. Regardless of how these options are set, `grep` never outputs any given line more than once. If the `-o` (`--only-matching`) option is specified, these options have no effect and a warning is given upon their use.

`-A num`
`--after-context=num`
 Print *num* lines of trailing context after matching lines.

`-B num`
`--before-context=num`
 Print *num* lines of leading context before matching lines.

`-C num`
`-num`
`--context=num`
 Print *num* lines of leading and trailing output context.

`--group-separator=string`
 When `-A`, `-B` or `-C` are in use, print *string* instead of `--` between groups of lines.

`--no-group-separator`
 When `-A`, `-B` or `-C` are in use, do not print a separator between groups of lines.

Here are some points about how `grep` chooses the separator to print between prefix fields and line content:

- Matching lines normally use `'.'` as a separator between prefix fields and actual line content.

- Context (i.e., non-matching) lines use ‘-’ instead.
- When context is not specified, matching lines are simply output one right after another.
- When context is specified, lines that are adjacent in the input form a group and are output one right after another, while by default a separator appears between non-adjacent groups.
- The default separator is a ‘--’ line; its presence and appearance can be changed with the options above.
- Each group may contain several matching lines when they are close enough to each other that two adjacent groups connect and can merge into a single contiguous one.

2.1.6 File and Directory Selection

`-a`

`--text` Process a binary file as if it were text; this is equivalent to the ‘`--binary-files=text`’ option.

`--binary-files=type`

If a file’s data or metadata indicate that the file contains binary data, assume that the file is of type *type*. Non-text bytes indicate binary data; these are either output bytes that are improperly encoded for the current locale (see Section 2.2 [Environment Variables], page 9), or null input bytes when the `-z` (`--null-data`) option is not given (see Section 2.1.7 [Other Options], page 9).

By default, *type* is ‘`binary`’, and `grep` suppresses output after null input binary data is discovered, and suppresses output lines that contain improperly encoded data. When some output is suppressed, `grep` follows any output with a one-line message saying that a binary file matches.

If *type* is ‘`without-match`’, when `grep` discovers null input binary data it assumes that the rest of the file does not match; this is equivalent to the `-I` option.

If *type* is ‘`text`’, `grep` processes binary data as if it were text; this is equivalent to the `-a` option.

When *type* is ‘`binary`’, `grep` may treat non-text bytes as line terminators even without the `-z` (`--null-data`) option. This means choosing ‘`binary`’ versus ‘`text`’ can affect whether a pattern matches a file. For example, when *type* is ‘`binary`’ the pattern ‘`q$`’ might match ‘`q`’ immediately followed by a null byte, even though this is not matched when *type* is ‘`text`’. Conversely, when *type* is ‘`binary`’ the pattern ‘`.`’ (period) might not match a null byte.

Warning: The `-a` (`--binary-files=text`) option might output binary garbage, which can have nasty side effects if the output is a terminal and if the terminal driver interprets some of it as commands. On the other hand, when reading files whose text encodings are unknown, it can be helpful to use `-a` or to set ‘`LC_ALL=C`’ in the environment, in order to find more matches even if the matches are unsafe for direct display.

`-D action`

`--devices=action`

If an input file is a device, FIFO, or socket, use *action* to process it. If *action* is ‘read’, all devices are read just as if they were ordinary files. If *action* is ‘skip’, devices, FIFOs, and sockets are silently skipped. By default, devices are read if they are on the command line or if the `-R` (`--dereference-recursive`) option is used, and are skipped if they are encountered recursively and the `-r` (`--recursive`) option is used. This option has no effect on a file that is read via standard input.

`-d action`

`--directories=action`

If an input file is a directory, use *action* to process it. By default, *action* is ‘read’, which means that directories are read just as if they were ordinary files (some operating systems and file systems disallow this, and will cause `grep` to print error messages for every directory or silently skip them). If *action* is ‘skip’, directories are silently skipped. If *action* is ‘recurse’, `grep` reads all files under each directory, recursively, following command-line symbolic links and skipping other symlinks; this is equivalent to the `-r` option.

`--exclude=glob`

Skip any command-line file with a name suffix that matches the pattern *glob*, using wildcard matching; a name suffix is either the whole name, or a trailing part that starts with a non-slash character immediately after a slash (‘/’) in the name. When searching recursively, skip any subfile whose base name matches *glob*; the base name is the part after the last slash. A pattern can use ‘*’, ‘?’, and ‘[?...]’ as wildcards, and \ to quote a wildcard or backslash character literally.

`--exclude-from=file`

Skip files whose name matches any of the patterns read from *file* (using wildcard matching as described under `--exclude`).

`--exclude-dir=glob`

Skip any command-line directory with a name suffix that matches the pattern *glob*. When searching recursively, skip any subdirectory whose base name matches *glob*. Ignore any redundant trailing slashes in *glob*.

`-I`

Process a binary file as if it did not contain matching data; this is equivalent to the `'--binary-files=without-match'` option.

`--include=glob`

Search only files whose name matches *glob*, using wildcard matching as described under `--exclude`.

`-r`

`--recursive`

For each directory operand, read and process all files in that directory, recursively. Follow symbolic links on the command line, but skip symlinks that are encountered recursively. Note that if no file operand is given, `grep` searches the working directory. This is the same as the `'--directories=recurse'` option.

-R
--dereference-recursive
 For each directory operand, read and process all files in that directory, recursively, following all symbolic links.

2.1.7 Other Options

--
 Delimit the option list. Later arguments, if any, are treated as operands even if they begin with '-'. For example, '`grep PAT -- -file1 file2`' searches for the pattern `PAT` in the files named `-file1` and `file2`.

--line-buffered
 Use line buffering on output. This can cause a performance penalty.

-U
--binary On platforms that distinguish between text and binary I/O, use the latter when reading and writing files other than the user's terminal, so that all input bytes are read and written as-is. This overrides the default behavior where `grep` follows the operating system's advice whether to use text or binary I/O. On MS-Windows when `grep` uses text I/O it reads a carriage return-newline pair as a newline and a Control-Z as end-of-file, and it writes a newline as a carriage return-newline pair.

When using text I/O **--byte-offset** (**-b**) counts and **--binary-files** heuristics apply to input data after text-I/O processing. Also, the **--binary-files** heuristics need not agree with the **--binary** option; that is, they may treat the data as text even if **--binary** is given, or vice versa. See Section 2.1.6 [File and Directory Selection], page 7.

This option has no effect on GNU and other POSIX-compatible platforms, which do not distinguish text from binary I/O.

-z
--null-data
 Treat input and output data as sequences of lines, each terminated by a zero byte (the ASCII NUL character) instead of a newline. Like the **-Z** or **--null** option, this option can be used with commands like '`sort -z`' to process arbitrary file names.

2.2 Environment Variables

The behavior of `grep` is affected by the following environment variables.

The locale for category `LC_foo` is specified by examining the three environment variables `LC_ALL`, `LC_foo`, and `LANG`, in that order. The first of these variables that is set specifies the locale. For example, if `LC_ALL` is not set, but `LC_COLLATE` is set to '`pt_BR`', then the Brazilian Portuguese locale is used for the `LC_COLLATE` category. As a special case for `LC_MESSAGES` only, the environment variable `LANGUAGE` can contain a colon-separated list of languages that overrides the three environment variables that ordinarily specify the `LC_MESSAGES` category. The 'C' locale is used if none of these environment variables are set, if the locale catalog is not installed, or if `grep` was not compiled with national language support (NLS). The shell command `locale -a` lists locales that are currently available.

Many of the environment variables in the following list let you control highlighting using Select Graphic Rendition (SGR) commands interpreted by the terminal or terminal emulator. (See the section in the documentation of your text terminal for permitted values and their meanings as character attributes.) These substring values are integers in decimal representation and can be concatenated with semicolons. `grep` takes care of assembling the result into a complete SGR sequence (`\33[...'m`). Common values to concatenate include '1' for bold, '4' for underline, '5' for blink, '7' for inverse, '39' for default foreground color, '30' to '37' for foreground colors, '90' to '97' for 16-color mode foreground colors, '38;5;0' to '38;5;255' for 88-color and 256-color modes foreground colors, '49' for default background color, '40' to '47' for background colors, '100' to '107' for 16-color mode background colors, and '48;5;0' to '48;5;255' for 88-color and 256-color modes background colors.

The two-letter names used in the `GREP_COLORS` environment variable (and some of the others) refer to terminal “capabilities,” the ability of a terminal to highlight text, or change its color, and so on. These capabilities are stored in an online database and accessed by the `terminfo` library.

`GREP_OPTIONS`

This variable specifies default options to be placed in front of any explicit options. As this causes problems when writing portable scripts, this feature will be removed in a future release of `grep`, and `grep` warns if it is used. Please use an alias or script instead. For example, if `grep` is in the directory `/usr/bin` you can prepend `$HOME/bin` to your `PATH` and create an executable script `$HOME/bin/grep` containing the following:

```
#!/bin/sh
export PATH=/usr/bin
exec grep --color=auto --devices=skip "$@"
```

`GREP_COLOR`

This variable specifies the color used to highlight matched (non-empty) text. It is deprecated in favor of `GREP_COLORS`, but still supported. The 'mt', 'ms', and 'mc' capabilities of `GREP_COLORS` have priority over it. It can only specify the color used to highlight the matching non-empty text in any matching line (a selected line when the `-v` command-line option is omitted, or a context line when `-v` is specified). The default is '01;31', which means a bold red foreground text on the terminal's default background.

`GREP_COLORS`

This variable specifies the colors and other attributes used to highlight various parts of the output. Its value is a colon-separated list of `terminfo` capabilities that defaults to `'ms=01;31:mc=01;31:s1=:cx=:fn=35:ln=32:bn=32:se=36'` with the 'rv' and 'ne' boolean capabilities omitted (i.e., false). Supported capabilities are as follows.

`s1=` SGR substring for whole selected lines (i.e., matching lines when the `-v` command-line option is omitted, or non-matching lines when `-v` is specified). If however the boolean 'rv' capability and the `-v` command-line option are both specified, it applies to context matching lines instead. The default is empty (i.e., the terminal's default color pair).

- `cx=` SGR substring for whole context lines (i.e., non-matching lines when the `-v` command-line option is omitted, or matching lines when `-v` is specified). If however the boolean `rv` capability and the `-v` command-line option are both specified, it applies to selected non-matching lines instead. The default is empty (i.e., the terminal's default color pair).
- `rv` Boolean value that reverses (swaps) the meanings of the `s1=` and `cx=` capabilities when the `-v` command-line option is specified. The default is false (i.e., the capability is omitted).
- `mt=01;31` SGR substring for matching non-empty text in any matching line (i.e., a selected line when the `-v` command-line option is omitted, or a context line when `-v` is specified). Setting this is equivalent to setting both `ms=` and `mc=` at once to the same value. The default is a bold red text foreground over the current line background.
- `ms=01;31` SGR substring for matching non-empty text in a selected line. (This is used only when the `-v` command-line option is omitted.) The effect of the `s1=` (or `cx=` if `rv`) capability remains active when this takes effect. The default is a bold red text foreground over the current line background.
- `mc=01;31` SGR substring for matching non-empty text in a context line. (This is used only when the `-v` command-line option is specified.) The effect of the `cx=` (or `s1=` if `rv`) capability remains active when this takes effect. The default is a bold red text foreground over the current line background.
- `fn=35` SGR substring for file names prefixing any content line. The default is a magenta text foreground over the terminal's default background.
- `ln=32` SGR substring for line numbers prefixing any content line. The default is a green text foreground over the terminal's default background.
- `bn=32` SGR substring for byte offsets prefixing any content line. The default is a green text foreground over the terminal's default background.
- `se=36` SGR substring for separators that are inserted between selected line fields (`:`), between context line fields (`-`), and between groups of adjacent lines when nonzero context is specified (`--`). The default is a cyan text foreground over the terminal's default background.
- `ne` Boolean value that prevents clearing to the end of line using Erase in Line (EL) to Right (`\33[K`) each time a colorized item ends. This is needed on terminals on which EL is not supported. It is otherwise useful on terminals for which the `back_color_erase` (`bce`) boolean `terminfo` capability does not apply, when the chosen highlight colors do not affect the background, or when EL is too slow

or causes too much flicker. The default is false (i.e., the capability is omitted).

Note that boolean capabilities have no ‘=’... part. They are omitted (i.e., false) by default and become true when specified.

`LC_ALL`

`LC_COLLATE`

`LANG` These variables specify the locale for the `LC_COLLATE` category, which might affect how range expressions like ‘[a-z]’ are interpreted.

`LC_ALL`

`LC_CTYPE`

`LANG` These variables specify the locale for the `LC_CTYPE` category, which determines the type of characters, e.g., which characters are whitespace. This category also determines the character encoding, that is, whether text is encoded in UTF-8, ASCII, or some other encoding. In the ‘C’ or ‘POSIX’ locale, all characters are encoded as a single byte and every byte is a valid character. In more-complex encodings such as UTF-8, a sequence of multiple bytes may be needed to represent a character, and some bytes may be encoding errors that do not contribute to the representation of any character. POSIX does not specify the behavior of `grep` when patterns or input data contain encoding errors or null characters, so portable scripts should avoid such usage. As an extension to POSIX, GNU `grep` treats null characters like any other character. However, unless the `-a` (`--binary-files=text`) option is used, the presence of null characters in input or of encoding errors in output causes GNU `grep` to treat the file as binary and suppress details about matches. See Section 2.1.6 [File and Directory Selection], page 7.

`LANGUAGE`

`LC_ALL`

`LC_MESSAGES`

`LANG` These variables specify the locale for the `LC_MESSAGES` category, which determines the language that `grep` uses for messages. The default ‘C’ locale uses American English messages.

`POSIXLY_CORRECT`

If set, `grep` behaves as POSIX requires; otherwise, `grep` behaves more like other GNU programs. POSIX requires that options that follow file names must be treated as file names; by default, such options are permuted to the front of the operand list and are treated as options. Also, `POSIXLY_CORRECT` disables special handling of an invalid bracket expression. See [invalid-bracket-expr], page 16.

`_N_GNU_nonoption_argv_flags_`

(Here *N* is `grep`’s numeric process ID.) If the *i*th character of this environment variable’s value is ‘1’, do not consider the *i*th operand of `grep` to be an option, even if it appears to be one. A shell can put this variable in the environment for each command it runs, specifying which operands are the results of file name wildcard expansion and therefore should not be treated as options. This behavior is available only with the GNU C library, and only when `POSIXLY_CORRECT` is not set.

2.3 Exit Status

Normally the exit status is 0 if a line is selected, 1 if no lines were selected, and 2 if an error occurred. However, if the `-L` or `--files-without-match` is used, the exit status is 0 if a file is listed, 1 if no files were listed, and 2 if an error occurred. Also, if the `-q` or `--quiet` or `--silent` option is used and a line is selected, the exit status is 0 even if an error occurred. Other `grep` implementations may exit with status greater than 2 on error.

2.4 `grep` Programs

`grep` searches the named input files for lines containing a match to the given patterns. By default, `grep` prints the matching lines. A file named `-` stands for standard input. If no input is specified, `grep` searches the working directory `.` if given a command-line option specifying recursion; otherwise, `grep` searches standard input. There are four major variants of `grep`, controlled by the following options.

- `-G`
`--basic-regexp`
Interpret patterns as basic regular expressions (BREs). This is the default.
- `-E`
`--extended-regexp`
Interpret patterns as extended regular expressions (EREs). (`-E` is specified by POSIX.)
- `-F`
`--fixed-strings`
Interpret patterns as fixed strings, not regular expressions. (`-F` is specified by POSIX.)
- `-P`
`--perl-regexp`
Interpret patterns as Perl-compatible regular expressions (PCREs). PCRE support is here to stay, but consider this option experimental when combined with the `-z` (`--null-data`) option, and note that ‘`grep -P`’ may warn of unimplemented features. See Section 2.1.7 [Other Options], page 9.

In addition, two variant programs `egrep` and `fgrep` are available. `egrep` is the same as ‘`grep -E`’. `fgrep` is the same as ‘`grep -F`’. Direct invocation as either `egrep` or `fgrep` is deprecated, but is provided to allow historical applications that rely on them to run unmodified.

3 Regular Expressions

A *regular expression* is a pattern that describes a set of strings. Regular expressions are constructed analogously to arithmetic expressions, by using various operators to combine smaller expressions. `grep` understands three different versions of regular expression syntax: basic (BRE), extended (ERE), and Perl-compatible (PCRE). In GNU `grep`, there is no difference in available functionality between the basic and extended syntaxes. In other implementations, basic regular expressions are less powerful. The following description applies to extended regular expressions; differences for basic regular expressions are summarized afterwards. Perl-compatible regular expressions give additional functionality, and are documented in the *pcresyntax(3)* and *pcrpattern(3)* manual pages, but work only if PCRE is available in the system.

3.1 Fundamental Structure

The fundamental building blocks are the regular expressions that match a single character. Most characters, including all letters and digits, are regular expressions that match themselves. Any meta-character with special meaning may be quoted by preceding it with a backslash.

The period `.` matches any single character. It is unspecified whether `.` matches an encoding error.

A regular expression may be followed by one of several repetition operators:

- `'?'` The preceding item is optional and will be matched at most once.
- `'*'` The preceding item will be matched zero or more times.
- `'+'` The preceding item will be matched one or more times.
- `'{n}'` The preceding item is matched exactly n times.
- `'{n,}'` The preceding item is matched n or more times.
- `'{,m}'` The preceding item is matched at most m times. This is a GNU extension.
- `'{n,m}'` The preceding item is matched at least n times, but not more than m times.

The empty regular expression matches the empty string. Two regular expressions may be concatenated; the resulting regular expression matches any string formed by concatenating two substrings that respectively match the concatenated expressions.

Two regular expressions may be joined by the infix operator `'|'`; the resulting regular expression matches any string matching either alternate expression.

Repetition takes precedence over concatenation, which in turn takes precedence over alternation. A whole expression may be enclosed in parentheses to override these precedence rules and form a subexpression. An unmatched `'')` matches just itself.

3.2 Character Classes and Bracket Expressions

A *bracket expression* is a list of characters enclosed by '[' and ']'. It matches any single character in that list. If the first character of the list is the caret '^', then it matches any character **not** in the list, and it is unspecified whether it matches an encoding error. For example, the regular expression '[0123456789]' matches any single digit, whereas '[^()]' matches any single character that is not an opening or closing parenthesis, and might or might not match an encoding error.

Within a bracket expression, a *range expression* consists of two characters separated by a hyphen. It matches any single character that sorts between the two characters, inclusive. In the default C locale, the sorting sequence is the native character order; for example, '[a-d]' is equivalent to '[abcd]'. In other locales, the sorting sequence is not specified, and '[a-d]' might be equivalent to '[abcd]' or to '[aBbCcDd]', or it might fail to match any character, or the set of characters that it matches might even be erratic. To obtain the traditional interpretation of bracket expressions, you can use the 'C' locale by setting the LC_ALL environment variable to the value 'C'.

Finally, certain named classes of characters are predefined within bracket expressions, as follows. Their interpretation depends on the LC_CTYPE locale; for example, '[:alnum:]' means the character class of numbers and letters in the current locale.

'[:alnum:]'

Alphanumeric characters: '[:alpha:]' and '[:digit:]'; in the 'C' locale and ASCII character encoding, this is the same as '[0-9A-Za-z]'.

'[:alpha:]'

Alphabetic characters: '[:lower:]' and '[:upper:]'; in the 'C' locale and ASCII character encoding, this is the same as '[A-Za-z]'.

'[:blank:]'

Blank characters: space and tab.

'[:cntrl:]'

Control characters. In ASCII, these characters have octal codes 000 through 037, and 177 (DEL). In other character sets, these are the equivalent characters, if any.

'[:digit:]'

Digits: 0 1 2 3 4 5 6 7 8 9.

'[:graph:]'

Graphical characters: '[:alnum:]' and '[:punct:]'.

'[:lower:]'

Lower-case letters; in the 'C' locale and ASCII character encoding, this is a b c d e f g h i j k l m n o p q r s t u v w x y z.

'[:print:]'

Printable characters: '[:alnum:]', '[:punct:]', and space.

'[:punct:]'

Punctuation characters; in the 'C' locale and ASCII character encoding, this is ! " # \$ % & ' () * + , - . / : ; < = > ? @ [\] ^ _ ` { | } ~.

`[:space:]`

Space characters: in the ‘C’ locale, this is tab, newline, vertical tab, form feed, carriage return, and space. See Chapter 4 [Usage], page 18, for more discussion of matching newlines.

`[:upper:]`

Upper-case letters: in the ‘C’ locale and ASCII character encoding, this is A B C D E F G H I J K L M N O P Q R S T U V W X Y Z.

`[:xdigit:]`

Hexadecimal digits: 0 1 2 3 4 5 6 7 8 9 A B C D E F a b c d e f.

Note that the brackets in these class names are part of the symbolic names, and must be included in addition to the brackets delimiting the bracket expression.

If you mistakenly omit the outer brackets, and search for say, `[:upper:]`, GNU `grep` prints a diagnostic and exits with status 2, on the assumption that you did not intend to search for the nominally equivalent regular expression: `[:epru]`. Set the `POSIXLY_CORRECT` environment variable to disable this feature.

Most meta-characters lose their special meaning inside bracket expressions.

`]` ends the bracket expression if it’s not the first list item. So, if you want to make the `]` character a list item, you must put it first.

`[.` represents the open collating symbol.

`.]` represents the close collating symbol.

`[=` represents the open equivalence class.

`=]` represents the close equivalence class.

`[:` represents the open character class symbol, and should be followed by a valid character class name.

`:]` represents the close character class symbol.

`-` represents the range if it’s not first or last in a list or the ending point of a range.

`^` represents the characters not in the list. If you want to make the `^` character a list item, place it anywhere but first.

3.3 The Backslash Character and Special Expressions

The `\` character, when followed by certain ordinary characters, takes a special meaning:

`\b` Match the empty string at the edge of a word.

`\B` Match the empty string provided it’s not at the edge of a word.

`\<` Match the empty string at the beginning of word.

`\>` Match the empty string at the end of word.

`\w` Match word constituent, it is a synonym for `[_[:alnum:]]`.

`\W` Match non-word constituent, it is a synonym for `[^_[:alnum:]]`.

`\s` Match whitespace, it is a synonym for `[[[:space:]]]`.

`\S` Match non-whitespace, it is a synonym for `[^[:space:]]`.

For example, `\brat\b` matches the separate word `rat`, `\Brat\B` matches `crate` but not `furry rat`.

3.4 Anchoring

The caret `^` and the dollar sign `$` are meta-characters that respectively match the empty string at the beginning and end of a line. They are termed *anchors*, since they force the match to be “anchored” to beginning or end of a line, respectively.

3.5 Back-references and Subexpressions

The back-reference `\n`, where *n* is a single digit, matches the substring previously matched by the *n*th parenthesized subexpression of the regular expression. For example, `(a)\1` matches `aa`. When used with alternation, if the group does not participate in the match then the back-reference makes the whole match fail. For example, `a(.)|b\1` will not match `ba`. When multiple regular expressions are given with `-e` or from a file (`-f file`), back-references are local to each expression.

See Section 6.1 [Known Bugs], page 23, for some known problems with back-references.

3.6 Basic vs Extended Regular Expressions

In basic regular expressions the meta-characters `?`, `+`, `{`, `|`, `(`, and `)` lose their special meaning; instead use the backslashed versions `\?`, `\+`, `\{`, `\|`, `\(`, and `\)`.

Traditional `egrep` did not support the `{` meta-character, and some `egrep` implementations support `\{` instead, so portable scripts should avoid `{` in `grep -E` patterns and should use `[{]` to match a literal `{`.

GNU `grep -E` attempts to support traditional usage by assuming that `{` is not special if it would be the start of an invalid interval specification. For example, the command `grep -E '{1}'` searches for the two-character string `{1}` instead of reporting a syntax error in the regular expression. POSIX allows this behavior as an extension, but portable scripts should avoid it.

4 Usage

Here is an example command that invokes GNU `grep`:

```
grep -i 'hello.*world' menu.h main.c
```

This lists all lines in the files `menu.h` and `main.c` that contain the string `'hello'` followed by the string `'world'`; this is because `'.*'` matches zero or more characters within a line. See Chapter 3 [Regular Expressions], page 14. The `-i` option causes `grep` to ignore case, causing it to match the line `'Hello, world!'`, which it would not otherwise match.

Here is a more complex example session, showing the location and contents of any line containing `'f'` and ending in `'.c'`, within all files in the current directory whose names contain `'g'` and end in `'.h'`. The `-n` option outputs line numbers, the `--` argument treats any later arguments starting with `'-'` as file names not options, and the empty file `/dev/null` causes file names to be output even if only one file name happens to be of the form `'*g*.h'`.

```
$ grep -n -- 'f.*\.c$' *g*.h /dev/null
argmatch.h:1:/* definitions and prototypes for argmatch.c
```

The only line that contains a match is line 1 of `argmatch.h`. Note that the regular expression syntax used in the pattern differs from the globbing syntax that the shell uses to match file names.

See Chapter 2 [Invoking], page 2, for more details about how to invoke `grep`.

Here are some common questions and answers about `grep` usage.

1. How can I list just the names of matching files?

```
grep -l 'main' test-*.c
```

lists names of `'test-*.c'` files in the current directory whose contents mention `'main'`.

2. How do I search directories recursively?

```
grep -r 'hello' /home/gigi
```

searches for `'hello'` in all files under the `/home/gigi` directory. For more control over which files are searched, use `find` and `grep`. For example, the following command searches only C files:

```
find /home/gigi -name '*.c' ! -type d \
  -exec grep -H 'hello' '{}' +
```

This differs from the command:

```
grep -H 'hello' /home/gigi/*.c
```

which merely looks for `'hello'` in non-hidden C files in `/home/gigi` whose names end in `'.c'`. The `find` command line above is more similar to the command:

```
grep -r --include='*.c' 'hello' /home/gigi
```

3. What if a pattern or file has a leading `'-'`?

```
grep -- '--cut here--' *
```

searches for all lines matching `'--cut here--'`. Without `--`, `grep` would attempt to parse `'--cut here--'` as a list of options, and there would be similar problems with any file names beginning with `'-'`.

Alternatively, you can prevent misinterpretation of leading `'-'` by using `-e` for patterns and leading `./` for files:

```
grep -e '--cut here--' ./*
```

4. Suppose I want to search for a whole word, not a part of a word?

```
grep -w 'hello' test*.log
```

searches only for instances of ‘hello’ that are entire words; it does not match ‘Othello’. For more control, use ‘\<’ and ‘\>’ to match the start and end of words. For example:

```
grep 'hello\>' test*.log
```

searches only for words ending in ‘hello’, so it matches the word ‘Othello’.

5. How do I output context around the matching lines?

```
grep -C 2 'hello' test*.log
```

prints two lines of context around each matching line.

6. How do I force `grep` to print the name of the file?

Append `/dev/null`:

```
grep 'eli' /etc/passwd /dev/null
```

gets you:

```
/etc/passwd:eli:x:2098:1000:Eli Smith:/home/eli:/bin/bash
```

Alternatively, use `-H`, which is a GNU extension:

```
grep -H 'eli' /etc/passwd
```

7. Why do people use strange regular expressions on `ps` output?

```
ps -ef | grep '[c]ron'
```

If the pattern had been written without the square brackets, it would have matched not only the `ps` output line for `cron`, but also the `ps` output line for `grep`. Note that on some platforms, `ps` limits the output to the width of the screen; `grep` does not have any limit on the length of a line except the available memory.

8. Why does `grep` report “Binary file matches”?

If `grep` listed all matching “lines” from a binary file, it would probably generate output that is not useful, and it might even muck up your display. So GNU `grep` suppresses output from files that appear to be binary files. To force GNU `grep` to output lines even from files that appear to be binary, use the `-a` or ‘`--binary-files=text`’ option. To eliminate the “Binary file matches” messages, use the `-I` or ‘`--binary-files=without-match`’ option.

9. Why doesn’t ‘`grep -lv`’ print non-matching file names?

‘`grep -lv`’ lists the names of all files containing one or more lines that do not match. To list the names of all files that contain no matching lines, use the `-L` or `--files-without-match` option.

10. I can do “OR” with ‘`|`’, but what about “AND”?

```
grep 'paul' /etc/motd | grep 'franc,ois'
```

finds all lines that contain both ‘paul’ and ‘franc,ois’.

11. Why does the empty pattern match every input line?

The `grep` command searches for lines that contain strings that match a pattern. Every line contains the empty string, so an empty pattern causes `grep` to find a match on each line. It is not the only such pattern: ‘`^`’, ‘`$`’, and many other patterns cause `grep` to match every line.

To match empty lines, use the pattern `'^$',` To match blank lines, use the pattern `^[[[:blank:]]*$',` To match no lines at all, use the command `grep -f /dev/null`.

12. How can I search in both standard input and in files?

Use the special file name `-`:

```
cat /etc/passwd | grep 'alain' - /etc/motd
```

13. Why is this back-reference failing?

```
echo 'ba' | grep -E '(a)\1|b\1'
```

This gives no output, because the first alternate `(a)\1` does not match, as there is no `aa` in the input, so the `\1` in the second alternate has nothing to refer back to, meaning it will never match anything. (The second alternate in this example can only match if the first alternate has matched—making the second one superfluous.)

14. How can I match across lines?

Standard `grep` cannot do this, as it is fundamentally line-based. Therefore, merely using the `[:space:]` character class does not match newlines in the way you might expect.

With the GNU `grep` option `-z` (`--null-data`), each input and output “line” is null-terminated; see Section 2.1.7 [Other Options], page 9. Thus, you can match newlines in the input, but typically if there is a match the entire input is output, so this usage is often combined with output-suppressing options like `-q`, e.g.:

```
printf 'foo\nbar\n' | grep -z -q 'foo[[[:space:]]\n]+bar'
```

If this does not suffice, you can transform the input before giving it to `grep`, or turn to `awk`, `sed`, `perl`, or many other utilities that are designed to operate across lines.

15. What do `grep`, `fgrep`, and `egrep` stand for?

The name `grep` comes from the way line editing was done on Unix. For example, `ed` uses the following syntax to print a list of matching lines on the screen:

```
global/regular expression/print
g/re/p
```

`fgrep` stands for Fixed `grep`; `egrep` stands for Extended `grep`.

5 Performance

Typically `grep` is an efficient way to search text. However, it can be quite slow in some cases, and it can search large files where even minor performance tweaking can help significantly. Although the algorithm used by `grep` is an implementation detail that can change from release to release, understanding its basic strengths and weaknesses can help you improve its performance.

The `grep` command operates partly via a set of automata that are designed for efficiency, and partly via a slower matcher that takes over when the fast matchers run into unusual features like back-references. When feasible, the Boyer–Moore fast string searching algorithm is used to match a single fixed pattern, and the Aho–Corasick algorithm is used to match multiple fixed patterns.

Generally speaking `grep` operates more efficiently in single-byte locales, since it can avoid the special processing needed for multi-byte characters. If your patterns will work just as well that way, setting `LC_ALL` to a single-byte locale can help performance considerably. Setting `LC_ALL='C'` can be particularly efficient, as `grep` is tuned for that locale.

Outside the `'C'` locale, case-insensitive search, and search for bracket expressions like `'[a-z]'` and `'[[=a=]b]'`, can be surprisingly inefficient due to difficulties in fast portable access to concepts like multi-character collating elements.

A back-reference such as `'\1'` can hurt performance significantly in some cases, since back-references cannot in general be implemented via a finite state automaton, and instead trigger a backtracking algorithm that can be quite inefficient. For example, although the pattern `'^(.*)\1{14}(.*)\2{13}$'` matches only lines whose lengths can be written as a sum $15x + 14y$ for nonnegative integers x and y , the pattern matcher does not perform linear Diophantine analysis and instead backtracks through all possible matching strings, using an algorithm that is exponential in the worst case.

On some operating systems that support files with holes—large regions of zeros that are not physically present on secondary storage—`grep` can skip over the holes efficiently without needing to read the zeros. This optimization is not available if the `-a (--binary-files=text)` option is used (see Section 2.1.6 [File and Directory Selection], page 7), unless the `-z (--null-data)` option is also used (see Section 2.1.7 [Other Options], page 9).

For more about the algorithms used by `grep` and about related string matching algorithms, see:

- Aho AV. Algorithms for finding patterns in strings. In: van Leeuwen J. *Handbook of Theoretical Computer Science*, vol. A. New York: Elsevier; 1990. p. 255–300. This surveys classic string matching algorithms, some of which are used by `grep`.
- Aho AV, Corasick MJ. Efficient string matching: an aid to bibliographic search. *CACM*. 1975;18(6):333–40. <https://dx.doi.org/10.1145/360825.360855>. This introduces the Aho–Corasick algorithm.
- Boyer RS, Moore JS. A fast string searching algorithm. *CACM*. 1977;20(10):762–72. <https://dx.doi.org/10.1145/359842.359859>. This introduces the Boyer–Moore algorithm.
- Faro S, Lecroq T. The exact online string matching problem: a review of the most recent results. *ACM Comput Surv*. 2013;45(2):13. <https://dx.doi.org/10.1145/>

2431211.2431212. This surveys string matching algorithms that might help improve the performance of `grep` in the future.

6 Reporting bugs

Bug reports can be found at the GNU bug report logs for `grep` (<https://debbugs.gnu.org/cgi/pkgreport.cgi?package=grep>). If you find a bug not listed there, please email it to `bug-grep@gnu.org` to create a new bug report.

6.1 Known Bugs

Large repetition counts in the ‘`{n,m}`’ construct may cause `grep` to use lots of memory. In addition, certain other obscure regular expressions require exponential time and space, and may cause `grep` to run out of memory.

Back-references can greatly slow down matching, as they can generate exponentially many matching possibilities that can consume both time and memory to explore. Also, the POSIX specification for back-references is at times unclear. Furthermore, many regular expression implementations have back-reference bugs that can cause programs to return incorrect answers or even crash, and fixing these bugs has often been low-priority—for example, as of 2019 the GNU C library bug database contained back-reference bugs 52, 10844, 11053, and 25322, with little sign of forthcoming fixes. Luckily, back-references are rarely useful and it should be little trouble to avoid them in practical applications.

7 Copying

GNU `grep` is licensed under the GNU GPL, which makes it *free software*.

The “free” in “free software” refers to liberty, not price. As some GNU project advocates like to point out, think of “free speech” rather than “free beer”. In short, you have the right (freedom) to run and change `grep` and distribute it to other people, and—if you want—charge money for doing either. The important restriction is that you have to grant your recipients the same rights and impose the same restrictions.

This general method of licensing software is sometimes called *open source*. The GNU project prefers the term “free software” for reasons outlined at <https://www.gnu.org/philosophy/open-source-misses-the-point.html>.

This manual is free documentation in the same sense. The documentation license is included below. The license for the program is available with the source code, or at <https://www.gnu.org/licenses/gpl.html>.

7.1 GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
<https://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and

is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will

remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <https://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Index

*	
*	14
+	
+	14
-	
--	9
--after-context	6
--basic-regexp	13
--before-context	6
--binary	9
--binary-files	7
--byte-offset	5
--color	4
--colour	4
--context	6
--count	3
--dereference-recursive	9
--devices	8
--directories	8
--exclude	8
--exclude-dir	8
--exclude-from	8
--extended-regexp	13
--file	2
--files-with-matches	4
--files-without-match	4
--fixed-strings	13
--group-separator	6
--help	2
--ignore-case	2
--include	8
--initial-tab	6
--invert-match	3
--label	5
--line-buffered	9
--line-number	6
--line-regexp	3
--max-count	4
--no-filename	5
--no-ignore-case	3
--no-messages	5
--null	6
--null-data	9
--only-matching	5
--perl-regexp	13
--quiet	5
--recursive	8
--regexp=patterns	2
--silent	5
--text	7
--version	2
--with-filename	5
--word-regexp	3
-a	7
-A	6
-b	5
-B	6
-c	3
-C	6
-d	8
-D	8
-e	2
-E	13
-f	2
-F	13
-G	13
-h	5
-H	5
-i	2
-l	4
-L	4
-m	4
-n	6
-num	6
-o	5
-P	13
-q	5
-r	8
-R	9
-s	5
-T	6
-U	9
-v	3
-V	2
-w	3
-x	3
-y	2
-z	9
-Z	6
.	
.....	14
?	
?	14
_	
_GNU_nonoption_argv_flags_ environment variable	12

{	
{,m}	14
{n,}	14
{n,m}	14
{n}	14

A

after context	6
alnum character class	15
alpha character class	15
alphabetic characters	15
alphanumeric characters	15
anchoring	17
asterisk	14

B

back-reference	17
back-references	21
backslash	16
basic regular expressions	17
before context	6
binary files	7
binary I/O	9
blank character class	15
blank characters	15
bn GREP_COLORS capability	11
braces, first argument omitted	14
braces, one argument	14
braces, second argument omitted	14
braces, two arguments	14
bracket expression	15
Bugs, known	23
bugs, reporting	23
byte offset	5

C

case insensitive search	2, 21
changing name of standard input	5
character class	15
character classes	15
character type	12
classes of characters	15
cntrl character class	15
context lines	4, 6
context lines, after match	6
context lines, before match	6
control characters	15
copying	24
counting lines	3
cx GREP_COLORS capability	11

D

default options environment variable	10
device search	8
digit character class	15
digit characters	15
directory search	8
dot	14

E

encoding error	12
environment variables	10
exclude directories	8
exclude files	8
exit status	13

F

FAQ about grep usage	18
files which don't match	4
fn GREP_COLORS capability	11

G

graph character class	15
graphic characters	15
grep programs	13
GREP_COLOR environment variable	10
GREP_COLORS environment variable	10
GREP_OPTIONS environment variable	10
group separator	6

H

hexadecimal digits	16
highlight markers	10
highlight, color, colour	4
holes in files	21

I

include files	8
interval specifications	17
invert matching	3

L

LANG environment variable 9, 12
 language of messages 12
 LANGUAGE environment variable 9, 12
 LC_ALL environment variable 9, 12
 LC_COLLATE environment variable 12
 LC_CTYPE environment variable 12
 LC_MESSAGES environment variable 9, 12
 line buffering 9
 line numbering 6
ln GREP_COLORS capability 11
 locales 21
lower character class 15
 lower-case letters 15

M

match expression at most *m* times 14
 match expression at most once 14
 match expression from *n* to *m* times 14
 match expression *n* or more times 14
 match expression *n* times 14
 match expression one or more times 14
 match expression zero or more times 14
 match the whole line 3
 matching basic regular expressions 13
 matching extended regular expressions 13
 matching fixed strings 13
 matching Perl-compatible regular expressions 13
 matching whole words 3
 max-count 4
mc GREP_COLORS capability 11
 message language 12
ms GREP_COLORS capability 11
 MS-Windows binary I/O 9
mt GREP_COLORS capability 11

N

names of matching files 4
 national language support 12
ne GREP_COLORS capability 11
 NLS 12
 no filename prefix 5
 null character 12
 numeric characters 15

O

only matching 5
 option delimiter 9

P

patterns from file 2
 patterns option 2
 performance 21
 period 14
 plus sign 14
 POSIXLY_CORRECT environment variable 12
print character class 15
 print non-matching lines 3
 printable characters 15
punct character class 15
 punctuation characters 15

Q

question mark 14
 quiet, silent 5

R

range expression 15
 recursive search 8, 9
 regular expressions 14
 return status 13
rv GREP_COLORS capability 11

S

searching directory trees 8, 9
 searching for patterns 1
s1 GREP_COLORS capability 10
space character class 16
 space characters 16
 subexpression 17
 suppress binary data 7
 suppress error messages 5
 symbolic links 8, 9

T

tab-aligned content lines 6
 translation of message language 12

U

upper character class 16
 upper-case letters 16
 usage summary, printing 2
 usage, examples 18
 using **grep**, Q&A 18

V

variants of **grep** 13
 version, printing 2

W

whitespace characters 16

with filename prefix 5

X`xdigit` character class 16`xdigit` class 16**Z**

zero-terminated file names 6

zero-terminated lines 9