

Guile-CV

Edition 0.2.0, revision 1, for use with Guile-CV 0.2.0

The Guile-CV Developpers

This manual documents Guile-CV version 0.2.0.

Copyright (C) 2016 - 2017 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License.”

Table of Contents

Preface	1
Contributors to this Manual	1
The Guile-CV License	1
1 Introduction	1
1.1 About Guile-CV	1
1.2 Obtaining and Installing Guile-CV	2
1.3 Contact	5
1.4 Reporting Bugs	5
2 Using Guile-CV	6
2.1 Configuring Guile for Guile-CV	6
2.1.1 Configuring Guile's repl-print procedure	6
2.1.2 Configuring Guile's raised exception system	6
2.2 Images used in Guile-CV's documentation	8
2.3 Starting Guile-CV	8
3 API Reference	9
3.1 API Overview	9
3.1.1 Naming Conventions	9
3.1.2 Abbreviations	9
3.2 Guile-CV	9
3.2.1 Image Structure and Accessors	9
3.2.2 Kernel Structure and Accessors	12
3.2.3 Import Export	18
3.2.4 Processing	19
3.2.5 Features	24
3.2.6 Texture	27
3.2.7 Filters	29
3.2.8 Morphology	32
3.2.9 Segmentation	35
3.2.10 Utilities	36
3.3 Support	39
3.3.1 Modules	39
3.3.2 Goops	40
3.3.3 G-export	40
3.3.4 Pi	40
3.3.5 Utils	40
Appendix A GNU Free Documentation License ..	40

Concept Index	49
Procedure Index	50
Variable Index	52
Type Index	53

Preface

This manual describes how to use Guile-CV. It relates particularly to Guile-CV version 0.2.0.

Contributors to this Manual

Like Guile-CV itself, the Guile-CV reference manual is a living entity. Right now, the contributor to this manual is:

- David Pirotte

who is also the author and maintainer of Guile-CV.

You are most welcome to join and help. Visit Guile-CV (<http://www.gnu.org/software/guile-cv>) web site to find out how to get involved.

The Guile-CV License

Guile-CV is Free Software. Guile-CV is copyrighted, not public domain, and there are restrictions on its distribution or redistribution:

- Guile-CV and supporting files are published under the terms of the GNU General Public License version 3 or later. See the file `LICENSE`.
- This manual is published under the terms of the GNU Free Documentation License (see Appendix A [GNU Free Documentation License], page 40).

You must be aware there is no warranty whatsoever for Guile-CV. This is described in full in the license.

1 Introduction

1.1 About Guile-CV

GNU Guile-CV

Image Processing and Analysis in Guile (<http://www.gnu.org/software/guile>) a Computer Vision functional programming library

Guile-CV (<http://www.gnu.org/software/guile-cv>) - Image Processing and Analysis in Guile (<http://www.gnu.org/software/guile>) - is a Computer Vision functional programming library for the Guile (<http://www.gnu.org/software/guile>) Scheme language.

Based on Vigna (<http://ukoethe.github.io/vigra/>) (Vision with Generic Algorithms - a C++ image processing and analysis library), Guile-CV (<http://www.gnu.org/software/guile-cv>) comprises a direct binding to Vigna C (https://github.com/BSeppke/vigra_c) (a C wrapper to most of the Vigna functionality), enriched with pure Guile scheme algorithms, all accessible through a nice, clean and easy to use high level API.

Guile-CV (<http://www.gnu.org/software/guile-cv>) is natively multi-threaded, and takes advantage of multiple cores, using high-level and fine grained application-level parallelism constructs available in Guile (<http://www.gnu.org/software/guile>), based on its support to POSIX threads.

Objective

Guile-CV (<http://www.gnu.org/software/guile-cv>) objective is to be a robust, reliable and fast - Image Processing and Analysis - Computer Vision functional programming library for the Guile (<http://www.gnu.org/software/guile>) Scheme language. Guile-CV (<http://www.gnu.org/software/guile-cv>) also wants to be easy to use, study, modify and extend.

Guile-CV (<http://www.gnu.org/software/guile-cv>) can be used as an educational software, a research toolbox but it can also be used 'in production': Guile-CV (<http://www.gnu.org/software/guile-cv>) is robust, reliable and fast, and we will make sure Guile-CV (<http://www.gnu.org/software/guile-cv>) remains robust, reliable and fast as it grows.

Savannah

Guile-CV (<http://www.gnu.org/software/guile-cv>) also has a Savannah project page (<http://savannah.gnu.org/projects/guile-cv>).

1.2 Obtaining and Installing Guile-CV

Guile-CV (<http://www.gnu.org/software/guile-cv>) can be obtained from the following archive site (<http://ftp.gnu.org/gnu/guile-cv>). The file will be named `guile-cv-version.tar.gz`. The current version is 0.2.0, so the file you should grab is:

`http://ftp.gnu.org/gnu/guile-cv/guile-cv-0.2.0.tar.gz`

Dependencies

Guile-CV (<http://www.gnu.org/software/guile-cv>) needs the following software to run:

- Autoconf \geq 2.69
- Automake \geq 1.14
- Makeinfo \geq 6.3
- Guile (<http://www.gnu.org/software/guile>) \geq 2.0.13
- Guile-Lib (<http://www.nongnu.org/guile-lib>) \geq 0.2.5
- Vigna (<http://ukoethe.github.io/vigra/>) \geq 1.11.0

Special notes:

If you manually install Vigna (<http://ukoethe.github.io/vigra/>), make sure you pass the `cmake DCMMAKE_BUILD_TYPE=RELEASE` option, which triggers absolutely essential adequate runtime optimization flags.

- Vigna C (https://github.com/BSeppke/vigra_c) \geq commit 245b4ca64 Jan 3, 2018
Vigna C - a C wrapper [to some of] the Vigna functionality - is currently only available by cloning its source code git (<https://git-scm.com/>) repository: there is no release and no versioning scheme either¹. But no big deal, its home page has an 'Installation' section which guides you step by step.

¹ We do our best to check that the `libvigra_c` installed library does contain the required Guile-CV functionality though, and these checks are listed as part of our `configure` steps

Notes:

1. Make sure you pass the `cmake DCMMAKE_BUILD_TYPE=RELEASE` option, which triggers absolutely essential adequate runtime optimization flags;
 2. Vigna C says it depends on `cmake >= 3.1`, but this is only true if you want to build its documentation, probably not the case. Most distribution still have `cmake 2.8`, if that is your case, you may safely edit `/your/path/vigra_c/CMakeLists.txt` and downgrade this requirement to the `cmake` version installed on your machine;
 3. Make sure the directory where `libvigra_c.so` has been installed is 'known', either because it is defined in `/etc/ld.so.conf.d`, or you set the environment variable `LD_LIBRARY_PATH`, otherwise Guile won't find it and `configure` will report an error.
- LaTeX (<http://www.latex-project.org/>)
Any modern latex distribution will do, we use TexLive (<https://tug.org/texlive/>).
Guile-CV will check that it can find the `standalone` documentclass, as well as the following packages: `inputenc`, `fontenc`, `lmodern`, `xcolor`, `booktabs`, `siunitx`, `iwona`.
Iwona (<http://www.tug.dk/FontCatalogue/iwona/>): this is the font used to create [im-histogram], page 37, headers, legend indices and footers. Note that it could be that it is not part of your 'basic' LaTeX distro, on debian for example, `iwona` is part of the `texlive-fonts-extra` package.

Install from the tarball

Assuming you have satisfied the dependencies, open a terminal and proceed with the following steps:

```
cd <download-path>
tar xzf guile-cv-0.2.0.tar.gz
cd guile-cv-0.2.0
./configure [--prefix=/your/prefix] [--with-guile-site=yes]
make
make install
```

Special notes:

Before you start to use Guile-CV (<http://www.gnu.org/software/guile-cv/>), make sure you read and implement the recommendation made in the manual, section See Section 2.1 [Configuring Guile for Guile-CV], page 6.

Happy Guile-CV (<http://www.gnu.org/software/guile-cv/>)!

Install from the source

Guile-CV (<http://www.gnu.org/software/guile-cv/>) uses Git (<https://git-scm.com/>) for revision control, hosted on Savannah (<http://savannah.gnu.org/projects/guile-cv/>), you may browse the sources repository here (<http://git.savannah.gnu.org/cgit/guile-cv.git>).

There are currently 2 [important] branches: `master` and `devel`. Guile-CV (<http://www.gnu.org/software/guile-cv/>) stable branch is `master`, developments occur on the `devel` branch.

So, to grab, compile and install from the source, open a terminal and:

```
git clone git://git.savannah.gnu.org/guile-cv.git
cd guile-cv
./autogen.sh
./configure [--prefix=/your/prefix] [--with-guile-site=yes]
make
make install
```

Special notes:

Before you start to use Guile-CV (<http://www.gnu.org/software/guile-cv>), make sure you read and implement the recommendation made in the manual, section See Section 2.1 [Configuring Guile for Guile-CV], page 6.

The above steps ensure you're using Guile-CV (<http://www.gnu.org/software/guile-cv>) bleeding edge `stable` version. If you wish to participate to developments, checkout the `devel` branch:

```
git checkout devel
```

Happy hacking!

Notes:

1. The `default` and `--prefix` installation locations for source modules and compiled files (in the absence of `--with-guile-site=yes`) are:

```
$(datadir)/guile-cv
$(libdir)/guile-cv/guile/$(GUILLE_EFFECTIVE_VERSION)/site-ccache
```

If you pass `--with-guile-site=yes`, these locations become the Guile site and site-ccache directories, respectively.

The `configure` step reports these locations as the content of the `sitedir` and `siteccachedir` variables, respectively the source modules and compiled files install locations. After installation, you may consult these variables using `pkg-config`:

```
pkg-config guile-cv-1.0 --variable=sitedir
pkg-config guile-cv-1.0 --variable=siteccachedir
```

You will need - unless you have used `--with-guile-site=yes`, or unless these locations are already 'known' by Guile - to define or augment your `GUILLE_LOAD_PATH` and `GUILLE_COMPILED_PATH` environment variables with these locations, respectively (or `%load-path` and `%load-compiled-path` at run time if you prefer² (See Environment Variables (<https://www.gnu.org/software/guile/manual/guile.html#Environment-Variables>) and Load Path (<https://www.gnu.org/software/guile/manual/guile.html#Load-Paths>) in the Guile Reference Manual).

2. Guile-CV also installs its `libguile-cv.*` library files, in `$(libdir)`. The `configure` step reports its location as the content of the `libdir` variable, which depends on on

² In this case, you may as well decide to either alter your `$HOME/.guile` personal file, or, if you are working in a mult-user environmet, you may also opt for a global configuration. In this case, the file must be named `init.scm` and placed it here (evaluate the following expression in a terminal): `guile -c "(display (%global-site-dir))(newline)".`

the content of the `prefix` and `exec_prefix` variables (also reported). After installation, you may consult these variables using `pkg-config`:

```
pkg-config guile-cv-1.0 --variable=prefix
pkg-config guile-cv-1.0 --variable=exec_prefix
pkg-config guile-cv-1.0 --variable=libdir
```

You will need - unless the `$(libdir)` location is already 'known' by your system - to either define or augment your `$LD_LIBRARY_PATH` environment variable, or alter the `/etc/ld.so.conf` (or add a file in `/etc/ld.so.conf.d`) and run (as root) `ldconfig`, so that Guile-CV finds its `libguile-cv.*` library files³.

3. To install Guile-CV, you must have write permissions to the default or `$(prefix)` directory and its subdirs, as well as to both Guile's site and site-ccache directories if `--with-guile-site=yes` was passed.
4. Like for any other GNU Tool Chain compatible software, you may install the documentation locally using `make install-info`, `make install-html` and/or `make install-pdf`.
5. Last but not least :), Guile-CV comes with a `test-suite`, which we recommend you to run (especially before Section 1.4 [Reporting Bugs], page 5):

```
make check
```

1.3 Contact

Mailing lists

Guile-CV uses the following mailing list:

- `guile-user@gnu.org` is for general user help and discussion.
- `guile-devel@gnu.org` is used to discuss most aspects of Guile-CV, including development and enhancement requests.

When sending emails to `guile-user` and/or `guile-devel`, please use 'Guile-CV: ' to prefix the subject line of any Guile-CV related email, thanks!

IRC

Most of the time you can find me on irc, channel `#guile`, `#guix` and `#scheme` on *irc.freenode.net*, `#clutter` and `#introspection` on *irc.gnome.org*, under the nickname `daviid`.

1.4 Reporting Bugs

Guile-CV uses the following bug reports mailing list:

- `bugs-guile-cv@gnu.org`

You can (un)subscribe to the bugs report list by following instructions on the list information page (<https://lists.gnu.org/mailman/listinfo/bug-guile-cv>).

³ Contact your administrator if you opt for the second solution but don't have write privileges on your system.

2 Using Guile-CV

Guile-CV Reference Manual still is a mock-up: any help is more then welcome to improve this situation, thanks!

2.1 Configuring Guile for Guile-CV

Guile must be modified, with respect to two `core` functionalities, before to start to use Guile-CV: (a) its `repl-print` procedure and (b) its `raised exception system`.

2.1.1 Configuring Guile's `repl-print` procedure

Guile's `repl-print` procedure calls `(write val)`, which is inadequate for images, even very small images⁴. Fortunately, Guile provides us both a simple mechanism to alter the default `repl` printer and the alternate `repl` printer procedure we need: `truncated-print`.

To modify the default `repl` printer, place the following lines either in your `~/.guile` or in the file `$prefix/share/guile/site/init.scm` if you want the change to affect all users⁵.

```
(use-modules (ice-9 pretty-print)
             (system repl common))

(repl-default-option-set! 'print
                          (lambda (repl obj)
                            (truncated-print obj) (newline)))
```

2.1.2 Configuring Guile's `raised exception system`

Guile's default `raised exception system` calls `simple-format`, which is inadequate for images, even very small images (see the related footnote of the previous section, it explains how 'inadequate' this default is for images).

Because Guile's module we need to patch has changed in between 2.0, 2.2 and 2.2.3, we will guide you to manually update your local version, just don't be scared, be meticulous and it will be all fine. But if you think it is 'too much' for you, get in touch with us, and we will guide you or provide a 'ready to use module', depending on your version of Guile.

The module we need to modify is `(ice-9 boot-9)`, so let's first figure out where it is on your system⁶, in a `guile` session, enter the following:

```
(string-append (%package-data-dir) "/" (effective-version))
-|
$2 = "/opt2/share/guile/2.2"
```

⁴ Even for very small images, using `write` is inadequate, in a terminal, and will definitely kill your Emacs/Geiser session. Not to mention it will raise your electricity bill :) - till you succeed to delete its process, Emacs will use one core at more then 100%, desperately trying to display hundreds of thousands of floating point values, heating your laptop (if you have a laptop) up to the point you'll be able to cook an egg on it, and get its fans crazy... You've been warned :).

⁵ You need write privileges to modify this module, contact your admin if you're not in charge of the system you are working on.

⁶ You need write privileges to modify this module, contact your admin if you're not in charge of the system you are working on.

The above returned value is an example of course, just proceed with the value returned by your system. So, the file we need to edit, in our example, is here:

```
/opt2/share/guile/2.2/ice-9/boot-9.scm
```

Edit the above file and:

1. Search for the line `(define format simple-format)` (for Guile 2.2.3, it is the line 327), and below, add the following lines:

```
;; instead of using the above, let's define a specific format binding
;; for exception printers, to allow its user customization.
(define exception-format simple-format)
```

2. In the core of the following procedure, (and only in the core of the following procedures), you will replace all occurrences calls to `format` by calls to `exception-format`:

```
dispatch-exception - line 731 for Guile 2.2.3
  1 occurrence
```

```
(let ((exception-printers '())) - line 864 for Guile 2.2.3
  5 occurrences
```

```
scm-error-printer - line 910 for Guile 2.2.3
  2 occurrences
```

```
syntax-error-printer - line 921 for Guile 2.2.3
  7 occurrences
```

```
keyword-error-printer - line 941 for Guile 2.2.3
  1 occurrence
```

```
getaddrinfo-error-printer - line 941 for Guile 2.2.3
  1 occurrence
```

```
false-if-exception - line 1063 for Guile 2.2.3
  2 occurrences
```

```
make-record-type - line 1200 for Guile 2.2.3
  1 occurrence
```

3. Let's compile it, and install the compiled version where it should (in the following lines, you'll need to substitute `/opt2` by your `$prefix` value, and the username by yours):

```
cd /opt2/share/guile/2.2/ice-9
guild compile boot-9.scm
+ ;;; note: source file /opt2/share/guile/2.2/ice-9/boot-9.scm
;;;      newer than compiled /opt2/lib/guile/2.2/ccache/ice-9/boot-9.go
wrote '/home/david/.cache/guile/ccache/2.2-LE-8-3.A/opt2/share/guile/2.2/ice-9/boot
```

Now we move it, so all users benefit from the new compiled version:

```
mv /home/david/.cache/guile/ccache/2.2-LE-8-3.A/opt2/share/guile/2.2/ice-9/boot-9.
```

Once the above is completed, to effectively modify the default raised exception printers, add the following lines to your `~/.guile` or to the file `$prefix/share/guile/site/init.scm` if you want the change to affect all users⁷:

```
(when (defined? 'exception-format)
  (set! exception-format
    (lambda (port fmt . args)
      (for-each (lambda (arg)
                  (truncated-print arg #:port port))
                args))))
```

You are now ready to use Guile-CV!

2.2 Images used in Guile-CV's documentation

All images used in Guile-CV's documentation are distributed with the source and installed here:

```
$prefix/share/doc/guile-cv/images
```

All examples using `im-load` and `im-save` given in this manual, unless a full pathname is specified, assume that these images are available from the guile current working directory, see `getcwd` and `chdir` in Guile's manual

Our best recommendation, at least to start with, is to create a working directory, such as `mkdir $HOME/guile-cv/images`, for example, and as you need them, copy the distributed images you are interested in.

2.3 Starting Guile-CV

Special note:

Before you start to use Guile-CV, make sure you read and implement the recommendation made in Section 2.1 [Configuring Guile for Guile-CV], page 6,

With the previous Section 2.2 [Images used in Guile-CV's documentation], page 8, recommendations in mind, open a terminal and:

```
cd ~/guile-cv/images
guile
scheme@(guile-user)> ,use (cv)
scheme@(guile-user)> (im-load "sand.tif")
└─
$2 = (512 512 1 (#f32(125.0 128.0 124.0 118.0 108.0 75.0 76.0 # ...)))
```

Or if you use Emacs (<https://www.gnu.org/software/emacs>) which, coupled with Geiser (<http://www.nongnu.org/geiser>) absolutely rocks :-), then a typical session becomes:

```
fire Emacs
M-x cd
└─
Change default directory: ~/guile-cv/images
```

⁷ Note that these lines assume you did perform the steps recommended in the previous section, which means `(use-modules (ice-9 pretty-print))` is already in there

```

M-x run-guile
scheme@(guile-user)> ,use (cv)
scheme@(guile-user)> (im-load "sand.tif")
└─
$2 = (512 512 1 (#f32(125.0 128.0 124.0 118.0 108.0 75.0 76.0 # ...)))

```

Note that to benefit from Emacs's Tab completion mechanism, while typing image filenames, Emacs itself must be in that directory, hence the above first step `M-x cd ...`

3 API Reference

3.1 API Overview

Guile-CV Low Level API

The Guile-CV low level API is ...

Guile-CV High Level API

Guile-CV will also provide a higher level API ...

3.1.1 Naming Conventions

Vigra Functions

Guile-CV low level API procedure names that bind a Vigra function always start with `vigra-` ...

```

bluefox
->
redbear

```

3.1.2 Abbreviations

In the table below we list respectively the abbreviation ...

3.2 Guile-CV

3.2.1 Image Structure and Accessors

The Guile-CV procedures and methods related to images data structure, creating, accessing and copying images.

Image Data Structure

A Guile-CV image is represented by a list containing the following elements:

```
(width height n-channel idata)
```

where *idata* is a list of *n-channel* elements, each element being a vector of (** width height*) cells. More precisely, each element is an `srfi-4` homogeneous numeric vector of 32 bit floats, called `f32vector`, knowing that `f32` is the C type `float`.

The external representation (ie. read syntax) for *idata* vectors is `#f32(...)`. As an example, a gray scale image of width 3 and height 2, initialized to 0.0 is represented by the following expression:

```
(3 2 1 (#f32(0.0 0.0 0.0 0.0 0.0 0.0)))
```

The *n-channel* is an integer ≥ 1 , with no limit but the memory size. This said, most Guile-CV procedures and methods expect either GRAY scale (*n-channel*=1), or RGB (*n-channel*=3) images. For the later, the channels are **Red**, **Green** and **Blue** in that order.

Guile-CV provides usefull accessors for all these fields. However, very often, you will need them all, in which case your best friend is (`ice-9 match`), here is an example:

```
,use (cv)
(define image (im-make 4 3 3))
(match image
  ((width height n-chan idata)
   (match idata
     ((r g b)
      ... your code here ...))))
```

You will find many examples of such a ‘pattern’ in Guile-CV’s source code itself of course, along with some other ‘techniques’ that might be useful, so we invite you to read it, and if you do so: feedback, design and code review is more then welcome! This section describes what is in the module (`cv idata`).

Note that the (`cv`) module imports and re-exports, among may others, the public interface of (`ice-9 match`).

Procedures

`im-make` *width height n* [*value*] [Procedure]

`im-make-channel` *width height* [*value*] [Procedure]

`im-make-channels` *width height n* [*value*] [Procedure]

Returns a new image, list of channels or channel.

Each channel is an `srfi-4` homogeneous vector of 32 bit floats (`f32vector`), of *width* by *height* initialized to *value*. The default *value* is 0.0

`im-copy` *image* [Procedure]

`im-copy-channel` *channel width height* [Procedure]

Returns a new fresh copy of *image* or *channel*.

`im-size` *image* [Method]

Returns the list of (*width height n-channel*)for *image*.

`im-width` *image* [Method]

`im-height` *image* [Method]

`im-n-channel` *image* [Method]

`im-channels` *image* [Method]

`im-channel` *image n* [Procedure]

Returns, respectively the *width*, the *height*, *n-channel*, *channels* or the *nth* channel for *image*.

- `im-image? image` [Procedure]
`im-gray? image` [Method]
`im-rgb? image` [Method]
 Returns `#t` if *image* is respectively a Guile-CV image, a GRAY scale or an RGB image.
- `im-binary? i1 i2 i3 ...` [Procedure]
`im-binary-channel? width height c1 c2 c3 ...` [Procedure]
 Returns `#t` if *i1 i2 i3 ...* or *c1 c2 c3 ...* respectively are BINARY (Black and White) images or channels respectively.
 Note that when more then one image or channel is passed, they must all be of the same size.
- `im-=? [precision] i1 i2 i3 ...` [Procedure]
`im==channel? width height [precision] c1 c2 c3 ...` [Procedure]
 Returns `#t` if *i1 i2 i3 ...* or *c1 c2 c3 ...* respectively are of the same size, have the same number of channels that all respectively contain the same values.
 If the first argument is a number, it is used as the precision to compare pixel values. The default precision value is `1.0e-4`. Note that if you are certain your images or channels contain 'discrete' float values, you may pass `0.0` as the precision to be used, in which case values will be compared using `=` (instead of `float=?`, which is faster).
- `im-ref image i j [k]` [Procedure]
`im-fast-ref image i j [k]` [Procedure]
 Returns the pixel value stored at position *i* and *j* of the *image* channel *k*. The default value for *k* is 0.
im-fast-ref does not check the validity of its arguments: use it at your own risk.
- `im-set! image i j [k] value` [Procedure]
`im-fast-set! image i j [k] value` [Procedure]
 Returns nothing.
 Sets the pixel value stored at position *i* and *j* of the *image* channel *k* to *value*. The default value for *k* is 0.
im-fast-set! does not check the validity of its arguments: use it at your own risk.
- `im-channel-offset i j width height` [Procedure]
`im-fast-channel-offset i j width` [Procedure]
 Returns the channel offset for the *i* and *j* indices, based on the *width* and *height* of the channel.
 This procedure converts the matrix indices *i* and *j* to a vector offset for a channel of size *width* and *height*.
im-fast-channel-offset does not check the validity of its arguments: use it at your own risk.
- `im-channel-ref channel i j width height` [Procedure]
`im-fast-channel-ref channel i j width` [Procedure]
 Returns the pixel value stored at position *i* and *j* of the channel of size *width* and *height*.

im-fast-channel-ref does not check the validity of its arguments: use it at your own risk.

`im-channel-set!` *channel i j width height value* [Procedure]

`im-fast-channel-set!` *channel i j width value* [Procedure]

Returns nothing.

Sets the pixel at position *i* and *j* of *channel* of size *width* and *height* to *value*.

im-fast-channel-set! does not check the validity of its arguments: use it at your own risk.

`im-collect` *what i1 i2 i3 ...* [Procedure]

Returns a list of *what* collected from *i1 i2 i3 ...*

The valid *what* symbols are:

`size`

`width`

`height`

`n-channel`

`channels`

`chan-0`, `gray`, `red`

`chan-1`, `green`

`chan-2`, `blue`

`chan-k (*)`

(*): with k being a valid channel indice, [0 (- n 1)].

3.2.2 Kernel Structure and Accessors

The Guile-CV procedures and methods related to kernels data structure, creating and accessing kernels.

Kernel Data Structure

A Guile-CV kernel ([https://en.wikipedia.org/wiki/Kernel_\(image_processing\)](https://en.wikipedia.org/wiki/Kernel_(image_processing))) is represented by a list containing the following elements:

`(width height kdata)`

where *kdata* is a vector of `(* width height)` cells. More precisely, *kdata* is an `srfi-4` homogeneous numeric vector of 64 bit floats, called `f64vector`, knowing that `f64` is the C type `double`.

The external representation (ie. read syntax) for *kdata* vectors is `#f64(...)`. As an example, the `identity` kernel of width 3 and height 3, initialized to 0.0 is represented by the following expression:

`(3 3 #f64(0.0 0.0 0.0 0.0 1.0 0.0 0.0 0.0 0.0))`

The kernel *width* and *height* can be different (kernels can be rectangular), but both *width* and *height* must be odd values.

Guile-CV provides useful accessors for kernel fields, however, if you need them all, just like for accessing image fields, your best friend is `(ice-9 match)`, here is an example:

`,use (cv)`


```
(match kernel
  ((width height kdata)
   ... your code here ...))
```

Note that the `(cv)` module imports and re-exports, among many others, the public interface of `(ice-9 match)`.

Guile-CV defines a few useful kernels, see [kernel variables], page 15, at the end of this section, that you both may want to use and reuse: it will be easier, if you need to do so, to define your own kernels reusing an existing one, see the `(cv kdata)` module.

Procedures

k-make *width height* [*values #f*] [*norm #f*] [Procedure]

Returns a new kernel.

The `kdata` value of this new kernel is an `srfi-4` homogeneous numeric vector of 64 bit floats, `f64vector`, composed of *width* by *height* cells.

The optional *values* argument can be:

#f `kdata` is initialized to the ‘identity’ kernel (all zeros except the center of the kernel, initialized to 1)

a single value
all `kdata` cells are initialized using that single value

a list of values
a list of *width* by *height* values, used to initialize `kdata`, in the order they are given

The optional *norm* argument can be:

#f in this case, `kdata` is not normalized

#t unless *values* would be `#f`, `kdata` is normalized using `(reduce + 0 values)`

a single value
all `kdata` cells are normalized using that value, which must be a number different from 0

When both *values* and *norm* are passed - which is mandatory if you want to pass *norm* (since these are optional arguments, as opposed to keyword arguments) - *values* must precede *norm* on the arguments list.

As an example, here is how to define a 3 x 3 normalized mean kernel:

```
,use (cv)
(k-make 3 3 1 #t)
+
$2 = (3 3 #f64(0.1111111111111111 0.1111111111111111 # # # # ...))
(k-display $2)
+

```

```
0.11111  0.11111  0.11111
0.11111  0.11111  0.11111
0.11111  0.11111  0.11111
```

`k-make-circular-mask` *radius* [*value* 1] [*norm* #*f*] [Procedure]

Returns a new circular mask kernel.

The `kdata` value of this new kernel is an `srfi-4` homogeneous numeric vector of 64 bit floats, `f64vector`, composed of *width* by *height* cells where *width* and *height* are equal and odd values determined by the procedure.

The mandatory `radius` argument must be a floating point number satisfying the following predicate: `(float>=? radius 0.5)`.

The optional `norm` argument can be:

- #`f` in this case, `kdata` is not normalized
- #`t` `kdata` values are normalized using `(* n value)`, where `n` is the number of non zero elements of the circular kernel mask being defined.

When both *value* and *norm* are passed - which is mandatory if you want to pass *norm* (since these are optional arguments, as opposed to optional keyword arguments) - *value* must precede *norm* on the arguments list.

To illustrate, here are the circular kernel masks of *radius* 0.5, 1, 1.5 respectively:

```
...
(for-each (lambda (i)
           (k-display (k-make-circular-mask i)
                     #:proc float->int))
  '(0.5 1.0 1.5))
┌
  0 1 0
  1 1 1
  0 1 0

  1 1 1
  1 1 1
  1 1 1

  0 0 1 0 0
  0 1 1 1 0
  1 1 1 1 1
  0 1 1 1 0
  0 0 1 0 0
```

To better illustrate, let's define a bigger circular kernel mask, transform it to an image and `[im-show]`, page 38, it:

```
...
(match (k-make-circular-mask 49)
  ((w h kdata) (list w h 1 (list (f64vector->f32vector kdata))))))
┌
$6 = (99 99 1 (#f32(0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 # ...)))
```

```
(im-show $6 'scale)
```

And you should see the following image⁸

`k-width kernel` [Procedure]

`k-height kernel` [Procedure]

`k-size kernel` [Procedure]

`k-channel kernel` [Procedure]

Returns, respectively, the *width*, the *height*, the list of *width* and *height* or the *kdata* for *kernel*.

`kernel? kernel` [Procedure]

Returns `#t` if *kernel* is a Guile-CV kernel.

`k-ref kernel i j` [Procedure]

`k-fast-ref kernel i j` [Procedure]

Returns the value stored at position *i* and *j* of the *kernel*.

k-fast-ref does not check the validity of its arguments: use it at your own risk.

`k-set! kernel i j value` [Procedure]

`k-fast-set! kernel i j value` [Procedure]

Returns nothing.

Sets the value stored at position *i* and *j* of the *kernel* to *value*.

k-fast-set! does not check the validity of its arguments: use it at your own risk.

`k-offset i j width height` [Procedure]

`k-fast-offset i j width` [Procedure]

Returns the kernel offset for the *i* and *j* indices, based on the *width* and *height* of the kernel.

This procedure converts the matrix indices *i* and *j* to a vector offset for a kernel of size *width* and *height*.

k-fast-offset does not check the validity of its arguments: use it at your own risk.

`k-display image [#:proc #f] [#:port (current-output-port)]` [Procedure]

Returns nothing.

Displays the content of *kernel* on *port*, applying *proc* to each kernel value.

```
,use (cv)
(k-display %k-laplacian)
+
  0.37500   0.25000   0.37500
  0.25000  -2.50000   0.25000
  0.37500   0.25000   0.37500
```

⁸ The `'scale` optional argument passed to `[im-show]`, page 38, as its name indicate, is so that kernel values will be scaled, which in this case means that `1.0` values will become `255.0` - otherwise, it would be almost impossible for a human eye to actually see the shape of the circle . . .

Variables

Notes: (a) the following kernels are merely offered as ‘didactic’ examples, some of these were used ‘in the old days’, but in most cases, you will find and prefer to use a ‘specific’ and ‘modern’ procedure that will give (much) better results, such as, [im-gaussian-blur], page 29, [im-gaussian-sharp], page 30, [im-sharpen], page 30, (a simple sharpening procedure), [im-canny], page 36, (edge detection) ... and (b) in order to make these definitions easier to read, we’ve added some spaces and newlines.

`%k-identity` [Variable]

```
(k-display %k-identity #:proc float->int)
+
  0 0 0
  0 1 0
  0 0 0
```

`%k-edge0` [Variable]

```
(k-make 3 3
  '( 1 0 -1
      0 0 0
      -1 0 1 ))
```

`%k-edge1` [Variable]

```
(k-make 3 3
  '( 0 1 0
      1 -4 1
      0 1 0 ))
```

`%k-sharpen` [Variable]

```
(k-make 3 3
  '( -1 -1 -1
      -1 9 -1
      -1 -1 -1 ))
```

`%k-mean` [Variable]

```
(k-make 3 3
  '( 1 1 1
      1 1 1
      1 1 1 )
  9)
```

`%k-gaussian-blur0` [Variable]

```
(k-make 3 3
  '( 1 2 1
      2 4 2
      1 2 1 )
  16)
```

`%k-gaussian-blur1` [Variable]

```
(k-make 5 5
```

```

      '( 1  4  6  4  1
         4 16 24 16  4
         6 24 36 24  6
         4 16 24 16  4
         1  4  6  4  1 )
256)

```

`%k-unsharp` [Variable]

```

(k-make 5 5
      '( 1  4  6  4  1
         4 16 24 16  4
         6 24 -476 24  6
         4 16 24 16  4
         1  4  6  4  1 )
-256)

```

`%k-emboss` [Variable]

Also called `%k-compass` or `%k-directional`, this kind of filter is useful to enhance edges in given directions. With a 3×3 kernel, one normally uses filters for 0, 45, 90 and 135 degrees. The various angles are obtained ‘rotating’ the positive and negative values to ‘align’ with the various directions.

```

(k-make 3 3
      '( -2 -2  0
         -2  6  0
          0  0  0 ))

```

`%k-laplacian` [Variable]

This is a variation of the more traditional Laplacian kernels, that are meant to enhance edges, in this case in an isotropic fashion (non-directional). This the implementation in the Vigna code and it attributes large weights to the diagonal pixels of the kernel. Nevertheless, the total weight is zero.

```

(k-make 3 3
      '( 0.375  0.25  0.375
         0.25  -2.5  0.25
         0.375  0.25  0.375 ))

```

Prewitt filtering

`%k-prewitt-y` [Variable]

A 3×3 kernel which emphasizes horizontal edges by approximating a vertical gradient.

```

(k-make 3 3
      '( 1  1  1
         0  0  0
        -1 -1 -1 ))

```

`%k-prewitt-x` [Variable]

A 3×3 kernel which emphasizes vertical edges by approximating an horizontal gradient.

```

(k-make 3 3

```

```
'( 1 0 -1
   1 0 -1
   1 0 -1 ))
```

Sobel filtering

Filtering an image using a ‘Sobel filter’ requires a three steps approach: (1) filtering the image using the ‘Sobel y filter’, (2) dito using the ‘Sobel x filter’, and (3) combining the results to obtain ‘Sobel magnitude’: `(sqrt (+ (sqrt sobel-y) (sqrt sobel-x)))`.

```
%k-sobel-y [Variable]
```

```
(k-make 3 3
 '( 1 2 1
    0 0 0
   -1 -2 -1 ))
```

```
%k-sobel-x [Variable]
```

```
(k-make 3 3
 '( 1 0 -1
    2 0 -2
    1 0 -1 ))
```

3.2.3 Import Export

The Guile-CV procedures and methods to load, save and query file system images.

Procedures

```
im-load filename [Procedure]
```

Returns a Guile-CV image.

Loads the image pointed by *filename* and returns a Guile-CV image. *filename* can either be a GRAY or an RGB image.

At this point, Guile-CV supports the following file formats: GIF, TIFF, JPEG, BMP, EXR, HDR, PNM (PBM, PGM, PPM), PNG, SunRaster, KHOROS-UIFF.

```
im-save image filename [scale #f] [Procedure]
```

Returns *#t*.

Saves *image* in *filename*.

The optional *scale* argument can take the following values:

```
#f      pixel values are ‘clipped’: values < 0 are saved as 0, values > 255
        are saved as 255, and otherwise are saved unchanged
#t      all pixel values are scaled9 to the [0 255] range
```

The type in which *image* is saved is determined by the *filename* extension, as in the following example:

```
(im-load "edx.png")
...
(im-save $4 "/tmp/edx.jpg")
```

⁹ Note that in this particular context, *scale* does not mean a change in dimension, but rather bringing pixel values from the range they occupy in memory to the [0 255] range

`im-size filename` [Method]
Returns the list of (*width height n-channel*) for *filename*.

`im-width filename` [Method]

`im-height filename` [Method]

`im-n-channel filename` [Method]
Returns, respectively the *width*, the *height* and the *n-channel* for *filename*.

`im-gray? filename` [Method]

`im-rgb? filename` [Method]

Returns `#t` if *filename* is respectively a GRAY scale or an RGB image.

3.2.4 Processing

The Guile-CV procedures and methods to process images.

Procedures

`im-resize image new-width new-height [#:i-mode 'bilinear]` [Procedure]

`im-resize-channel channel width height new-width new-height` [Procedure]
`[:i-mode 'bilinear]`

Returns a new image or channel resized to *new-width*, *new-height*.

The interpolation mode *#:i-mode*, can be one of:

`none`

`bilinear`

`biquadratic`

`bicubic`

`? (fixme)`

`im-rotate image angle [#:i-mode 'bilinear]` [Procedure]

`im-rotate-channel channel width height angle [#:i-mode 'bilinear]` [Procedure]

Returns a new image or channel rotated by *angle*.

The *angle* is in degrees: `+/- [0.0 360.0]`.

It is necessary, for rotations other than multiples of 90° , to recalculate the target coordinates, since after the rotation, they might be floats. The 'next neighbor' interpolation possible modes, *#:i-mode*, are:

`bilinear`

`biquadratic`

`bicubic`

`? (fixme)`

`im-flip image plane` [Procedure]

`im-flip-channel channel width height plane` [Procedure]

Returns a new image or channel flipped according to the selected *plane*.

Valid flipping *plane* values are:

```
hori horizontal
vert vertical
both
```

`im-invert` *image* [Procedure]

`im-invert-channel` *channel width height* [Procedure]

Returns a new inversed image or channel.

Calculating the inverse of an *image* or a *channel* consist of applying the exponent function, `expt`, to all pixel values, raising them to the power of -1.

`im-transpose` *image* [Procedure]

`im-transpose-channel` *channel width height* [Procedure]

Returns a new tranposed image or channel.

Transposing an *image* or a *channel* consist of flipping it over its main diagonal. In the transposed result, switched in size, row values are the original column values and column values are the original row values.

`im-normalize` *image* [#:value 255.0] [Procedure]

`im-normalize-channel` *channel width height* [#:value 255.0] [Procedure]

Returns a new normalized image or channel.

Normalizing an *image* or a *channel* consist of dividing all pixels by a value so they all fall in the [0.0 -> 1.0] range. The default #:value is 255.0.

`im-clip` *image* [#:lower 0.0] [#:upper 255.0] [Procedure]

`im-clip-channel` *channel width height* [#:lower 0.0] [#:upper 255.0] [Procedure]

Returns a new clipped image or channel.

Clipping an *image* or a *channel* consist of replacing all pixel values below `lower` by the `lower` value and all pixel values above `upper` by the `upper` value.

`im-crop` *image left top right bottom* [Procedure]

`im-crop-channel` *channel width height left top right bottom* [Procedure]
[#:new-w #f] [#:new-h #f]

Returns a new image, resulting of the crop of *image* at *left*, *top*, *right* and *bottom*.

`im-crop-size` *width height left top right bottom* [Procedure]

Returns a list, (`new-width new-height`).

Given the original image *width* and *height*, this procedure checks that *left*, *top*, *right* and *bottom* are valid and return a list, (`new-width new-height`), otherwise, it raises an error.

`im-padd` *image left top right bottom* [#:color '(0.0 0.0 0.0)] [Procedure]

`im-padd-channel` *channel width height left top right bottom* [Procedure]
[#:new-w #f] [#:new-h #f] [#:value 0.0]

Returns a new image or channel, respectively padding *image* or *channel* by *left*, *top*, *right* and *bottom* pixels initialized respectively to *color* or *value*. Note that when

`im-padd` is called upon a GRAY image, *color* is reduced to its corresponding gray value:

```
(/ (reduce + 0 color) 3)
```

`im-padd-size` *width height left top right bottom* [Procedure]
Returns a list, (*new-width new-height*).

Given the original image *width* and *height*, this procedure checks that *left*, *top*, *right* and *bottom* are ≥ 0 and return a list, (*new-width new-height*), otherwise, it raises an error.

`im-rgba->rgb` *image* [*#:bg* '(0.0 0.0 0.0)] [Procedure]

`im-rgba->gray` *image* [*#:bg* '(0.0 0.0 0.0)] [Procedure]

`im-rgb->gray` *image* [Procedure]

Returns a new RGB or GRAY image.

In the RGBA case, *image* channels are first normalized. The new RGB channels are obtained by applying the following pseudo code algorithm:

```
R = (((1 - Source.A) * BG.R) + (Source.A * Source.R)) * 255.0
G = (((1 - Source.A) * BG.G) + (Source.A * Source.G)) * 255.0
B = (((1 - Source.A) * BG.B) + (Source.A * Source.B)) * 255.0
```

`im-threshold` *image threshold* [*#:bg* 'black] [Procedure]

Returns a new BLACK and WHITE image.

The *image* argument can either be a GRAY or an an RGB image, in which case each pixel is converted to GRAY as it is processed. Valid *#:bg* values are **black** (the default) and **white**.

Pixels for which the original value is \geq *threshold* are set to 255.0 if *#:bg* is 'black, and set to 0.0 if *#:bg* is 'white. The other pixels are set to 0.0 or 255.0 respectively.

`im-add` *image val* [Method]

`im-add` *i1 i2 i3 ...* [Method]

`im-add-channel` *channel width height val* [Method]

`im-add-channel` *width height c1 c2 c3 ...* [Method]

Returns a new image or channel.

Performs the scalar addition of *image* with *val* or the matrix addition of *i1 i2 i3 ...* or *c1 c2 c3 ...* respectively.

`im-subtract` *image val* [Method]

`im-subtract` *i1 i2 i3 ...* [Method]

`im-subtract-channel` *channel width height val* [Method]

`im-subtract-channel` *width height c1 c2 c3 ...* [Method]

Returns a new image or channel.

Performs the scalar subtraction of *image* with *val* or the matrix subtraction of *i1 i2 i3 ...* or *c1 c2 c3 ...* respectively.

`im-times` *image val* [Method]

`im-times` *i1 i2 i3 ...* [Method]

`im-times-channel` *channel width height val* [Method]

`im-times-channel` *c1 w1 h1 c2 w2 h2 c3 w3 h3 ...* [Method]

Returns a new image or channel.

Performs the scalar multiplication of *image* with *val* or the element by element multiplication of *i1 i2 i3 ...* or *c1 c2 c3 ...* respectively.

`im-mtimes` *i1 i2 i3 ...* [Procedure]

`im-mtimes-channel` *width height c1 c2 c3 ...* [Procedure]

Returns a new image or channel.

Performs matrix multiplication of *i1 i2 i3 ...* or *c1 w1 h1 c2 w2 h2 c3 w3 h3 ...* recursively. The number of lines of the next image must equal the number of columns of the previous intermediate result.

`im-divide` *image val* [Method]

`im-divide` *i1 i2 i3 ...* [Method]

`im-divide-channel` *channel width height val* [Method]

`im-divide-channel` *c1 w1 h1 c2 w2 h2 c3 w3 h3 ...* [Method]

Returns a new image or channel.

Performs the scalar division of *image* with *val* or the element by element division of *i1 i2 i3 ...* or *c1 c2 c3 ...* respectively.

It is the user responsibility to insure that none of the *c2 c3 ...* values is **zero**.

`im-mdivide` *i1 i2 i3 ...* [Procedure]

`im-mdivide-channel` *width height c1 c2 c3 ...* [Procedure]

Returns a new image or channel.

Performs the matrix multiplication of *i1* or *c1* by the inverse of *i2 i3 ...* or *c2 c3 ...* recursively. The number of lines of the next image must equal the number of columns of the previous intermediate result¹⁰.

It is the user responsibility to insure that none of the *c2 c3 ...* values is **zero**.

`im-range` *image* [Procedure]

`im-range-channel` *channel width* [Procedure]

Returns a list of six values (*min row col max row col*) if *image* is GRAY, and a list of list of these values if *image* is RGB or for any *n-chan > 1* images.

`im-min` *image* [Procedure]

`im-max` *image* [Procedure]

`im-min-channel` *channel width* [Procedure]

`im-max-channel` *channel width* [Procedure]

Returns three multiple values if *image* is GRAY: *min row col* or *max row col* respectively. If *image* is RGB or for any *n-chan > 1* images, it returns a list of list of these values.

`im-map` *proc i1 i2 i3 ...* [Procedure]

`im-map-channel` *proc width height c1 c2 c3 ...* [Procedure]

Returns a new image or channel.

¹⁰ Technically speaking, there is no such thing as matrix division. Dividing a matrix by another matrix is an undefined function. The closest equivalent is to multiply the matrix by the inverse of the other matrix.

Apply *proc* to each pixel value of each channel of *i1* (if only two arguments are given), or to the corresponding pixel values of each channels of *i1 i2 i3 ...* (if more than two arguments are given).

`im-reduce image proc default` [Procedure]
`im-reduce-channel channel proc default` [Procedure]

Returns one value if *image* is GRAY. If *image* is RGB or for any `n-chan > 1`, it returns a list of values.

If *image* is empty, `im-reduce` returns *default* (this is the only use for default). If *image* has only one pixel, then the pixel value is what is returned. Otherwise, *proc* is called on the pixel values of *image*.

Each *proc* call is (`proc elem prev`), where *elem* is a pixel value from the channel (the second and subsequent pixel values of the channel), and *prev* is the returned value from the previous call to *proc*. The first pixel value - for each channel - is the *prev* for the first call to *proc*.

For example:

```
,use (cv)
(im-load "edx.png")
+
$2 = (128 128 1 (#f32(4.0 26.0 102.0 97.0 58.0 10.0 9.0 21.0 # ...)))
(im-reduce $2 + 0)
+
$3 = 556197.0
```

`im-and i1 i2 i3 ...` [Procedure]
`im-and-channel width height c1 c2 c3 ...` [Procedure]
`im-or i1 i2 i3 ...` [Procedure]
`im-or-channel width height c1 c2 c3 ...` [Procedure]
`im-xor i1 i2 i3 ...` [Procedure]
`im-xor-channel width height c1 c2 c3 ...` [Procedure]

Returns *image* if one argument only, otherwise, it returns a new image or channel, as the result of computing the logical AND, OR or XOR of all images or channels.

In the case of AND, for all positive results, the pixel values (of each channel) of the new image are set to the one obtained from *i1* or *c1* respectively, and 0.0 otherwise.

In the case of OR, the pixel values (of each channel) of the new image are set to the one obtained from the first non zero *ii* or *ci* respectively, otherwise it is set to 0.0.

In the case of XOR, the pixel values (of each channel) of the new image are set to the value obtained from successively computing (`logior (logand a (- 255 b)) (logand (- 255 a) b)`) where *a* would be the previous result and *b* the current *image* or *channel* pixel value, until all images passed in arguments have been processed¹¹.

All images must have the same *width*, *height* and *n-channel*.

There are, of course, scientific use and examples of images logical XOR, and that is why Guile-CV (<http://www.gnu.org/software/guile-cv>) is being developed for, but let's have a bit of fun here, and see if our levitating GNU likes apples!

¹¹ Note that there is no mathematically valid XOR operation on floating points, hence as they are 'accessed', pixel values are converted to integer, using `float->int`, defined in the `(cv support libguile-cv)` module).

im-complement *image* [Procedure]

Returns a new image.

This procedure computes the mathematical complement of *image*, which for Guile-CV means that for each pixel of each channel, the new value is `(- 255.0 pixel-value)`.

im-scrap *image size* [#:pred <] [#:con 8] [#:bg 'black] [Procedure]
[exclude-on-edges #f]

Returns a new image.

Scraping an image is the operation of removing objects depending on their *size* (in pixels). When *exclude-on-edges* is #t, all objects that are on any edges are also removed.

The procedure first calls [im-label], page 35, using *con* and *bg*, then calls [im-features], page 24. The **area** feature of each object is then compared to *size* using *pred* and the object is removed if the result is #t.

Note that *image* must be a binary image.

im-particles *image features* [#:clean #t] [Procedure]

Returns two values, a list of images (the particles) and a list of their bounding boxes in the original *image*.

Each returned image is a ‘particle’, which is a subpart of *image* determined by its bounding box, given by the **left top right bottom** values of the corresponding ‘entry’ in *features* (see [im-features], page 24, for a complete description of a feature value list).

When #:clean is #t, which is the default, [im-particle-clean], page 24, is called upon each particle (see below for a description of the expected result).

im-particle-clean *particle* [Procedure]

Returns a new image.

Cleaning a *particle* (which is an image) means detecting and removing any object(s) that is(are) not connected to the ‘particle’ itself.

This procedure is based on the property that in a ‘particle’, which is an (sub)image resulting from a [im-crop], page 20, based on the bounding box coordinates as returned by **im-features**, there precisely is one object that, if you call **im-features** upon *particle*, would have its bounding box coordinates being the entire *particle*. In other words, if you call **im-particle-clean** upon an image that is not a ‘particle’, the result will just be a black image.

3.2.5 Features

The Guile-CV procedures and methods related to image features.

Procedures

im-features *image l-image* [#:n-label #f] [Procedure]

Returns a list of features, one list for each labeled object - including the background - in ascending order.

Notes: (a) *image* can either be an RGB or a GRAY image; (b) *l-image* is the ‘corresponding’ labeled image; (c) when used, the *#:n-label* optional keyword argument must be total number of label values used in *l-image*, as returned by [im-label], page 35, and [im-label-all], page 35.

The GRAY feature list values are:

area	The labeled object area in pixel
left top right bottom	The coordinates of the ‘bounding box’ labeled object ¹²
mean-x mean-y	Also sometimes called the ‘centroid’, these are the average of the x and y coordinates of all of the pixels in the labeled object. These two coordinate values are floating points, representing the ‘mathematical position’ of the mean x and y values of the labeled object
min max mean std-dev	The minimum, maximum, mean and standard gray deviaton labeled object values
major-ev-x major-ev-y minor-ev-x minor-ev-y	Respectively the major and minor eigen vectors (https://en.wikipedia.org/wiki/Eigenvalues_and_eigenvectors) x and y normalized coordinates ¹³ : $(= (\text{sqrt} (+ (\text{expt } x \ 2) (\text{expt } y \ 2))) \ 1)$
major-axis minor-axis	Respectively the major and minor eigen values (https://en.wikipedia.org/wiki/Eigenvalues_and_eigenvectors), optimized so that they actually correspond to major and minor radius of the ellipse covering the same area as the particle itself
angle	The angle of the major eigen vector axis, in degrees in the trigonometric circle reference system
center-mass-x center-mass-y	The center of mass x and y coordinates
perimeter	The labeled object perimeter in pixels
skewness kurtosis	Respectively the skewness (https://en.wikipedia.org/wiki/Skewness) and the kurtosis (https://en.wikipedia.org/wiki/Kurtosis) of the labeled object

¹² Note that when passed to [im-crop], page 20, **right** and **bottom** must be increased by 1: (im-crop image left top (+ right 1) (+ bottom 1)).

¹³ Note that Vigra calculates and returns these values in the image coordinate system, where the y-axis is ‘flipped’ compared to the trigonometric circle ‘traditional’ representation. Guile-CV however transforms and returns these values using the trigonometric circle reference system.

circularity aspect-ratio roundness
 Respectively the circularity ($(4 \pi \text{ area}) / (\text{expt perimeter}^2)$), the aspect ratio ($\text{major-axis} / \text{minor-axis}$) and the roundness ($\text{minor-axis} / \text{major-axis}$) of the labeled object

The RGB feature list values are:

area The labeled object area in pixel

left top right bottom
 The coordinates of the labeled object (the corresponding GRAY feature footnote applies here too of course)

mean-x mean-y
 Also sometimes called the ‘centroid’, these are the average of the x and y coordinates of all of the (red green blue) pixels in the labeled object. These two coordinate values are floating points, representing the ‘mathematical position’ of the mean x and y values of the labeled object

min-r min-g min-b max-r max-g max-b mean-r mean-g mean-b std-dev-r std-dev-g std-dev-b
 The minimum, maximum, mean and standard deviation labeled object values of the red, green and blue channels

major-axis minor-axis
 Respectively the major and minor eigen values (https://en.wikipedia.org/wiki/Eigenvalues_and_eigenvectors), optimized so that they actually correspond to major and minor radius of the ellipse covering the same area as the particle itself

angle The angle of the major eigen vector axis, in degrees in the trigonometric circle reference system

center-mass-x center-mass-y
 The center of mass x and y coordinates

perimeter
 The labeled object perimeter in pixels

skewness-r skewness-g skewness-b kurtosis-r kurtosis-g kurtosis-b
 Respectively the skewness (<https://en.wikipedia.org/wiki/Skewness>) and the kurtosis (<https://en.wikipedia.org/wiki/Kurtosis>) labeled object values of the red, green and blue channels

circularity aspect-ratio roundness
 Respectively the circularity ($(4 \pi \text{ area}) / (\text{expt perimeter}^2)$), the aspect ratio ($\text{major-axis} / \text{minor-axis}$) and the roundness ($\text{minor-axis} / \text{major-axis}$) of the labeled object

Though we did not make it public, Guile-CV has an internal feature display procedure that you might be interested to (re)use, so here is an example of a GRAY feature list display:

```
scheme@(guile-user)> ,use (cv)
```

```

scheme@(guile-user)> (im-load "pp-17-bf.png")
$2 = (85 95 3 (#f32(0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 ...)) ...)
scheme@(guile-user)> (im-rgb->gray $2)
$3 = (85 95 1 (#f32(0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 # ...)))
$4 = (0.0 251.0 128.3132714138286 8075)
scheme@(guile-user)> (im-threshold $3 136)
$5 = (85 95 1 (#f32(0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 # ...)))
scheme@(guile-user)> (im-label $5)
$6 = (85 95 1 (#f32(0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 # ...)))
$7 = 2
scheme@(guile-user)> (im-features $2 $6)
$8 = ((3782 0 0 84 94 43.19196319580078 45.657588958740234 0.0 # ...) ...)
scheme@(guile-user)> ((@ (cv features) f-display) (match $8 ((bg a) a)))

```

```

                                area : 4293 (pixels)
          left top right bottom : 0 0 84 94
                mean-x mean-y : 40.94992 48.18262
          min (red, green, blue) : 137.00000 136.00000 135.00000
          max (red, green, blue) : 255.00000 250.00000 250.00000
          mean (red, green, blue) : 236.13417 232.84999 232.84207
          std. dev. (red, green, blue) : 20.23275 19.41402 19.84854
                major ev x, y : 0.22202 0.97504
                minor ev x, y : 0.97504 -0.22202
          major, minor axis : 39.86419 34.27900 (radius)
                angle : 77.17241 (degrees)
          center of mass x, y : 40.73749 48.28692
                perimeter : 367.74725
          skewness (red, green, blue) : -2.90164 -2.99066 -2.91777
          kurtosis (red, green, blue) : 8.53371 9.05482 8.61162
                circularity : 0.39891
                aspect ratio : 1.16293
                roundness : 0.85989

```

As we mentioned above, `f-diplay` is defined in the `(cv features)` module, but it is not exported: in Guile, calling none exported procedure (which should not be ‘abused’) is done using the syntax `@@ module-name binding-name`, which in this example translates to `@@ (cv features) f-display`.

3.2.6 Texture

The Guile-CV procedures and methods related to image texture measures.

First described here¹⁴, image texture measures are still very ‘actual’, with new research and practice applications in many areas, as described in this (highly recommended) document¹⁵.

¹⁴ R. M. Haralick, K. Shanmugam, and I. Dinstein, Textural Features of Image Classification, IEEE Transactions on Systems, Man and Cybernetics, vol. SMC-3, no. 6, Nov. 1973.

¹⁵ M. Hall-Beyer, GLCM Texture: A Tutorial v. 3.0 March 2017

Image texture measures are ‘**descriptive statistics**’, derived from the ‘**Gray Level Co-occurrence Matrices (GLCM)**’ and its associated set of ‘**Gray Level Co-occurrence Probability (GLCP)**’ matrices.

Guile-CV **GLCM** and **GLCP** data structures are identical to the one used for Guile-CV images (See Section 3.2.1 [Image Structure and Accessors], page 9). Although they are not images ‘**per se**’, they are composed of four square matrices (four channels), of size **n-gl** (the number of gray levels to consider), and upon which we (and users) need to run linear algebra procedures, already defined and available in Guile-CV.

Guile-CV offers the 11th first **texture measures**, out of the 14th originally proposed by Haralick et al., which are the most commonly used and adopted ones.

This reference manual assumes you are familiar with the concepts, terminology and mathematic formulas involved in the calculations of **GLCMs**, **GLCPs** and **image texture measures**. If that is not the case, consider carefully reading one or both of the documents cited above (or any other tutorial or reference material of your choice of course).

Procedures

im-texture *image n-gl* [**#:dist** 1] [**#:p-max** 255] [**#:use-log2** **#f**] [Procedure]
 [**#:no-px-y0** **#f**]

Returns a list.

The procedure calls [im-glcp], page 29, passing *image*, *n-gl* (the number of gray levels to consider), *dist* (the distance between the ‘**reference**’ and the ‘**neighbour**’ pixels) and *p-max* (the *image* (pixel) maximum value), then computes and returns a list of the 11th first texture measures proposed by Haralick et al., which are:

- (h1) **uniformity (angular second moment)**
- (h2) **contrast**
- (h3) **correlation**
- (h4) **variance (sum of squares)**
- (h5) **homogeneity (inverse difference moment)**
- (h6) **sum average**
- (h7) **sum variance**
- (h8) **sum entropy**
- (h9) **entropy**
- (h10) **difference variance**
- (h11) **difference entropy**

The **#:use-log2** optional keyword argument, which defaults to **#f**, is passed to the internal procedures that calculate the parameters **h8**, **h9** and **h11**. The original formulas proposed by Haralck and al. use **log**, but I have seen a couple of implementations using **log2**¹⁶.

The **#:no-px-y0** optional keyword argument, which defaults to **#f**, is passed to the internal procedure that calculate the parameter **h10**. For some obscure reason, and only with respect to this parameter, I have seen some implementations eliminating

¹⁶ Since it is used as a **factor** in all three formulas, the final result obtained using **log2** is equivalent to the result obtained using **log** multiplied by 1.4426950408889634

the first element of the so-called **Px-y**, an intermediate **f32vector** result, which holds, as its first element, the sum of the elements of the main diagonal of the **GLCP**¹⁷.

im-glcp *image n-gl* [#:dist 1] [#:p-max 255] [Procedure]

Returns the **GLCP** for *image*.

The procedure calls `[im-g lcm]`, page 29, passing *image*, *n-gl* (the number of gray levels to consider), *dist* (the distance between the ‘reference’ and the ‘neighbour’ pixels) and *p-max* (the *image* (pixel) maximum value), adds **GLCM**’ (the transposed version of **GLCM**, so the result is symmetrical around the diagonal), then computes and returns the **GLCP**.

The returned **GLCP** is an ‘image’ composed four channels (four square matrices of size *n-gl*), corresponding to the (symmetrical) Gray Level Co-occurrences expressed as probabilities, each calculated at a specific ‘angle’, respectively 0°, 45°, 90°, and 135°.

im-g lcm *image n-gl* [#:dist 1] [#:p-max 255] [Procedure]

Returns the **GLCM** for *image*.

The procedure scales the original *image* (it brings its values in the range [0 (- *n-gl* 1)]), then computes and returns the **GLCM**.

The returned **GLCM** is an ‘image’ composed four channels (four square matrices of size *n-gl*), corresponding to the Gray Level Co-occurrences, each calculated at a specific ‘angle’, respectively 0°, 45°, 90°, and 135°.

3.2.7 Filters

The Guile-CV procedures and methods to filter images.

Procedures

im-gaussian-blur *image sigma* [Procedure]

im-gaussian-blur-channel *channel width height sigma* [Procedure]

Returns a new image or channel.

The new image or new channel is the result of the computation of the Gaussian blurring, also known as the Gaussian smoothing, by means of a convolution of *image* or *channel* with a 2D Gaussian function, where *sigma* is the standard deviation of the Gaussian distribution.

im-gaussian-gradient *image sigma* [Procedure]

im-gaussian-gradient-channel *channel width height sigma* [Procedure]

Returns a new image or channel.

The new image or new channel is the result of the computation of the strength of the first order partial derivatives by means of a convolution of *image* or *channel* with the first order derivative of a 2D Gaussian function, where *sigma* is the standard deviation of the Gaussian distribution.

¹⁷ Guile-CV computes the **difference average** using all elements of the **Px-y**, by default, but offers this option as a courtesy, for users who would want to use Guile-CV as an immediate substitute to compute image texture measures for a (large) image set for which they would already have trained a classifier. It is not recommended to use it otherwise.

`im-gaussian-sharp` *image factor scale* [Procedure]

`im-gaussian-sharp-channel` *channel width height factor scale* [Procedure]

Returns a new image or channel.

The new image or new channel is the result of the computation of the Gaussian sharpening: the procedure does (a) perform a Gaussian smoothing at the given *scale* to create a temporary image `smooth` and (b) blends *image* and `smooth` according to the formula $(- (* (+ factor 1) image) (* smooth factor))$.

`im-sharpen` *image factor* [Procedure]

`im-sharpen-channel` *channel width height factor* [Procedure]

Returns a new image or channel.

This procedure performs a ‘simple sharpening’ operation on *image*. It actually calls [im-convolve], page 30, with the following kernel:

$$\begin{pmatrix} -1/16 & -1/8 & -1/16 & 0 & 0 & 0 \\ * factor & -1/8 & 3/4 & -1/8 & 0 & 1 & 0 \\ -1/16 & -1/8 & -1/16 & 0 & 0 & 0 \end{pmatrix} +$$

and uses `mirror` as the ‘out of bound strategy’.

`im-median-filter` *image w-width w-height [#:obs 'repeat]* [Procedure]

`im-median-filter-channel` *channel width height w-width w-height [#:obs 'repeat]* [Procedure]

Returns a new image or channel.

In the new image or channel, each pixel value is the ‘median’ value of neighboring entries. The pattern of neighbors is called a ‘window’, the size of which is given by *w-width* and *w-height* (see Median Filter (https://en.wikipedia.org/wiki/Median_filter) for more information). Both *w-width* and *w-height* must be odd numbers, inferior to *width* and *height* respectively.

The optional keyword argument *#:obs* determines the ‘out-of-bound strategy’. Valid *#:obs* symbols are:

<code>avoid</code>	do not operate on pixels upon which (centering) the kernel does not fit in the image
<code>repeat</code>	repeat the nearest pixels
<code>mirror</code>	mirror the nearest pixels
<code>wrap</code>	wrap image around (periodic boundary conditions)
<code>zero</code>	out-of-bound pixel values to be 0.0

`im-convolve` *image kernel [#:obs 'repeat]* [Procedure]

`im-convolve-channel` *channel width height kernel k-width k-height [#:obs 'repeat]* [Procedure]

Returns a new image or channel.

The new image or new channel is the result of the convolution ([https://en.wikipedia.org/wiki/Kernel_\(image_processing\)#Convolution](https://en.wikipedia.org/wiki/Kernel_(image_processing)#Convolution)) of *image* using *kernel*. The kernel ([https://en.wikipedia.org/wiki/Kernel_\(image_processing\)](https://en.wikipedia.org/wiki/Kernel_(image_processing)))

k-width and *k-height* values can be different, but they must be odd numbers, inferior to *width* and *height* respectively.

The optional keyword argument `#:obs` determines the ‘out-of-bound strategy’. Valid `#:obs` symbols are:

<code>avoid</code>	do not operate on pixels upon which (centering) the kernel does not fit in the image
<code>clip</code>	clip the kernel when operating on pixels upon which (centering) the kernel does not fit in the image (this is only useful if the kernel is ≥ 0 everywhere)
<code>repeat</code>	repeat the nearest pixels
<code>mirror</code>	mirror the nearest pixels
<code>wrap</code>	wrap image around (periodic boundary conditions)
<code>zero</code>	out-of-bound pixel values to be 0.0

Kernel data structure, accessors, procedures and predefined kernels are all described in this node of the Guile-CV manual: Section 3.2.2 [Kernel Structure and Accessors], page 12.

`im-nl-means` *image arg...* [Procedure]
`im-nl-means-channel` *channel width height arg...* [Procedure]

Returns a new image or channel.

The new image or new channel is the result of a non-local means (https://en.wikipedia.org/wiki/Non-local_means) denoising as described here¹⁸. The following table lists the optional keyword arguments and their default values:

Policy arguments:

<code>#:policy-type</code>	1	accepts 0 (ratio policy) or 1 (norm policy)
<code>#:sigma</code>	15.0	default to 5.0 if the policy-type is 0
<code>#:mean-ratio</code>	5.0	default to 0.95 if the policy-type is 0
<code>#:variance-ratio</code>	0.5	
<code>#:epsilon</code>	1.0e-5	

Filter arguments:

<code>#:spatial-sigma</code>	2.0
<code>#:search-radius</code>	3
<code>#:patch-radius</code>	1
	the patch-radius can be either 1 or 2

¹⁸ P. Coupe, P. Yger, S. Prima, P. Hellier, C. Kervrann, C. Barillot. An Optimized Blockwise Non Local Means Denoising Filter for 3D Magnetic Resonance Images . IEEE Transactions on Medical Imaging, 27(4):425-441, Avril 2008.

```
#:mean-sigma 1.0
#:step-size 2
#:n-iteration 1
```

The `im-nl-means-channel` procedure accepts one additional optional keyword argument:

```
#:n-thread (- (current-processor-count) 1)
```

FIXME need to describe the parameters

3.2.8 Morphology

The Guile-CV procedures and methods related to morphology.

Procedures

`im-disc-erode` *image radius* [Procedure]

`im-disc-erode-channel` *channel width height radius* [Procedure]

Returns a new image or channel.

Performs the morphological erosion of *image* using a disc of a given *radius*. Here is an example:

```
(im-make 5 5 1 1.0)
+
$2 = (5 5 1 (#f32(1.0 1.0 1.0 1.0 1.0 1.0 ...)))
(im-set! $2 1 2 0.0)
(im-disc-erode $2 1)
+
$3 = (5 5 1 (#f32(1.0 0.0 0.0 0.0 1.0 ...)))
(im-display $2 #:proc inexact->exact)
+
Channel 1
  1 1 1 1 1
  1 1 0 1 1
  1 1 1 1 1
  1 1 1 1 1
  1 1 1 1 1
(im-display $3 #:proc inexact->exact)
+
Channel 1
  1 0 0 0 1
  1 0 0 0 1
  1 0 0 0 1
  1 1 1 1 1
  1 1 1 1 1
```

`im-disc-dilate` *image radius* [Procedure]

`im-disc-dilate-channel` *channel width height radius* [Procedure]

Returns a new image or channel.

Performs the morphological dilation of *image* using a disc of a given *radius*. Here is an example:

```

...
└
$13 = (11 11 1 (#f32(0.0 0.0 0.0 0.0 0.0 ...)))
(im-disc-dilate $13 1)
└
$14 = (11 11 1 (#f32(1.0 1.0 1.0 1.0 1.0 ...)))
(im-display $13 #:proc inexact->exact)
└
Channel 1
  0 0 0 0 0 0 0 0 0 0 0
  0 1 1 1 1 0 0 1 1 1 0
  0 1 1 1 1 0 0 1 1 1 0
  0 1 1 1 1 1 1 1 1 1 0
  0 1 1 1 1 1 1 1 1 1 0
  0 1 1 0 0 0 1 1 1 1 0
  0 1 1 0 0 0 1 1 1 1 0
  0 1 1 0 0 0 1 1 1 1 0
  0 1 1 1 1 1 1 1 0 0 0
  0 1 1 1 1 1 1 1 0 0 0
  0 0 0 0 0 0 0 0 0 0 0
(im-display $14 #:proc inexact->exact)
└
Channel 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 0 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 1 1
  1 1 1 1 1 1 1 1 1 0 0
  1 1 1 1 1 1 1 1 1 0 0

```

`im-open` *image radius* [Procedure]

`im-open-channel` *channel width height radius* [Procedure]

Returns a new image or channel.

Performs the dilation of the erosion of *image* using *radius*. Opening removes small objects.

`im-close` *image radius* [Procedure]

`im-close-channel` *channel width height radius* [Procedure]

Returns a new image or channel.

Performs the erosion of the dilation of *image* using *radius*. Closing removes small holes.

`im-fill-holes image` [Procedure]

`im-fill-holes-channel channel width height` [Procedure]

Returns a new image or channel.

The argument must be a BINARY *image*. As its name indicate, this procedure fill the holes of all and every objects in the image.

`im-delineate image [#:threshold 10] [#:radius 2]` [Procedure]

`im-delineate-channel channel width height [#:threshold 10] [#:radius 2]` [Procedure]

Returns a new image or channel.

Also known as ‘Edge Enhancement’, this procedure performs the delineation of *image*, obtained by applying the following pseudo code algorithm:

```
;; with
;; Min = (im-disc-erode image radius)
;; Max = (im-disc-dilate image radius)
D = Max - Min
If D < threshold
  ;; not an edge
  output pixel = input pixel
  ;; it is an edge
  If (pixel -- Min) < (Max -- pixel)
    output pixel = Min
    output pixel = Max
```

Here above, left being the original image - a small part of an optical microscope capture of a sinter sample - you can see the difference between `im-delineate` called with the default *threshold* and *radius* values, then called using `#:threshold 25` and `#:radius 5`.

`im-distance-map image [#:bg 'black] [#:mode 'euclidean]` [Procedure]

`im-distance-map-channel channel width height [#:bg 'black] [#:mode 'euclidean]` [Procedure]

Returns a new image or channel.

Also know as ‘Distance Transform’, this procedure performs the distance map of *image*, which consist of, for each background pixel, calculating its distance to the nearest object or contour. In the return new image or channel, all background pixels will be assigned the their distance value, all other pixels will be assigned to 0. Distances larger than 255 are labelled as 255.

The default background pixel value is ‘black’, the optional `#:bg` keyword argument also accepts ‘white’.

The default distance map mode is ‘euclidean’ (https://en.wikipedia.org/wiki/Euclidean_distance). Other valid optional `#:mode` keyword argument are ‘chessboard’ (https://en.wikipedia.org/wiki/Chessboard_distance) and ‘manhattan’ (https://en.wikipedia.org/wiki/Taxicab_geometry).

Here above, left being the original image - a few cells - you can see the results obtained by calling `im-distance-map` using respectively the 'euclidean', 'manhattan' and 'chessboard' modes.

`im-reconstruct` *image seeds* [#:con 8] [Procedure]

Returns a new image.

This procedure implements a 'binary morphological reconstruction' algorithm, which extracts the connected components of *image* that are 'marked' by (any of) the connected components contained in *seeds*.

Morphological reconstruction is part of a set of image operators often referred to as 'geodesic' (geodesic distance, geodesic dilation ...). Morphological (or geodesic) operations upon digital images come from and use the Mathematical morphology (MM) (https://en.wikipedia.org/wiki/Mathematical_morphology) theory and technique developed for the analysis and processing of geometrical structures.

First described here¹⁹, this implementation is based on a revision of the same article published in 'the IEEE Transactions on Image Processing, Vol. 2, No. 2, pp. 176-201, April 1993', available here (http://www.vincent-net.com/luc/papers/93ieeeeip_recons.pdf).

3.2.9 Segmentation

The Guile-CV procedures and methods related to segmentation.

Procedures

`im-label` *image* [#:con 8] [#:bg 'black'] [Procedure]

`im-label-channel` *channel width height* [#:con 8] [#:bg 'black'] [Procedure]

`im-label-all` *image* [#:con 8] [Procedure]

`im-label-all-channel` *channel width height* [#:con 8] [Procedure]

Returns two values: a new GRAY image or channel, and the total number of labels²⁰.

The `im-label` and `im-label-channel` procedures label foreground objects in the binary *image*. In the new image or channel, 0.0 indicates a background pixel, 1.0 indicates that the pixel belongs to object number 1, 2.0 that the pixel belongs to object number 2, etc.

The `im-label-all` and `im-label-all-channel` procedures label all objects in the binary *image*, with no specific distinction for any *background value*. As a result, these two procedures will label not only the continuous background, if any, but also any hole(s). As an example, they are used by `[im-fill-holes]`, page 34, defined in the module (`cv morphology`), which you may have a look at for a better understanding of how it works.

¹⁹ in Serra, Jean and Vincent, Luc (1992), "An overview of morphological filtering", Circuits, Systems and Signal Processing (Springer) 11 (1): 47-108

²⁰ The number of labels correspond to the highest label value + 1: earlier version of Guile-CV, prior to version 1.8.0, did return the number of objects, which correspond to the highest label value. This was less than optimal, since not only 0.0 is a label, but other procedures, `im-features` for example, do consider and return an element for the background as well.

Two pixels belong to the same object if they are neighbors. By default the algorithm uses 8-connectivity to define a neighborhood, but this can be changed through the keyword argument `#:con`, which can be either 4 or 8.

```
im-canny image [#:sigma 1.0] [#:threshold 0.0] [#:marker 255.0] [Procedure]
im-canny-channel channel width height [#:sigma 1.0] [#:threshold 0.0] [#:marker 255.0] [Procedure]
```

Returns a new image or channel.

Detect and mark edges using a Canny Edge Detector (https://en.wikipedia.org/wiki/Canny_edge_detector) algorithm: (a) compute the *image* Gaussian gradient using *sigma*, (b) remove edges whose strength is below *threshold*, then for all remaining edges, (d) remove the non-local maxima (edge thinning (https://en.wikipedia.org/wiki/Edge_detection#Edge_thinning)) and (e) set their intensity using *marker*.

3.2.10 Utilities

Other Guile-CV procedures and methods utilities.

Procedures

```
im-compose position alignment [#:color '(0 0 0)] img-1 img-2 . . . [Procedure]
im-compose-channels position alignment channels widths heights [Procedure]
[#:value '0.0]
```

Returns a new image or a new channel.

The valid *position* and *alignment* symbols are:

```
left right
      top center bottom
above below
      left center right
```

When used, the optional `#:color` keyword argument must come after the mandatory *alignment* argument and precede *img-1*, otherwise Guile will raise an exception. For RGB images, it is the color used to padd images passed in argument that are inferior, in width or height (depending on the position), to the biggest of them. For GRAY images, the `#:color` is reduced to its corresponding gray value:

```
(/ (reduce + 0 color) 3)
```

For the `im-compose-channels` procedure, the list of *channels*, *widths* and *heights* must be of equal length and equally ordered, so the *nth* element of *widths* and *heights* are the *width* and *height* of the *nth* element of *channels*. The optional `#:value` keyword argument is used to padd *channels* that are inferior, in width or height (depending on the position), to the biggest of them.

```
im-display image [#:proc #f] [#:port (current-output-port)] [Procedure]
im-display-channel channel width height [#:proc #f] [#:port (current-output-port)] [Procedure]
```

Returns nothing.

Displays the content of *image* or *channel* on *port*.

The optional `#:proc` keyword argument must either be `#f`, the default, or a procedure that accepts a single (32 bits float) argument. When `#:proc` is `#f`, `im-display` will use an internally defined procedure which formats its argument ‘à la octave’: nine positions, six decimals, all number aligned on the dot. any value ≥ 1000 is converted to use the exponential float notation. Here is an ‘hand made’ example:

```
...
$2 = (4 3 3 (#f32(0.0 1.0 2.0 3.0 4.0 5.0) ... ...))
scheme@(guile-user)> (im-divide $2 99)
$3 = (4 3 3 (#f32(10.1010103225708 0.010101010091602802 ...) ...))
scheme@(guile-user)> (im-set! $3 0 0 0 10000)
$4 = (4 3 3 (#f32(10000.0 0.010101010091602802 # # # # ...) ...))
scheme@(guile-user)> (im-display $4)
└
```

Channel 1

1.0E+4	0.01010	0.02020	0.03030
0.04040	0.05051	0.06061	0.07071
0.08081	0.09091	0.10101	0.11111

Channel 2

0.12121	0.13131	0.14141	0.15152
0.16162	0.17172	0.18182	0.19192
0.20202	0.21212	0.22222	0.23232

Channel 3

0.24242	0.25253	0.26263	0.27273
0.28283	0.29293	0.30303	0.31313
0.32323	0.33333	0.34343	0.35354

Caution: unless you specify *port*, both this and `[im-display-channel]`, page 36, procedures are ment to be used on very small and testing images, otherwise even on a small image, it might be ok in a terminal, but it will definitely will kill your emacs.

`im-histogram image` [`#:subtitle` “Untitled”] [Procedure]

Returns two values: (1) an image; (2) a list (or a list of list) of significant values for *image*: one list if *image* is GRAY, a list of list of values per channel if *image* is RGB.

The returned image is composed of a header (title, `#:subtitle`), either the GRAY or the RGB channel histogram(s) for *image* and a footer, which is a table containg, for each channel, the following values: **mean**, **standard deviation**, **minimum**, **maximum**, the **mode**²¹ followed by its **value**.

²¹ The mode is the integer corresponding to the histogram entry that received the maximum of hits, and the value displayed in parens precisely is the number of hits.

Here below, the call sequence and the histogram for the GRAY image `sinter.png` given along with Guile-CV documentation and examples:

```
scheme@(guile-user)> (im-load "sinter.png")
$32 = (212 128 1 (#f32(25.0 39.0 50.0 52.0 51.0 45.0 # ...)))
scheme@(guile-user)> (im-histogram $32 #:subtitle "sinter.png")
$34 = (282 271 1 (#f32(255.0 255.0 255.0 255.0 255.0 # ...)))
$35 = (27136 163.346 75.081 0 243 215 727)
```

Note that histogram images returned by `im-histogram` have no borders, the above histogram has been padded - using `(im-padd $34 1 1 1 1 #:color '(96 96 96))` - for better readability, otherwise the title above and the table below would look as if they were not centered.

```
im-show filename [Method]
im-show image [scale #f] [Method]
im-show image name [scale #f] [Method]
```

Returns the string `"#<Image: ...>"`, where `"..."` is either *filename* or a filename constructed by `im-show`, see below.

The optional *scale* argument can take the following values:

```
#f      pixel values are 'clipped': values < 0 are saved as 0, values > 255
        are saved as 255, and otherwise are saved unchanged
#t      all pixel values are scaled22 to the [0 255] range
```

These three methods will also effectively display the image if you are using Geiser (<http://www.nongnu.org/geiser>), which analyzes Guile's procedures and methods returned values (through the use of its pattern matcher), and when appropriate, triggers its image display mechanism.

Geiser has two variables that allow you to choose either to inline images in its Emacs (<https://www.gnu.org/software/emacs>) (Guile repl) buffer, or to display them using external viewer: `geiser-image-viewer` and `geiser-repl-inline-images-p`. You may choose to add these variables in your `.emacs` file, for example:

```
(setq geiser-image-viewer "eog")
(setq geiser-repl-inline-images-p nil)
```

Note that `(setq geiser-repl-inline-images-p t)` will only work if you are using a graphics-aware Emacs, and otherwise, will fall on the external viewer approach, if the variable `geiser-image-viewer` has been defined. When using Geiser in a non graphics-aware Emacs, or when using the external viewer approach, images will appear as buttons: press return on them to invoke (or raise) the external viewer (window containing that image).

Except for the first `im-show` method, Guile-CV has to save the *image* first, and does it in the location defined by the `[%image-cache]`, page 39, variable. If you call `im-show` passing *name*, the *image* is saved as `%image-cache/name.png`, otherwise under a generated name, the result of `(symbol->string (gensym "im-show-"))`.

²² Note that in this particular context, *scale* does not mean a change in dimension, but rather bringing pixel values from the range they occupy in memory to the [0 255] range

Note that if you do not specify *name*, a new external viewer window is opened at each `im-show` invocation, even for identical *image* calls: this because in Guile-CV, on purpose, images are just list, with no (unique) identifier, and there is no way for `im-show` to know ... Further to this point, when you pass *name* as an argument, you are not ‘identifying’ *image*, which may actually differ, but rather just ask to reuse the filename and hence the external viewer window associated with it.

Last note: many external viewers, such as Eog (the Gnome Eye Viewer), will try to apply, per default, some sort of smoothing techniques, especially on `zoom-in` and `zoom-out`: where this is fine for viewing ‘lazer’ pictures, you probably want to check and disable these options when working with Guile-CV.

Variables

`%image-cache` [Variable]

Specifies the location used by `[im-show]`, page 38, to save images.

The default value is `/tmp/<username>/guile-cv`, but you may **set!** it. If you’d like to reuse that location for future guile-cv sessions, you may save it in guile-cv’s ‘per user’ config file `<userdir>/.config/guile-cv` as an assoc pair, here is an example:

```
cat ~/.config/guile-cv.conf
((image-cache . "~/tmp"))
```

Note that if used, the ‘~’ is expanded at load time, so in geiser, it becomes:

```
scheme@(guile-user)> ,use (cv)
scheme@(guile-user)> %image-cache
-
$2 = "/home/david/tmp"
```

`%image-cache-format` [Variable]

Specifies the format used by `[im-show]`, page 38, to save images.

The default value is `"png"`, but you may **set!** it. If you’d like to reuse that format for future guile-cv sessions, you may save it in guile-cv’s ‘per user’ config file `<userdir>/.config/guile-cv`, as an assoc pair, here is an example:

```
cat ~/.config/guile-cv.conf
((image-cache-format . "jpg"))
```

3.3 Support

Guile-CV uses a series of support modules, each documented in the following subsections. You may either import them all, like this (`use-modules (cv support)`), or individually, such as (`use-modules (cv support modules)`), (`use-modules (cv support goops)`), ...

3.3.1 Modules

`[re-export-public-interface]`, page 39

`re-export-public-interface . args` [Special Form]

Re-export the public interface of a module or modules. Invoked as (`re-export-modules (mod1) (mod2)...`).

3.3.2 Goops

3.3.3 G-export

3.3.4 Pi

Procedures

`radian->degree` *rad* [Procedure]

`degree->radian` *deg* [Procedure]

Returns respectively a degree or a radian value.

Variables

`%pi` [Variable]

`%2pi` [Variable]

`%pi/2` [Variable]

Respectively bound to `(acos -1)`, `(* 2 %pi)` and `(/ %pi 2)`.

3.3.5 Utils

Appendix A GNU Free Documentation License

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms

of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the

title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network

protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published

- at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
 - L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
 - M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
 - N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
 - O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment

to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and

subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C) year your name.  
Permission is granted to copy, distribute and/or modify this document  
under the terms of the GNU Free Documentation License, Version 1.3  
or any later version published by the Free Software Foundation;  
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover  
Texts. A copy of the license is included in the section entitled ‘‘GNU  
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with  
the Front-Cover Texts being list, and with the Back-Cover Texts  
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Concept Index

This index contains concepts, keywords and non-Schemey names for several features, to make it easier to locate the desired sections.

C

Copying 1

D

Distance Map 34

Distance Transform 34

E

Edge Detection 36

Edge Enhancement 34

Euclidean Distance 34

F

Features 24

G

Gaussian Blur 29

Gaussian Gradient 29

Gaussian Sharp 30

Gaussian Smooth 29

Geodesic Operators 35

GLCM 29

GLCP 29

GPL 1

Gray Level Co-occurrence Matrix 29

Gray Level Co-occurrence Probability 29

I

Image Convolution 30

Image Particles 24

L

License 1

M

Mathematical Morphology 35

Matrix Division 22

Matrix Multiplication 22

Median Filter 30

Morphological Reconstruction 35

N

Non-Local Means Denoising 31

T

Texture 28

U

User Configuration 39

Procedure Index

This is an alphabetical list of all the procedures, methods and macros in Guile-CV.

D

degree->radian 40

I

im-==-channel? 11
 im-=? 11
 im-add 21
 im-add-channel 21
 im-and 23
 im-and-channel 23
 im-binary-channel? 11
 im-binary? 11
 im-canny 36
 im-canny-channel 36
 im-channel 10
 im-channel-offset 11
 im-channel-ref 11
 im-channel-set! 12
 im-channels 10
 im-clip 20
 im-clip-channel 20
 im-close 33
 im-close-channel 33
 im-collect 12
 im-complement 24
 im-compose 36
 im-compose-channels 36
 im-convolve 30
 im-convolve-channel 30
 im-copy 10
 im-copy-channel 10
 im-crop 20
 im-crop-channel 20
 im-crop-size 20
 im-delineate 34
 im-delineate-channel 34
 im-disc-dilate 32
 im-disc-dilate-channel 32
 im-disc-erode 32
 im-disc-erode-channel 32
 im-display 36
 im-display-channel 36
 im-distance-map 34
 im-distance-map-channel 34
 im-divide 22
 im-divide-channel 22
 im-fast-channel-offset 11
 im-fast-channel-ref 11
 im-fast-channel-set! 12
 im-fast-ref 11
 im-fast-set! 11

im-features 24
 im-fill-holes 34
 im-fill-holes-channel 34
 im-flip 19
 im-flip-channel 19
 im-gaussian-blur 29
 im-gaussian-blur-channel 29
 im-gaussian-gradient 29
 im-gaussian-gradient-channel 29
 im-gaussian-sharp 30
 im-gaussian-sharp-channel 30
 im-glcm 29
 im-glcp 29
 im-gray? 11, 19
 im-height 10, 19
 im-histogram 37
 im-image? 11
 im-invert 20
 im-invert-channel 20
 im-label 35
 im-label-all 35
 im-label-all-channel 35
 im-label-channel 35
 im-load 18
 im-make 10
 im-make-channel 10
 im-make-channels 10
 im-map 22
 im-map-channel 22
 im-max 22
 im-max-channel 22
 im-mdivide 22
 im-mdivide-channel 22
 im-median-filter 30
 im-median-filter-channel 30
 im-min 22
 im-min-channel 22
 im-mtimes 22
 im-mtimes-channel 22
 im-n-channel 10, 19
 im-nl-means 31
 im-nl-means-channel 31
 im-normalize 20
 im-normalize-channel 20
 im-open 33
 im-open-channel 33
 im-or 23
 im-or-channel 23
 im-padd 20
 im-padd-channel 20
 im-padd-size 21
 im-particle-clean 24
 im-particles 24

<code>im-range</code>	22	<code>im-transpose</code>	20
<code>im-range-channel</code>	22	<code>im-transpose-channel</code>	20
<code>im-reconstruct</code>	35	<code>im-width</code>	10, 19
<code>im-reduce</code>	23	<code>im-xor</code>	23
<code>im-reduce-channel</code>	23	<code>im-xor-channel</code>	23
<code>im-ref</code>	11		
<code>im-resize</code>	19	K	
<code>im-resize-channel</code>	19	<code>k-channel</code>	15
<code>im-rgb->gray</code>	21	<code>k-display</code>	15
<code>im-rgb?</code>	11, 19	<code>k-fast-offset</code>	15
<code>im-rgba->gray</code>	21	<code>k-fast-ref</code>	15
<code>im-rgba->rgb</code>	21	<code>k-fast-set!</code>	15
<code>im-rotate</code>	19	<code>k-height</code>	15
<code>im-rotate-channel</code>	19	<code>k-make</code>	13
<code>im-save</code>	18	<code>k-make-circular-mask</code>	14
<code>im-scrap</code>	24	<code>k-offset</code>	15
<code>im-set!</code>	11	<code>k-ref</code>	15
<code>im-sharpen</code>	30	<code>k-set!</code>	15
<code>im-sharpen-channel</code>	30	<code>k-size</code>	15
<code>im-show</code>	38	<code>k-width</code>	15
<code>im-size</code>	10, 19	<code>kernel?</code>	15
<code>im-subtract</code>	21		
<code>im-subtract-channel</code>	21	R	
<code>im-texture</code>	28	<code>radian->degree</code>	40
<code>im-threshold</code>	21	<code>re-export-public-interface</code>	39
<code>im-times</code>	21		
<code>im-times-channel</code>	21		

Variable Index

This is an alphabetical list of all the important variables and constants in Guile-CV.

<code>%2pi</code>	40	<code>%k-mean</code>	16
<code>%image-cache</code>	39	<code>%k-prewitt-x</code>	17
<code>%image-cache-format</code>	39	<code>%k-prewitt-y</code>	17
<code>%k-edge0</code>	16	<code>%k-sharpen</code>	16
<code>%k-edge1</code>	16	<code>%k-sobel-x</code>	18
<code>%k-emboss</code>	17	<code>%k-sobel-y</code>	18
<code>%k-gaussian-blur0</code>	16	<code>%k-unsharp</code>	17
<code>%k-gaussian-blur1</code>	16	<code>%pi</code>	40
<code>%k-identity</code>	16	<code>%pi/2</code>	40
<code>%k-laplacian</code>	17		

Type Index

This is an alphabetical list of all the important data types defined in the Guile-CV Programmers Manual.

(Index is nonexistent)